



Cisco Catalyst 8500/LightStream 1010 IOS Release 12.1(12c)EY

Introduction

This Product Bulletin describes the content and delivery information concerning Cisco IOS™ software release 12.1(12c)EY. It should be used in conjunction with Product Bulletin titles, Cisco IOS Software Release 12.1E. 12.1(12c)EY is an Early Deployment (ED) release supporting Cisco Catalyst 8510/8540 and Lightstream 1010 platforms.

New Features in 12.1(12c)EY

New features are supported on the Cisco Catalyst 8510MSR, 8540MSR, and Lightstream 1010. New features are not available on the Cisco Catalyst 8510CSR nor 8540CSR. Stabilizing bug fixes have been added for all platforms.

New Feature	8510MSR	8540MSR	LS1010	8510CSR	8540CSR
CES SVC's	Y	Y	Y	N	N
SNMP v3	Y	Y	Y	N	N
SSH Secure Shell (SSH)	Y	Y	Y	N	N
New MIB Support	Y	Y	Y	N	N

Table 1. Cisco IOS Release 12.1(12c)EY Features

Detailed Information

CES SVC's

Circuit Emulation Service (CES) is currently supported on the CES Port Adapter Modules (PAM) via Permanent Virtual Circuits (PVC) or Soft Permanent Virtual Circuits (SPVC). The ATM signaling for CES Switched Virtual Circuits (SVC) is different than for the existing CES SPVC's. The new CES SVC feature supports standard ATM signaling of CES SVC's to allow increased interoperability with other equipment.

SNMP v3

Simple Network Management Protocol version 3 (SNMP v3) adds additional security features to existing versions of SNMP. SNMP v3 has been supported on other Cisco products. It is now available on Cisco Catalyst 8510MSR, 8540MSR, and LS1010.



SSH Secure Shell (SSH)

Secure Shell (SSH) is a protocol that provides secure, remote connections via the Internet. It consists of Server and Client applications. There are multiple versions of SSH available. SSH Version 1 of the SSH Server is implemented in Cisco IOS software. The SSH server feature enables an SSH client to make a secure, encrypted connection to a Cisco device. This connection provides functionality that is similar to an inbound Telnet connection. The SSH server in Cisco IOS software works with publicly and commercially available SSH clients.

New MIBs

The following MIBs for SNMPv3 are supported:

SNMP-FRAMEWORK-MIB

SNMP-VACM-MIB

SNMP-USM-MIB

SNMP-MPD-MIB

SNMP-TARGET-MIB

SNMP-NOTIFICATION-MIB

Documents

For more detailed information about the platforms and features being delivered in 12.1(12c)EY, please reference the following documents:

http://www.cisco.com/univercd/cc/td/doc/product/atm/c8540/12_1/12c_ey/index.htm

Support

Cisco IOS software release 12.1(12c)EY follows the standard Cisco support policy as indicated in the following link:

<http://www.cisco.com/warp/public/437/27.html>

Download Information

Customers can download Cisco IOS Release 12.1(5)EY software from Cisco Connection Online (CCO) in the Software Image Library.

<http://www.cisco.com/public/sw-center>



Product Numbers

Cisco IOS Release 12.1(12c)EY Feature Sets, Images, and Memory Recommendations

Platform	Software Feature Set	Product Codes	Image	Flash	DRAM
LS1010	Cisco LS1010 Series IOS Lightstream IISP/PNNI	SL10R2-12112EY SL10R2-12112EY=	ls1010-w p-mz	16MB	64MB
LS1010	Cisco LS1010 Series IOS Lightstream IISP/PNNI SSH 3DES	SL10R2K2-12112EY SL10R2K2-12112EY=	ls1010-wpk2-mz	16MB	64MB
8510MSR	Cisco CAT8510 Series IOS ATM/Layer3	S851R2-12112EY S851R2-12112EY=	cat8510m-w p-mz	16MB	64MB
8510MSR	Cisco CAT8510 Series IOS ATM/Layer3 SSH 3DES	S851R2K2-12112EY S851R2K2-12112EY=	cat8510m-wpk2-mz	16MB	64MB
8540MSR	Cisco CAT8540 Series IOS ATM/Layer3	S854R2-12112EY S854R2-12112EY=	cat8540m-w p-mz	16MB	256MB
8540MSR	Cisco CAT8540 Series IOS ATM/Layer3 SSH 3DES	S854R2K2-12112EY S854R2K2-12112EY=	cat8540m-wpk2-mz	16MB	256MB
8510CSR	Cisco CAT8510 Series IOS IP/Bridging	S851R3-12112EY S851R3-12112EY=	cat8510c-w p-mz	16MB	64MB
8540CSR	Cisco CAT8540 Series IOS IP/Bridging	S854R3-12112EY S854R3-12112EY=	cat8540c-w p-mz	16MB	256MB

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
Capital Tower
168 Robinson Road
#22-01 to #29-01
Singapore 068912
www.cisco.com
Tel: +65 317 7777
Fax: +65 317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the

Cisco Web site at www.cisco.com/go/offices

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland
Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland
Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

All contents are Copyright © 1992–2002, Cisco Systems, Inc. All rights reserved. CCIP, the Cisco Arrow logo, the Cisco *Powered* Network mark, the Cisco Systems Verified logo, Cisco Unity, Follow Me Browsing, FormShare, Internet Quotient, iQ Breakthrough, iQ Expertise, iQ FastTrack, the iQ logo, iQ Net Readiness Scorecard, Networking Academy, ScriptShare, SMARTnet, TransPath, and Voice LAN are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, Discover All That's Possible, The Fastest Way to Increase Your Internet Quotient, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, IOS, IP/TV, LightStream, MGX, MICA, the Networkers logo, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, SlideCast, StrataView Plus, Stratum, SwitchProbe, TeleRouter, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company.
(0206R)