



Embedded Event Manager 2.2

Embedded Event Manager (EEM) is a flexible, policy-driven framework that supports in-box monitoring of different system components with the help of software agents known as event detectors. EEM 2.2 introduces the enhanced object tracking, resource, and redundancy framework (RF) event detectors. The enhanced object tracking event detector publishes an event when the tracked object changes. Enhanced object tracking provides complete separation between the objects to be tracked and the action to be taken by a client when a tracked object changes. The resource event detector publishes an event when the Embedded Resource Manager (ERM) reports an event for the specified policy. The RF event detector publishes an event when one or more RF events occur during synchronization in a dual Route Processor (RP) system. The RF event detector can also detect an event when a dual RP system continuously switches from one RP to another RP (referred to as a ping-pong situation). EEM 2.2 also introduces the following actions:

- Reading the state of a tracked object
- Setting the state of a tracked object

Configuration Information

Configuration information is included in the “Embedded Event Manager Overview” module in the “Embedded Event Manager” part of the *Cisco IOS Network Management Configuration Guide*, Release 12.4T, at the following URL:

http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/tnm_c/eem/t_eemo.htm

The following sections provide information about this feature:

- Embedded Event Manager 2.2
- Event Detectors
- Embedded Event Manager Actions
- Embedded Event Manager Environment Variables
- Embedded Event Manager Policy Creation

Configuration information is also included in the “Writing Embedded Event Manager Policies Using the Cisco IOS CLI” module in the “Embedded Event Manager” part of the *Cisco IOS Network Management Configuration Guide*, Release 12.4T, at the following URL:

http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/tnm_c/eem/t_eemc.htm



The following sections provide information about this feature:

- Embedded Event Manager Policies
- EEM Event Detectors Available by Cisco IOS Release
- EEM Actions Available by Cisco IOS Release
- Configuring and Tracking a Stub Object Using Embedded Event Manager
- Configuring and Tracking a Stub Object Using Embedded Event Manager: Example

Configuration information is also included in the “Writing Embedded Event Manager Policies Using Tcl” module in the “Embedded Event Manager” part of the *Cisco IOS Network Management Configuration Guide*, Release 12.4T, at the following URL:

http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/tnm_c/eem/t_eemt.htm

The following sections provide information about this feature:

- EEM Event Detectors Available by Cisco IOS Release
- EEM Actions Available by Cisco IOS Release
- Modifying the Sample EEM Policies
- EEM Policy Tcl Command Extension Reference

For a complete list of features included in the “Embedded Event Manager Overview,” the “Writing Embedded Event Manager Policies Using the Cisco IOS CLI,” and the “Writing Embedded Event Manager Policies Using Tcl” modules, see the Feature Information Table located toward the end of the modules.

Command Reference Information

Command reference information is included in the *Cisco IOS Network Management Command Reference*, Release 12.2SB, at the following URL:

http://www.cisco.com/univercd/cc/td/doc/product/software/ios122sb/cr/sbnm_r/index.htm

New or Modified Commands

The following commands are new or modified for this feature:

- **action track read**
- **action track set**
- **default-state**
- **event resource**
- **event rf**
- **event track**
- **show track**
- **track stub**

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007 Cisco Systems, Inc. All rights reserved.

