



Enhanced Tracking Support

The Enhanced Tracking Support feature separates the tracking mechanism from Hot Standby Router Protocol (HSRP) and creates a separate standalone tracking process that can be used by other Cisco IOS processes as well as HSRP. This feature allows tracking of other objects in addition to the interface line-protocol state.

Configuration Information

Configuration information is included in the “Configuring Enhanced Object Tracking” chapter in the *Cisco IOS IP Application Services Configuration Guide*, Release 12.4T at the following URL:

- http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/tiap_c/index.htm

Command Reference Information

Command reference information is included in the *Cisco IOS IP Application Services Command Reference*, Release 12.2SR, at the following URL:

- http://www.cisco.com/univercd/cc/td/doc/product/software/ios122sr/cr/sriap_r/index.htm

New or Modified Commands

The following commands are new or modified for this feature:

- **debug track**
- **delay (tracking)**
- **ip vrf**
- **show track**
- **standby track**
- **threshold metric**
- **track interface**
- **track ip route**
- **track timer**

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2006 Cisco Systems, Inc. All rights reserved.

