



User Defined Source Port Ranges for PAT

The User Defined Source Port Ranges for PAT feature enables the specification of source port ranges for Port Address Translation (PAT) for Session Initiation Protocol (SIP), H.323, and Skinny Real-Time Transport Protocol (RTP) and RTP Control Protocol (RTCP).

Configuration Information

Configuration information is included in the “Using Application level Gateways with NAT” module in the *Cisco IOS NAT Configuration Guide*, Release 12.4T, at the following URL:

- http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/tnat_c/index.htm

Command Reference Information

Command reference information is included in the “**NAT Commands**” chapter of the *Cisco IOS IP Addressing Services Command Reference* at the following URL:

- http://www.cisco.com/en/US/docs/ios/ipaddr/command/reference/iad_book.html

New or Modified Commands

The following commands are new or modified for this feature:

- **ip nat port-map**
- **ip nat service**

List of All Release 12.4T Commands

An alphabetical list of all Cisco IOS Release 12.4T commands is in the *Cisco IOS Master Command List*, Release 12.4T, at the following URL:

- http://www.cisco.com/en/US/docs/ios/mcl/124tmcl/124t_book.html

List of All New, Modified, Removed, and Replaced Release 12.4T Commands

Alphabetized lists of all new, modified, removed, and replaced commands for each Cisco IOS Release 12.4T release are in the *Cisco IOS New, Modified, Removed, and Replaced Commands*, Release 12.4T, document at the following URL:

- http://www.cisco.com/en/US/products/ps6441/products_product_index09186a00805db026.html

