



OER Voice Traffic Optimization Using Active Probes

The OER Voice Traffic Optimization Using Active Probes feature provides support for outbound optimization of voice traffic based on the voice metrics, jitter and Mean Opinion Score (MOS). Jitter and MOS are important quantitative quality metrics for voice traffic and these voice metrics are measured using Optimized Edge Routing (OER) active probes.

Configuration Information

Configuration information is included in the *Cisco IOS Optimized Edge Routing Configuration Guide*, Release 12.4T, at the following URL:

- http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcg/toer_c/index.htm

Command Reference Information

Command reference information is included in the *Cisco IOS Optimized Edge Routing Command Reference*, Release 12.4T, at the following URL:

- http://www.cisco.com/univercd/cc/td/doc/product/software/ios124/124tcr/toer_r/index.htm

New or Modified Commands

The following commands are new or modified for this feature:

- **active-probe**
- **jitter**
- **mos**
- **resolve**
- **set jitter**
- **set mos**
- **set probe**
- **set resolve**
- **show oer master active-probes**

- **show oer master policy**
- **show oer master prefix**

List of All Release 12.4T Commands

An alphabetical list of all Cisco IOS Release 12.4T commands is in the *Cisco IOS Master Commands List*, Release 12.4T, at the following URL:

- http://www.cisco.com/en/US/docs/ios/mcl/124tmcl/124t_book.html

List of All New, Modified, Removed, and Replaced Release 12.4T Commands

Alphabetized lists of all new, modified, removed, and replaced commands for each Cisco IOS Release 12.4T release are in the *Cisco IOS New, Modified, Removed, and Replaced Commands*, Release 12.4T, document at the following URL:

- http://www.cisco.com/en/US/products/ps6441/products_product_index09186a00805db026.html