



SIP:SIP Support for PAI and PPI

Provides support for RFC 3323 and RFC 3325 that allow you to enable either P-Asserted-Identity (PAI) or P-Preferred-Identity (PPI) privacy headers in outgoing SIP request or response messages to assert the identity of authenticated users in trusted domains.

Configuration Information

Configuration information is included in the “Configuring SIP Message, Timer, and Response Features” chapter of the *Cisco IOS SIP Configuration Guide*, Release 12.4T, at the following URL:

http://www.cisco.com/en/US/docs/ios/voice/sip/configuration/guide/12_4t/sip_12_4t_book.html

Command Reference Information

Command reference information is included in the *Cisco IOS Voice Command Reference* at the following URL:

http://www.cisco.com/en/US/docs/ios/voice/command/reference/vr_book.html

New or Modified Commands

The following commands are new or modified for this feature:

- **asserted-id**
- **calling-info pstn-to-sip**
- **privacy**

List of All Release 12.4T Commands

An alphabetical list of all Cisco IOS Release 12.4T commands is in the *Cisco IOS Master Commands List*, Release 12.4T, at the following URL:

http://www.cisco.com/en/US/docs/ios/mcl/124tmcl/124t_book.html

List of All New, Modified, Removed, and Replaced Release 12.4T Commands

Alphabetized lists of all new, modified, removed, and replaced commands for each Cisco IOS Release 12.4T release are in the *Cisco IOS New, Modified, Removed, and Replaced Commands*, Release 12.4T, document at the following URL:

http://www.cisco.com/en/US/docs/ios/mcl/124tmcl/124t_nml.html



Americas Headquarters:

Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007-2008 Cisco Systems, Inc. All rights reserved.

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2007-2008 Cisco Systems, Inc. All rights reserved.