



CHAPTER 4

Support Information for Cisco Security Appliances

This chapter contains support information for Virtual Network Elements (VNEs) that manage Cisco security appliances in Cisco ANA Version 3.6.7. For more information about the objects and attributes described in this chapter, see [Cisco Active Network Abstraction 3.6.7 Technology Support and Information Model Reference Manual](#).

This chapter contains the following topics:

- [Cisco Adaptive Security Appliance 5550 Series, page 4-1](#)
- [Supported Technologies on Cisco Security Appliances, page 4-3](#)

Cisco Adaptive Security Appliance 5550 Series

This section includes the following information about Cisco ASA 5550 Series security appliances (for information on the NE types supported in Cisco ANA Version 3.6.7, see [Cisco Adaptive Security Appliance 5550 Series](#)):

- [Cisco ASA 5550 Series—Supported Software Versions, page 4-2](#)
- [Cisco ASA 5550 Series—Supported Topologies, page 4-2](#)
- [Cisco ASA 5550 Series—Supported Modules, page 4-2](#)
- [Cisco ASA 5550 Series—Supported Technologies, page 4-2](#)
- [Cisco ASA 5550 Series—Supported Service Events, page 4-3](#)

Cisco ASA 5550 Series—Supported Software Versions

Table 4-1 Supported Software Versions for Cisco ASA 5550 Series—Cisco ANA Version 3.6.7

Software Version	ANA Version	Certification Level
7.2(3)12	3.6.3	S



Note

Software versions marked with an asterisk (representing a wildcard) are supported by Cisco ANA Version 3.6.7. Specific software versions that have been tested and verified are listed individually and marked as V.

Cisco ASA 5550 Series—Supported Topologies

Table 4-2 Supported Topologies for Cisco ASA 5550 Series—Cisco ANA Version 3.6.7

Topology Type	Link Type	ANA Version
Ethernet	Ethernet	3.6.3

Cisco ASA 5550 Series—Supported Modules

Table 4-3 Supported Modules for Cisco ASA 5550 Series—Cisco ANA Version 3.6.7

Module Name	ANA Version	Module Description	Certification Level
SSM-4GE-INC	3.6.3	SSM-4GE Included with ASA 5550 System	S

Cisco ASA 5550 Series—Supported Technologies

The following technologies are supported by the Cisco ASA 5550 Series in Cisco ANA Version 3.6.7:

- [IP, page 4-4](#)
- [Ethernet \(IEEE 802.3\), page 4-6](#)
- [Physical Equipment, page 4-10](#)
- [Base Logical Components, page 4-11](#)
- [Common, page 4-12](#)

Cisco ASA 5550 Series—Supported Service Events

Table 4-4 Supported Service Events for Cisco ASA 5550 Series—Cisco ANA Version 3.6.7

Event Name	ANA Version	Expedited
Primary HSRP Interface Active/Inactive	3.6.0	Y
All IP Interfaces Down / Active IP Interfaces Found	3.6.3	Y
Interface Status Down/Up	3.6.3	Y
Card In/Out	3.6.3	Y
Link Down/Up	3.6.3	Y
Device Unreachable	3.6.3	Y
CPU Over Utilized	3.6.3	Y
Memory Over Utilized	3.6.3	Y
Device Unsupported	3.6.3	Y
Discard Packets	3.6.3	N
Dropped Packets	3.6.3	N
Module Unsupported	3.6.3	N
Port Down	3.6.3	Y
Card Up/Down	3.6.3	Y

Supported Technologies on Cisco Security Appliances

The following sections list the objects and attributes that are supported on Cisco security appliances in Cisco ANA Version 3.6.7 per technology:

- [IP](#), page 4-4
- [Ethernet \(IEEE 802.3\)](#), page 4-6
- [Physical Equipment](#), page 4-10
- [Base Logical Components](#), page 4-11
- [Common](#), page 4-12

IP

Table 4-5 IP Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7

Attribute	ASA5550
IMO Name—IIPInterface	
IP Address	Y
Subnetwork Mask	Y
IP Interface Addresses Array	Y
Interface Name	Y
Interface Description	Y
IP Interface State	Y
OSPF Interface Cost	
Broadcast Address	
MTU	
Lookup Method	
Address Resolution Type	
ARP Timeout	
Secured ARP	
ICMP Mask Reply	
IGMP Proxy	
HSRP Groups	
IP Multiplexing Table	
IANA Type	
Containing CTPs	
Contained CTPs	
IMO Name—IIPMuxEntry	
Termination Point	
Destination IP Subnet	
IMO Name—IIRoutingEntity	
Routing Table	Y
ARP Entity	Y
Routing Table Changes	
Name	Y
Logical Sons	Y
IMO Name—IIRoutingEntry	
Destination IP Subnet	Y

Table 4-5 IP Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7

Attribute	ASA5550
Next Hop IP Address	Y
Type	Y
Routing Protocol Type	Y
Outgoing Interface Name	Y
IMO Name—IARPEntity	
ARP Table	Y
IMO Name—IARPEntity	
IP Address	Y
MAC Address	Y
Port	Y
Entry Type	Y
IMO Name—IIPPool	
IP Address Pool Entries	
Name	
Index	
IMO Name—IIPRangeBasedIPPoolEntry	
Start IP Address	
End IP Address	
Unused Addresses	
Used Addresses	
Reserved Addresses	
IMO Name—IIPSubnetBasedIPPoolEntry	
IP Subnet	
Unused Addresses	
Used Addresses	
Reserved Addresses	
IMO Name—HSRPGroupEntry	
Group Number	
Port Description	
Priority	
Coupled Router	
State	
Tracking Interfaces	
Virtual IP Address	
Virtual MAC Address	

Table 4-5 *IP Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7*

Attribute	ASA5550
IMO Name—I Tunnel GRE	
Name	
Tunnel Destination and Source	
IP Address	
IP Interface State	
IANA Type	
Containing CTPs	
Contained CTPs	
Keep Alive Time	
Keep Alive Retry	

Ethernet (IEEE 802.3)

Table 4-6 *Ethernet (IEEE 802.3) Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7*

Attribute	ASA5550
IMO Name—I Link Aggregation Group 802.3ad	
dot3adAggMACAddress	
dot3adAggActorSystemPriority	
dot3adAggActorSystemID	
dot3adAggActorAdminKey	
dot3adAggActorOperKey	
dot3adAggPartnerSystemID	
dot3adAggPartnerSystemPriority	
dot3adAggPartnerOperKey	
dot3adAggCollectorMaxDelay	
GroupNumber	
AggregationProtocolType	
MacAddress	
ChannelAdminStatus	
ChannelOperStatus	
IMO Name—I Ethernet	
MAC Address	Y

Table 4-6 Ethernet (IEEE 802.3) Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)

Attribute	ASA5550
Duplex Mode	
Output Flow Control	
Input Flow Control	
IANA Type	Y
Containing CTPs	
Contained CTPs	
Port Type	
IMO Name—IVlanInterface	
Mode	
Native VLAN Identification	
Virtual LAN Table	
IANA Type	
Containing CTPs	
Contained CTPs	
vlanAdminType	
vlanencapType	
getAccess	
Allowed Vlans	
IMO Name—IVlanEncapMux	
IANA Type	
Containing CTPs	
Contained CTPs	
IMO Name—IIEEE802	
VLAN Identification	
Binding Information	
Binding Status	
IANA Type	
Containing CTPs	
Contained CTPs	
IMO Name—IStpService	
StpProtocol	
StpMaxAge	
StpHelloTime	
StpBridgeForwardDelay	

Table 4-6 Ethernet (IEEE 802.3) Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)

Attribute	ASA5550
StpInstanceInfoTable	
Same as ISystemService	
StpUplinkFastState	
StpBackboneFastState	
StpForwardDelay	
StpBridgeMaxAge	
StpBridgeHelloTime	
IMO Name—IMstService	
MstProperties	
Same as IStpService	
IMO Name—IPvstpService	
UpLinkFast	
BackboneFast	
IMO Name—IMstProperties	
MstForceVersion	
MstCfgIdFmtSel	
MstExternalRootCost	
MstMaxInstances	
MstCfgIdName	
MstCfgIdRevLevel	
IMO Name—IStpInstanceInfo	
Object Identification	
StpBridgeId	
BridgePriority	
Designated Parent and Root Bridges	
StpRootCost	
IsRoot	
StpRootPort	
StpPortInfoTable	
STP Instance Id	
Vlan Id	
StpDesignatedBridge	
StpDesignatedRoot	

Table 4-6 Ethernet (IEEE 802.3) Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)

Attribute	ASA5550
IMO Name—IMstInstanceInfo	
MstVlanIds	
Same as IStpInstanceInfo	
IMO Name—IPvstpInstanceInfo	
Protocol Type	
StpBridgeMaxAge	
StpBridgeHelloTime	
StpBridgeForwardDelay	
StpProtocolSpecification	
StpVlanId	
StpForwardDelay	
StpMaxAge	
IMO Name—IRstpInstanceInfo	
StpForceVersion	
Same as IStpInstanceInfo	
IMO Name—IStpPortInfo	
StpPort	
StpPortPriority	
StpPortState	
StpPortPathCost	
StpPortEdgePort	
StpPortPointToPoint	
StpPortRole	
StpDesignatedPortIdentifier	
StpDesignatedBridge	
StpPortIdentifier	
StpPortBpduGuardState	
StpPortBpduFilterState	
IMO Name—IMstPortInfo	
MstPortHelloTime	
Same as IStpPortInfo	
IMO Name—IPvstpPortInfo	
PvstpPortFastState	

Table 4-6 Ethernet (IEEE 802.3) Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)

Attribute	ASA5550
IMO Name—IEthernetChannel	
Group Number	
Bandwidth	
Aggregation Protocol	
IANA Type	
Containing CTPs	
Contained CTPs	
Mac Address	
Admin Status	
Oper Status	

Physical Equipment

Table 4-7 Physical Equipment Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7

Attribute	ASA5550
IMO Name—IChassis	
Description	
Equipment Holder Type	Y
Contained Equipment Holders	
Contained Equipments	
Serial Number	
IMO Name—IShelf	
Description	
Status	
Equipment Holder Type	
Contained Equipment Holders	
Contained Equipments	
Serial Number	
IMO Name—IModule	
Module Name	Y
Module Description	Y

Table 4-7 *Physical Equipment Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)*

Attribute	ASA5550
Software Version	Y
Operational Status	Y
Hardware Type + Version	Y
Managed IP Address	
Redundant Equipment	
Configured Redundancy	
Redundancy Status	
Operational Status Last Changed	
Supported Physical Termination Points	
Serial Number (soft property)	Y
Slots Number	

Base Logical Components

Table 4-8 *Base Logical Components Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7*

Attribute	ASA5550
IMO Name—IManagedElement	
IP Address	Y
Communication State	Y
Investigation State	Y
Element Category	Y
Element Type and Key	Y
Device Name	Y
System Name	Y
System Description	Y
Up Time	Y
Software Version	Y
Vendor Identity	Y
Memory and CPU Usage	Y
DRAM Free	
DRAM Used	

Table 4-8 *Base Logical Components Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7 (continued)*

Attribute	ASA5550
Flash Device Size	Y
NVRAM Size	Y
Processor DRAM	
Sys Contact	Y
Sys Location	Y
Serial Number	Y
File Systems	
IMO Name—IContext	
Name	
Bounded Connections	
IP Address Pools	
Forwarding Components List	
Traffic Descriptors List	
Tunnel Containers List	
Data Link Aggregation Containers List	
IMO Name—ISystemService	
Type	
Status	
Up Time	Y

Common

Table 4-9 *Common Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7*

Attribute	ASA5550
IMO Name—IPhysicalLayer	
Media Type	Y
Clocking Source	
Maximum Speed	Y
Is Internal Port	Y
Discarded Bandwidth	
Dropped Bandwidth	
Input Bandwidth	

Table 4-9 Common Attribute Support on Cisco Security Appliances—Cisco ANA Version 3.6.7

Attribute	ASA5550
Output Bandwidth	
Discarded and Received Input Data Counters	
Dropped and Forward Output Data Counters	
Administrative Status	Y
Operational Status	Y
Last Changed	
IANA Type	Y
Containing CTPs	
Contained CTPs	
Port Alias	Y
Location	Y
Sending Alarms	Y
Connector Description	Y
Part ID	Y
Connectort Serial Num	Y
Product	Y
Status	Y
Managed	Y
IMO Name—IBridge	
Bridge Table	
Type	
MAC Address	
IP Interface	
Name	
Logical Sons	
Vlan Type	
IMO Name—IBridgeEntry	
Destination MAC	
Outgoing Interface	
IMO Name—IVcSwitchingEntity	
Cross Connect Table	
Cross Connect Table Size	
Logical Sons	

