



APPENDIX **E**

Performance Data

This appendix describes the performance management (PM) tables that are available in Cisco Prime Optical. This appendix includes the following sections:

- [E.1 ONS 15305-Specific PM Tables, page E-1](#)
- [E.2 PM Tables for CTC-Based NEs, page E-9](#)
- [E.3 ONS 15530 and ONS 15540 PM Tables, page E-204](#)

**Note**

PM data collection is not available for the ONS 15216.

E.1 ONS 15305-Specific PM Tables

This section describes the PM tables that are specific to ONS 15305 NEs.

E.1.1 Overview of Supported PM Parameters

ONS 15305 PM parameters are available on any of the following cards:

- S1.1-2-LC
- S1.1-8-LC
- S4.1-2-LC
- S4.1-4-LC
- S16.1-1-LC
- GE-1-LC
- GE-2-LC
- E100-8
- E3T3-6
- E1-8
- E1-21
- E1-63

- L4.2-2-LC
- L16.2-1LC
- S1.1-2-LC/E1-21
- 2xGE+MAP
- 8xFE+MAP

E.1.1.1 Edge SDH

Table E-1 to Table E-7 list all the ONS 15305 Edge SDH PM parameters with the corresponding description and a list of cards supported.

Table E-1 Regenerator Section PM Parameters—Near End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|---|---|
| RS-SES | Regenerator section—severely errored seconds (near end) | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21 |
| RS-BBE | Regenerator section—background block errors (near end) | |
| RS-ES | Regenerator section—errored seconds (near end) | |
| RS-UAS | Regenerator section—unavailable seconds (near end) | |

Table E-2 Multiplex Section PM Parameters—Near End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|---|---|
| MS-BBE | Multiplex section—background block errors (near end) | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21 |
| MS-ES | Multiplex section—errored seconds (near end) | |
| MS-SES | Multiplex section—severely errored seconds (near end) | |
| MS-UAS | Multiplex section—unavailable seconds (near end) | |

Table E-3 Multiplex Section PM Parameters—Far End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|--|---|
| MS-BBE | Multiplex section—background block errors (far end) | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21 |
| MS-ES | Multiplex section—errored seconds (far end) | |
| MS-SES | Multiplex section—severely errored seconds (far end) | |
| MS-UAS | Multiplex section—unavailable seconds (far end) | |

Table E-4 Higher-Order Virtual Container PM Parameters—Near End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|---|---|
| HP-BBE | High-order path—background block errors (near end) | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21 |
| HP-ES | High-order path—errored seconds (near end) | |
| HP-SES | High-order path—severely errored seconds (near end) | |
| HP-UAS | High-order path—unavailable seconds (near end) | |

Table E-5 Higher-Order Virtual Container PM Parameters—Far End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|--|---|
| HP-BBE | High-order path—background block errors (far end) | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21 |
| HP-ES | High-order path—errored seconds (far end) | |
| HP-SES | High-order path—severely errored seconds (far end) | |
| HP-UAS | High-order path—unavailable seconds (far end) | |

Table E-6 Lower-Order Virtual Container PM Parameters—Near End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|--|---|
| LP-BBE | Low-order path—background block errors (near end) | S1.1-8-LC, E3T3-6(3), E1-8(1), E1-21(1), E1-63(1), S1.1-2-LC/E1-21(1) |
| LP-ES | Low-order path—errored seconds (near end) | |
| LP-SES | Low-order path—severely errored seconds (near end) | |
| LP-UAS | Low-order path—unavailable seconds (near end) | |

Table E-7 Lower-Order Virtual Container PM Parameters—Far End

| Parameter | Description | ONS 15305 Cards Supported |
|-----------|---|---|
| LP-BBE | Low-order path—background block errors (far end) | S1.1-8-LC, E3T3-6(3), E1-8(1), E1-21(1), E1-63(1), S1.1-2-LC/E1-21(1) |
| LP-ES | Low-order path—errored seconds (far end) | |
| LP-SES | Low-order path—severely errored seconds (far end) | |
| LP-UAS | Low-order path—unavailable seconds (far end) | |

E.1.1.2 Edge Statistics

The following table lists all the ONS 15305 PM parameters with the corresponding description and a list of cards supported.

Table E-8 **Statistics PM Parameters—DCC/WAN/LAN**

| Parameter | Description | ONS 15305 Cards Supported |
|-------------------|--|--|
| RxUnicPkt | Number of inbound subnetwork/unicast packets. | S1.1-2-LC, S1.1-8-LC, S4.1-2-LC, S4.1-4-LC, S16.1-1-LC, L4.2-2-LC, L16.2-1LC, S1.1-2-LC/E1-21, GE-1-LC(2), GE-2-LC(2), E100-8(2), 2xGE+MAP(2), 8xFE+MAP(2) |
| RxDiscards | Number of inbound discarded packets. | |
| RxErr | Number of erroneous inbound packets. | |
| RxBytes | Number of received bytes. | |
| TxBytes | Number of transmitted bytes. | |
| RxNotUnicPkt | Number of inbound not unicast packets. | |
| IfInUnknownProtos | Number of discarded packets because of unknown protocol. | |
| TxUnicPkt | Number of requested subnetwork/unicast packets. | |
| TxNotUnicPkt | Number of requested not unicast packets. | |
| TxDiscards | Number of discarded packets—free buffer space. | |
| TxErr | Number of erroneous outbound packets. | |
| RxMultPkt | Number of inbound multicast packets. | |
| RxBroadPkt | Number of inbound broadcast packets. | |
| TxMultPkt | Number of outbound multicast packets. | |
| TxBroadPkt | Number of outbound broadcast packets. | |

E.1.2 Edge Statistics DCC PM Table

The Edge Statistics DCC PM table shows 15-minute and 1-day data communications channel (DCC) edge statistics performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge Statistics DCC PM table.

Table E-9 **Field Descriptions for the Edge Statistics DCC PM Table**

| Field | Description |
|-------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |

Table E-9 *Field Descriptions for the Edge Statistics DCC PM Table (continued)*

| Field | Description |
|---------------------------|--|
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| Rx Unic Pkt | Number of inbound subnetwork/unicast packets. |
| Rx Discards | Number of inbound discarded packets. |
| Rx Err | Number of inbound errored packets. |
| Rx Bytes | Number of received bytes. |
| Tx Bytes | Number of bytes transmitted since the last counter reset. |
| Rx Not Unic Pkt | Number of inbound not unicast packets. |
| Rx Unknown | Number of discarded packets due to unknown protocol. |
| Tx Unic Pkt | Number of requested subnetwork/unicast packets. |
| Tx Not Unic Pkt | Number of requested not unicast packets. |
| Tx Discards | Number of discarded packets with free buffer space. |
| Tx Err | Number of outbound errored packets. |
| Rx Mult Pkt | Number of inbound multicast packets. |
| Rx Broad Pkt | Number of inbound broadcast packets. |
| Tx Mult Pkt | Number of multicast frames transmitted error free. |
| Tx Broad Pkt | Total number of packets that higher-level protocols requested be transmitted, and which were addressed to a broadcast address at this sublayer, including those that were discarded or not sent. |
| NE ID | Name of the selected NE. |

E.1.3 Edge Statistics LAN PM Table

The Edge Statistics LAN PM table shows 15-minute and 1-day LAN edge statistics performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge Statistics LAN PM table.

Table E-10 *Field Descriptions for the Edge Statistics LAN PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |

Table E-10 *Field Descriptions for the Edge Statistics LAN PM Table (continued)*

| Field | Description |
|-----------------|--|
| Rx Unic Pkt | Number of inbound subnetwork/unicast packets. |
| Rx Discards | Number of inbound discarded packets. |
| Rx Err | Number of inbound errored packets. |
| Rx Bytes | Number of received bytes. |
| Tx Bytes | Number of bytes transmitted since the last counter reset. |
| Rx Not Unic Pkt | Number of inbound not unicast packets. |
| Rx Unknown | Number of discarded packets due to unknown protocol. |
| Tx Unic Pkt | Number of requested subnetwork/unicast packets. |
| Tx Not Unic Pkt | Number of requested not unicast packets. |
| Tx Discards | Number of discarded packets with free buffer space. |
| Tx Err | Number of outbound errored packets. |
| Rx Mult Pkt | Number of inbound multicast packets. |
| Rx Broad Pkt | Number of inbound broadcast packets. |
| Tx Mult Pkt | Number of multicast frames transmitted error free. |
| Tx Broad Pkt | Total number of packets that higher-level protocols requested be transmitted, and which were addressed to a broadcast address at this sublayer, including those that were discarded or not sent. |
| NE ID | Name of the selected NE. |

E.1.4 Edge Statistics WAN PM Table

The Edge Statistics WAN PM table shows 15-minute and 1-day WAN edge statistics performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge Statistics WAN PM table.

Table E-11 *Field Descriptions for the Edge Statistics WAN PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| Rx Unic Pkt | Number of inbound subnetwork/unicast packets. |
| Rx Discards | Number of inbound discarded packets. |
| Rx Err | Number of inbound errored packets. |

Table E-11 *Field Descriptions for the Edge Statistics WAN PM Table (continued)*

| Field | Description |
|-----------------|--|
| Rx Bytes | Number of received bytes. |
| Tx Bytes | Number of bytes transmitted since the last counter reset. |
| Rx Not Unic Pkt | Number of inbound not unicast packets. |
| Rx Unknown | Number of discarded packets due to unknown protocol. |
| Tx Unic Pkt | Number of requested subnetwork/unicast packets. |
| Tx Not Unic Pkt | Number of requested not unicast packets. |
| Tx Discards | Number of discarded packets with free buffer space. |
| Tx Err | Number of outbound errored packets. |
| Rx Mult Pkt | Number of inbound multicast packets. |
| Rx Broad Pkt | Number of inbound broadcast packets. |
| Tx Mult Pkt | Number of multicast frames transmitted error free. |
| Tx Broad Pkt | Total number of packets that higher-level protocols requested be transmitted, and which were addressed to a broadcast address at this sublayer, including those that were discarded or not sent. |
| NE ID | Name of the selected NE. |

E.1.5 Edge SDH High Order VC PM Table

The Edge SDH High Order VC PM table shows near- and far-end 15-minute and 1-day SDH high-order Virtual Container (VC) performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge SDH High Order VC PM table.

Table E-12 *Field Descriptions for the Edge SDH High Order VC PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| HP BBE | High path section background block errors. |
| HP ES | High path section errored seconds. |
| HP SES | High path section severely errored seconds. |
| HP UAS | High path section unavailable seconds. |
| NE ID | Name of the selected NE. |

E.1.6 Edge SDH Low Order VC PM Table

The Edge SDH Low Order VC PM table shows near- and far-end 15-minute and 1-day SDH low-order VC performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge SDH Low Order VC PM table.

Table E-13 *Field Descriptions for the Edge SDH Low Order VC PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| LP BBE | Low path background block errors. |
| LP ES | Low path errored seconds. |
| LP SES | Low path severely errored seconds. |
| LP UAS | Low path unavailable seconds. |
| NE ID | Name of the selected NE. |

E.1.7 Edge SDH Multiplex Section PM Table

The Edge SDH Multiplex Section PM table shows near- and far-end 15-minute and 1-day SDH multiplex section performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge SDH Multiplex Section PM table.

Table E-14 *Field Descriptions for the Edge SDH Multiplex Section PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| MS BBE | Multiplex section background block errors. |

Table E-14 *Field Descriptions for the Edge SDH Multiplex Section PM Table (continued)*

| Field | Description |
|--------|---|
| MS ES | Multiplex section errored seconds. |
| MS SES | Multiplex section severely errored seconds. |
| MS UAS | Multiplex section unavailable seconds. |
| NE ID | Name of the selected NE. |

E.1.8 Edge SDH Regenerator Section PM Table

The Edge SDH Regenerator Section PM table shows 15-minute and 1-day SDH regenerator section performance data for the ONS 15305. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Edge SDH Regenerator Section PM table.

Table E-15 *Field Descriptions for the Edge SDH Regenerator Section PM Table*

| Field | Description |
|---------------------------|--|
| Alias ID | Alias name of the selected NE. |
| Module Name | Module for which PM data is displayed. |
| Physical Location | Slot and port number for which PM data is displayed. |
| Interface | Interface name of the selected NE. |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. |
| RS BBE | Regenerator section background block errors. |
| RS ES | Regenerator section errored seconds. |
| RS SES | Regenerator section severely errored seconds. |
| RS UAS | Regenerator section unavailable seconds. |
| NE ID | Name of the selected NE. |

E.2 PM Tables for CTC-Based NEs

This section describes the PM tables that are specific to the CTC-based NEs: ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MS SDH, ONS 15327, ONS 15454 SONET, ONS 15454 SDH, ONS 15600 SONET, and ONS 15600 SDH.



Note

Performance management for the CTC-based ONS 15305 R3.0 is similar to the performance management for the non-CTC-based ONS 15305. See [E.1 ONS 15305-Specific PM Tables, page E-1](#).

For CTC-based NEs, each 15-minute or 1-day PM table has a corresponding real-time PM table that allows you to examine the current value of a PM parameter in granularities finer than 15 minutes or 1 day. Not all of the fields in the historical PM tables are shown in the real-time PM tables. The first fields in real-time PM tables are NE ID, Module Name, Physical Location, Interface, Time Stamp, and Validity; the remaining fields are the actual real-time attributes being polled. The Validity column indicates whether the data in the entry is valid: “true” indicates that the entry is valid; “false” indicates that the entry is invalid.

The following conventions apply to PM tables for CTC-based NEs:

- Invalidity in the historical PM table is shown with the corresponding table cell rendered gray and marked with an asterisk (*).



Note Real-time PM tables do not support invalidity coloring.

- Threshold crossing alerts (TCAs) for a specific statistic in a particular row in the historical PM table are indicated with a purple rendering for the corresponding cell.



Note Real-time PM tables do not support TCAs.

- Fields that are not applicable for a particular module in a given PM table are indicated by displaying *N/A* (not applicable) in the corresponding table cell.
- 1-day PM data is collected at 00:00 hours Greenwich Mean Time (GMT) (time on the Prime Optical server host).
- For release 4.0 and later NEs, PM data collected for cards that are preprovisioned and not physically present on a slot are indicated by the symbol *ENEQ* displayed for the corresponding table cell.



Note For an RTPM query for remote NEs, select the slot number and port number required for a PM query (do not select slot *All* and port *All*).



Note The PM parameters that Prime Optical supports for CTC-based NEs are also supported by Prime Optical GateWay/CORBA.

E.2.1 8B10B PM Table—ONS 15454 SONET, ONS 15454 SDH

The 8B10B PM table shows performance data for ONS 15454 SONET and ONS 15454 SDH DWDM cards that support Fibre Channel (FC) or Gigabit Ethernet payloads. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the 8B10B PM table.

Table E-16 **Field Descriptions for the 8B10B PM Table**

| Field | Description | Cards Supported |
|---------------------------------|---|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Data Payload | The payload provisioned on the client port of the card. | <ul style="list-style-type: none"> • ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME • ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Valid Packets | Number of received packets that contain nonerrored data code groups that have start and end delimiters. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> • ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME • ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Invalid Packets | Number of received packets that contain errored data code groups that have start and end delimiters. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> • ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME • ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Code Group Violations | Number of received code groups that do not contain a start or end delimiter. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> • ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME • ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Idle Ordered Sets | Number of received packets containing idle ordered sets. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> • ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME • ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |

Table E-16 *Field Descriptions for the 8B10B PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------------|---|--|
| Non-idle Ordered Sets | Number of received packets containing nonidle ordered sets. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Data Code Groups | Number of received data code groups that do not contain ordered sets. This parameter applies to the FC and Gigabit Ethernet payload configured on the TXPP_MR_2.5G and TXP_MR_2.5G cards. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Stats Encoding DispErrors | Number of encoding disparity errors received at the port. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Data Ordered Sets | Number of received packets containing data ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| rxTotalPackets | Total number of packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| ifInErrors | Total number of errors received. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Invalid Ordered Sets | Number of invalid ordered sets received at this port. | <ul style="list-style-type: none"> ONS 15454 SONET: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME ONS 15454 SDH: TXP_MR_2.5G, TXPP_MR_2.5G, MXP_MR_10DME |
| Invalid Ordered Sets Disp Errors Sum | Sum of invalid ordered sets of encoding disparity errors received at this port. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME ONS 15454 SDH: MXP_MR_10DME |
| rx8b10bWords | Number of code violations/running disparity errors in the 8b/10b encoded characters received. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| tx8b10bWords | Number of code violations/running disparity errors in the 8b/10b encoded characters transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| NE ID | Name of the selected NE. | — |

E.2.2 ESCON PM Table—ONS 15454 SONET, ONS 15454 SDH

The ESCON PM table shows performance data for ONS 15454 SONET and ONS 15454 SDH DWDM cards that support ESCON payload. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the ESCON PM table.

Table E-17 Field Descriptions for the ESCON PM Table

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Stats Last Cleared Time | When the statistics were last reset. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| ifInOctets | Number of bytes received since the last counter reset. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| rxTotalPkts | Number of packets received since the last counter reset. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| ifInErrors | Total number of received errors. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |

Table E-17 *Field Descriptions for the ESCON PM Table (continued)*

| Field | Description | Cards Supported |
|-----------------------------------|---|--|
| txTotalPkts | Number of packets transmitted since the last counter reset. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| mediaIndStatsRxFrameBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| mediaIndStatsRxLineCodeViolations | Number of L1 line code violations received for constant bit rate protocols that equate to invalid 8b10b ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| mediaIndStatsTxLineCodeViolations | Number of L1 line code violations transmitted for constant bit rate protocols that equate to invalid 8b10b ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| Rx Utilization (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| Tx Utilization (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | ONS 15454 SONET and ONS 15454 SDH: 2.5G_DM, 2.5G_DMP |
| NE ID | Name of the selected NE. | — |

E.2.3 CoS PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The CoS PM table shows Class of Service (CoS) performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH ML-series cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the CoS PM table.

Table E-18 *Field Descriptions for the CoS PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Interface Name | Name of the interface. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| Interface Direction | Input or output direction of the interface. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| Class of Service Level | CoS level. The level ranges from 0 to 7. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |

Table E-18 *Field Descriptions for the CoS PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------|--|---|
| Post Policy Packets | Packet count after executing QoS policies. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| Post Policy Bytes | Octet count after executing QoS policies. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| Drop Packets | Dropped packet count as the result of all QoS features that can produce drops. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| Drop Bytes | Dropped octet count as the result of all QoS features that can produce drops. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000 • ONS 15454 SDH: ML100T, ML1000 |
| NE ID | Name of the selected NE. | — |

E.2.4 DS1 PM Table (Far End)

The DS1 PM table shows far-end DS-1 performance data. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the DS1 PM table.

Table E-19 **Field Descriptions for the DS1 PM Table (Far End)**

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-P (Rx) | Coding violations—path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| ES-P (Rx) | Errored seconds—path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |

Table E-19 Field Descriptions for the DS1 PM Table (Far End) (continued)

| Field | Description | Cards Supported |
|-------------|--------------------------------------|---|
| ESA-P (Rx) | Errored seconds type A-path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| ESB-P (Rx) | Errored seconds type B-path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| SES-P (Rx) | Severely errored seconds-path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| SEFS-P (Rx) | Severely errored frame seconds-path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| CSS-P (Rx) | Controlled slip seconds-path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |

Table E-19 *Field Descriptions for the DS1 PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|------------|---|---|
| UAS-P (Rx) | Unavailable seconds–path. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| FC-P (Rx) | Failure count–path. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56 |
| ES-L (Rx) | Errored seconds–line. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| ESR-P | Received path errored seconds ratio is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | — |
| SESR-P | Received path severely errored seconds ratio is the ratio of SES to total seconds in available time during a fixed measurement interval. | — |
| ESNE-NP | Network performance errored seconds during a fixed measurement interval for near end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |
| SESNE-NP | Network performance severely errored seconds during a fixed measurement interval for near end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |
| UASNE-NP | Network performance unavailable seconds during a fixed measurement interval for near end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |

Table E-19 *Field Descriptions for the DS1 PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|----------|---|--|
| ESFE-NP | Network performance errored seconds during a fixed measurement interval for far end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |
| SESFE-NP | Network performance severely errored seconds during a fixed measurement interval for far end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |
| UASFE-NP | Network performance unavailable seconds during a fixed measurement interval for far end. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS1_E1_56, DS3XM_12 |
| NE ID | Name of the selected NE. | — |

E.2.5 DS1 PM Table

The DS1 PM table contains PM information at the line layer. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the DS1 PM table.

Table E-20 *Field Descriptions for the DS1 PM Table*

| Field | Description | Cards Supported |
|-------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |

Table E-20 *Field Descriptions for the DS1 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|--|---|
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-L | CV-L indicates the number of coding violations occurring on the line. This parameter is a count of BPVs and EXZs occurring over the accumulation period. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| ES-L | ES-L is a count of the seconds containing one or more anomalies (BPV + EXZ) and/or defects (loss of signal) on the line. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| SES-L | SES-L is a count of the seconds containing more than a particular quantity of anomalies (BPV + EXZ > 1544) and/or defects on the line. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| LOSS-L | LOSS-L is a count of one-second intervals containing one or more LOS defects. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| CV-P (Rx) | Received path coding violation (Rx CV-P) means that a coding violation occurred on the received end of the path. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |

Table E-20 *Field Descriptions for the DS1 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|---|--|
| ES-P (Rx) | Received path errored seconds (Rx ES-P) is a count of the seconds containing one or more anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| SES-P (Rx) | Received path severely errored seconds (Rx SES-P) is a count of the seconds containing more than a particular quantity of anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| SAS-P (Rx) | Received path severely errored seconds frame/alarm indication signal (Rx SAS-P) is a count of one-second intervals containing one or more SEFs or one or more AIS defects on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| UAS-P (Rx) | Received path unavailable seconds (Rx UAS-P) is a count of one-second intervals when the DS-1 path is unavailable on the received end of the signal. The DS-1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. Once unavailable, the DS-1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from unavailable time. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| AISS-P (Rx) | Received path alarm indication signal seconds (Rx AISS-P) means an alarm indication signal occurred on the received end of the path. This parameter is a count of seconds containing one or more AIS defects. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |

Table E-20 *Field Descriptions for the DS1 PM Table (continued)*

| Field | Description | Cards Supported |
|------------|---|---|
| FC-P (Rx) | Failure count–near-end path. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| CV-P (Tx) | Transmitted path coding violation (Tx CV-P) means that a coding violation occurred on the transmitted end of the path. For DS-1 ESF paths, this parameter is a count of detected CRC-6 errors. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| ES-P (Tx) | Transmitted path errored seconds (Tx ES-P) is a count of the seconds containing one or more anomalies and/or defects for paths on the transmitted end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| SES-P (Tx) | Transmitted path severely errored seconds (Tx SES-P) is a count of the seconds containing more than a particular quantity of anomalies and/or defects for paths on the transmitted end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| SAS-P (Tx) | Transmitted path severely errored seconds frame/alarm indication signal (Tx SAS-P) is a count of one-second intervals containing one or more severely errored framing seconds (SEFS) or one or more AIS defects on the transmitted end of the signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| UAS-P (Tx) | Transmitted path unavailable seconds (Tx UAS-P) is a count of one-second intervals when the DS-1 path is unavailable on the transmitted end of the signal. The DS-1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. Once unavailable, the DS-1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from unavailable time. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |

Table E-20 *Field Descriptions for the DS1 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|--|---|
| AISS-P (Tx) | Transmitted path alarm indication signal seconds (Tx AISS-P) means that an alarm indication signal occurred on the transmitted end of the path. This parameter is a count of seconds containing one or more AIS defects. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56 |
| FC-P (Tx) | Failure count—near-end path. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM_12 |
| NE ID | Name of the selected NE. | — |

E.2.6 DS3 PM Table

The DS3 PM table contains PM information at the DS-3 layer. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the DS3 PM table.

Table E-21 *Field Descriptions for the DS3 PM Table*

| Field | Description | Cards Supported |
|-------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |

Table E-21 *Field Descriptions for the DS3 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|--|---|
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-L | Number of coding violations (CVs) occurring on the line. This parameter is a count of BPVs and EXZs occurring over the accumulation period. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15327: XTC ONS 15454 SONET: DS-3, DS3E, DS3_EC1_48, DS3I, DS3N, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| ES-L | Number of seconds containing one or more anomalies (BPVs + EXZs) and/or defects (loss of signal [LOS]) on the line. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15327: XTC ONS 15454 SONET: DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| SES-L | Number of seconds containing more than a particular quantity of anomalies (BPV + EXZ > 1544) and/or defects on the line. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15327: XTC ONS 15454 SONET: DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |

Table E-21 *Field Descriptions for the DS3 PM Table (continued)*

| Field | Description | Cards Supported |
|------------|--|---|
| LOSS-L | Number of one-second intervals containing one or more LOS defects. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15327: XTC ONS 15454 SONET: DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| AISSP-PBIT | Number of alarm indication signal seconds (AISS) encountered by a DS-3 interface in the parity bit (PBIT) of the interface in the interval. The PBIT is the bit position at the beginning of the third and fourth subframes, which contains parity information. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| CVP-PBIT | Number of coding violations encountered by a DS-3 interface in the PBIT of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| ESP-PBIT | Number of errored seconds encountered by a DS-3 interface in the PBIT of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |

Table E-21 *Field Descriptions for the DS3 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|---|---|
| SESP-PBIT | Number of severely errored seconds (SES) encountered by a DS-3 interface in the PBIT of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| SASP-PBIT | Number of severely alarmed seconds (SAS) encountered by a DS-3 interface in the PBIT of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| UASP-PBIT | Number of unavailable seconds (UAS) encountered by a DS-3 interface in the PBIT of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| CVP (C-bit) | Number of coding violations encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |

Table E-21 *Field Descriptions for the DS3 PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|--|---|
| ESP (C-bit) | Number of errored seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| SESP (C-bit) | Number of SESs encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| SASP (C-bit) | Number of severely alarmed seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3_EC1_48 |
| UASP (C-bit) | Number of unavailable seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| NE ID | Name of the selected NE. | — |

E.2.7 DS3 and DS3I PM Table (Far End)—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The DS3 and DS3I PM table shows far-end performance data for the DS-3 and DS3I cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the DS3 and DS3I PM table.

Table E-22 *Field Descriptions for the DS3 and DS3I PM Table (Far End)*

| Field | Description | Cards Supported |
|----------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Coding Violations – Path (C-Bit) | Number of coding violations encountered by a DS-3 interface in the C-bit of the interface in the interval. The C-bit is a bit format used to increase far-end performance monitoring. This is a path variable. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 • ONS 15454 SDH: DS3I, DS3IN |

Table E-22 *Field Descriptions for the DS3 and DS3I PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|---|--|---|
| Errored Seconds – Path (C-Bit) | Number of errored seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| Severely Alarmed Seconds – Path (C-Bit) | Number of severely alarmed seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| Severely Errored Seconds – Path (C-Bit) | Number of severely errored seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| Unavailable Seconds – Path (C-Bit) | Number of unavailable seconds encountered by a DS-3 interface in the C-bit of the interface in the interval. This is a path variable. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS3E, DS3_EC1_48, DS3I, DS3IN, DS3NE, DS3XM, DS3XM_12 ONS 15454 SDH: DS3I, DS3IN |
| NE ID | Name of the selected NE. | — |

E.2.8 E1 PM Table—ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The E1 PM table shows performance data for the following cards:

- ONS 15310 MA SDH: E1_21_E3_DS3_3 and E1_63_E3_DS3_3
- ONS 15454 SONET: DS1_E1_56
- ONS 15454 SDH: E1

You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the E1 PM table.

Table E-23 **Field Descriptions for the E1 PM Table**

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-L | CV-L indicates the number of coding violations occurring on the line. This parameter is a count of BPVs and EXZs occurring over the accumulation period. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SONET: DS1_E1_56 • ONS 15454 SDH: E1N, E1, E1_42 |

Table E-23 *Field Descriptions for the E1 PM Table (continued)*

| Field | Description | Cards Supported |
|------------|--|---|
| ES-L | ES-L is a count of the seconds containing one or more anomalies (BPV + EXZ) and/or defects (loss of signal) on the line. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| SES-L | SES-L is a count of the seconds containing more than a particular quantity of anomalies (BPV + EXZ > 1544) and/or defects on the line. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| LOSS-L | LOSS-L is a count of one-second intervals containing one or more LOS defects. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| EB-P (Rx) | Received path errored block (EB-P) is a count of the number of bits in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| ES-P (Rx) | Received path errored seconds (ES-P) is a count of the seconds containing one or more anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| SES-P (Rx) | Received path severely errored seconds (SES-P) is a count of the seconds containing more than a particular quantity of anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-23 *Field Descriptions for the E1 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|--|---|
| BBE-P (Rx) | Received path background block errors (BBE-P) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| UAS-P (Rx) | Received path unavailable seconds (UAS-P) is a count of one-second intervals when the DS-1 path is unavailable on the received end of the signal. The DS-1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. Once unavailable, the DS-1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from unavailable time. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| ESR-P (Rx) | Received path errored second ratio (ESR-P) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| SESR-P (Rx) | Received path severely errored seconds ratio (SESR-P) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| BBER-P (Rx) | Received path background block error ratio (BBER-P) is a ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| AISS-P (Rx) | Received path AISS-P is a count of seconds containing one or more AIS defects. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-23 *Field Descriptions for the E1 PM Table (continued)*

| Field | Description | Cards Supported |
|------------|--|---|
| EB-P (Tx) | Transmitted path errored block (EB-P) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| ES-P (Tx) | Transmitted path errored seconds (ES-P) is a count of the seconds containing one or more anomalies and/or defects for paths on the transmitted end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| SES-P (Tx) | Transmitted path severely errored seconds (SES-P) is a count of the seconds containing more than a particular quantity of anomalies and/or defects for paths on the transmitted end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| BBE-P (Tx) | Transmitted path background block error (BBE-P) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| UAS-P (Tx) | Transmitted path unavailable seconds (UAS-P) is a count of one-second intervals when the DS-1 path is unavailable on the transmitted end of the signal. The DS-1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. Once unavailable, the DS-1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from unavailable time. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| ESR-P (Tx) | Transmitted path errored second ratio (ESR-P) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-23 *Field Descriptions for the E1 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|--|---|
| SESR-P (Tx) | Transmitted path severely errored second ratio (SESR-P) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| BBER-P (Tx) | Transmitted path background block error ratio (BBER-P) is a ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| AISS-P (Tx) | Transmitted path AISS-P is a count of seconds containing one or more AIS defects. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| NE ID | Name of the selected NE. | — |

E.2.9 E1 PM Table (Far End)—ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The E1 PM table shows far-end performance data for the following cards:

- ONS 15310 MA SDH: E1_21_E3_DS3_3 and E1_63_E3_DS3_3
- ONS 15454 SONET: DS1_E1_56
- ONS 15454 SDH: E1, E1N, and E1_42 cards.

You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the E1 PM table.

Table E-24 *Field Descriptions for the E1 PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| RXP-EB | Received path errored blocks (RXP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXP-ES | Received path errored seconds (RXP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXPS-ES | Received path severely errored seconds (RXP-SES) is a one-second period containing 30 percent or more errored blocks or at least one defect; SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-24 *Field Descriptions for the E1 PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|----------|--|---|
| RXP-BBE | Received path background block errors (RXP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXP-UAS | Received path unavailable seconds (RXP-UAS) is a count of one-second intervals when the E1 path is unavailable on the signal received end. The E1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. After it has become unavailable, the E1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from the unavailable time. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXP-ESR | Received path errored second ratio (RXP-ESR) is the ratio of SESs to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXP-SESR | Received path severely errored second ratio (RXP-SESR) is the ratio of SESs to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| RXP-BBER | Received path background block error ratio (RXP-BBER) is a ratio of BBEs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-EB | Transmitted path errored blocks (TXP-EB) is a count of bits that are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-24 *Field Descriptions for the E1 PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|----------|--|---|
| TXP-ES | Transmitted path errored seconds (TXP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-SES | Transmitted path severely errored seconds (TXP-SES) is a one-second period containing 30 percent or more errored blocks or at least one defect; SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-BBE | Transmitted path background block errors (TXP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-UAS | Transmitted path unavailable seconds (TXP-UAS) is a count of one-second intervals when the E1 path is unavailable on the signal transmitted. The E1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. After it has become unavailable, the E1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from the unavailable time. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-ESR | Transmitted path errored second ratio (TXP-ESR) is the ratio of SESs to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| TXP-SESR | Transmitted path severely errored second ratio (TXP-SESR) is the ratio of SESs to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |

Table E-24 *Field Descriptions for the E1 PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|----------|--|---|
| TXP-BBER | Transmitted path background block error ratio (TXP-BBER) is a ratio of BBERs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SONET: DS1_E1_56 ONS 15454 SDH: E1N, E1, E1_42 |
| NE ID | Name of the selected NE. | — |

E.2.10 E3 PM Table—ONS 15310 MA SDH, ONS 15454 SDH

The E3 PM table shows performance data for the ONS 15310 MA SDH E1_21_E3_DS3_3 and E1_63_E3_DS3_3 cards and the ONS 15454 SDH E3 card. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the E3 PM table.

Table E-25 *Field Descriptions for the E3 PM Table*

| Field | Description | Cards Supported |
|---------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-25 *Field Descriptions for the E3 PM Table (continued)*

| Field | Description | Cards Supported |
|--------|---|---|
| CV-L | CV-L indicates the number of coding violations occurring on the line. This parameter is a count of BPVs and EXZs occurring over the accumulation period. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| ES-L | ES-L is a count of the seconds containing one or more anomalies (BPV + EXZ) and/or defects (loss of signal) on the line. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| SES-L | SES-L is a count of the seconds containing more than a particular quantity of anomalies (BPV + EXZ > 1544) and/or defects on the line. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| LOSS-L | LOSS-L is a count of one-second intervals containing one or more LOS defects. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| P-ES | Received path errored seconds (Rx ES-P) is a count of the seconds containing one or more anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| P-SES | Received path severely errored seconds (Rx SES-P) is a count of the seconds containing more than a particular quantity of anomalies and/or defects for paths on the received end of the signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| P-UAS | Received path unavailable seconds (Rx UAS-P) is a count of one-second intervals when the DS-1 path is unavailable on the received end of the signal. The DS-1 path is unavailable when ten consecutive SESs occur. The ten SESs are included in unavailable time. Once unavailable, the DS-1 path becomes available when ten consecutive seconds occur with no SESs. The ten seconds with no SESs are excluded from unavailable time. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| P-ESR | Received path errored second ratio (RX P-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| P-SESR | Received path severely errored second ratio (RX P-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E3 |
| NE ID | Name of the selected NE. | — |

E.2.11 CE-Series Ethernet PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The CE-Series Ethernet PM table shows performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH CE-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the CE-Series Ethernet PM table.



Note

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | <ul style="list-style-type: none"> • ONS 15454 SONET: CE-MR-10 • ONS 15454 SDH: CE-MR-10 |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------|--|---|
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifInUCastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifInMulticastPkts | Number of multicast packets received. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifInBroadcastPkts | Number of broadcast packets received. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|----------------|---|---|
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifOutUCastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------|--|---|
| ifOutMulticastPkts | Number of multicast packets transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifOutBroadcastPkts | Number of broadcast packets transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| dot3StatsFCSErrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6 ONS 15310 MA SDH: CE-100T-8, CE-MR-6 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 Field Descriptions for the CE-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|---|---|
| dot3StatsSingleCollisionFrames | Number of successfully transmitted frames that had exactly one collision. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------------|---|---|
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 Field Descriptions for the CE-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|--|---|
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsBroadcastPkts | Total number of good broadcast packets received. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsMulticastPkts | Total number of good multicast (nonbroadcast) packets received. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------|---|---|
| etherStatsOversizePkts | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsJabbers | Total number of frames received that exceed the maximum 1548 bytes and contain CRC errors. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsCollisions | Best estimate of the total number of collisions on the Ethernet segment. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsCollisionFrames | Best estimate of the total number of collision frames on the Ethernet segment. | <ul style="list-style-type: none"> • ONS 15454 SONET: CE-MR-10 • ONS 15454 SDH: CE-MR-10 |

Table E-26 Field Descriptions for the CE-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------|---|---|
| etherStatsCRCAlignErrors | Total number of packets received that had a length (excluding framing bits, but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| etherStatsDropEvents | Total number of events in which packets were dropped by the probe due to lack of resources. The value indicates the number of times this condition has been detected. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 |
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15310 MA SONET: CE-100T-8, CE-MR-6 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6 • ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10 • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10 |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> • ONS 15310 CL: CE-100T-8 • ONS 15454 SONET: CE-1000-4, CE-100T-8 |
| ifOutErrors | Total number of transmitted errors. | — |
| txPauseFrames | Number of transmitted pause frames. | — |
| rxPauseFrames | Number of received pause frames. | — |

Table E-26 *Field Descriptions for the CE-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------------|--|-----------------|
| rxPktsDroppedInternalCongestion | Number of received packets dropped due to overflow in G1000-4 frame buffer. | — |
| txPktsDroppedInternalCongestion | Number of transmitted queue drops due to drops in the G1000-4 frame buffer. | — |
| rxControlFrames | Number of MAC control frames passed by the MAC sublayer to the MAC control sublayer. | — |
| mediaIndStatsRxFramesTruncated | Total number of frames received that are less than 5 bytes. This value is a part of HDLC and GFP port statistics. | — |
| mediaIndStatsRxFramesTooLong | Number of received frames that exceed the maximum transmission unit (MTU). This value is part of HDLC and generic framing procedure (GFP) port statistics. | — |
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | — |
| mediaIndStatsTxFramesBadCRC | Number of transmitted data frames with payload CRC errors when HDLC framing is used. | — |
| mediaIndStatsRxShortPkts | Number of packets below the minimum packet size received. | — |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | — |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | — |
| NE ID | Name of the selected NE. | — |

E.2.12 E-Series Ethernet PM Table—ONS 15327, ONS 15454 SONET, ONS 15454 SDH

The E-Series Ethernet PM table shows performance data for the ONS 15327, ONS 15454 SONET, and ONS 15454 SDH E-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the E-Series Ethernet PM table.

**Note**

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-27 **Field Descriptions for the E-Series Ethernet PM Table**

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SONET: ETH100, ETH1000 • ONS 15454 SDH: ETH100, ETH1000 |
| ifInUCastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SDH: ETH100, ETH1000 |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SONET: ETH100, ETH1000 • ONS 15454 SDH: ETH100, ETH1000 |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SONET: ETH100, ETH1000 • ONS 15454 SDH: ETH100, ETH1000 |
| ifOutUCastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SDH: ETH100, ETH1000 |
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | <ul style="list-style-type: none"> • ONS 15327: ETH100 • ONS 15454 SDH: ETH100, ETH1000 |

Table E-27 *Field Descriptions for the E-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|----------------------------------|---|---|
| dot3StatsFCSErrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| dot3StatsSingleCollisionFrames | Number of successfully transmitted frames that had exactly one collision. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SDH: ETH100, ETH1000 |
| dot3StatsMultipleCollisionFrames | Number of successfully transmitted frames that had multiple collisions. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100 ONS 15454 SDH: ETH100 |
| dot3StatsDeferredTransmissions | Number of packets deferred. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100 ONS 15454 SDH: ETH100 |
| dot3StatsLateCollisions | Number of times that a collision was detected later than 64 octets into the transmission (also added into the collision count). | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100 ONS 15454 SDH: ETH100 |
| dot3StatsExcessiveCollisions | Number of consecutive collisions. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100 ONS 15454 SDH: ETH100 |
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |

Table E-27 Field Descriptions for the E-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|---|---|
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsOversizePackets | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsJabbers | Total number of frames received that exceed the maximum 1548 bytes and contain CRC errors. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsCollisions | Best estimate of the total number of collisions on the Ethernet segment. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SDH: ETH100 |
| etherStatsCollisionFrames | Best estimate of the total number of frame collisions on the segment. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherStatsCRCAlignErrors | Total number of packets received that had a length (excluding framing bits, but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100 |
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| txTotalPkts | Number of packets transmitted since the last counter reset. Note This column is no longer supported for R 4.y and later NEs. For those NEs, this column displays <i>N/A</i> . | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |

Table E-27 Field Descriptions for the E-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|-----------------------------|---|---|
| txCollision | Number of transmitted collisions since the last counter reset. Note This column is no longer supported for NE R4.7 and later. For NE R4.7 and later this column displays <i>N/A</i> . | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15327: ETH100 ONS 15454 SONET: ETH100, ETH1000 ONS 15454 SDH: ETH100, ETH1000 |
| etherUtilizationStats (%) | Average Ethernet utilization statistics (release 3.4 and earlier). | <ul style="list-style-type: none"> ONS 15454 SONET R3.3 and R3.4: ETH100, ETH1000 |
| NE ID | Name of the selected NE. | — |

E.2.13 G-Series Ethernet PM Table—ONS 15327, ONS 15454 SONET, ONS 15454 SDH

The G-Series Ethernet PM table shows performance data for the ONS 15327, ONS 15454 SONET, and ONS 15454 SDH G-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the G-Series Ethernet PM table.



Note

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-28 **Field Descriptions for the G-Series Ethernet PM Table**

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | — |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifInUcastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifInMulticastPkts | Number of multicast packets received. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifInBroadcastPkts | Number of broadcast packets received. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |

Table E-28 *Field Descriptions for the G-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------|---|--|
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4 |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifOutUcastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifOutMulticastPkts | Number of multicast packets transmitted. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifOutBroadcastPkts | Number of broadcast packets transmitted. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4 • ONS 15454 SDH: G1000_4 |
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| dot3StatsFCSerrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | <ul style="list-style-type: none"> • ONS 15327: G1000_2 • ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP • ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |

Table E-28 Field Descriptions for the G-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|------------------------------|--|---|
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| dot3StatsCarrierSenseErrors | Number of transmission errors on a particular interface that are not otherwise counted. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| dot3StatsSQETestErrors | Number of times that the SQE test error message is generated by the PLS sublayer for a particular interface. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, ONS 15454 SDH: GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |

Table E-28 *Field Descriptions for the G-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------|---|--|
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsOversizePkts | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsJabbers | Total number of frames received that exceed the maximum 1548 bytes and contain CRC errors. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| etherStatsCRCAlignErrors | Total number of packets received that had a length (excluding framing bits, but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: G1000_4, GE_XP, 10GE_XP |
| rxPauseFrames | Number of received pause frames. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |

Table E-28 Field Descriptions for the G-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------------|---|---|
| txPauseFrames | Number of transmitted pause frames. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| rxPktsDroppedInternalCongestion | Number of received packets dropped due to overflow in G1000-4 frame buffer. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| txPktsDroppedInternalCongestion | Number of transmitted queue drops due to drops in the G1000-4 frame buffer. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: GE_XP, 10GE_XP |
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4, GE_XP, 10GE_XP ONS 15454 SDH: GE_XP, 10GE_XP |
| rxGiants | Number of packets received that are greater than 1530 bytes in length. | — |
| hdlcPktDrops | Total number of packets that are dropped when the card is in HDLC mode and traffic is oversubscribed. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| etherStatsBroadCastPkts | Total number of good broadcast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: GE_XP, 10GE_XP ONS 15454 SDH: GE_XP, 10GE_XP |
| etherStatsMultiCastPkts | Total number of good multicast (nonbroadcast) packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: GE_XP, 10GE_XP ONS 15454 SDH: GE_XP, 10GE_XP |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15327: G1000_2 ONS 15454 SONET: G1000_4 ONS 15454 SDH: G1000_4 |

Table E-28 *Field Descriptions for the G-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------|--|---|
| etherUtilizationStats (%) | Average Ethernet utilization statistics (release 3.4 and earlier). | <ul style="list-style-type: none"> ONS 15454 SONET R3.3 and R3.4: G-series cards |
| NE ID | Name of the selected NE. | — |

E.2.14 ML-Series Ethernet PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The ML-Series Ethernet PM table shows performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH ML-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the ML-Series Ethernet PM table.

**Note**

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------|--|---|
| Time Last Cleared | When the statistics were last reset. | <ul style="list-style-type: none"> ONS 15454 SONET: ML-MR-10 ONS 15454 SDH: ML-MR-10 |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifInUCastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------|---|---|
| ifInMulticastPkts | Number of multicast packets received. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifInBroadcastPkts | Number of broadcast packets received. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15310 MA SONET: ML-100T-8 • ONS 15310 MA SDH: ML-100T-8 • ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| Port Drop Counts | Number of received frames dropped at the port level. | <ul style="list-style-type: none"> • ONS 15310 CL: ML-100T-8 • ONS 15454 SONET: ML1000 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|----------------------|---|---|
| Rx Runts | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| Rx Giants | Number of packets received that are greater than 1530 bytes in length. | <ul style="list-style-type: none"> ONS 15454 SONET: ML1000 |
| Tx Giants | Number of packets transmitted that are greater than 1548 bytes in length. | <ul style="list-style-type: none"> ONS 15454 SONET: ML1000 |
| Tx Collisions | Number of collisions transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: ML1000 |
| Rx Total Errors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| RxGMACDropCounts | Number of received frames dropped by MAC module. | <ul style="list-style-type: none"> ONS 15454 SONET: ML1000 |
| RxThresholdOversizes | Number of received packets with a length longer than 1518 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: ML1000 |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------|---|---|
| ifOutUCastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifOutMulticastPkts | Number of multicast packets transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifOutBroadcastPkts | Number of broadcast packets transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |

Table E-29 **Field Descriptions for the ML-Series Ethernet PM Table (continued)**

| Field | Description | Cards Supported |
|--------------------------------|--|---|
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| dot3StatsFCSErrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| dot3StatsSingleCollisionFrames | Number of successfully transmitted frames that had exactly one collision. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------------|---|---|
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 Field Descriptions for the ML-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|--|---|
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000 |
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsBroadcastPkts | Total number of good broadcast packets received. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------------|---|---|
| etherStatsMulticastPkts | Total number of good multicast (nonbroadcast) packets received. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsOversizePkts | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsJabbers | Total number of octets of data (including bad packets) received on the network. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------|---|---|
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsCollisions | Best estimate of the total number of collisions on the Ethernet segment. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsCollisionFrames | Best estimate of the total number of frame collisions on the segment. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| etherStatsCRCAlignErrors | Total number of packets received that had a length (excluding framing bits, but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |

Table E-29 *Field Descriptions for the ML-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------------|---|---|
| etherStatsDropEvents | Total number of events in which packets were dropped by the probe due to lack of resources. The value indicates the number of times this condition has been detected. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML-MR-10 ONS 15454 SDH: ML-MR-10 |
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH: ML100T, ML1000, ML-MR-10 |
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| mediaIndStatsRxFramesTooLong | Number of received frames that exceed the maximum transmission unit (MTU). This value is part of HDLC and generic framing procedure (GFP) port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |

Table E-29 Field Descriptions for the ML-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|---|---|
| mediaIndStatsOversizeDropped | Number of received packets larger than the ML-series remote monitoring (RMON) threshold. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| txPauseFrames | Number of transmitted pause frames. | <ul style="list-style-type: none"> ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| rxPauseFrames | Number of received pause frames. | <ul style="list-style-type: none"> ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: ML100T, ML1000 ONS 15454 SDH: ML100T, ML1000 |
| dot3adAggPortStatsLACPDUUsRx | Number of valid LAC PDUs received on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| dot3adAggPortStatsMarkerPDUsRx | Number of valid marker PDUs received on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |

Table E-29 Field Descriptions for the ML-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--|--|---|
| dot3adAggPortStatsMarkerResponsePDUsRx | Number of valid marker response PDUs received on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| dot3adAggPortStatsUnknownRx | Number of frames received that either carry the slow protocols Ethernet type value (43B.4), but contain an unknown PDU, or are addressed to the slow protocols group MAC address (43B.3), but do not carry the slow protocols Ethernet type. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| dot3adAggPortStatsIllegalRx | Number of frames received that carry the slow protocols Ethernet type value (43B.4), but contain a badly formed PDU or an illegal value of protocol subtype (43B.4). | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| dot3adAggPortStatsLACPDUUsTx | Number of LAC PDUs transmitted on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |

Table E-29 Field Descriptions for the ML-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--|--|---|
| dot3adAggPortStatsMarkerPDUsTx | Number of marker PDUs transmitted on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| dot3adAggPortStatsMarkerResponsePDUsTx | Number of marker response PDUs transmitted on this aggregation port. | <ul style="list-style-type: none"> ONS 15310 CL: ML-100T-8 ONS 15310 MA SONET: ML-100T-8 ONS 15310 MA SDH: ML-100T-8 ONS 15454 SONET: ML1000, ML100T, ML100X-8 ONS 15454 SDH: ML1000, ML100T, ML100X-8 |
| NE ID | Name of the selected NE. | — |

E.2.15 ASAP-Series Ethernet PM Table—ONS 15600 SONET, ONS 15600 SDH

The ASAP-Series Ethernet PM table shows performance data for the ONS 15600 SONET and ONS 15600 SDH ASAP-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the ASAP-Series Ethernet PM table.

**Note**

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-30 **Field Descriptions for the ASAP-Series Ethernet PM Table**

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ifInOctets | Number of bytes received since the last counter reset. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifInUcastPkts | Number of unicast packets received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifInMulticastPkts | Number of multicast packets received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifInBroadcastPkts | Number of broadcast packets received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsOversizePkts | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsFCSErrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |

Table E-30 *Field Descriptions for the ASAP-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------|---|--|
| etherStatsJabbers | Total number of octets of data (including bad packets) received on the network. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutUcastPkts | Number of unicast packets transmitted. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutMulticastPkts | Number of multicast packets transmitted. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutBroadcastPkts | Number of broadcast packets transmitted. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsDropEvents | Total number of events in which packets were dropped by the probe due to lack of resources. The value indicates the number of times this condition has been detected. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts | Number of packets received with a length from 1024 to 1518 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |

Table E-30 *Field Descriptions for the ASAP-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------|---|--|
| etherStatsBroadcastPkts | Total number of good broadcast packets received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsMulticastPkts | Total number of good multicast (nonbroadcast) packets received. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |

Table E-30 **Field Descriptions for the ASAP-Series Ethernet PM Table (continued)**

| Field | Description | Cards Supported |
|------------------------------|--|--|
| ifInErrors | Total number of received errors. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| ifOutErrors | Total number of transmitted errors. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsInternalMacTxErrors | A count of frames for which transmission on a particular interface fails due to an internal MAC sublayer transmission error. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsInternalMacRxErrors | A count of frames for which reception on a particular interface fails due to an internal MAC sublayer received error. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| dot3StatsSymbolErrors | Number of times there was an invalid data symbol when a valid carrier was present on a particular interface. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| rxPauseFrames | Number of received pause frames. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| txPauseFrames | Number of transmitted pause frames. | ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| Tx Utilization (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | ONS 15600 SONET: ASAP_4 |
| Rx Utilization (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | ONS 15600 SONET: ASAP_4 |
| NE ID | Name of the selected NE. | — |

E.2.16 DWDM-Series Ethernet PM Table—ONS 15454 SONET, ONS 15454 SDH

The DWDM-Series Ethernet PM table shows performance data for the ONS 15454 SONET and ONS 15454 SDH DWDM-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the DWDM-Series Ethernet PM table.



Note

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | — |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> • ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G • ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|-------------------|---|--|
| ifInMulticastPkts | Number of multicast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifInBroadcastPkts | Number of broadcast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------|---|--|
| ifOutMulticastPkts | Number of multicast packets transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10G ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10G |
| ifOutBroadcastPkts | Number of broadcast packets transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10G ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10G |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| dot3StatsFCSErrors | Number of packets with an FCS error. FCS errors indicate frame corruption during transmission. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| dot3StatsFrameTooLong | Number of received frames that were larger than the maximum size permitted. | <ul style="list-style-type: none"> ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP |
| etherStatsUndersizePkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|------------------------------|---|--|
| etherStatsFragments | Total number of frames received that are less than 64 bytes in length and have a CRC error. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsPkts64Octets | Number of packets received with a length less than or equal to 64 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsPkts65to127Octets | Number of packets received with a length from 65 to 127 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsPkts128to255Octets | Number of packets received with a length from 128 to 255 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsPkts256to511Octets | Number of packets received with a length from 256 to 511 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|---|--|
| etherStatsPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsBroadcastPkts | Total number of good broadcast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsMulticastPkts | Total number of good multicast (nonbroadcast) packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsOversizePkts | Total number of packets received that were longer than 1518 octets (excluding framing bits, but including FCS octets) and were otherwise well formed. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------|---|--|
| etherStatsJabbers | Total number of frames received that exceed the maximum 1548 bytes and contain CRC errors. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| etherStatsCRCAlignErrors | Total number of packets received that had a length (excluding framing bits, but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP |
| etherStatsPkts1519toMaxOctets | Total number of packets (including bad packets) received that were 1591 octets in length (excluding framing bits, but including FCS octets). | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| mediaIndStatsTXShortPkts | Number of transmitted frames containing less than the minimum permitted frame size as programmed with the transmit MAC Min Frame Length Configuration Register. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| rxPauseFrames | Number of received pause frames. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------|---|---|
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, 2.5G_DM, 2.5G_DMP, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| mediaIndStatsRxFramesTruncated | Total number of frames received that are less than 5 bytes. This value is a part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| mediaIndStatsRxFramesTooLong | Number of received frames that exceed the MTU. This value is part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| mediaIndStatsTxFramesBadCRC | Number of transmitted data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| rxControlFrames | Number of MAC control frames passed by the MAC sublayer to the MAC control sublayer. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| rxUnknownOpcodeFrames | Number of MAC control frames received that contain an opcode that is not supported by the device. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifInErrorBytePkts | Number of received bytes with errors. | <ul style="list-style-type: none"> ONS 15454 SDH: ADM_10G |

Table E-31 *Field Descriptions for the DWDM-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|----------------------------------|--|--|
| ifInFramingErrorPkts | Number of received framing error counters. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: ADM_10G, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifInJunkInterPkts | Number of received interpacket junk counters. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME, TXP_MR_10G ONS 15454 SDH: ADM_10G, MXP_MR_10DME, TXP_MR_10G |
| etherStatsPkts | Number of packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP |
| Dot3StatsControlInUnknownOpCodes | Number of MAC control frames received on the interface that contain an opcode that is not supported by the device. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G ONS 15454 SDH: 10GE_XP, GE_XP, MXP_MR_10DME, TXP_MR_10E, TXP_MR_10G |
| ifOutUCastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, MXP_MR_10DME, TXP_MR_10E ONS 15454 SDH: ADM_10G, MXP_MR_10DME, TXP_MR_10E |
| Dot3StatsInPauseFrames | Number of received pause frames. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| Dot3StatsOutPauseFrames | Number of transmitted pause frames. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| Dot3StatsLcvErrors | A count of transmitted frames that are an integral number of octets in length and do not pass the FCS check. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |

Table E-31 *Field Descriptions for the DWDM-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------|---|--|
| dot3StatsLayer1Errors | <p>Number of Layer 1 errors as defined within the following conditions:</p> <ul style="list-style-type: none"> During Packet Reception—Layer 1 errors are counted only one time per packet. The error is indicated as a direct result of a line side protocol violation in which RX_DV is asserted. This is an uncommon event that could be the reason why a device loses synchronization. During Interpacket Reception—The Layer 1 error is indicated as a direct result of a line side protocol violation in which RX_DV is deasserted. This is an uncommon event. The Layer 1 error is also asserted on detection of a False Carrier indication and an errored byte (interpacket) signal encoding. When the error is asserted during interpacket reception, it is statistically asserted only in the vector. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| EtherStatsPkts1519to1522Octets | Number of packets received with a length from 1519 to 1522 octets. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP |
| ifInUCastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E |
| ifOutErrors | Total number of transmitted errors. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, ADM_10G, GE_XP ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP |
| dot3StatsAlignmentErrors | Number of received packets with alignment errors (incomplete frames). | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP, MXP_MR_10DME, TXP_MR_10E ONS 15454 SDH: 10GE_XP, ADM_10G, GE_XP, MXP_MR_10DME, TXP_MR_10E |
| ifHCInOctets | Number of bytes received since the last counter reset—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| ifHCInUcastPkts | Number of unicast packets received—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|--|--|--|
| ifHCInMulticastPkts | Number of multicast packets received—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| ifHCInBroadcastPkts | Number of broadcast packets received—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| ifHCOctets | Number of bytes transmitted since the last counter reset—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| ifHCOutMulticastPkts | Number of multicast packets transmitted—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| ifHCOutBroadcastPkts | Number of broadcast packets transmitted—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts | Number of packets received—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityOctets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets)—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts64Octets | Number of packets received with a length less than or equal to 64 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts65to127Octets | Number of packets received with a length from 65 to 127 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts128to255Octets | Number of packets received with a length from 128 to 255 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts256to511Octets | Number of packets received with a length from 256 to 511 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts512to1023Octets | Number of packets received with a length from 512 to 1023 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| etherStatsHighCapacityPkts1024to1518Octets | Number of packets received with a length from 1024 to 1518 octets—high capacity. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|--|--|
| cisRxReports | Total Internet Group Management Protocol (IGMP) membership reports received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisRxLeaves | Total IGMP leave messages received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisTxReports | Total IGMP membership reports transmitted through an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisTxLeaves | Total IGMP leave messages transmitted through an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisTxGeneralQueries | Total IGMP general queries transmitted through an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisTxGroupSpecificQueries | Total IGMP group-specific queries transmitted through an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisRxGeneralQueries | Total IGMP general queries received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisRxGroupSpecificQueries | Total IGMP group-specific queries received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisRxValidPackets | Total valid IGMP packets received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| cisRxInvalidPackets | Total invalid IGMP packets received at an interface. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| crepHflRxDpus | Number of hardware flood layer PDUs received on the port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| crepHflTxPpus | Number of hardware flood layer PDUs transmitted on the port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| crepLslRxDpus | Number of link status layer PDUs received on the port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |

Table E-31 Field Descriptions for the DWDM-Series Ethernet PM Table (continued)

| Field | Description | Cards Supported |
|-----------------------------|---|--|
| crepLsITxPdus | Number of link status layer PDUs transmitted on the port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| dot3adAggPortStatsLACPDUsRx | Number of valid LACPDU received on this Aggregation Port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| dot3adAggPortStatsLACPDUsTx | Number of LACPDU transmitted on this Aggregation Port. | <ul style="list-style-type: none"> ONS 15454 SONET: 10GE_XP, GE_XP ONS 15454 SDH: 10GE_XP, GE_XP |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME, TXP_MR_10E |
| NE ID | Name of the selected NE. | — |

E.2.17 CPT-Series Ethernet PM Table—ONS 15454 SONET, ONS 15454 SDH

The CPT-Series Ethernet PM table shows performance data for the ONS 15454 SONET and ONS 15454 SDH CPT-series Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the CPT-Series Ethernet PM table.

**Note**

Real-time PM data is not available for Ethernet cards on NE releases earlier than release 5.0.

Table E-32 **Field Descriptions for the CPT-Series Ethernet PM Table**

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| rxTotalPackets | Total number of packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifInUCastPkts | Number of unicast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifInMulticastPkts | Number of multicast packets received. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |

Table E-32 *Field Descriptions for the CPT-Series Ethernet PM Table (continued)*

| Field | Description | Cards Supported |
|-----------------------------|---|--|
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifOutUCastPkts | Number of unicast packets transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifOutMulticastPkts | Number of multicast packets transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| ifOutErrors | Total number of transmitted errors. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| rxEtherUtilizationStats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| txEtherUtilizationStats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15454 SONET: PTSA_GE, PTF_10GE_4, PT_10GE_4 ONS 15454 SDH: PTSA_GE, PTF_10GE_4, PT_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.18 GFP PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, ONS 15454 SDH, and ONS 15600 SDH

The GFP PM table provides monitoring capability to allow operators to identify performance degradation in the generic framing procedure (GFP) multiplexing and framing. GFP describes a framing and encapsulation format for transporting L2/L3 data over SONET, SDH, or OTN transport networks.

You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the GFP PM table.

Table E-33 *Field Descriptions for the GFP PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| GfpStatsRxSBitErrors | Number of GFP single-bit errors in the CHEC. | <ul style="list-style-type: none"> • ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 • ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 • ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME • ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME • ONS 15600 SDH: ASAP_4 |

Table E-33 *Field Descriptions for the GFP PM Table (continued)*

| Field | Description | Cards Supported |
|-----------------------|---|--|
| GfpStatsRxMBitErrors | Number of GFP multibit errors in the CHEC. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME ONS 15600 SDH: ASAP_4 |
| GfpStatsRxTypeInvalid | Number of GFP invalid UPI fields in the type field. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME ONS 15600 SDH: ASAP_4 |
| GfpStatsRxCRCErrors | Number of superblock CRC errors in the transparent GFP frame. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME ONS 15600 SDH: ASAP_4 |

Table E-33 *Field Descriptions for the GFP PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------------|---|---|
| GfpStatsRxCIDInvalid | Number of received frames with an invalid channel ID (CID). | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME |
| GfpStatsCSFRaised | Number of GFP client signal fail frames. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, ML-MR-10, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML-MR-10, MXP_MR_10DME |
| GfpStatsRxFrame | Number of received data frames. | ONS 15600 SDH: ASAP_4 |
| GfpStatsTxFrame | Number of transmitted data frames. | ONS 15600 SDH: ASAP_4 |
| GfpStatsRxOctets | Number of received data octets. | ONS 15600 SDH: ASAP_4 |
| GfpStatsTxOctets | Number of transmitted data octets. | ONS 15600 SDH: ASAP_4 |
| GfpStatsLFDRaised | Number of GFP LFD frames. | — |
| GfpStatsRoundTripLatency | Round-trip delay (in milliseconds [ms]) for the end-to-end FC transport. | — |
| GfpStatsRxBkCRCErrors | Number of super block CRC errors detected in the received GFP-T frames. | — |
| GfpStatsRxDistanceExtBuffers | Number of received buffer credits for GFP-T (valid only if distance extension is enabled). | — |
| GfpStatsTxDistanceExtBuffers | Number of transmitted buffer credits for GFP-T (valid only if distance extension is enabled). | — |
| gfpStatscHecRxMBitErrors | Number of received GFP frames with single bit errors in the core header (these errors are uncorrectable). | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| gfpStatstHecRxMBitErrors | Number of received GFP frames with single bit errors in the tHec (these errors are uncorrectable). | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| NE ID | Name of the selected NE. | — |

E.2.19 LEX PM Table—ONS 15454 SONET, ONS 15454 SDH

The LEX PM table provides monitoring of performance parameters related to HDLC particular framing (LEX) on optical interfaces. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).



Note

LEX monitors performance parameters only on ADM-10G cards.

The following table describes the fields in the LEX PM table.

Table E-34 **Field Descriptions for the LEX PM Table**

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Rx Total Packets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM-10G • ONS 15454 SDH: ADM-10G |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM-10G • ONS 15454 SDH: ADM-10G |
| Tx Total Packets | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM-10G • ONS 15454 SDH: ADM-10G |

Table E-34 **Field Descriptions for the LEX PM Table**

| Field | Description | Cards Supported |
|-----------------------------|---|--|
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| hdlcInOctets | Number of bytes received (from the SONET/SDH path) prior to the bytes undergoing HDLC decapsulation by the policy engine. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| hdlcRxAborts | Number of received packets aborted on input. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| hdlcOutOctets | Number of bytes transmitted (to the SONET/SDH path) after the bytes undergoing HDLC encapsulation by the policy engine. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |
| IfInPayloadCrcErrors | Number of payload CRC errors received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM-10G ONS 15454 SDH: ADM-10G |

E.2.20 High Order PM Table (Far End)—ONS 15310 MA SDH, ONS 15454 SDH

The SDH High Order PM table shows far-end performance data for the far-end ONS 15310 MA SDH and ONS 15454 SDH high-order sections. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the High Order PM table.

Table E-35 *Field Descriptions for the High Order PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| HP-EB | High-order path errored block. HP-EB indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-BBE | High-order path background block errors. HP-BBE is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-ES | High-order path errored seconds. HP-ES is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-35 Field Descriptions for the High Order PM Table (Far End) (continued)

| Field | Description | Cards Supported |
|---------|--|---|
| HP-SES | High-order path severely errored seconds. HP-SES is a one-second period containing 30 percent or more errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-UAS | High-order path unavailable seconds. HP-UAS is a count of the seconds when the VC path was unavailable. A high-order path becomes unavailable when ten consecutive seconds occur that qualify as HP-SESSs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as HP-SESSs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-ESR | High-order path errored seconds ratio. HP-ESR is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-SESR | High-order path severely errored seconds ratio. HP-SESR is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-BBER | High-order path background block error ratio. HP-BBER is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESSs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-35 *Field Descriptions for the High Order PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|-------|---|--|
| HP-FC | High-order path failure count. HP-FC is a count of the number of failed events. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX, E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: MRC_4, MRC_12_2.5G |
| NE ID | Name of the selected NE. | — |

E.2.21 High Order PM Table (Far End)—ONS 15600 SDH

The High Order PM table shows far-end performance data for the ONS 15600 SDH high-order section. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the High Order PM table.

Table E-36 *Field Descriptions for the High Order PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------------|--|---------------------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| HP-EB | High-order path errored blocks (HP-EB) indicates that bits are in error within a block. | ASAP_4, STM16_16, STM64_4 |
| HP-ES | High-order path errored seconds (HP-ES) is a one-second period with one or more errored blocks or at least one defect. | ASAP_4, STM16_16, STM64_4 |

Table E-36 *Field Descriptions for the High Order PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|---------|--|---------------------------|
| HP-SES | High-order path severely errored seconds (HP-SES) is a one-second period containing more than 30 percent errored blocks or at least one defect. SES is a subset of ES. | ASAP_4, STM16_16, STM64_4 |
| HP-UAS | High-order path unavailable seconds (HP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as HP-SESSs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as HP-SESSs. | ASAP_4, STM16_16, STM64_4 |
| HP-FC | High-order path failure count (HP-FC) is a count of the number of failed events. | ASAP_4, STM16_16, STM64_4 |
| HP-BBE | High-order path background block errors (HP-BBE) is an errored block not occurring as part of a severely errored second (SES). | ASAP_4, STM16_16, STM64_4 |
| HP-ESR | High-order path errored seconds ratio (HP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | ASAP_4, STM16_16, STM64_4 |
| HP-SESR | High-order path severely errored seconds ratio (HP-SESR) is the ratio of SESSs to total seconds in available time during a fixed measurement interval. | ASAP_4, STM16_16, STM64_4 |
| HP-BBER | High-order path background block error ratio (HP-BBER) is the ratio of background block errors (BBEs) to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESSs. | ASAP_4, STM16_16, STM64_4 |
| NE ID | Name of the selected NE. | — |

E.2.22 High Order PM Table—ONS 15310 MA SDH, ONS 15454 SDH

The High Order PM table shows performance data for the ONS 15310 MA SDH and ONS 15454 SDH physical sections. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the High Order PM table.

Table E-37 *Field Descriptions for the High Order PM Table*

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| HP-EB | High-order path errored blocks (HP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-ES | High-order path errored seconds (HP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-SES | High-order path severely errored seconds (HP-SES) is a one-second period containing greater than 30% errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-37 *Field Descriptions for the High Order PM Table (continued)*

| Field | Description | Cards Supported |
|--------|--|--|
| HP-UAS | High-order path unavailable seconds (HP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as HP-SESSs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as HP-SESSs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-FC | Number of failed events. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: MRC_4, MRC_12_2.5G |
| HP-BBE | High-order path background block errors (HP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-ESR | High-order path errored seconds ratio (HP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-37 *Field Descriptions for the High Order PM Table (continued)*

| Field | Description | Cards Supported |
|--|---|--|
| HP-SESR | High-order path severely errored seconds ratio (HP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-BBER | High-order path background block error ratio (HP-BBER) is the ratio of background block errors (BBEs) to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, DS3I, DS3IN, E1N, E1, E1_42, E3, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| Positive Pointer Justification Count Path Detected | Positive pointer justification count, path detected is a count of the positive pointer justifications detected on a particular path on an incoming SDH signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-NPJC-Pdet | HP-NPJC-Pdet multiplex section, negative pointer justification count, path detected (MS-NPJC-Pdet) is a count of the negative pointer justifications detected on a particular path on an incoming SDH signal. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-37 *Field Descriptions for the High Order PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|--|---|
| HP-PPJC-Pgen | HP-PPJC-Pgen multiplex section, positive pointer justification count, path generated (MS-PPJC-Pgen) is a count of the positive pointer justifications generated for a particular path. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-NPJC-Pgen | HP-NPJC-Pgen multiplex section, negative pointer justification count, path generated (MS-NPJC-Pgen) is a count of the negative pointer justifications generated for a particular path. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-PJ-DIFF | Sum of the absolute values of differences between positive transmitted and received, and negative transmitted and received. The important metric on pointer justification is not the exact counts, but how many were absorbed. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| HP-PJCS-Pdet | Number of high-order path pointer justification count seconds detected on a particular path. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |

Table E-37 *Field Descriptions for the High Order PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|--|---|
| HP-PJCS-Pgen | Number of high-order path pointer justification count seconds generated for a particular path. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC192_XFP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E |
| NE ID | Name of the selected NE. | — |

E.2.23 High Order PM Table—ONS 15600 SDH

The High Order PM table shows performance data for the ONS 15600 SDH physical section. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the High Order PM table.

Table E-38 *Field Descriptions for the High Order PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-38 *Field Descriptions for the High Order PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|--|---------------------------|
| HP-EB | High-order path errored blocks (HP-EB) indicates that one or more bits are in error within a block. | ASAP_4, STM16_16, STM64_4 |
| HP-ES | High-order path errored seconds (HP-ES) is a one-second period with one or more errored blocks or at least one defect. | ASAP_4, STM16_16, STM64_4 |
| HP-SES | High-order path severely errored seconds (HP-SES) is a one-second period containing greater than 30% errored blocks or at least one defect. SES is a subset of ES. | ASAP_4, STM16_16, STM64_4 |
| HP-UAS | High-order path unavailable seconds (HP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as HP-SESSs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as HP-SESSs. | ASAP_4, STM16_16, STM64_4 |
| HP-FC | High-order path failure count (HP-FC) is a count of the number of failed events. | ASAP_4, STM16_16, STM64_4 |
| HP-BBE | High-order path background block errors (HP-BBE) is an errored block not occurring as part of an SES. | ASAP_4, STM16_16, STM64_4 |
| HP-ESR | High-order path errored seconds ratio (HP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | ASAP_4, STM16_16, STM64_4 |
| HP-SESR | High-order path severely errored seconds ratio (HP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | ASAP_4, STM16_16, STM64_4 |
| HP-BBER | High-order path background block error ratio (HP-BBER) is the ratio of BBEs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | ASAP_4, STM64_4, STM16_16 |
| HP-PPJC-Pdet | HP-PPJC-Pdet multiplex section, positive pointer justification count, path detected (MS-PPJC-Pdet) is a count of the positive pointer justifications detected on a particular path on an incoming SDH signal. | STM64_4, STM16_16 |
| HP-NPJC-Pdet | HP-NPJC-Pdet multiplex section, negative pointer justification count, path detected (MS-NPJC-Pdet) is a count of the negative pointer justifications detected on a particular path on an incoming SDH signal. | STM64_4, STM16_16 |
| HP-PPJC-Pgen | HP-PPJC-Pgen multiplex section, positive pointer justification count, path generated (MS-PPJC-Pgen) is a count of the positive pointer justifications generated for a particular path. | STM64_4, STM16_16 |
| HP-NPJC-Pgen | HP-NPJC-Pgen multiplex section, negative pointer justification count, path generated (MS-NPJC-Pgen) is a count of the negative pointer justifications generated for a particular path. | STM64_4, STM16_16 |
| NE ID | Name of the selected NE. | — |

E.2.24 IP SLA PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, and ONS 15454 SDH

The IP SLA PM table allows you to monitor service-level agreements (SLAs) for IP networks. Service levels are measured by downtime, bandwidth, latency, jitter, packet loss, and so on. These measurements are controllable and do not depend on network traffic.

You can display IP SLA performance data in real time. When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).



Note

- You can launch the IP SLA PM table only from the IP SLA table, not from the Domain Explorer or the NE Explorer.
- Performance monitoring is disabled for the IP SLA echo operation. If you select an echo row in the IP SLA PM table, the Performance menu is disabled.

The following table describes the fields in the IP SLA PM table.

Table E-39 **Field Descriptions for the IP SLA PM Table**

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Alias NE ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| NE ID | Name of the selected NE. | — |
| Validity | Whether the data in the entry is valid. | — |
| rttMonJitterStatsCompletions | Number of jitter operations that have completed successfully. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| rttMonJitterStatsOverThresholds | Number of jitter operations that violate the threshold. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsNumOfRTT | Number of successful round trips. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsRTTSum | Sum of the round-trip values, in milliseconds (ms). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsRTTSum2Low | Sum of the squares of the low round-trip values, in ms. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsRTTSum2High | Sum of the squares of the high round-trip values, in ms. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|-----------------------------------|--|---|
| rttMonJitterStatsRTTMin | Minimum number of round-trip times (RTTs) that were measured successfully. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsRTTMax | Maximum number of RTTs that were measured successfully. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMinOfPositivesSD | Minimum positive jitter values from the source to the destination, in ms. Positive jitter values indicate delays in receiving time from one packet to another. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMaxOfPositivesSD | Maximum positive jitter values from the source to the destination, in ms. Positive jitter values indicate delays in receiving time from one packet to another. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsNumOfPositivesSD | Number of jitter values from the source to the destination that are positive (that is, network latency increases for two consecutive test packets). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 *Field Descriptions for the IP SLA PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------------|---|---|
| rttMonJitterStatsSumOfPositivesSD | Sum of the positive values, in ms. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2PositivesSDLow | Sum of the squares of the low positive values. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2PositivesSDHigh | Sum of the squares of the high positive values. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMinOfNegativesSD | Minimum negative jitter values from the source to the destination. The absolute value is given. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMaxOfNegativesSD | Maximum negative jitter values from the source to the destination. The absolute value is given. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------------------|---|---|
| rttMonJitterStatsNumOfNegativesSD | Number of jitter values from the source to the destination that are negative (that is, network latency decreases for two consecutive test packets). | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSumOfNegativesSD | Sum of the negative values. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2NegativesSDLow | Sum of the squares of the negative low values. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2NegativesSDHigh | Sum of the squares of the negative high values. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMinOfPositivesDS | Minimum of all positive jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|-----------------------------------|---|---|
| rttMonJitterStatsMaxOfPositivesDS | Maximum of all positive jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsNumOfPositivesDS | Sum of numbers of all positive jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSumOfPositivesDS | Sum of RTTs of all positive jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2PositivesDSL | Sum of squares of RTTs of all positive jitter values from packets sent from the destination to the source (low-order 32 bits). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2PositivesDSH | Sum of the squares of RTTs of all positive jitter values from packets sent from the destination to the source (high-order 32 bits). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------------|--|---|
| rttMonJitterStatsMinOfNegativesDS | Minimum of all negative jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsMaxOfNegativesDS | Maximum of all negative jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsNumOfNegativesDS | Sum of numbers of all negative jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSumOfNegativesDS | Sum of RTTs of all negative jitter values from packets sent from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsSum2NegativesDSLow | Sum of the squares of RTTs of all negative jitter values from packets sent from the destination to the source (low-order 32 bits). | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 *Field Descriptions for the IP SLA PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------------|---|---|
| rttMonJitterStatsSum2NegativesDSHigh | Sum of the squares of RTTs of all negative jitter values from packets sent from the destination to the source (high-order 32 bits). | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsPacketLossSD | Number of packets lost from the source to the destination. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsPacketLossDS | Number of packets lost from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsPacketOutOfSequence | Number of packets that were returned out of order. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsPacketMIA | Number of packets lost where the direction (source-to-destination or destination-to-source) cannot be determined. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|------------------------------------|---|---|
| rttMonJitterStatsPacketLateArrival | Number of packets that arrived after the timeout. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsError | Number of times an operation could not be started due to other internal failures. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsBusy | Number of times the operation could not be started because the previously scheduled run was not finished. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWSumSD | Sum of one-way times from the source to the destination. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWSum2SDLow | Sum of the squares of one-way times from the source to the destination (low-order 32 bits). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 *Field Descriptions for the IP SLA PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------------------|--|---|
| rttMonJitterStatsOWSum2SDHigh | Sum of the squares of one-way times from the source to the destination (high-order 32 bits). | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWMinSD | Minimum of all one-way times from the source to the destination. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWMaxSD | Maximum of all one-way times from the source to the destination. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWSumDS | Sum of one-way times from the destination to the source. | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWSum2DSLlow | Sum of the squares of one-way times from the destination to the source (low-order 32 bits). | <ul style="list-style-type: none"> • ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15310 MA SONET—ML-100T-8 • ONS 15310 MA SDH—ML-100T-8 • ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 • ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-39 Field Descriptions for the IP SLA PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------|--|---|
| rttMonJitterStatsOWSum2DSHigh | Sum of the squares of one-way times from the destination to the source (high-order 32 bits). | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWMinDS | Minimum of all one-way times from the destination to the source. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWMaxDS | Maximum of all one-way times from the destination to the source. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsNumOfOW | Number of one-way times that were measured successfully. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |
| rttMonJitterStatsOWMinSDNew | Minimum of all one-way times from the source to the destination. Replaces deprecated rttMonJitterStatsOWMinSD. | <ul style="list-style-type: none"> ONS 15310 CL—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15310 MA SONET—ML-100T-8 ONS 15310 MA SDH—ML-100T-8 ONS 15454 SONET—ML100T, ML100X-8, ML1000, ML-MR-10 ONS 15454 SDH—ML100T, ML100X-8, ML1000, ML-MR-10 |

E.2.25 Low Order VC11 PM Table—ONS 15454 SDH

The Low Order VC11 PM table shows performance data for the ONS 15454 SDH low-order VC11. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC11 PM table.

Table E-40 *Field Descriptions for the Low Order VC11 PM Table*

| Field | Description | Cards Supported |
|---------------------------------|---|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| VC11-LP-EB | Low-order path errored block (LP-EB) indicates that one or more bits are in error within a block. | — |
| VC11-LP-BBE | Low-order path background block error (LP-BBE) is an errored block not occurring as part of an SES. | — |
| VC11-LP-ES | Low-order path errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | — |
| VC11-LP-SES | Low-order path severely errored seconds (LP-SES) is a one-second period containing greater than 30% errored blocks or at least one defect. SES is a subset of ES. | — |
| VC11-LP-UAS | Low-order path unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESs. | — |

Table E-40 *Field Descriptions for the Low Order VC11 PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|---|-----------------|
| VC11-LP-ESR | Low-order path errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | — |
| VC11-LP-SESR | Low-order path severely errored second ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | — |
| VC11-LP-BBER | Low-order path background block error ratio (LP-BBER) is the ratio of BBERs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | — |
| NE ID | Name of the selected NE. | — |

E.2.26 Low Order VC12 PM Table—ONS 15310 MA SDH, ONS 15454 SDH

The Low Order VC12 PM table shows performance data for the ONS 15310 MA SDH and ONS 15454 SDH low-order VC12. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC12 PM table.

Table E-41 *Field Descriptions for the Low Order VC12 PM Table*

| Field | Description | Cards Supported |
|---------------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-41 *Field Descriptions for the Low Order VC12 PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|---|---|
| VC12-LP-EB | Low-order path errored block (LP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-BBE | Low-order path background block error (LP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-ES | Low-order path errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-SES | Low-order path severely errored seconds (LP-SES) is a one-second period containing greater than 30% errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-UAS | Low-order path unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-ESR | Low-order path errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-SESR | Low-order path severely errored second ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |

Table E-41 *Field Descriptions for the Low Order VC12 PM Table (continued)*

| Field | Description | Cards Supported |
|--------------|---|---|
| VC12-LP-BBER | Low-order path background block error ratio (LP-BBER) is the ratio of BBERs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| NE ID | Name of the selected NE. | — |

E.2.27 Low Order VC11 Section PM Table (Far End)—ONS 15454 SDH

The Low Order VC11 Section PM table shows far-end performance data for the ONS 15454 SDH low-order VC11 section far end. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC11 Section PM table.

Table E-42 *Field Descriptions for the Low Order VC11 Section PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| VC11-LP-EB | Low-order errored block (LP-EB) indicates that one or more one or more bits are in error within a block. | — |

Table E-42 *Field Descriptions for the Low Order VC11 Section PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|--------------|--|-----------------|
| VC11-LP-BBE | Low-order background block errors (LP-BBE) is an errored block not occurring as part of an SES. | — |
| VC11-LP-ES | Low-order errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | — |
| VC11-LP-SES | Low-order severely errored seconds (LP-SES) is a one-second period containing greater than or equal to 30 percent errored blocks or at least one defect. SES is a subset of ES. | — |
| VC11-LP-UAS | Low-order unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESs. | — |
| VC11-LP-ESR | Low-order errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | — |
| VC11-LP-SESR | Low-order severely errored second ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | — |
| VC11-LP-BBER | Low-order background block error ratio (LP-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | — |
| NE ID | Name of the selected NE. | — |

E.2.28 Low Order VC12 Section PM Table (Far End)—ONS 15310 MA SDH, ONS 15454 SDH

The Low Order VC12 Section PM table shows far-end performance data for the ONS 15310 MA SDH and ONS 15454 SDH low-order VC12 section far end. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC12 Section PM table.

Table E-43 *Field Descriptions for the Low Order VC12 Section PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| VC12-LP-EB | Low-order errored block (LP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-BBE | Low-order background block errors (LP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-ES | Low-order errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-SES | Low-order severely errored seconds (LP-SES) is a one-second period containing greater than or equal to 30 percent errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-UAS | Low-order unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESs. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-ESR | Low-order errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: E1, E1N, E1_42 |

Table E-43 *Field Descriptions for the Low Order VC12 Section PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|--------------|--|---|
| VC12-LP-SESR | Low-order severely errored second ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| VC12-LP-BBER | Low-order background block error ratio (LP-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: E1, E1N, E1_42 |
| NE ID | Name of the selected NE. | — |

E.2.29 Low Order VC3 PM Table—ONS 15310 MA SDH, ONS 15454 SDH

The Low Order VC3 PM table shows performance data for the ONS 15310 MA SDH and ONS 15454 SDH low-order VC3. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC3 PM table.

Table E-44 *Field Descriptions for the Low Order VC3 PM Table*

| Field | Description | Cards Supported |
|---------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |

Table E-44 *Field Descriptions for the Low Order VC3 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------|---|--|
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| VC3-LP-EB | Low-order path errored block (LP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-BBE | Low-order path background block error (LP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-ES | Low-order path errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-SES | Low-order path severely errored seconds (LP-SES) is a one-second period containing greater than 30% errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-UAS | Low-order path unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-ESR | Low-order path errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-SESR | Low-order path severely errored second ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-BBER | Low-order path background block error ratio (LP-BBER) is the ratio of BBEs to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| NE ID | Name of the selected NE. | — |

E.2.30 Low Order VC3 Section PM Table (Far End)—ONS 15310 MA SDH and ONS 15454 SDH

The Low Order VC3 Section PM table shows far-end performance data for the far-end ONS 15310 MA SDH and ONS 15454 SDH low-order VC3 sections. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Low Order VC3 Section PM table.

Table E-45 Field Descriptions for the Low Order VC3 Section PM Table (Far End)

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Interface | Interface name of the selected NE. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| VC3-LP-EB | Low-order section errored block (LP-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-BBE | Low-order section background block errors (LP-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 • ONS 15454 SDH: DS3I, DS3IN, E3 |

Table E-45 Field Descriptions for the Low Order VC3 Section PM Table (Far End) (continued)

| Field | Description | Cards Supported |
|-------------|--|--|
| VC3-LP-ES | Low-order section errored seconds (LP-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-SES | Low-order section severely errored seconds (LP-SES) is a one-second period containing greater than or equal to 30 percent errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-UAS | Low-order section unavailable seconds (LP-UAS) is a count of the seconds when the VC path was unavailable. A low-order path becomes unavailable when ten consecutive seconds occur that qualify as LP-SESSs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as LP-SESSs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-ESR | Low-order section errored second ratio (LP-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-SESR | Low-order section severely errored seconds ratio (LP-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| VC3-LP-BBER | Low-order section background block error ratio (LP-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESSs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: E1_21_E3_DS3_3, E1_63_E3_DS3_3 ONS 15454 SDH: DS3I, DS3IN, E3 |
| NE ID | Name of the selected NE. | — |

E.2.31 Multiplex Section PM Table (Far End)—ONS 15310 MA SDH, ONS 15454 SDH

The Multiplex Section PM table shows far-end performance data for the ONS 15310 MA SDH and ONS 15454 SDH multiplex sections (far-end). You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.

- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Multiplex Section PM table.

Table E-46 **Field Descriptions for the Multiplex Section PM Table (Far End)**

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| MS-EB | Multiplex section errored block (MS-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: CTX-2500 • ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-ES | Multiplex section errored seconds (MS-E) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: CTX-2500 • ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-46 *Field Descriptions for the Multiplex Section PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|--------|---|--|
| MS-SES | Multiplex section severely errored seconds (MS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. For more information, see ITU-T G.829 Section 5.1.3. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-UAS | Multiplex section unavailable seconds (MS-UAS) is a count of the seconds when the section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as MS-SEs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as MS-SEs. When the condition is entered, MS-SEs decrement and then count toward MS-UAS. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MRC_4, ADM_10G, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-FC | Multiplex section failure count (MS-FC) is a count of the number of failed events. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: ADM_10G |
| MS-BBE | Multiplex section background block errors (MS-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-ESR | Multiplex section errored seconds ratio (MS-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-46 *Field Descriptions for the Multiplex Section PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|---------|--|--|
| MS-SESR | Multiplex section severely errored seconds ratio (MS-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-BBER | Multiplex section background block errored ratio (MS-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| NE ID | Name of the selected NE. | — |

E.2.32 Multiplex Section PM Table (Far End)—ONS 15600 SDH

The Multiplex Section PM table shows far-end performance data for the ONS 15600 SDH multiplex section far end. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Multiplex Section PM table.

Table E-47 *Field Descriptions for the Multiplex Section PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------|--|---------------------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| MS-EB | Multiplex section errored block (MS-EB) indicates that one or more bits are in error within a block. | ASAP_4, STM16_16, STM64_4 |
| MS-ES | Multiplex section errored seconds (MS-ES) is a one-second period with one or more errored blocks or at least one defect. | ASAP_4, STM16_16, STM64_4 |
| MS-SES | Multiplex section severely errored seconds (MS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. For more information, see ITU-T G.829 Section 5.1.3. | ASAP_4, STM16_16, STM64_4 |
| MS-UAS | Multiplex section unavailable seconds (MS-UAS) is a count of the seconds when the section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as MS-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as MS-SESs. When the condition is entered, MS-SESs decrement and then count toward MS-UAS. | ASAP_4, STM16_16, STM64_4 |
| MS-FC | Multiplex section failure count (MS-FC) is a count of the number of failed events. | ASAP_4, STM16_16, STM64_4 |
| MS-BBE | Multiplex section background block errors (MS-BBE) is an errored block not occurring as part of an SES. | ASAP_4, STM16_16, STM64_4 |
| MS-ESR | Multiplex section errored seconds ratio (MS-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | — |
| MS-SESR | Multiplex section severely errored seconds ratio (MS-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | — |
| MS-BBER | Multiplex section background block errored ratio (MS-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | — |
| NE ID | Name of the selected NE. | — |

E.2.33 Multiplex Section PM Table (Near End)—ONS 15310 MA SDH, ONS 15454 SDH

The Multiplex Section PM table shows performance data for the ONS 15310 MA SDH and ONS 15454 SDH multiplex sections. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Multiplex Section PM table.

Table E-48 Field Descriptions for the Multiplex Section PM Table (Near End)

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| MS-EB | Multiplex section errored blocks (MS-EB) indicates that bits are in error within a block. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: CTX-2500 • ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-48 *Field Descriptions for the Multiplex Section PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|--------|--|---|
| MS-ES | Multiplex section errored seconds (MS-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-SES | Multiplex section severely errored seconds (MS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. For more information, see ITU-T G.829 Section 5.1.3. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-UAS | Multiplex section unavailable seconds (MS-UAS) is a count of the seconds when the section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as MS-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as MS-SESs. When the condition is entered, MS-SESs decrement and then count toward MS-UAS. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-FC | Multiplex section failure count (MS-FC) is a count of the number of failed events. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP |

Table E-48 Field Descriptions for the Multiplex Section PM Table (Near End) (continued)

| Field | Description | Cards Supported |
|----------|---|---|
| MS-BBE | Multiplex section background block errors (MS-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-PSC | <p>In a 1 + 1 protection scheme for a working card, protection switching count (PSC) is a count of the number of times service switches from a working card to a protection card plus the number of times service switches back to the working card.</p> <p>For a protection card, PSC is a count of the number of times service switches to a working card from a protection card plus the number of times service switches back to the protection card. The PSC PM applies to revertive and nonrevertive, line-level protection switching.</p> <p>Note MS-SPRing is not supported on the STM-1 card; therefore, the PSD-W, PSD-S, and PSD-R PMs do not increment.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM1, STM1_8, STM4, STM4_4, STM16, STM64 |
| MS-PSD | <p>Protection switching duration (PSD) applies to the length of time, in seconds, that service is carried on another line. For a working line, PSD is a count of the number of seconds that service was carried on the protection line. For the protection line, PSD is a count of the seconds that the line was used to carry service. The PSD PM applies to revertive and nonrevertive, line-level protection switching.</p> <p>Note MS-SPRing is not supported on the STM-1 card; therefore, the PSD-W, PSD-S, and PSD-R PMs do not increment.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM1, STM1_8, STM4, STM4_4, STM16, STM64 |
| MS-PSC-W | <p>For a working line in a 2-fiber MS-SPRing, protection switching count—working (PSC-W) is a count of the number of times traffic switches away from the working capacity in the failed line and back to the working capacity after the failure is cleared. PSC-W increments on the failed working line and PSC increments on the active protect line.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |

Table E-48 *Field Descriptions for the Multiplex Section PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|----------|---|---|
| MS-PSD-W | <p>For a working line in a 2-fiber MS-SPRing, protection switching duration–working (PSD-W) is a count of the number of seconds that service was carried on the protection line. PSD-W increments on the failed working line and PSD increments on the active protect line.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |
| MS-PSC-S | <p>In a 4-fiber MS-SPRing, protection switching count–span (PSC-S) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to the working line. A count is only incremented if span switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |
| MS-PSD-S | <p>In a 4-fiber MS-SPRing, protection switching duration–span (PSD-S) is a count of the seconds that the protection line was used to carry service. A count is only incremented if span switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |
| MS-PSC-R | <p>In a 4-fiber MS-SPRing, protection switching count–ring (PSC-R) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to a working line. A count is only incremented if ring switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |
| MS-PSD-R | <p>In a 4-fiber MS-SPRing, protection switching duration–ring (PSD-R) is a count of the seconds that the protection line was used to carry service. A count is only incremented if ring switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, STM4, STM4_4, STM16, STM64 |
| MS-ESR | <p>Multiplex section errored seconds ratio (MS-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval.</p> | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-48 *Field Descriptions for the Multiplex Section PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|---------|--|---|
| MS-SESR | Multiplex section severely errored seconds ratio (MS-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| MS-BBER | Multiplex section background block error ratio (MS-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| NE ID | Name of the selected NE. | — |

E.2.34 Multiplex Section PM Table—ONS 15600 SDH

The Multiplex Section PM table shows performance data for the ONS 15600 SDH multiplex section. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Multiplex Section PM table.

Table E-49 *Field Descriptions for the Multiplex Section PM Table*

| Field | Description | Cards Supported |
|-------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |

Table E-49 *Field Descriptions for the Multiplex Section PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------|---|---------------------------------|
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| MS-EB | Multiplex section errored blocks (MS-EB) indicates that one or more bits are in error within a block. | ASAP_4, STM16_16, STM64_4 |
| MS-ES | Multiplex section errored seconds (MS-ES) is a one-second period with one or more errored blocks or at least one defect. | ASAP_4, STM16_16, STM64_4 |
| MS-SES | Multiplex section severely errored seconds (MS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. For more information, see ITU-T G.829 Section 5.1.3. | ASAP_4, STM16_16, STM64_4 |
| MS-UAS | Multiplex section unavailable seconds (MS-UAS) is a count of the seconds when the section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as MS-SESs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as MS-SESs. When the condition is entered, MS-SESs decrement and then count toward MS-UAS. | ASAP_4, STM16_16, STM64_4 |
| MS-FC | Multiplex section failure count (MS-FC) is a count of the number of failed events. | ASAP_4, STM16_16, STM64_4 |
| MS-BBE | Multiplex section background block errors (MS-BBE) is an errored block not occurring as part of an SES. | ASAP_4, STM16_16, STM64_4 |
| MS-PSC | <p>In a 1 + 1 protection scheme for a working card, PSC is a count of the number of times service switches from a working card to a protection card plus the number of times service switches back to the working card.</p> <p>For a protection card, PSC is a count of the number of times service switches to a working card from a protection card plus the number of times service switches back to the protection card. The PSC PM applies to revertive and nonrevertive, line-level protection switching.</p> <p>Note MS-SPRing is not supported on the STM-1 card; therefore, the PSD-W, PSD-S, and PSD-R PMs do not increment.</p> | ASAP_4, STM16_16, STM64_4 |
| MS-PSD | <p>PSD applies to the length of time, in seconds, that service is carried on another line. For a working line, PSD is a count of the number of seconds that service was carried on the protection line. For the protection line, PSD is a count of the seconds that the line was used to carry service. The PSD PM applies to revertive and nonrevertive, line-level protection switching.</p> <p>Note MS-SPRing is not supported on the STM-1 card; therefore, the PSD-W, PSD-S, and PSD-R PMs do not increment.</p> | ASAP_4, STM16_16, STM64_4 |

Table E-49 *Field Descriptions for the Multiplex Section PM Table (continued)*

| Field | Description | Cards Supported |
|----------|--|---------------------------------|
| MS-PSC-W | For a working line in a 2-fiber MS-SPRing, protection switching count–working (PSC-W) is a count of the number of times traffic switches away from the working capacity in the failed line and back to the working capacity after the failure is cleared. PSC-W increments on the failed working line and PSC increments on the active protect line. | ASAP_4, STM16_16, STM64_4 |
| MS-PSD-W | For a working line in a 2-fiber MS-SPRing, protection switching duration–working (PSD-W) is a count of the number of seconds that service was carried on the protection line. PSD-W increments on the failed working line and PSD increments on the active protect line. | ASAP_4, STM16_16, STM64_4 |
| MS-PSC-S | In a 4-fiber MS-SPRing, protection switching count–span (PSC-S) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to the working line. A count is only incremented if span switching is used. | ASAP_4, STM16_16, STM64_4 |
| MS-PSD-S | In a 4-fiber MS-SPRing, protection switching duration–span (PSD-S) is a count of the seconds that the protection line was used to carry service. A count is only incremented if span switching is used. | ASAP_4, STM16_16, STM64_4 |
| MS-PSC-R | In a 4-fiber MS-SPRing, protection switching count–ring (PSC-R) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to a working line. A count is only incremented if ring switching is used. | ASAP_4, STM16_16, STM64_4 |
| MS-PSD-R | In a 4-fiber MS-SPRing, protection switching duration–ring (PSD-R) is a count of the seconds that the protection line was used to carry service. A count is only incremented if ring switching is used. | ASAP_4, STM16_16, STM64_4 |
| MS-ESR | Multiplex section errored seconds ratio (MS-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | — |
| MS-SESR | Multiplex section severely errored seconds ratio (MS-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | — |
| MS-BBER | Multiplex section background block error ratio (MS-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | — |
| NE ID | Name of the selected NE. | — |

E.2.35 Optical Physical PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15310 MA SDH, ONS 15454 SONET, ONS 15454 SDH, ONS 15600 SONET, and ONS 15600 SDH

The Optical Physical PM table shows physical-layer performance data. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.

- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Optical Service Channel (OSC) power—New optical power parameters are monitored for optical cards. Six new PM parameters are added to all the optical interfaces of all the supported cards for ONS 15454 SONET and ONS 15454 SDH. Using Prime Optical, you can monitor six new parameters for optical power: three each for received and transmitted power.

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Optical Physical PM table.

Table E-50 **Field Descriptions for the Optical Physical PM Table**

| Field | Description | Cards Supported |
|---------------------------|---|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Card-level interface. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Laser Bias Current | <p>Laser bias current, which is interpreted as a percentage value from 0 to 100.</p> <p>Note Laser bias current is not supported (N/A) for the TXP_MR_2.5G and TXPP_MR_2.5G cards.</p> | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: CTX_2500 • ONS 15310 MA SDH: CTX_2500 • ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP • ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP • ONS 15600 SONET: ASAP_4, OC48_16, OC192_4 • ONS 15600 SDH: ASAP_4, STM16_16, STM64_4 |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|---|---|
| Optical Power Transmitted | <p>Optical power transmitted, which is interpreted as a percentage value from 0 to 100.</p> <p>Note Optical power transmitted is not supported (N/A) for the TXP_MR_2.5G and TXPP_MR_2.5G cards.</p> | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500 ONS 15310 MA SDH: CTX_2500 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP ONS 15454 M2/M6: RAMAN_CTP, RAMAN_COP ONS 15600 SONET: ASAP_4, OC48_16, OC192_4 ONS 15600 SDH: ASAP_4, STM16_16, STM64_4 |
| Optical Power Received | <p>Optical power received, which is interpreted as a percentage value from 0 to 100.</p> <p>Note Optical power received is not supported (N/A) for the TXP_MR_2.5G and TXPP_MR_2.5G cards.</p> | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500 ONS 15310 MA SDH: CTX_2500 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP ONS 15454 SDH: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OC3_8/STM1_8, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP ONS 15454 M2/M6: RAMAN_CTP ONS 15600 SONET: ASAP_4, OC48_16, OC192_4 ONS 15600 SDH: ASAP_4, STM16_16, STM64_4 |
| Minimum Laser Bias | <p>Minimum laser bias, which is interpreted as a percentage value from 0 to 100.</p> | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C |

Table E-50 *Field Descriptions for the Optical Physical PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------|---|--|
| Average Laser Bias | Average laser bias, which is interpreted as a percentage value from 0 to 100. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C |
| Maximum Laser Bias | Maximum laser bias, which is interpreted as a percentage value from 0 to 100. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C |

Table E-50 *Field Descriptions for the Optical Physical PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Minimum Transmitted Power | <p>Minimum transmitted power level in increments of one-tenths of decibels referenced to 1 milliwatt (dBm). The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm.</p> <p>Note Transmitted power is not supported for trunk ports.</p> | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP, RAMAN_COP |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|---|---|
| Average Transmitted Power | <p>Average transmitted power level in increments of one-tenths of dBm. The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm.</p> <p>Note Transmitted power is not supported for trunk ports.</p> | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32MUX_O, 32DMX, 32DMX_L, 32DMX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP, RAMAN_COP |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|---|---|
| Maximum Transmitted Power | <p>Maximum transmitted power level in increments of one-tenths of dBm. The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm.</p> <p>Note Transmitted power is not supported for trunk ports.</p> | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OSC_CSM, OPT_PRE_L, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP, RAMAN_COP |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|------------------------|--|--|
| Minimum Received Power | Minimum received power level in increments of one-tenths of dBm. The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP |

Table E-50 *Field Descriptions for the Optical Physical PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------|--|--|
| Average Received Power | Average received power level in increments of one-tenths of dBm. The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Maximum Received Power | Maximum received power level in increments of one-tenths of dBm. The range is from -40.0 to 30.0 dBm for the following cards: TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, 2.5G_DM, 2.5G_DMP, MXP_2.5G_10E, and MXP_2.5G_10G. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, 32DMX, 32DMX_L, 32DMX_O, 32MUX_O, 32WSS, 32WSS_L, 40DMX_C, 40MUX_C, 40WSS_C, 40WXC_C, 80WXC_C, 4MD, AD_1B, AD_1C, AD_2C, AD_4B, AD_4C, ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C, OPT_BST, OPT_BST_E, OPT_BST_L, OPT_PRE, OPT_PRE_L, OSC_CSM, OSCM, OTU2_XP, PSM, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4, PT_10GE_4, 40G-MXP-C ONS 15454 M2/M6: RAMAN_CTP |
| Minimum Passthrough Power | Displays the minimum passthrough power value. | <ul style="list-style-type: none"> ONS 15454 SONET: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C ONS 15454 SDH: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C |
| Average Passthrough Power | Displays the average passthrough power value. | <ul style="list-style-type: none"> ONS 15454 SONET: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C ONS 15454 SDH: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C |
| Maximum Passthrough Power | Displays the maximum passthrough power value. | <ul style="list-style-type: none"> ONS 15454 SONET: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C ONS 15454 SDH: 32WSS, 32WSS_L, OPT_AMP_17_C, OPT_AMP_C, OPT_RAMP_C |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------|--|--|
| Minimum Transmitted OSC Power | Minimum transmitted OSC power in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |
| Average Transmitted OSC Power | Average transmitted OSC power level in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |
| Maximum Transmitted OSC Power | Maximum transmitted OSC power level in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |
| Minimum Received OSC Power | Minimum received OSC power level in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |
| Average Received OSC Power | Average received OSC power level in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |
| Maximum Received OSC Power | Maximum received OSC power level in increments of one-tenths of dBm. For the other supported DWDM cards, the range is from -50.0 to 30.0 dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 ONS 15454 SDH: OPT_AMP_17_C, OPT_AMP_C, OPT_AMP_L, OPT_BST, OPT_BST_E, OPT_BST_L, OSCM, OSC_CSM, SMR_1, SMR_2 |

Table E-50 Field Descriptions for the Optical Physical PM Table (continued)

| Field | Description | Cards Supported |
|--------------|--|--|
| Minimum PMD | Minimum polarization-mode dispersion (PMD) value, in picoseconds (ps). | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| Average PMD | Average PMD value, in ps. | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| Maximum PMD | Maximum PMD value, in ps. | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| Minimum OSNR | Minimum optical signal-to-noise ratio (OSNR), in dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| Average OSNR | Average OSNR, in dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| Maximum OSNR | Maximum OSNR, in dBm. | <ul style="list-style-type: none"> ONS 15454 SONET: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C ONS 15454 SDH: 40E-MXP-C, 40E-TXP-C, 40G-MXP-C |
| NE ID | Name of the selected NE. | — |

E.2.36 OTN FEC PM Table—ONS 15454 SONET, ONS 15454 SDH

The OTN FEC PM table shows OTN forward error correction (FEC) performance data for trunk ports on the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the OTN FEC PM table.

Table E-51 *Field Descriptions for the OTN FEC PM Table*

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Bit Errors Corrected | Number of bit errors corrected. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| Uncorrectable Words | Ratio of uncorrected codewords to codewords transmitted. A codeword is a block of N symbols that carry K information symbols and R redundant symbols ($N = K+R$). | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.37 OTN Path PM Table (Far End)—ONS 15454 SONET, ONS 15454 SDH

The OTN Path PM table shows OTN path performance data for trunk ports on the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the OTN Path PM table.

Table E-52 Field Descriptions for the OTN Path PM Table (Far End)

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ES-P | Errored seconds–path. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 • ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-52 *Field Descriptions for the OTN Path PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|-------|--------------------------------|--|
| SES-P | Severely errored seconds–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| UAS-P | Unavailable seconds–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBE-P | Background block errors–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| FC-P | Failure count–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-52 Field Descriptions for the OTN Path PM Table (Far End) (continued)

| Field | Description | Cards Supported |
|--------|--------------------------------------|--|
| ESR-P | Errored seconds ratio–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SESR-P | Severely errored seconds ratio–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBER-P | Background block errors ratio–path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.38 OTN Path PM Table (Near End)—ONS 15454 SONET, ONS 15454 SDH

The OTN Path PM table shows near-end OTN path performance data for trunk ports on the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the OTN Path PM table.

Table E-53 *Field Descriptions for the OTN Path PM Table (Near End)*

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ES-P | Displays the errored seconds-path. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 • ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SES-P | Displays the severely errored seconds-path. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 • ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-53 *Field Descriptions for the OTN Path PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|--------|---|--|
| UAS-P | Displays the unavailable seconds-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBE-P | Displays the background block errors-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| FC-P | Displays the failure count-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| ESR-P | Displays the errored seconds ratio-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SESR-P | Displays the severely errored seconds ratio-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-53 *Field Descriptions for the OTN Path PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|--------|--|--|
| BBER-P | Displays the background block errors ratio-path. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.39 OTN Section PM Table (Far End)—ONS 15454 SONET, ONS 15454 SDH

The OTN Section PM table shows OTN section performance data for trunk ports on the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the OTN Section PM table.

Table E-54 *Field Descriptions for the OTN Section PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |

Table E-54 Field Descriptions for the OTN Section PM Table (Far End) (continued)

| Field | Description | Cards Supported |
|-------------|---|--|
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ES-S | Errored seconds—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SES-S | Severely errored seconds—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| UAS-S | Unavailable seconds—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBE-S | Background block errors—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-54 *Field Descriptions for the OTN Section PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|--------|---|--|
| FC-S | Failure count—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| ESR-S | Errored seconds ratio—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SESR-S | Severely errored seconds ratio—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBER-S | Background block error ratio—section. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.40 OTN Section PM Table (Near End)—ONS 15454 SONET, ONS 15454 SDH

The OTN Section PM table shows near-end OTN section performance data for trunk ports on the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the OTN Section PM table.

Table E-55 **Field Descriptions for the OTN Section PM Table (Near End)**

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| ES-S | Section Errored Seconds (ES-S) indicates the errored seconds recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> • ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 • ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-55 *Field Descriptions for the OTN Section PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|-------|--|--|
| SES-S | Section Severely Errored Seconds (SES-S) indicates the severely errored seconds recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| UAS-S | Section unavailable seconds (UAS-S) indicates the unavailable seconds recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBE-S | Section Background Block Errors (BBE-S) indicates the number of background block errors recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| FC-S | Section Failure Counts (FC-S) indicates the failure counts recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |

Table E-55 *Field Descriptions for the OTN Section PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|--------|---|--|
| ESR-S | Section Errored Seconds Ratio (ESR-S) indicates the errored seconds ratio recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| SESR-S | Section Severely Errored Seconds Ratio (SESR-S) indicates the severely errored seconds ratio recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| BBER-S | Section Background Block Errors Ratio (BBER-S) indicates the background block errors ratio recorded in the OTN section during the PM time interval. | <ul style="list-style-type: none"> ONS 15454 SONET: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G, PTF_10GE_4 ONS 15454 SDH: ADM_10G, GE_XP, 10GE_XP, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G, PTF_10GE_4 |
| NE ID | Name of the selected NE. | — |

E.2.41 POS PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15454 SONET, ONS 15310 MA SDH, ONS 15454 SDH, ONS 15600 SONET, ONS 15600 SDH

The POS PM table shows POS performance data for Ethernet cards. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the POS PM table.



Note

Real-time PM data is not available for POS cards on NE releases earlier than release 5.0.

Table E-56 Field Descriptions for the POS PM Table

| Field | Description | Cards Supported |
|--------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | — |
| Rx Pre HDLC Bytes | Number of bytes received prior to the bytes undergoing HDLC encapsulation by the policy engine. | — |
| Rx Post HDLC Bytes | Number of bytes received after the bytes undergoing HDLC encapsulation by the policy engine. | — |

Table E-56 Field Descriptions for the POS PM Table (continued)

| Field | Description | Cards Supported |
|------------------------|---|--|
| Rx Total Packets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8, ML-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10, ML100T, ML100X-8, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| Rx Normal Packets | Number of packets between the minimum and maximum packet size received. | — |
| Rx Shorts | Number of packets below the minimum packet size received. | — |
| Rx Runts | Total number of frames received that are less than 64 bytes in length and have a CRC error. | — |
| Rx Longs | Counter for the number of received frames that exceed the maximum valid packet length of 1518 bytes. | — |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-MR-10 ONS 15454 SDH: CE-MR-10 |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-MR-10 ONS 15454 SDH: CE-MR-10 |
| Rx Crc Errors | Number of received CRC errors. | — |
| Rx Input Drop Packets | Number of received packets dropped on input. | — |
| Rx Input Abort Packets | Number of received packets aborted on input. | <ul style="list-style-type: none"> ONS 15600 SONET: ASAP_4 |
| Tx Pre HDLC Bytes | Number of bytes transmitted prior to the bytes undergoing HDLC encapsulation by the policy engine. | — |
| Tx Post HDLC Bytes | Number of bytes transmitted after the bytes undergoing HDLC encapsulation by the policy engine. | — |

Table E-56 *Field Descriptions for the POS PM Table (continued)*

| Field | Description | Cards Supported |
|------------------|---|--|
| Tx Total Packets | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8, ML-100T-8 ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-100T-8, CE-MR-10, ML100T, ML100X-8, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| Port Drop Counts | Number of received frames dropped at the port level. | — |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100X-8, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, MXP_MR_10DME |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100T, ML100X-8, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, ML100T, ML1000, MXP_MR_10DME |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15310 MA SONET: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15310 MA SDH: CE-100T-8, CE-MR-6, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-MR-10, ML100T, ML100X-8, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-MR-10, ML100T, ML1000, MXP_MR_10DME |

Table E-56 Field Descriptions for the POS PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------------|---|---|
| etherStatsDropEvents | Total number of events in which packets were dropped by the probe due to lack of resources. The value indicates the number of times this condition has been detected. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-100T-8, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME |
| rxPktsDroppedInternalCongestion | Number of received packets dropped due to overflow in G1000-4 frame buffer. | <ul style="list-style-type: none"> ONS 15310 CL: CE-100T-8, ML-100T-8 ONS 15454 SONET: CE-1000-4, CE-100T-8, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| mediaIndStatsRxFramesTruncated | Total number of frames received that are less than 5 bytes. This value is a part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| mediaIndStatsRxFramesTooLong | Number of received frames that exceed the MTU. This value is part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| mediaIndStatsRxShortPkts | Number of packets below the minimum packet size received. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |

Table E-56 Field Descriptions for the POS PM Table (continued)

| Field | Description | Cards Supported |
|--------------------------|---|---|
| hdlcInOctets | Number of bytes received (from the SONET/SDH path) prior to the bytes undergoing HLDC decapsulation by the policy engine. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| hdlcRxAborts | Number of received packets aborted on input. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, CE-100T-8, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| hdlcOutOctets | Number of bytes transmitted (to the SONET/SDH path) after the bytes undergoing HLDC encapsulation by the policy engine. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, ML100T, ML1000, MXP_MR_10DME ONS 15600 SONET: ASAP_4 ONS 15600 SDH: ASAP_4 |
| IfInPayloadCrcErrors | Number of payload CRC errors received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, MXP_MR_10DME |
| IfOutPayloadCrcErrors | Number of payload CRC errors transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, MXP_MR_10DME |
| IfOutOversizePackets | Number of oversize packets transmitted since the last counted reset. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-MR-10 ONS 15454 SDH: CE-1000-4, CE-100T-8, CE-MR-10, MXP_MR_10DME |
| hdlcPktDrops | Total number of packets that are dropped when the card is in HDLC mode and traffic is oversubscribed. | <ul style="list-style-type: none"> ONS 15454 SONET: CE-1000-4, MXP_MR_10DME ONS 15454 SDH: CE-1000-4, MXP_MR_10DME |
| Rx Utilization Stats (%) | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15600 SONET: ASAP_4 |
| Tx Utilization Stats (%) | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | <ul style="list-style-type: none"> ONS 15600 SONET: ASAP_4 |
| NE ID | Name of the selected NE. | — |

E.2.42 Regenerator Section PM Table—ONS 15310 MA SDH, ONS 15454 SDH

The Regenerator Section PM table shows performance data for the ONS 15310 MA SDH and ONS 15454 SDH regenerator section. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Regenerator Section PM table.

Table E-57 **Field Descriptions for the Regenerator Section PM Table**

| Field | Description | Cards Supported |
|---------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| RS-EB | Regenerator Section Errored Block (RS-EB) indicates that one or more bits are in error within a block. | <ul style="list-style-type: none"> • ONS 15310 MA SDH: CTX-2500 • ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-57 *Field Descriptions for the Regenerator Section PM Table (continued)*

| Field | Description | Cards Supported |
|--------|--|---|
| RS-ES | Regenerator Section Errored Second (RS-ES) is a one-second period with one or more errored blocks or at least one defect. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-SES | Regenerator Section Severely Errored Second (RS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-BBE | Regenerator Section Background Block Error (RS-BBE) is an errored block not occurring as part of an SES. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1, STM1_8, STM1E_12, STM4, STM4_4, STM16, STM64, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-UAS | Regenerator Section Unavailable Second (RS-UAS) is a count of the seconds when the regenerator section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as RS-UASs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as RS-UASs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MRC_4, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC192_XFP, OSC_CSM, OTU2_XP, STM1E_12, TXP_MR_10G, TXP_MR_10E, TXP_MR_2.5G, TXPP_MR_2.5G |

Table E-57 *Field Descriptions for the Regenerator Section PM Table (continued)*

| Field | Description | Cards Supported |
|---------|--|---|
| RS-ESR | Regenerator Section Errored Second Ratio (RS-ESR) is the ratio of errored seconds to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-SESR | Regenerator Section Severely Errored Second Ratio (RS-SESR) is the ratio of SES to total seconds in available time during a fixed measurement interval. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-BBER | Regenerator Section Background Block Error Ratio (RS-BBER) is the ratio of BBE to total blocks in available time during a fixed measurement interval. The count of total blocks excludes all blocks during SESs. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, ADM_10G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OTU2_XP, STM1E_12, TXP_MR_10E, TXP_MR_10G, TXP_MR_2.5G, TXPP_MR_2.5G |
| RS-OFS | Regenerator Section Out of Frame Seconds (RS-OSF) is the count of seconds when the Regenerator Section was out of frame. | <ul style="list-style-type: none"> ONS 15310 MA SDH: CTX-2500 ONS 15454 SDH: MRC_4, MRC_12_2.5G, MXP_MR_10DME, OC192_XFP, OTU2_XP |
| NE ID | Name of the selected NE. | — |

E.2.43 Regenerator Section PM Table—ONS 15600 SDH

The Regenerator Section PM table shows performance data for the ONS 15600 SDH regenerator section. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the Regenerator Section PM table.

Table E-58 **Field Descriptions for the Regenerator Section PM Table**

| Field | Description | Cards Supported |
|---------------------------|--|---------------------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| RS-EB | Regenerator Section Errored Block (RS-EB) indicates that one or more bits are in error within a block. | ASAP_4, STM16_16, STM64_4 |
| RS-ES | Regenerator Section Errored Second (RS-ES) is a one-second period with one or more errored blocks or at least one defect. | ASAP_4, STM16_16, STM64_4 |
| RS-SES | Regenerator Section Severely Errored Second (RS-SES) is a one-second period that contains 30 percent or more errored blocks or at least one defect. SES is a subset of ES. | ASAP_4, STM16_16, STM64_4 |
| RS-BBE | Regenerator Section Background Block Error (RS-BBE) is an errored block not occurring as part of an SES. | ASAP_4, STM16_16, STM64_4 |
| RS-UAS | Regenerator Section Unavailable Second (RS-UAS) is a count of the seconds when the regenerator section was unavailable. A section becomes unavailable when ten consecutive seconds occur that qualify as RS-UASs, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as RS-UASs. | — |
| RS-OFS | Regenerator Section Out of Frame Seconds (RS-OSF) is the count of seconds when the regenerator section was out of frame. | ASAP_4, STM16_16, STM64_4 |
| NE ID | Name of the selected NE. | — |

E.2.44 RPR 802.17 PM Table—ONS 15454 SONET, ONS 15454 SDH

The RPR 802.17 PM table shows performance data for the ONS 15454 SONET and ONS 15454 SDH ML-series cards in Resilient Packet Ring (RPR) mode (IEEE 802.17). You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the RPR 802.17 PM table. The fields shown depend on the RPR type selection.

Table E-59 **Field Descriptions for the RPR 802.17 PM Table**

| Field | Description | Cards Supported |
|-------------------------------------|--|---|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | — |
| rprSpanStatsInUcastClassA Frames | Number of received (PHY to MAC) class A unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassA Octets | Number of received (PHY to MAC) class A unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassB CirFrames | Number of received (PHY to MAC) class B CIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassB CirOctets | Number of received (PHY to MAC) class B CIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 *Field Descriptions for the RPR 802.17 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------------------------|---|---|
| rprSpanStatsInUcastClassB EirFrames | Number of received (PHY to MAC) class B EIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassB EirOctets | Number of received (PHY to MAC) class B EIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassC Frames | Number of received (PHY to MAC) class C unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInUcastClassC Octets | Number of received (PHY to MAC) class C unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassA Frames | Number of received (PHY to MAC) class A multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassA Octets | Number of received (PHY to MAC) class A multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassB CirFrames | Number of received (PHY to MAC) class B CIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassB CirOctets | Number of received (PHY to MAC) class B CIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassB EirFrames | Number of received (PHY to MAC) class B EIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassB EirOctets | Number of received (PHY to MAC) class B EIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassC Frames | Number of received (PHY to MAC) class C multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInMcastClassC Octets | Number of received (PHY to MAC) class C multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInCtrlFrames | Number of received (PHY to MAC) control frames processed by this MAC. This does not include control frames in transit; that is, a multicast control frame received from a ringlet will be counted as In but not Out. This does not include fairness or idle frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInOamEchoFrames | Number of received (PHY to MAC) OAM echo frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 Field Descriptions for the RPR 802.17 PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------------|---|---|
| rprSpanStatsInOamFlushFrames | Number of received (PHY to MAC) OAM flush frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInOamOrgFrames | Number of received (PHY to MAC) OAM org frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInTopoAtdFrames | Number of received (PHY to MAC) topology ATD frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInTopoChkSumFrames | Number of received (PHY to MAC) topology checksum frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsInTopoTpFrames | Number of received (PHY to MAC) topology TP frames processed by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassAFrames | Number of transmitted (PHY to MAC) class A unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassAOctets | Number of transmitted (PHY to MAC) class A unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassBCirFrames | Number of transmitted (PHY to MAC) class B CIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassBCirOctets | Number of transmitted (PHY to MAC) class B CIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassBEirFrames | Number of transmitted (PHY to MAC) class B EIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassBEirOctets | Number of transmitted (PHY to MAC) class B EIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassCFrames | Number of transmitted (PHY to MAC) class C unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutUcastClassCOctets | Number of transmitted (PHY to MAC) class C unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassAFrames | Number of transmitted (PHY to MAC) class A multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 *Field Descriptions for the RPR 802.17 PM Table (continued)*

| Field | Description | Cards Supported |
|-------------------------------------|---|---|
| rprSpanStatsOutMcastClassAOctets | Number of transmitted (PHY to MAC) class A multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassBCirFrames | Number of transmitted (PHY to MAC) class B CIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassBCirOctets | Number of transmitted (PHY to MAC) class B CIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassBEirFrames | Number of transmitted (PHY to MAC) class B EIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassBEirOctets | Number of transmitted (PHY to MAC) class B EIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassCFrames | Number of transmitted (PHY to MAC) class C multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutMcastClassCOctets | Number of transmitted (PHY to MAC) class C multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutCtrlFrames | Number of transmitted (PHY to MAC) control frames generated by this MAC. This does not include control frames in transit; that is, a multicast control frame transmitted from a ringlet will be counted as In but not Out. This does not include fairness or idle frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutOamEchoFrames | Number of transmitted (PHY to MAC) OAM echo frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutOamFlushFrames | Number of transmitted (PHY to MAC) OAM flush frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutOamOrgFrames | Number of transmitted (PHY to MAC) OAM org frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutTopoAtdFrames | Number of transmitted (PHY to MAC) topology ATD frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutTopoChkSumFrames | Number of transmitted (PHY to MAC) topology checksum frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanStatsOutTopoTpFrames | Number of transmitted (PHY to MAC) topology TP frames generated by this MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 *Field Descriptions for the RPR 802.17 PM Table (continued)*

| Field | Description | Cards Supported |
|--|---|---|
| rprClientStatsInUcastClass AFrames | Number of MAC-to-client class A unicast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass AOctets | Number of MAC-to-client class A unicast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass BCirFrames | Number of MAC-to-client class B CIR unicast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass BCirOctets | Number of MAC-to-client class B CIR unicast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass BEirFrames | Number of MAC-to-client class B EIR unicast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass BEirOctets | Number of MAC-to-client class B EIR unicast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass CFrames | Number of MAC-to-client class C unicast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInUcastClass COctets | Number of MAC-to-client class C unicast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass AFrames | Number of MAC-to-client class A multicast and broadcast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass AOctets | Number of MAC-to-client class A multicast and broadcast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass BCirFrames | Number of MAC-to-client class B CIR multicast and broadcast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass BCirOctets | Number of MAC-to-client class B CIR multicast and broadcast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass BEirFrames | Number of MAC-to-client class B EIR multicast and broadcast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClass BEirOctets | Number of MAC-to-client class B EIR multicast and broadcast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 *Field Descriptions for the RPR 802.17 PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------------------|--|---|
| rprClientStatsInMcastClassCFrames | Number of MAC-to-client class C multicast and broadcast frames in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInMcastClassCOctets | Number of MAC-to-client class C multicast and broadcast octets in the current interval. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsInBcastFrames | Number of MAC-to-client broadcast frames. This value is used only when deriving the multicast and broadcast packet counters for the interface MIB. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassAFrames | Number of client-to-MAC class A unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassAOctets | Number of client-to-MAC class A unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassBCirFrames | Number of client-to-MAC class B CIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassBCirOctets | Number of client-to-MAC class B CIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassBEirFrames | Number of client-to-MAC class B EIR unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassBEirOctets | Number of client-to-MAC class B EIR unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassCFrames | Number of client-to-MAC class C unicast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutUcastClassCOctets | Number of client-to-MAC class C unicast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassAFrames | Number of client-to-MAC class A multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassAOctets | Number of client-to-MAC class A multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassBCirFrames | Number of client-to-MAC class B CIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 Field Descriptions for the RPR 802.17 PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------------------|--|---|
| rprClientStatsOutMcastClassBCirOctets | Number of client-to-MAC class B CIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassBEirFrames | Number of client-to-MAC class B EIR multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassBEirOctets | Number of client-to-MAC class B EIR multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassCFrames | Number of client-to-MAC class C multicast and broadcast frames. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutMcastClassCOctets | Number of client-to-MAC class C multicast and broadcast octets. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprClientStatsOutBcastFrames | Number of client-to-MAC broadcast frames. This value is used only when deriving the multicast and broadcast packet counters for the interface MIB. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsTtlExpFrames | Number of received (PHY to MAC) frames that were dropped due to zero Time To Live (TTL). | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsTooLongFrames | Number of received (PHY to MAC) frames that exceed the maximum permitted frame size. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsTooShortFrames | Number of received (PHY to MAC) frames shorter than the minimum permitted frame size. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsBadHecFrames | Number of received (PHY to MAC) frames with HEC errors. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsBadFcsFrames | Number of received (PHY to MAC) data and control frames where the FCS value did not match the expected FCS value. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsSelfSrcUnicastFrames | Number of received (PHY to MAC) unicast frames that were transmitted by the station itself; that is, the source MAC is equal to the interface MAC. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsPmdAbortFrames | Number of received (PHY to MAC) frames that were aborted by the PMD. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsBadAddrFrames | Number of received (PHY to MAC) frames with invalid SA values. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |

Table E-59 Field Descriptions for the RPR 802.17 PM Table (continued)

| Field | Description | Cards Supported |
|----------------------------------|---|---|
| rprSpanErrorStatsBadParityFrames | Number of received (PHY to MAC) frames where the parity value does not match the expected parity value. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsContainedFrames | Number of received (PHY to MAC) frames that were removed due to context containment. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprSpanErrorStatsScffErrors | Number of received (PHY to MAC) errored SCFFs with bad parity, bad FCS, or both. | ONS 15454 SONET and SDH: ML100T, ML100X-8, ML1000, ML-MR-10 |
| rprErrorOversizeFrames | On the ML-MR-10 card, due to the limitation of the current field programmable gate array (FPGA), the frames coming from a gigabit port to an RPR port are sent to an ASIC driver, which discards the packets. | ONS 15454 SONET and SDH: ML-MR-10 |
| NE ID | Name of the selected NE. | — |

E.2.45 FC PM Table—ONS 15454 SONET, ONS 15454 SDH

The FC PM table shows performance data for the ONS 15454 SONET and ONS 15454 SDH. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the FC PM table.

Table E-60 Field Descriptions for the FC PM Table

| Field | Description | Cards Supported |
|-------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |

Table E-60 **Field Descriptions for the FC PM Table (continued)**

| Field | Description | Cards Supported |
|-------------------------------|--|--|
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | — |
| Rx Frames | Number of FC frames received without errors. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME |
| ifInOctets | Number of bytes received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME |
| Tx Frames | Number of transmitted FC frames. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, MXP_MR_10DME |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME |
| 8b10bInvalidOrderedSets | Number of 8b10b code violations. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| 8b10bStatsEncodingDisparities | Number of 8b10b disparity violations on the FC line side. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| fcStatsLinkRecoveries | Number of link recoveries. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME |

Table E-60 *Field Descriptions for the FC PM Table (continued)*

| Field | Description | Cards Supported |
|--------------------------------|---|--|
| mediaIndStatsRxFramesBadCRC | Number of received data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME |
| mediaIndStatsTxFramesBadCRC | Number of transmitted data frames with payload CRC errors when HDLC framing is used. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME |
| mediaIndStatsRxFramesTruncated | Total number of frames received that are less than 5 bytes. This value is a part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, FCMR, MXP_MR_10DME |
| mediaIndStatsRxFramesTooLong | Number of received frames that exceed the MTU. This value is part of HDLC and GFP port statistics. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E, MXP_MR_10DME ONS 15454 SDH: 2.5G_DM, FCMR, TXP_MR_10E, MXP_MR_10DME |
| mediaIndStatsRxLcvErrors | Number of L1 line code violations received for lower rate FC, which equate to invalid 8b10b ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| mediaIndStatsTxLcvErrors | Number of L1 line code violations transmitted for lower rate FC, which equate to invalid 8b10b ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| gfpStatsRxSBitErrors | Number of GFP single-bit errors in the CHEC. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| gfpStatsRxMBitErrors | Number of GFP multibit errors in the CHEC. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| gfpStatsRxTypeInvalid | Number of GFP invalid UPI fields in the type field. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |

Table E-60 Field Descriptions for the FC PM Table (continued)

| Field | Description | Cards Supported |
|-------------------------------|---|--|
| gfpStatsRxCRCErrors | Number of superblock CRC errors in the transparent GFP frame. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| ifInDiscards | Number of inbound packets that were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| ifOutDiscards | Number of outbound packets that were chosen to be discarded even though no errors had been detected to prevent their being transmitted. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| fcIngressRxDistanceExtBuffers | Number of buffers that are available to receive FC data from GFP frames. | — |
| fcEgressTxDistanceExtBuffers | Number of buffers that are available on the far end to receive FC data over GFP frames. | — |
| fcStatsRxCredits | Number of current received buffer-to-buffer credits. (Valid only if distance extension is enabled.) | — |
| fcStatsTxCredits | Number of current transmitted buffer-to-buffer credits. (Valid only if distance extension is enabled.) | — |
| fcStatsZeroTxCredits | Number of transmitted attempts that failed because of unavailable credits. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| gfpStatsCSFRaised | Number of GFP client signal fail frames. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| gfpStatsRoundTripLatency | Round-trip delay (in milliseconds [ms]) for the end-to-end FC transport. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| ifInErrors | Total number of received errors. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| txTotalPkts | Number of packets transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |

Table E-60 *Field Descriptions for the FC PM Table (continued)*

| Field | Description | Cards Supported |
|------------------------|---|--|
| rxTotalPkts | Number of packets received since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E ONS 15454 SDH: 2.5G_DM, 2.5G_DMP, FCMR, TXP_MR_10E |
| Rx Utilization | Received utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | — |
| Tx Utilization | Transmitted utilization, which is a percentage of utilization of the Ethernet segment on a scale of 0 to 100 percent. | — |
| FibreStatsRxRecvrReady | Number of current received receiver-ready buffer-to-buffer credits. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME ONS 15454 SDH: MXP_MR_10DME |
| FibreStatsTxRecvrReady | Number of current transmitted receiver-ready buffer-to-buffer credits. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME ONS 15454 SDH: MXP_MR_10DME |
| NE ID | Name of the selected NE. | — |

E.2.46 ISC PM Table—ONS 15454 SONET, ONS 15454 SDH

The ISC PM table shows performance data for the ONS 15454 SONET and ONS 15454 SDH. You can display 15-minute or 1-day increments.

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.4 Managing Real-Time PM Data, page 10-26](#).

The following table describes the fields in the ISC PM table.

Table E-61 *Field Descriptions for the ISC PM Table*

| Field | Description | Cards Supported |
|-------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |

Table E-61 Field Descriptions for the ISC PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Time Last Cleared | When the statistics were last reset. | <ul style="list-style-type: none"> ONS 15454 SONET: MXP_MR_10DME ONS 15454 SDH: MXP_MR_10DME |
| rxTotalPkts | Number of packets received since the last counter reset. | |
| ifInOctets | Number of bytes received since the last counter reset. | |
| txTotalPkts | Number of packets transmitted since the last counter reset. | |
| ifOutOctets | Number of bytes transmitted since the last counter reset. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| mediaIndStatsRxCvErrors | Number of L1 line code violations received for constant bit rate protocols, which equate to invalid 8b10b ordered sets. | |
| mediaIndStatsTxLcvErrors | Number of L1 line code violations transmitted for constant bit rate protocols, which equate to invalid 8b10b ordered sets. | <ul style="list-style-type: none"> ONS 15454 SONET: AR_MXP, AR_XP ONS 15454 SDH: AR_MXP, AR_XP |
| NE ID | Name of the selected NE. | — |

E.2.47 SONET Line PM Table (Far End)—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, ONS 15600 SONET

The SONET Line PM table shows far-end performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, and ONS 15600 SONET line. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET Line PM table.

Table E-62 *Field Descriptions for the SONET Line PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-L | Coding violations–line (CV-L) is a count of bit interleaved parity (BIP) errors detected at the line layer (that is, using the B2 bytes in the incoming SONET signal). Up to 8 x N BIP errors can be detected per STS-N frame; each error increments the current CV-L second register. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| ES-L | Errored seconds–line (ES-L) is a count of the seconds when at least one line-layer BIP error was detected or a line alarm indication signal (AIS-L) defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-62 *Field Descriptions for the SONET Line PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|-------|---|--|
| SES-L | Severely errored seconds–line (SES-L) is a count of the seconds when K (see GR-253 for values) or more line-layer BIP errors were detected or an AIS-L defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| UAS-L | Unavailable seconds–line (UAS-L) is a count of the seconds when the line is unavailable. A line becomes unavailable when ten consecutive seconds occur that qualify as SES-Ls, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Ls. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| FC-L | Failure count–line (FC-L) is a count of the number of near-end line failure events. A failure event begins when an AIS-L failure or a lower-layer traffic-related, near-end failure is declared. This failure event ends when the failure is cleared. A failure event that begins in one period and ends in another period is counted only in the period where it begins. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NE ID | Name of the selected NE. | — |

E.2.48 SONET Line PM Table (Near End)—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, ONS 15600 SONET

The SONET Line PM table shows near-end performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, and ONS 15600 SONET line. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET Line PM table.

Table E-63 **Field Descriptions for the SONET Line PM Table (Near End)**

| Field | Description | Cards Supported |
|---------------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-63 Field Descriptions for the SONET Line PM Table (Near End) (continued)

| Field | Description | Cards Supported |
|-------|--|--|
| CV-L | CV-L lists a count of bit interleaved parity (BIP) errors detected at the line-layer (using the B2 bytes in the incoming SONET signal). Up to 8 x N BIP errors can be detected per STS-N frame, with each error incrementing the current CV-L second register. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| ES-L | ES-L lists a count of the seconds when at least one line-layer BIP error was detected or a line alarm indication signal (AIS-L) defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| SES-L | SES-L lists a count of the seconds when K (see GR-253-CORE for values) or more line-layer BIP errors were detected or an AIS-L defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-63 Field Descriptions for the SONET Line PM Table (Near End) (continued)

| Field | Description | Cards Supported |
|-------|--|--|
| UAS-L | Unavailable seconds–line (UAS-L) lists a count of the seconds when the line is unavailable. A line becomes unavailable when ten consecutive seconds occur that qualify as SES-Ls, and continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Ls. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| FC-L | Failure count–line (FC-L) lists a count of the number of near-end line failure events. A failure event begins when an AIS-L failure is declared, or when a lower-layer, traffic-related, near-end failure is declared. This failure event ends when the failure is cleared. A failure event that begins in one period and ends in another period is counted only in the period where it begins. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSC | <p>In a 1 + 1 protection scheme for a working card, PSC is a count of the number of times service switches from a working card to a protection card plus the number of times service switches back to the working card. For a protection card, PSC is a count of the number of times service switches to a working card from a protection card plus the number of times service switches back to the protection card. The PSC PM is only applicable if revertive line-level protection switching is used. PSC is supported in revertive and nonrevertive modes.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-63 *Field Descriptions for the SONET Line PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|-------|---|--|
| PSD | <p>PSD applies to the length of time, in seconds, that service is carried on another line. For a working line, PSD is a count of the number of seconds that service was carried on the protection line. For the protection line, it is a count of the seconds that the line was used to carry service. The PSD PM is only applicable if revertive line-level protection switching is used. PSD is supported in revertive and nonrevertive modes.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC3, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSC-W | <p>For a working line in a 2-fiber BLSR, protection switching count–working (PSC-W) is a count of the number of times traffic switches away from the working capacity in the failed line and back to the working capacity after the failure is cleared. PSC-W increments on the failed working line and PSC increments on the active protect line.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSD-W | <p>For a working line in a 2-fiber BLSR, protection switching duration–working (PSD-W) is a count of the number of seconds that service was carried on the protection line. PSD-W increments on the failed working line and PSD increments on the active protect line.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSC-S | <p>In a four-fiber BLSR, protection switching count–span (PSC-S) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to the working line. A count is only incremented if span switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSD-S | <p>In a four-fiber BLSR, protection switching duration–span (PSD-S) is a count of the seconds that the protection line was used to carry service. A count is only incremented if span switching is used.</p> <p>Note This parameter is not supported for transponder or muxponder cards.</p> | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-63 *Field Descriptions for the SONET Line PM Table (Near End) (continued)*

| Field | Description | Cards Supported |
|-------|---|---|
| PSC-R | In a 4-fiber BLSR, protection switching count–ring (PSC-R) is a count of the number of times service switches from a working line to a protection line plus the number of times it switches back to a working line. A count is only incremented if ring switching is used. Note This parameter is not supported for transponder or muxponder cards. | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PSD-R | In a 4-fiber BLSR, protection switching duration–ring (PSD-R) is a count of the seconds that the protection line was used to carry service. A count is only incremented if ring switching is used. Note This parameter is not supported for transponder or muxponder cards. | <ul style="list-style-type: none"> ONS 15327: OC12, OC48 ONS 15454 SONET: MRC_4, MRC_12, MRC_12_2.5G, MXP_MR_10DME, OC12, OC12_4, OC48, OC192, OC192_XFP ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NE ID | Name of the selected NE. | — |

E.2.49 SONET Section PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, ONS 15600 SONET

The SONET Section PM table shows performance data at the section layer. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET Section PM table.

Table E-64 *Field Descriptions for the SONET Section PM Table*

| Field | Description | Cards Supported |
|-------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |

Table E-64 Field Descriptions for the SONET Section PM Table (continued)

| Field | Description | Cards Supported |
|---------------------------|---|---|
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Coding Violations–Section | Number of BIP errors detected at the section-layer (using the B1 byte in the incoming SONET signal). Up to eight section BIP errors can be detected per STS-N frame, with each error incrementing the current CV-S second register. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| Errored Seconds–Section | Number of seconds when at least one section-layer BIP error was detected or an SEF or LOS defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-64 Field Descriptions for the SONET Section PM Table (continued)

| Field | Description | Cards Supported |
|--|---|---|
| Severely Errored Seconds—Section | Number of seconds when K (see GR-253-CORE for value) or more section-layer BIP errors were detected or an SEF or LOS defect was present. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| Severely Errored Framing Seconds—Section | Number of seconds when an SEF defect was present. A SEF defect is expected to be present during most seconds when a LOS or LOF defect is present. However, there can be situations when that is not the case, and the SEFS-S parameter is only incremented based on the presence of the SEF defect. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, ADM_10G, DS3_EC1_48, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, MXP_2.5G_10G, MXP_MR_10DME, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OSC_CSM, OTU2_XP, TXP_MR_2.5G, TXPP_MR_2.5G, TXP_MR_10E, TXP_MR_10G ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NE ID | Name of the selected NE. | — |

E.2.50 SONET STS Path PM Table (Far End)—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, ONS 15600

The SONET STS Path PM table shows far-end performance data for the ONS 15310 CL, ONS 15310 MA, ONS 15327, ONS 15454 SONET, and ONS 15600 SONET STS path. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET STS Path PM table.

Table E-65 **Field Descriptions for the SONET STS Path PM Table (Far End)**

| Field | Description | Cards Supported |
|---------------------------|---|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-P | STS path coding violations (STS CV-P) is a count of BIP errors detected at the STS path layer (that is, using the B3 byte). Up to eight BIP errors can be detected per frame; each error increments the current CV-P second register. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: OC3, OC12, OC48, XTC • ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS1_E1_56, DS3N, DS3NE, DS3XM, DS3XM_12, FCMR, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OTU2_XP, TXP_MR_10E • ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-65 *Field Descriptions for the SONET STS Path PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|-------|--|--|
| ES-P | STS path errored seconds (STS ES-P) is a count of the seconds when at least one STS path BIP error was detected. A path alarm indication signal (AIS-P) defect (or a lower-layer, traffic-related, near-end defect) or a path loss of pointer (LOP-P) defect can also cause an STS ES-P. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, FCMR, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OTU2_XP, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| SES-P | STS path severely errored seconds (STS SES-P) is a count of the seconds when K (2400) or more STS path BIP errors were detected. An AIS-P defect (or a lower-layer, traffic-related, near-end defect) or an LOP-P defect can also cause an STS SES-P. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, FCMR, EC1, EC1N, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OTU2_XP, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| UAS-P | STS path unavailable seconds (STS UAS-P) is a count of the seconds when the STS path was unavailable. An STS path becomes unavailable when ten consecutive seconds occur that qualify as SES-Ps, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Ps. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OTU2_XP, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-65 *Field Descriptions for the SONET STS Path PM Table (Far End) (continued)*

| Field | Description | Cards Supported |
|-------|--|--|
| FC-P | STS path failure counts (STS FC-P) is a count of the number of near-end STS path failure events. A failure event begins when an AIS-P failure, an LOP-P failure, a UNEQ-P failure, or a path trace identifier mismatch (TIM-P) failure is declared, or if the STS PTE that is monitoring the path supports ERDI-P for that path. The failure event ends when these failures are cleared. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, MXP_2.5G_10E, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, OTU2_XP, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NE ID | Name of the selected NE. | — |

E.2.51 SONET STS Path PM Table—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, ONS 15600 SONET

The SONET STS Path PM table shows performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET, and ONS 15600 SONET STS path. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET STS Path PM table.

Table E-66 *Field Descriptions for the SONET STS Path PM Table*

| Field | Description | Cards Supported |
|-------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |

Table E-66 *Field Descriptions for the SONET STS Path PM Table (continued)*

| Field | Description | Cards Supported |
|---------------------------------|--|---|
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-P | STS path coding violations (STS CV-P) is a count of BIP errors detected at the STS path layer (that is, using the B3 byte). Up to eight BIP errors can be detected per frame; each error increments the current CV-P second register. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| ES-P | STS path errored seconds (STS ES-P) is a count of the seconds when at least one STS path BIP error was detected. A path alarm indication signal (AIS-P) defect (or a lower-layer, traffic-related, near-end defect) or a path loss of pointer (LOP-P) defect can also cause an STS ES-P. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-66 **Field Descriptions for the SONET STS Path PM Table (continued)**

| Field | Description | Cards Supported |
|-------|--|---|
| SES-P | STS path severely errored seconds (STS SES-P) is a count of the seconds when K (2400) or more STS path BIP errors were detected. An AIS-P defect (or a lower-layer, traffic-related, near-end defect) or an LOP-P defect can also cause an STS SES-P. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| UAS-P | STS path unavailable seconds (STS UAS-P) is a count of the seconds when the STS path was unavailable. An STS path becomes unavailable when ten consecutive seconds occur that qualify as SES-Ps, and it continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Ps. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| FC-P | STS path failure counts (STS FC-P) is a count of the number of near-end STS path failure events. A failure event begins when an AIS-P failure, an LOP-P failure, a UNEQ-P failure, or a path trace identifier mismatch (TIM-P) failure is declared, or if the STS PTE that is monitoring the path supports ERDI-P for that path. The failure event ends when these failures are cleared. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, XTC ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS-1, DS1N, DS1_E1_56, DS-3, DS3E, DS3_EC1_48, DS3I, DS3IN, DS3N, DS3NE, DS3XM, DS3XM_12, EC1, EC1N, FCMR, MRC_4, MRC_12, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-66 *Field Descriptions for the SONET STS Path PM Table (continued)*

| Field | Description | Cards Supported |
|-----------|--|---|
| PPJC-PDET | Positive pointer justification count, STS path detected (PPJC-Pdet) is a count of the positive pointer justifications detected on a particular path on an incoming SONET signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48, ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, MRC_4, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NPJC-PDET | Negative pointer justification count, STS path detected (NPJC-Pdet) is a count of the negative pointer justifications detected on a particular path on an incoming SONET signal. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, MRC_4, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| PPJC-PGEN | Positive pointer justification count, STS path generated (PPJC-Pgen) is a count of the positive pointer justifications generated for a particular path to reconcile the frequency of the SPE with the local clock. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, MRC_4, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |
| NPJC-PGEN | Negative pointer justification count, STS path generated (NPJC-Pgen) is a count of the negative pointer justifications generated for a particular path to reconcile the frequency of the SPE with the local clock. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, MRC_4, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E ONS 15600 SONET: ASAP_4, OC192_4, OC48_16 |

Table E-66 Field Descriptions for the SONET STS Path PM Table (continued)

| Field | Description | Cards Supported |
|-----------|--|---|
| PJ-DIFF | Sum of the absolute values of differences between positive transmitted and received, and negative transmitted and received. The important metric on pointer justification is not the exact counts, but how many were absorbed. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, MRC_4, MRC_12_2.5G, OC3, OC3_8, OC12, OC12_4, OC48, OC192, OC192_XFP, MXP_2.5G_10E, TXP_MR_10E |
| PJCS-Pdet | Number of pointer justification count seconds detected on a particular path. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: MRC_4, MRC_12_2.5G, OC192_XFP |
| PJCS-Pgen | Number of pointer justification count seconds generated for a particular path. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15454 SONET: MRC_4, MRC_12_2.5G, OC192_XFP |
| PJP-SEC | Number of positive pointer justification seconds. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, OC3, OC3_8, OC12, OC12_4, OC48, OC192, MXP_2.5G_10E, TXP_MR_10E |
| PJN-SEC | Number of negative pointer justification seconds. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15327: OC3, OC12, OC48 ONS 15454 SONET: 2.5G_DM, 2.5G_DMP, CE-100T-8, DS3_EC1_48, EC1, EC1N, FCMR, OC3, OC3_8, OC12, OC12_4, OC48, OC192, MXP_2.5G_10E, TXP_MR_10E |
| NE ID | Name of the selected NE. | — |

E.2.52 SONET VT1.5 PM Table

The SONET VT1.5 PM table contains PM information at the virtual tributary (VT1.5) layer. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.

- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET VT1.5 PM table.

Table E-67 **Field Descriptions for the SONET VT1.5 PM Table**

| Field | Description | Cards Supported |
|-------------------|---|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-V | Code violations VT layer (CV-V) is a count of the BIP errors detected at the VT path layer. Up to two BIP errors can be detected per VT Super Frame, with each error incrementing the current CV-V second register. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| ES-V | Errored seconds VT layer (ES-V) is a count of the seconds when at least one VT Path BIP error was detected. An AIS-V defect (a lower-layer, traffic-related, near-end defect) or a LOP-V defect can also cause an ES-V. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| SES-V | Severely errored seconds VT layer (SES-V) is a count of seconds when K (600) or more VT Path BIP errors were detected. SES-V can also be caused by an AIS-V defect (a lower-layer, traffic-related, near-end defect) or a LOP-V defect. | <ul style="list-style-type: none"> • ONS 15310 CL: CTX • ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 • ONS 15327: XTC • ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |

Table E-67 *Field Descriptions for the SONET VT1.5 PM Table (continued)*

| Field | Description | Cards Supported |
|-------|---|--|
| UAS-V | Unavailable second VT layer (UAS-V) is a count of the seconds when the VT path was unavailable. A VT path becomes unavailable when ten consecutive seconds occur that qualify as SES-Vs, and continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Vs. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| NE ID | Name of the selected NE. | — |

E.2.53 SONET VT2 PM Table

The SONET VT2 PM table contains PM information at the virtual tributary (VT2) layer. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET VT2 PM table.

Table E-68 *Field Descriptions for the SONET VT2 PM Table*

| Field | Description | Cards Supported |
|-------------------|--|-----------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-68 *Field Descriptions for the SONET VT2 PM Table (continued)*

| Field | Description | Cards Supported |
|-------|---|--|
| CV-V | Code violations VT layer (CV-V) is a count of the BIP errors detected at the VT path layer. Up to two BIP errors can be detected per VT Super Frame, with each error incrementing the current CV-V second register. | <ul style="list-style-type: none"> ONS 15454 SONET: DS1_E1_56 |
| ES-V | Errored seconds VT layer (ES-V) is a count of the seconds when at least one VT Path BIP error was detected. An AIS-V defect (a lower-layer, traffic-related, near-end defect) or a LOP-V defect can also cause an ES-V. | <ul style="list-style-type: none"> ONS 15454 SONET: DS1_E1_56 |
| SES-V | Severely errored seconds VT layer (SES-V) is a count of seconds when K (600) or more VT Path BIP errors were detected. SES-V can also be caused by an AIS-V defect (a lower-layer, traffic-related, near-end defect) or a LOP-V defect. | <ul style="list-style-type: none"> ONS 15454 SONET: DS1_E1_56 |
| UAS-V | Unavailable second VT layer (UAS-V) is a count of the seconds when the VT path was unavailable. A VT path becomes unavailable when ten consecutive seconds occur that qualify as SES-Vs, and continues to be unavailable until ten consecutive seconds occur that do not qualify as SES-Vs. | <ul style="list-style-type: none"> ONS 15454 SONET: DS1_E1_56 |
| NE ID | Name of the selected NE. | — |

E.2.54 SONET VT PM Table (Far End)—ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, ONS 15454 SONET

The SONET VT PM table shows far-end performance data for the ONS 15310 CL, ONS 15310 MA SONET, ONS 15327, and ONS 15454 SONET VT. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for *x* number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET VT PM table.

Table E-69 *Field Descriptions for the SONET VT PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------------|--|--|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-V | Coding violations—VT. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| ES-V | Errored seconds—VT. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS3XM, DS1_E1_56, DS3XM_12 |
| SES-V | Severely errored seconds—VT. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS3XM, DS1_E1_56, DS3XM_12 |
| UAS-V | Unavailable seconds—VT. | <ul style="list-style-type: none"> ONS 15310 CL: CTX ONS 15310 MA SONET: CTX_2500, DS1_28_DS3_EC1_3, DS1_84_DS3_EC1_3 ONS 15327: XTC ONS 15454 SONET: DS-1, DS1N, DS1_E1_56, DS3XM, DS3XM_12 |
| NE ID | Name of the selected NE. | — |

E.2.55 SONET VT2 PM Table (Far End)—ONS 15454 SONET

The SONET VT2 PM table shows far-end performance data for the ONS 15454 SONET VT2. You can display performance data for 15-minute, 1-day, or real-time increments:

- 15-minute—Data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- 1-day—Data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.
- Real-time—When a real-time PM session is running, it polls the NE for x number of attributes every 10 to 900 seconds. This feature allows you to examine the current value of a PM parameter in granularities finer than the standard 15-minute or 1-day interval. For more information, see [10.4.4 Managing Real-Time PM Data, page 10-26](#).

Performance monitoring can be done either on selected modules, or on specific locations in the NE. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

The following table describes the fields in the SONET VT2 PM table.

Table E-70 *Field Descriptions for the SONET VT2 PM Table (Far End)*

| Field | Description | Cards Supported |
|---------------------------------|--|------------------------------|
| Alias ID | Alias name of the selected NE. | — |
| Module Name | Module for which PM data is displayed. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| CV-V | Coding violations—VT. | • ONS 15454 SONET: DS1_E1_56 |
| ES-V | Errored seconds—VT. | • ONS 15454 SONET: DS1_E1_56 |
| SES-V | Severely errored seconds—VT. | • ONS 15454 SONET: DS1_E1_56 |
| UAS-V | Unavailable seconds—VT. | • ONS 15454 SONET: DS1_E1_56 |
| NE ID | Name of the selected NE. | — |

E.3 ONS 15530 and ONS 15540 PM Tables

This section describes the PM tables that are specific to ONS 15530 and ONS 15540 NEs.

E.3.1 Overview of Supported PM Parameters

The following ONS 15530 and ONS 15540 PM parameters are available on any of the interfaces listed in the following table. [Table E-72](#) to [Table E-77](#) list all the ONS 15530 and ONS 15540 PM parameters with the corresponding description and a list of interfaces supported.

Table E-71 ONS 155xx Optical Interfaces

| ONS 15530 | ONS 15540 |
|---------------------|--------------------|
| cevPortTransparent | cevPortTransparent |
| cevPortWave | cevPortWave |
| cevPortWaveEthPhy | cevPortWaveEthPhy |
| cevPort10GigEthPhy | cevport10GigEthBhy |
| cevPortWavePatch | cevPortWavePatch |
| cevPortEsconPhy | cevportWaveOSC |
| cevPortGEFCPhy | |
| cevPortVOAIn | |
| cevPortVOAFilterIn | |
| cevPortWaveOSC | |
| cevPortWaveSonetPhy | |
| cevPort2GFCPhy | |

Table E-72 Section PM Parameters—Near End

| Parameter | Description | Interfaces Supported |
|---------------------------|---|----------------------|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (time zone) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |

Table E-72 Section PM Parameters—Near End (continued)

| Parameter | Description | Interfaces Supported |
|-------------|---|---|
| CV-S | Coding violations—section. | cevPortTransparent ¹ , cevPortWave ¹ , cevPortWaveSonetPhy ¹ |
| ES-S | Errored seconds—section. | |
| SES-S | Severely errored seconds—section. | |
| SEFS-S | Severely errored framing seconds—section. | |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

1. Available on ONS 15530 and ONS 15540 NEs

Table E-73 Line PM Parameters

| Parameter | Description | Interfaces Supported |
|---------------------------------|---|---|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |
| Rx CVRD | Represents the counter associated with the number of code violations and running disparity errors encountered in the received direction. | cevPortTransparent ¹ , cevPortWave ¹ , cevPortWaveEthPhy ¹ , cevPort10GigEthPhy ¹ , cevPortEsconPhy, cevPortGEFCPhy |
| RX CRC | Represents the counter associated with CRC errors. It has a valid value only for interfaces that provide CRC error monitoring. | cevPortWaveEthPhy ² , cevPort10GigEthPhy ² , cevPortEsconPhy ² , cevPortGEFCPhy ² |
| TxEncapFarEndPacketErrors | Represents the counter associated with ESCON ingress error indications from the far end of an Ethernet network, where an ESCON stream. | cevPortEsconPhy ² |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

1. Available on ONS 15530 and ONS 15540 NEs.

2. Available on ONS 15530.

Table E-74 *CDL PM Parameters*

| Parameter | Description | Interfaces Supported |
|---------------------------------|---|--|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |
| Rx Header CRC Error | Number of CDL frames received with CDL header CRC errors. | cevPortWaveEthPhy ¹ , cevPort10GigEthPhy ¹ , cevPortWaveOSC ¹ |
| Rx Invalid FlowID | Number of CDL flow identifier lookup errors in the received direction. | cevPortWaveEthPhy ² , cevPort10GigEthPhy ² |
| Rx Non CDL Packets | Number of packets received without a CDL header on this interface. This counter is incremented only when CDL is enabled on this interface. | cevPortWaveEthPhy ¹ , cevPort10GigEthPhy ¹ |
| Net Ethernet CRC | Number of Ethernet packets with CRC errors. | cevPortGEFCPhy |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

1. Available on ONS 15530 and ONS 15540 NEs.

2. Available on ONS 15530.

Table E-75 *Physical PM Parameters*

| Parameter | Description | Interfaces Supported |
|---------------------------------|--|----------------------|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-75 Physical PM Parameters (continued)

| Parameter | Description | Interfaces Supported |
|----------------------|---|---|
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |
| Mean Optical Power | Mean optical power, received direction. | cevPortWavePatch ¹ |
| Optical Power (Max) | Maximum optical power, received direction. | |
| Optical Power (Min) | Minimum optical power, received direction. | |
| Optical Power (Max) | Maximum optical power, received direction, post adjustment. | cevPortVOAIn ² , cevPortVOAFilterIn ² |
| Optical Power (Min) | Minimum optical power, received direction, post adjustment. | |
| Optical Power (Mean) | Mean optical power, received direction, post adjustment. | |
| Ambient Temp (Max) | Maximum ambient temperature, received direction, post adjustment. | |
| Ambient Temp (Min) | Minimum ambient temperature, received direction, post adjustment. | |
| Ambient Temp (Mean) | Mean ambient temperature, received direction, post adjustment. | |
| Available Seconds | Number of seconds for which the performance data was accounted for in the interval. | cevPortWavePatch ¹ , cevPortVOAIn ² , cevPortVOAFilterIn ² |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

1. Available on ONS 15530 and ONS 15540 NEs.

2. Available on ONS 15530.

Table E-76 ONS 15530 Fiber Channel Port Errors PM Parameters

| Parameter | Description | Interfaces Supported |
|---------------------------------|--|----------------------|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |

Table E-76 ONS 15530 Fiber Channel Port Errors PM Parameters (continued)

| Parameter | Description | Interfaces Supported |
|---------------------------|---|-----------------------------------|
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |
| Rx Link Resets | Number of link resets (LR primitives) that are received. | cevPortGEFCPhy, cevPort2GFCPhy |
| Tx Link Resets | Number of link resets (LR primitives) that are transmitted. | |
| Link Resets | Number of times the reset link protocol was initiated on this port. | |
| Rx Offline Sequences | Number of offline primitive OLS received on this port. | |
| Tx Offline Sequences | Number of offline primitive OLS transmitted by this port. | |
| Loss of Synchs | Number of instances of synchronization loss detected at this port. This count is part of FC-PH's link error status block (LESB). | |
| Loss of Signals | Number of instances of signal loss detected at this port. This count is part of FC-PH's LESB. | cevPortGEFCPhy |
| Link Failures | Number of link failures. This count is part of FC-PH's LESB. | |
| Prim Seq Protocol Errors | Number of primitive sequence protocol errors detected at this port. This count is part of FC-PH's LESB. | |
| Invalid Tx Words | Number of invalid transmission words received at this port. This count is part of FC-PH's LESB. | |
| Invalid CRCs | Number of frames received with invalid CRC. This count is part of FC-PH's LESB. | |
| Invalid Ordered Sets | Number of invalid ordered sets received at this port. | |
| FrameTooLong | Number of frames received at this port where the frame length was greater than what was agreed to in FLOG/PLOGI. | |
| Truncated Frames | Number of frames received at this port where the frame length was less than the minimum indicated by the frame header, which is normally 24 bytes. | |
| Address Errors | Number of frames received with unknown addressing. | |
| Delimiter Errors | Number of invalid frame delimiters received at this port. | |
| Encoding Disparity Errors | Number of encoding disparity errors received at this port. | |
| Other Errors | Number of errors that were detected on this port but were not counted by another error counter in this row. | |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

Table E-77 ONS 15530 RMON Ethernet History PM Parameters

| Parameter | Description | Interfaces Supported |
|-------------------|--|----------------------|
| Alias ID | Alias name of the selected NE. | — |
| Physical Location | Slot and port number for which PM data is displayed. | — |

Table E-77 ONS 15530 RMON Ethernet History PM Parameters (continued)

| Parameter | Description | Interfaces Supported |
|---------------------------------|---|----------------------|
| Interface | Interface name of the selected NE. | — |
| Time Stamp (<i>time zone</i>) | When the data was collected. You can select GMT, Local, or User-Defined time for the Time Stamp display. Use the User Preferences dialog box to make your time zone selection. | — |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. | — |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” | — |
| Octets | Total number of octets of data (including the bad packets) received in the network. This also includes FCS octets but excludes framing bits. | cevPortGEFCPhy |
| Packets | Number of packets (including bad packets) received during the sampling interval. | |
| CRCAAlignErrors | Number of packets received during the sampling interval that had a length of 64 to 1518 octets but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). | |
| Undersize Packets | Number of packets received during the sampling interval that were less than 64 octets long excluding framing bits but including FCS octets. | |
| Oversize Packets | Number of packets received during the sampling interval that were longer than 1518 octets excluding framing bits but including FCS octets. | |
| Module Name | Module for which PM data is displayed. | — |
| NE ID | Name of the selected NE. | — |

E.3.2 CDL PM Table—ONS 15530 and ONS 15540

The Converged Data Link (CDL) PM table provides OAM&P in Ethernet packet-based optical networks without a SONET/SDH layer.

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- For the 1-day table, data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry. (Baseline entries are always marked invalid.) You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs](#), page 10-28.

Entries for performance parameters with associated threshold alarms (traps) are flagged in red. Orange represents a major performance problem, yellow represents a minor problem, and blue represents a warning.

**Note**

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the CDL PM table.

Table E-78 **Field Descriptions for the CDL PM Table**

| Field | Description |
|--------------------------------------|---|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE: slot, subslot, and port. |
| Interface | Whether the interface is transparent or trunk side. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| RX HEC | Number of CDL frames received with CDL Header CRC errors. |
| RX Non CDL | Number of packets received without a CDL header on this interface. |
| RX Invalid Flow ID | Number of CDL Flow Identifier lookup errors in the received direction. |
| Net Ethernet CRC (ONS 15530 only) | Number of net Ethernet CRC errors. |
| Module Name | Name of the module. |
| NE ID | Name of the selected NE. |

E.3.3 Ethernet History PM Table—ONS 15530

The Ethernet History PM table shows Ethernet history performance data for ONS 15530 interfaces.

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- For the 1-day table, data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry. (Baseline entries are always marked invalid.) You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

Entries for performance parameters with associated threshold alarms (traps) are flagged in red. Orange represents a major performance problem, yellow represents a minor problem, and blue represents a warning.

**Note**

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the Ethernet History PM table.

Table E-79 **Field Descriptions for the Ethernet History PM Table**

| Field | Description |
|----------------------|--|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE: slot, subslot, and port. |
| Interface | Name of the interface on which the performance data was collected. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| Octets | Total number of octets of data (including those in bad packets) received on the network (excluding framing bits but including FCS octets). |
| Packets | Number of packets (including bad packets) received during this sampling interval. |
| CRC Alignment Errors | Number of packets received during this sampling interval that had a length (excluding framing bits but including FCS octets) from 64 to 1518 octets, inclusive, but had either a bad FCS with an integral number of octets (FCS error) or a bad FCS with a nonintegral number of octets (alignment error). |
| Under Size Packets | Number of packets received during this sampling interval that were less than 64 octets long (excluding framing bits but including FCS octets) and were otherwise well formed. |
| Over Size Packets | Number of packets received during this sampling interval that were longer than 1518 octets (excluding framing bits but including FCS octets) but were otherwise well formed. |
| Module Name | Name of the selected NE module. |
| NE ID | Name of the selected NE. |

E.3.4 FC Port Error PM Table—ONS 15530

The Fibre Channel (FC) Port Error PM table shows performance data for the ONS 15530.

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- For the 1-day table, data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry. (Baseline entries are always marked invalid.) You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

Entries for performance parameters with associated threshold alarms (traps) are flagged in red. Orange represents a major performance problem, yellow represents a minor problem, and blue represents a warning.

**Note**

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the FC Port Error PM table.

Table E-80 **Field Descriptions for the FC Port Error PM Table**

| Field | Description |
|------------------------------------|---|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE—slot, subslot, and port. |
| Interface | Whether the interface is transparent or trunk side. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| Rx Link Resets | Number of link resets (LR primitives) received. |
| Tx Link Resets | Number of link resets (LR primitive) transmitted. |
| Link Resets | Number of times the reset link protocol was initiated on the port. This includes the number of Loop Initialization Primitive (LIP) events on an arbitrated loop port. |
| Rx Offline Sequences | Number of offline primitive OLS received at the port. |
| Tx Offline Sequences | Number of offline primitive OLS transmitted by the port. |
| Link Failures | Number of link failures. This count is part of the FC-PH Link Error Status Block (LESB). |
| Loss of Synchs | Number of instances of synchronization loss detected at the port. This count is part of the FC-PH LESB. |
| Loss of Signals | Number of instances of signal loss detected at the port. This count is part of the FC-PH LESB. |
| Primitive Sequence Protocol Errors | Number of primitive sequence protocol errors detected at the port. This count is part of the CFC-PH LESB. |
| Invalid Tx Words | Number of invalid transmission words received at the port. This count is part of the FC-PH LESB. |
| Invalid CRCs | Number of frames received with an invalid CRC. This count is part of the FC-PH LESB. |
| Invalid Ordered Sets | Number of invalid ordered sets received at the port. |
| Frame Too Longs | Number of frames received at the port where the frame length was greater than what was agreed to in FLOGI/PLOGI. This could be caused by losing the end of frame delimiter. |

Table E-80 **Field Descriptions for the FC Port Error PM Table (continued)**

| Field | Description |
|---------------------------|--|
| Truncated Frames | Number of frames received at the port where the frame length was less than the minimum indicated by the frame header (normally 24 bytes, but it could be more if the DFCTL field indicates an optional header should have been present). |
| Address Errors | Number of frames received with unknown addressing, such as an unknown SID or DID. The SID or DID is not known to the routing algorithm. |
| Delimiter Errors | Number of invalid frame delimiters received at the port. An example is a frame with a class 2 start and a class 3 at the end. |
| Encoding Disparity Errors | Number of encoding disparity errors received at the port. |
| Other Errors | Number of errors that were detected on the port but were not counted by any other error counter in the row. |
| Module Name | Name of the selected NE module. |
| NE ID | Name of the selected NE. |

E.3.5 Line PM Table—ONS 15530 and ONS 15540

The Line PM table shows physical performance data for ONS 15530 and ONS 15540 client and trunk side interfaces. The data shown is from the following modules:

- The transparent and trunk side interfaces of the transponders
- The Optical Supervisory Channel (OSC) interface on the MUX cards

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- For the 1-day table, data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry. (Baseline entries are always marked invalid.) You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

Entries for performance parameters with associated threshold alarms (traps) are flagged in red. Orange represents a major performance problem, yellow represents a minor problem, and blue represents a warning.



Note

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the Line PM table.

Table E-81 **Field Descriptions for the Line PM Table**

| Field | Description |
|-------------------|---|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE—slot, subslot, and port. |
| Interface | Whether the interface is transparent or trunk side. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| RX CVRD | Code violations and running disparity errors encountered in the received direction for both types of interfaces. A threshold is associated with this parameter, and the table cell will be flagged in red when the parameter exceeds the threshold. You can set thresholds by using the command line interface (CLI). |
| RX CRC | Number of CRC errors. This column has a valid value only for interfaces that provide CRC error monitoring. This column is not applicable to ONS 15540. |
| Tx Packet Errors | Number of ingress error indications from the far end of an Ethernet network, where an ESCON stream is encapsulated in Ethernet packets. This number is incremented whenever an ESCON packet or control character has 8b/10b code violations or running disparity errors in the ingress direction at the far end of the Ethernet network. This column has a valid value only for ESCON interfaces where Ethernet encapsulation is performed. This column is not applicable to ONS 15540. |
| Module Name | Name of the selected module. |
| NE ID | Name of the selected NE. |

E.3.6 Physical PM Table—ONS 15530 and ONS 15540

The Physical PM table shows physical performance data for ONS 15530 and ONS 15540 client and trunk side interfaces. The data shown is from the following modules:

- The transparent and trunk side interfaces of the transponders
- The OSC interface on the MUX cards

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on). The data shown represents the difference in counter values between successive 15-minute intervals.
- For the 1-day table, data is collected at midnight GMT. The data shown represents the difference between the counter values read at successive midnights.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry. (Baseline entries are always marked invalid.) You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs](#), page 10-28.

Entries for performance parameters with associated threshold alarms (traps) are flagged in red. Orange represents a major performance problem, yellow represents a minor problem, and blue represents a warning.

**Note**

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the Physical PM table.

Table E-82 **Field Descriptions for the Physical PM Table**

| Field | Description |
|----------------------------|---|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE: slot, subslot, and port. |
| Interface | Whether the interface is transparent or trunk side. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as the baseline entry. The description of the baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| Mean Power | Mean laser power in dBm. |
| Maximum Power | Maximum laser power in dBm. |
| Minimum Power | Minimum laser power in dBm. |
| Mean Device Temperature | Mean device temperature in degrees Celsius. Note This field applies only to the ONS 15530 NE. |
| Maximum Device Temperature | Maximum device temperature in degrees Celsius. Note This field applies only to the ONS 15530 NE. |
| Minimum Device Temperature | Minimum device temperature in degrees Celsius. Note This field applies only to the ONS 15530 NE. |
| Direction | Line direction. |
| Available Seconds | Available seconds. |
| Module Name | Name of the module. |
| NE ID | Name of the selected NE. |

E.3.7 SONET Section PM Table—ONS 15530 and ONS 15540

The SONET Section PM table shows section layer performance data for ONS 15530 and ONS 15540 SONET interfaces. The data shown is from modules with the protocol configured as SONET or SDH. You can use the Plot tab to plot the data in a graphical view that is stored in the Prime Optical database. See [10.4.6 Using PM Data Graphs, page 10-28](#).

You can display performance data for 15-minute or 1-day increments:

- For the 15-minute table, data is collected at the quarter-hour (for example, at 10:00, 10:15, and so on).
- For the 1-day table, the values shown are the total of 96 15-minute values, ending at midnight GMT.

Entries for performance parameters with associated threshold alarms (traps) are shown in red. Orange represents a major problem, yellow represents a minor problem, and blue represents a warning.

When the NE is rebooted, all performance data is cleared on the NE and the first new entry for each interface becomes the new baseline entry (baseline entries are always marked invalid).


Note

Display of performance data is affected by settings in the Control Panel.

The following table describes the fields in the SONET Section PM table.

Table E-83 **Field Descriptions for the SONET Section PM Table**

| Field | Description |
|--|--|
| Alias ID | Alias name of the selected NE. |
| Physical Location | Physical location of the NE—slot, subslot, and port. |
| Interface | Whether the interface is transparent or wave. |
| Time Stamp | Time when the performance statistics were collected. |
| Validity | Whether the data in the entry is valid. Note The first entry for each interface and port is always invalid and is used as a baseline entry. The description field of a baseline entry is “invalid—not enough time has elapsed.” |
| Maintenance | Whether the NE was under maintenance when the performance data was collected. |
| Errored Seconds—Section | Number of errored seconds encountered by the SONET/SDH section in the current interval. An errored second is a one-second period with one or more coding violations at that layer or one or more incoming defects at that layer. |
| Severely Errored Seconds—Section | Number of severely errored seconds encountered by the SONET/SDH section in the current interval. A severely errored second is a one-second period with x or more coding violations at that layer one or more incoming defects at that layer. The value of x depends on the line rate and bit error rate. |
| Severely Errored Framing Seconds—Section | Number of severely errored framing seconds encountered by the SONET/SDH section in the current interval. A severely errored framing second is a one-second period containing one or more severely errored framing events. |
| Code Violations—Section | Number of coding violations encountered by the SONET/SDH section in the interval. Coding violations are bit interleaved parity errors that are detected in the incoming signal. A threshold is associated with this parameter, and the table cell will be flagged in red when it exceeds the threshold. You can set thresholds by using the CLI. |

Table E-83 *Field Descriptions for the SONET Section PM Table (continued)*

| Field | Description |
|-------------|------------------------------|
| Module Name | Name of the selected module. |
| NE ID | Name of the selected NE. |