

Release Notes for Cisco RV110W Firmware Version 1.2.0.10

December, 2013

Contents

This document includes the following topics:

- Changes Since Firmware Release 1.2.0.9
- Related Information

Changes Since Firmware Release 1.2.0.9

Important Notes

Code optimization for web GUI interfaces.

Resolved Issues in Firmware Version 1.2.0.10

| Ref Number | Description |
|------------|---|
| CSCto97111 | Port Forwarding cannot forward traffic after the RV110W operates for a long time. |

Known Issues in Release 1.2.0.10

Issue—The RV110W cannot block previously-installed ActiveX applications when *Block ActiveX* is enabled.

Workaround—Clear the cache on the browser before beginning configuration.

Issue—When adding a new VLAN, the user loses connection to the GUI.

Workaround—None; the management interface should become available in approximately 15 seconds.

Issue—If DHCP server is turned off on the RV110W, the status page still displays the DHCP server as "on," even if there is only one VLAN.

Workaround-None.

Issue—In the Logging page, the email Settings Test button is unavailable when the *authentication with SMTP server* parameter is set to *none*.

Workaround—Do not use the *none* option; use one of the other authentication methods.

Issue—When the SNMPv3 traps are set with the *Authentication and No Privacy* or *Authentication and Privacy* security levels, no SNMPv3 traps are seen.

Workaround—Set SNMPv3 traps with the security level of *No Authentication and No Privacy.*

Issue—Minor online help navigation bar display issue in Google Chrome browser.

Workaround—Open Chrome browser using the command-line interface:

- Windows: chrome.exe --allow-file-access-from-files
- Mac: open /Applications/Google\ Chrome.app --args --allow-file-accessfrom-files

Issue—Text-based configuration files cannot be modified by the user and then uploaded to the router.

Workaround-None

Issue—Degraded performance with certain wireless client adapters.

Workaround—Upgrade to the latest drivers. Enable Wireless Multimedia (WMM) and disable the power save mode in the wireless client driver properties.

Related Information

| Support | | |
|---------------------------|--|--|
| Support | 1 | |
| Cisco Small Business | www.cisco.com/go/smallbizsupport | |
| Support Community | | |
| Cisco Small Business | www.cisco.com/go/smallbizhelp | |
| Support and Resources | | |
| Phone Support Contacts | www.cisco.com/en/US/support/ | |
| | tsd_cisco_small_business | |
| | _support_center_contacts.html | |
| Cisco Small Business | www.cisco.com/go/software | |
| Firmware Downloads | | |
| | Select a link to download firmware for Cisco Small | |
| | Business Products. No login is required. | |
| Product Documentation | | |
| Cisco Small Business RV | www.cisco.com/go/smallbizrouters | |
| Series Routers | | |
| Cisco Small Business | 1 | |
| Cisco Partner Central for | www.cisco.com/web/partners/sell/smb | |
| Small Business (Partner | · | |
| Login Required) | | |
| Cisco Small Business | www.cisco.com/smb | |
| Home | | |
| | | |

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2013 Cisco Systems, Inc. All rights reserved.

OL-31269-01