



## **A**

<b>AAA</b>	Authentication, Authorization, and Accounting.
<b>ACS</b>	Cisco Access Control Server.
<b>AES</b>	Advanced Encryption Standard.
<b>AP</b>	Access point.

## **B**

<b>BSSID</b>	Basic service set identifier.
--------------	-------------------------------

## **C**

<b>CAM</b>	Clean Access Manager.
<b>CCMP</b>	Counter Mode with Cipher Block Chaining Message Authentication Code Protocol.
<b>CCX</b>	Cisco Compatible Extensions.
<b>CKIP</b>	Cisco Key Integrity Protocol.
<b>CMIC</b>	Cisco Message Integrity Check.
<b>CSA</b>	Cisco Security Agent.
<b>CSSC</b>	Cisco Secure Services Client. Cisco Key Integrity Protocol (CKIP) and Cisco Message Integrity Check (CMIC).

## **D**

<b>DoS</b>	Denial of service.
------------	--------------------

## **E**

<b>EAP</b>	Extensible Authentication Protocol.
<b>EAP-FAST</b>	EAP-Flexible Authentication via Secured Tunnel.

<b>EAP-TLS</b>	EAP-Transport Layer Security.
<b>EIRP</b>	Effective Isotropic Radiated Power.
<b>ESSID</b>	Extended service set identifier, commonly referred to as an SSID.

## **F**

<b>FWSM</b>	Firewall Services Module.
-------------	---------------------------

## **I**

<b>IDS</b>	Intrusion detection system.
<b>IPS</b>	Intrusion prevention system.

## **L**

<b>LAP</b>	LWAPP Access Point.
<b>LBS</b>	Location-based service
<b>LWAPP</b>	Lightweight Access Point Protocol.

## **M**

<b>MAP</b>	Mesh AP
<b>MFP</b>	Management frame protection.
<b>MIC</b>	Message integrity check.

## **N**

<b>NAC</b>	Network Admission Control.
------------	----------------------------

## **O**

<b>OFDM</b>	Orthogonal Frequency Division Multiplexing.
-------------	---

**P**

<b>PEAP GTC</b>	Protected EAP Generic Token Card.
<b>PEAP MSCHAP</b>	Protected EAP Microsoft Challenge Handshake Authentication Protocol.
<b>PKI</b>	Public Key Infrastructure.

**R**

<b>RADIUS</b>	Remote Authentication Dial-In User Service.
<b>RF</b>	Radio frequency.
<b>RFID</b>	Radio frequency. Radio-frequency identification.
<b>RLDP</b>	Rogue Location Discovery Protocol.
<b>RSSI</b>	Received signal strength indication.

**S**

<b>SNR</b>	Signal-to-noise ratio.
<b>SSID</b>	IEEE Extended Service Set Identifier.
<b>SSO</b>	Single sign-on.
<b>SVI</b>	Switched virtual interfaces.

**T**

<b>TKIP</b>	Temporal Key Integrity Protocol.
<b>TLS</b>	Transport Layer Security.

**W**

<b>WCS</b>	Wireless Control System.
<b>WEP</b>	Wired Equivalent Privacy.
<b>Wi-Fi</b>	Wi-Fi is the brand of the Wi-Fi Alliance, which certifies interoperability of products and services based on IEEE 802.11 technology.
<b>WiSM</b>	Wireless Services Module.

<b>WLAN</b>	Wireless LAN.
<b>WLC</b>	Wireless LAN Controller.
<b>WLCM</b>	Wireless LAN Controller Module.
<b>WLSM</b>	Wireless LAN Services Module.
<b>WMM</b>	Wi-Fi Multimedia
<b>WPA</b>	Wi-Fi Protected Access.