

L Commands

This chapter describes the Cisco NX-OS Border Gateway Protocol (BGP) commands that begin with L.

Send comments to nexus5k-docfeedback@cisco.com

local-as

To configure the Border Gateway Protocol (BGP) local autonomous system (AS) number, use the **local-as** command.

local-as as-number

Syntax Description	as-number	(Optional) Autonomous system number. The AS number can be a 16-bit integer or a 32-bit integer in the form of <higher 16-bit="" decimal="" number="">.<lower 16-bit="" decimal="" number="">.</lower></higher>	
Command Default	None		
Command Modes	Router VRF m	ode	
Command History	Release	Modification	
	5.0(3)N1(1)	This command was introduced.	
Usage Guidelines	This command	l requires the LAN Enterprise Services license.	
Examples	This example shows how to configure the local AS number for BGP:		
	<pre>switch# configure terminal switch(config)# router bgp 65536.33 switch(config-router)# vrf red switch(config-router-vrf)# local-as 65536.33</pre>		
Related Commands	Command	Description	
	show bgp	Displays information about BGP.	

Send comments to nexus5k-docfeedback@cisco.com

low-memory exempt

To exempt a Border Gateway Protocol (BGP) neighbor from a low-memory shutdown, use the **low-memory exempt** command. To make a BGP neighbor eligible for a low-memory shutdown, use the **no** form of this command.

low-memory exempt

no low-memory exempt

Syntax Description	This command has no arguments or keywords.		
Command Default	Some eBGP peers shut down for severe memory alerts.		
Command Modes	Neighbor configuration mode		
Command History	Release	Modification	
	5.0(3)N1(1)	This command was introduced.	
Usage Guidelines	This command requires the LAN Enterprise Services license.		
Examples	This example shows how to exempt a neighbor from low-memory shutdown:		
	<pre>switch(config)# router bgp 1.0 switch(config-router)# neighbor 192.0.2.0/24 remote-as 1.5 switch(config-router-af)# low-memory exempt</pre>		
Related Commands	Command	Description	
	feature bgp	Enables BGP.	

Send comments to nexus5k-docfeedback@cisco.com