

B Commands

This chapter describes the Cisco NX-OS commands that begin with B that are used to manage a Cisco Nexus 2000 Series Fabric Extender from a Cisco Nexus 5000 Series switch.

Send comments to nexus5k-docfeedback@cisco.com

beacon

To turn on the locator beacon LED of a Fabric Extender, use the **beacon** command. To turn off the locator beacon LED, use the **no** form of this command.

beacon

no beacon

- **Syntax Description** This command has no arguments or keywords.
- Command Default None

Command Modes Fabric extender configuration mode

Command History	Release	Modification
	4.0(1a)N2(1)	This command was introduced.
	4.1(3)N1(1)	This command was deprecated, and the locator-led command was introduced.

Usage Guidelines Use the **beacon** command to toggle the locator beacon LED of a Fabric Extender, which allows you to easily identify the machine in a busy data center.

Examples

This example shows how to turn on the locator beacon LED for a specific Fabric Extender chassis:

switch# configure terminal
switch(config)# fex 101
switch(config-fex)# beacon

This example shows how to turn off the locator beacon LED for a specific Fabric Extender chassis:

switch# configure terminal
switch(config)# fex 101
switch(config-fex)# no beacon

Related Commands	Command	Description
	fex	Creates a Fabric Extender and enters Fabric Extender configuration mode.
	show fex	Displays all configured Fabric Extender chassis connected to the switch.