

E Commands

This chapter describes the basic Cisco NX-OS system commands that begin with E.

echo

To display a text string on the terminal, use the **echo** command.

echo [text]

Syntax Description	text	(Optional) Text string to display. The text string is alphanumeric, case sensitive, can contain spaces, and has a maximum length of 200 characters. The text string can also contain references to CLI variables.	
Command Default	Blank line		
Command Modes	EXEC mode		
Command History	Release	Modification	
	5.0(2)N1(1)	This command was introduced.	
Usage Guidelines	You can use this command in a command script to display status information or prompts while the script is running.		
Examples	This example shows how to display a blank line at the command prompt: switch# echo		
	This example shows how to display a line of text at the command prompt:		
	switch# echo Script	run at \$(TIMESTAMP).	
Related Commands	Command	Description	
	run-script	Runs command scripts.	
	show cli variables	Displays the CLI variables.	

end			
	To end the current configuration session and return to EXEC mode, use the end command.		
	end		
Syntax Description	This command has no arguments or keywords.		
Command Default	None		
Command Modes	Global configuration mode		
Command History	Release	Modification	
	5.0(2)N1(1)	This command was introduced.	
Usage Guidelines	This command returns you to EXEC mode regardless of which configuration mode you are in. Use this command when you are done configuring the system and you want to return to EXEC mode to perform verification steps.		
Examples	This example shows how the end command is used to exit from interface configuration mode and return to EXEC mode. A show command is used to verify the configuration.		
	<pre>switch# configure terminal switch(config)# interface ethernet 1/1 switch(config-if)# switchport host switch(config-if)# end switch# show interface ethernet 1/1</pre>		
Related Commands	Command	Description	
	exit (EXEC)	Terminates the active terminal session by logging off the switch.	

Exits from the current configuration mode.

exit (global)

exec-timeout

To configure the inactive session timeout on the console port or the virtual terminal, use the **exec-timeout** command. To revert to the default, use the **no** form of this command.

exec-timeout *minutes*

no exec-timeout

Syntax Description	minutes	Number of minutes. The range is from 0 to 525600. A setting of 0 minutes disables the timeout.		
Command Default	Timeout is disabled.			
Command Modes	Terminal line configuration mode			
Command History	Release	Modification		
	5.0(2)N1(1)	This command was introduced.		
Usage Guidelines	You can configure the console port only from a session on the console port.			
Examples	This example shows how to configure the inactive session timeout for the console port: switch# configure terminal switch(config)# line console switch(config-console)# exec-timeout 30			
	This example shows how to revert to the default inactive session timeout for the console port:			
	<pre>switch# configure terminal switch(config)# line console switch(config-console)# no exec-timeout</pre>			
	This example shows how to configure the inactive session timeout for the virtual terminal:			
	<pre>switch# configure terminal switch(config)# line vty switch(config-line)# exec-timeout 30</pre>			
	This example shows how to revert to the default inactive session timeout for the virtual terminal:			
	switch# configure terminal switch(config)# line vty switch(config-line)# no exec-timeout			

Related Commands	Command	Description
	line console	Enters the console terminal configuration mode.
	line vty	Enters the virtual terminal configuration mode.
	show running-config	Displays the running configuration.

exit (EXEC)

To close an active terminal session by logging off the switch, use the exit command.

exit **Syntax Description** This command has no arguments or keywords. **Command Default** None **Command Modes** EXEC mode **Command History** Release Modification 5.0(2)N1(1) This command was introduced. Examples This example shows how the exit (global) command is used to move from configuration mode to EXEC mode and the exit (EXEC) command is used to log off (exit the active session): switch(config)# exit switch# exit **Related Commands** Command Description end Ends your configuration session by exiting to EXEC mode. exit (global) Exits from the current configuration mode to the next highest configuration mode.

exit (global)

To exit any configuration mode to the next highest mode in the CLI mode hierarchy, use the **exit** command in any configuration mode.

exit

Syntax Description	This command has no arguments or keywords.		
Command Default	None		
Command Modes	All configuration modes		
Command History	Release	Modification	
	5.0(2)N1(1)	This command was introduced.	
Usage Guidelines	Use the exit command in configuration mode to return to EXEC mode. Use the exit command in interface, VLAN, or zone configuration mode to return to configuration mode. At the highest level, EXEC mode, the exit command will exit the EXEC mode and disconnect from the switch (see the description of the exit (EXEC) command for details).		
Examples	This example shows how to exit from the interface configuration mode and to return to the configuration mode: switch(config-if)# exit switch(config)#		
Related Commands	Command	Description	
	end	Ends your configuration session by exiting to privileged EXEC mode.	
	exit (EXEC)	Terminates the active terminal session by logging off the switch.	