



S Commands

This chapter describes the Cisco NX-OS Enhanced Interior Gateway Routing Protocol (EIGRP) commands that begin with S.

shutdown (EIGRP)

To shut down an instance of Enhanced Interior Gateway Routing Protocol (EIGRP), use the **shutdown** command. To disable this function, use the **no** form of this command.

shutdown

no shutdown

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	Enabled
------------------------	---------

Command Modes	Address family configuration mode Router configuration mode Router VRF configuration mode
----------------------	---

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Usage Guidelines	Use the shutdown command to disable an instance of EIGRP without removing the configuration. This command requires the LAN Base Services license.
-------------------------	---

Examples	This example shows how to disable eigrp 209:
-----------------	--

```
switch(config)# router eigrp 209
switch(config-router)# shutdown
switch(config-router)#
```

Related Commands	Command	Description
	copy running-config startup-config	Saves the configuration in the startup configuration file.
	show ip eigrp interfaces	Displays information about EIGRP interfaces.

stub

To configure a router as a stub using the Enhanced Interior Gateway Routing Protocol (EIGRP), use the **stub** command. To disable the EIGRP stub routing feature, use the **no** form of this command.

stub [**direct** | **leak-map** *map-name*] **receive-only** | **redistributed**]

no stub [**direct** | **leak-map** *map-name*] **receive-only** | **redistributed**]

Syntax Description

direct	(Optional) Advertises directly connected routes.
leak-map <i>map-name</i>	(Optional) Allows dynamic prefixes based on the leak map.
receive-only	(Optional) Sets the router as a receive-only neighbor.
redistributed	(Optional) Advertises redistributed routes from other protocols and autonomous systems.

Command Default

Disabled

Command Modes

Address-family configuration mode
Router configuration mode
Router VRF configuration mode

Command History

Release	Modification
5.2(1)N1(1)	This command was introduced.

Usage Guidelines

Use the **stub** command to configure a router as a stub where the router directs all IP traffic to a distribution router.

The **direct** keyword permits EIGRP stub routing to advertise connected routes. This option is enabled by default.

The **receive-only** keyword restricts the router from sharing any of its routes with any other router in that EIGRP autonomous system, and the **receive-only** keyword does not permit any other option to be specified because it prevents any type of route from being sent.

The **redistributed** keyword permits EIGRP stub routing to send other routing protocols and autonomous systems. Without the configuration of this option, EIGRP does not advertise redistributed routes.

If you use any of these four keywords (**direct**, **leak-map**, **receive-only**, **redistributed**) with the **stub** command, only the route types specified by the particular keyword(s) are advertised.

This command requires the LAN Base Services license.

Examples

This example shows how to configure the router as a receive-only neighbor:

```
switch(config)# router eigrp 1
switch(config-router)# stub receive-only
```

```
switch(config-router)#
```

Related Commands

Command	Description
copy running-config startup-config	Saves the configuration changes to the startup configuration file.
show ip eigrp	Displays EIGRP information.
show ip eigrp neighbors	Displays EIGRP neighbor information.