



## T Commands

---

This chapter describes the Cisco NX-OS unicast Routing Information Base (RIB) and the Forwarding Information Base (FIB) commands that begin with T.

*Review Draft -- Cisco Confidential*

# test forwarding distribution perf

To test the forwarding distribution performance of the Forwarding Information Base (FIB), use the **test forwarding distribution perf** command.

**test forwarding distribution perf**

---

<b>Syntax Description</b>	This command has no arguments or keywords.
---------------------------	--

---

<b>Command Default</b>	None
------------------------	------

---

<b>Command Modes</b>	Any command mode
----------------------	------------------

---

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	6.0(2)N1(1)	This command was introduced.

---

---

<b>Examples</b>	This example shows how to test the forwarding distribution performance:  switch# <b>test forwarding distribution perf</b>
-----------------	---

---

<b>Related Commands</b>	<b>Command</b>	<b>Description</b>
	<b>show forwarding distribution</b>	Displays information about the FIB.

---

**Review Draft -- Cisco Confidential**

# test forwarding inconsistency

To trigger the Layer 3 inconsistency checker for the Forwarding Information Base (FIB), use the **test forwarding inconsistency** command.

**test forwarding inconsistency** [**ip** | **ipv4**] [**unicast**] [**vrf** *vrf-name*] [**module** {*slot* | **all**}] [**stop**]

Syntax Description		
<b>ip</b>	(Optional)	Specifies the inconsistency check for IPv4 routes.
<b>ipv4</b>	(Optional)	Specifies the inconsistency check for IPv4 routes.
<b>unicast</b>	(Optional)	Specifies the inconsistency check for unicast routes.
<b>vrf</b> <i>vrf-name</i>	(Optional)	Specifies the virtual routing and forwarding (VRF) context name. The name can be any case-sensitive, alphanumeric string up to 32 characters.
<b>module</b>	(Optional)	Specifies the inconsistency check for one or more modules.
<i>slot</i>		Module number. The range depends on the platform.
<b>all</b>	(Optional)	Specifies the inconsistency check for all modules.
<b>stop</b>	(Optional)	Stops the inconsistency check.

Command Default	None
-----------------	------

Command Modes	Any command mode
---------------	------------------

Command History	Release	Modification
	6.0(2)N1(1)	This command was introduced.

**Examples** This example shows how to trigger the Layer 3 inconsistency checker for all modules:

```
switch# test forwarding inconsistency module all
```

This example shows how to stop the Layer 3 inconsistency checker for all modules:

```
switch# test forwarding inconsistency module all stop
```

Related Commands	Command	Description
	<b>clear forwarding inconsistency</b>	Clears the FIB inconsistencies.
	<b>show forwarding inconsistency</b>	Displays information about the FIB inconsistencies.

***Review Draft -- Cisco Confidential***