



## V Commands

---

This chapter describes the Cisco NX-OS object tracking commands that begin with V.

**Review Draft -- Cisco Confidential**

# vrf member

To add an interface to a virtual routing and forwarding (VRF) instance or to configure object tracking on a VRF instance, use the **vrf member** command. To remove the object tracking for this route, use the **no** form of this command.

**vrf member** *vrf-name*

**no vrf member** *vrf-name*

<b>Syntax Description</b>	<i>vrf-name</i>	VRF name. The name can be any case-sensitive, alphanumeric string up to 32 characters.
---------------------------	-----------------	--

<b>Command Default</b>	None
------------------------	------

<b>Command Modes</b>	Interface configuration mode Object tracking configuration mode
----------------------	--

<b>Command History</b>	<b>Release</b>	<b>Modification</b>
	6.0(2)N1(1)	This command was introduced.

<b>Usage Guidelines</b>	Use the <b>vrf member</b> command in object tracking configuration mode to track objects in a nondefault VRF.
-------------------------	---

<b>Examples</b>	<p>This example shows how to track an IP route in VRF Red:</p> <pre>switch(config)# track 1 ip route 10.10.10.0/8 reachability switch(config-track)# vrf member Red switch(config-track)#</pre>
-----------------	---

This example shows how to add the Ethernet interface 1/5 to VRF RemoteOfficeVRF:

```
switch(config)# interface ethernet 1/5
switch(config-if)# no switchport
switch(config-if)# vrf member RemoteOfficeVRF
switch(config-if)#
```

<b>Related Commands</b>	<b>Command</b>	<b>Description</b>
	<b>show ip eigrp</b>	Displays Enhanced Interior Gateway Routing Protocol (EIGRP) information.
	<b>show ip ospf interface</b>	Displays Open Shortest Path First (OSPF) interface-related information.
	<b>show ip rip</b>	Displays a summary of RIP information for all RIP instances.

***Review Draft -- Cisco Confidential***

Command	Description
<b>show track</b>	Displays information about object tracking.
<b>track ip route</b>	Tracks an interface.

***Review Draft -- Cisco Confidential***