



INDEX

A

aaa accounting dot1x command **1**
aaa authentication dot1x command **3**
aaa authorization network command **5, 22, 27, 29, 31, 33, 136, 504, 5, 36**
AAA methods **3**
abort command **898**
access control entries
 See ACEs
access control lists
 See ACLs
access groups
 IP **200**
 MAC, displaying **636**
access list, IPv6 **271**
access map configuration mode **349**
access mode **839**
access ports **839**
ACEs **120, 425**
ACLs
 deny **118**
 displaying **486**
 for non-IP protocols **320**
 IP **200**
 matching **349**
 on Layer 2 interfaces **200**
 permit **423**
action command **6**
address aliasing **397**
aggregate-port learner **411**
allowed VLANs **859**
apply command **898**

archive copy-sw command **8**
archive download-sw command **11**
archive tar command **15**
archive upload-sw command **18**
arp access-list command **20**
authentication control-direction command **22**
authentication event command **24**
authentication failed VLAN
 See dot1x auth-fail vlan
authentication fallback command **27**
authentication host-mode command **29**
authentication open command **31**
authentication order command **33**
authentication periodic command **35**
authentication port-control command **37**
authentication priority command **39**
authentication timer command **41**
authentication violation command **43**
auth-fail max-attempts
 See dot1x auth-fail max-attempts
auth-fail vlan
 See dot1x auth-fail vlan
auth open command **31**
auth order command **33**
authorization state of controlled port **155**
auth timer command **41**
autonegotiation of duplex mode **169**
auto qos voip command **45**

B

BackboneFast, for STP [759](#)
 backup interfaces
 configuring [832](#)
 displaying [565](#)
 boot (boot loader) command [2](#)
 boot auto-copy-sw command [50](#)
 boot auto-download-sw command [51](#)
 boot config-file command [53](#)
 boot enable-break command [54](#)
 boot helper command [55](#)
 boot helper-config file command [56](#)
 booting
 Cisco IOS image [59](#)
 displaying environment variables [499](#)
 interrupting [51, 54](#)
 manually [57](#)
 boot loader
 accessing [1](#)
 booting
 Cisco IOS image [2](#)
 helper image [55](#)
 directories
 creating [15](#)
 displaying a list of [7](#)
 removing [19](#)
 displaying
 available commands [12](#)
 memory heap utilization [13](#)
 version [26](#)
 environment variables
 described [20](#)
 displaying settings [20](#)
 location of [21](#)
 setting [20](#)
 unsettting [24](#)

boot loader (continued)
 files
 copying [5](#)
 deleting [6](#)
 displaying a list of [7](#)
 displaying the contents of [4, 16, 23](#)
 renaming [17](#)
 file system
 formatting [10](#)
 initializing flash [9](#)
 running a consistency check [11](#)
 prompt [1](#)
 resetting the system [18](#)
 boot manual command [57](#)
 boot private-config-file command [58](#)
 boot system command [59](#)
 BPDU filtering, for spanning tree [760, 795](#)
 BPDU guard, for spanning tree [762, 795](#)
 broadcast storm control [816](#)

C

candidate switches
 See clusters
 cat (boot loader) command [4](#)
 Catalyst 3750G Integrated Wireless LAN Controller Switch [475](#)
 CDP, enabling protocol tunneling for [299](#)
 channel-group command [61](#)
 channel-protocol command [65](#)
 Cisco SoftPhone
 auto-QoS configuration [45](#)
 trusting packets sent from [388](#)
 CISP
 See Client Information Signalling Protocol
 cisp
 debug platform cisp command [36](#)
 cisp enable command [66](#)
 class command [67](#)

class-map command **69**
 class maps
 creating **69**
 defining the match criteria **351**
 displaying **505**
 class of service
 See CoS
 clear dot1x command **71**
 clear eap sessions command **72**
 clear energywise neighbors command **73**
 clear errdisable interface **74**
 clear ip arp inspection log command **75**
 clear ip arp inspection statistics command **76**
 clear ipc command **79**
 clear ip dhcp snooping database command **77**
 clear ipv6 dhcp conflict command **80**
 clear l2protocol-tunnel counters command **81**
 clear lacp command **82**
 clear mac address-table command **83, 85**
 clear nmsp statistics command **86**
 clear pagp command **87**
 clear port-security command **88**
 clear spanning-tree counters command **90**
 clear spanning-tree detected-protocols command **91**
 clear vmps statistics command **92**
 clear vtp counters command **93**
 Client Information Signalling Protocol **66, 136, 504, 5, 36**
 cluster commander-address command **94**
 cluster discovery hop-count command **96**
 cluster enable command **97**
 cluster holdtime command **98**
 cluster member command **99**
 cluster outside-interface command **101**
 cluster run command **102**
 clusters
 adding candidates **99**
 binding to HSRP group **103**
 building manually **99**
 communicating with
 devices outside the cluster **101**
 members by using Telnet **452**
 debug messages, display **6**
 displaying
 candidate switches **508**
 debug messages **6**
 member switches **510**
 status **506**
 hop-count limit for extended discovery **96**
 HSRP standby groups **103**
 redundancy **103**
 SNMP trap **747**
 cluster standby-group command **103**
 cluster timer command **105**
 command modes defined **2**
 command switch
 See clusters
 configuration files
 password recovery disable considerations **1**
 specifying the name **53, 58**
 configuring multiple interfaces **196**
 config-vlan mode
 commands **884**
 description **4**
 entering **883**
 summary **3**
 controller, wireless **475**
 copy (boot loader) command **5**
 CoS
 assigning default value to incoming packets **358**
 assigning to Layer 2 protocol packets **302**
 overriding the incoming value **358**

CoS-to-DSCP map **362**
 CPU ASIC statistics, displaying **512**
 crashinfo files **189**

D

debug auto qos command **2**
 debug backup command **4**
 debug cisp command **5**
 debug cluster command **6**
 debug dot1x command **8**
 debug dtp command **10**
 debug eap command **11**
 debug etherchannel command **12**
 debug ilpower command **14**
 debug interface command **15**
 debug ip dhcp snooping command **17**
 debug ip igmp filter command **19**
 debug ip igmp max-groups command **20**
 debug ip igmp snooping command **21**
 debug ip verify source packet command **18**
 debug lacp command **22**
 debug lldp packets command **23**
 debug mac-notification command **24**
 debug matm command **25**
 debug matm move update command **26**
 debug monitor command **27**
 debug mvrdbg command **29**
 debug nmsp command **31**
 debug nvram command **32**
 debug pagp command **33**
 debug platform acl command **34**
 debug platform backup interface command **35**
 debug platform cisp command **36**
 debug platform cli-redirection main command **37**
 debug platform configuration command **38, 46**
 debug platform cpu-queues command **39**
 debug platform device-manager command **41**
 debug platform dot1x command **42**

debug platform etherchannel command **43**
 debug platform fallback-bridging command **44**
 debug platform forw-tcam command **45**
 debug platform ip arp inspection command **48**
 debug platform ipc command **58**
 debug platform ip dhcp command **49**
 debug platform ip igmp snooping command **50**
 debug platform ip multicast command **52**
 debug platform ip source-guard command **54**
 debug platform ip unicast command **55**
 debug platform ip wccp command **57**
 debug platform led command **59**
 debug platform matm command **60**
 debug platform messaging application command **62**
 debug platform phy command **63**
 debug platform pm command **65**
 debug platform port-asic command **67**
 debug platform port-security command **68**
 debug platform qos-acl-tcam command **69**
 debug platform remote-commands command **70**
 debug platform resource-manager command **71**
 debug platform snmp command **72**
 debug platform span command **73**
 debug platform stack-manager command **74**
 debug platform supervisor-asic command **75**
 debug platform sw-bridge command **76**
 debug platform tcam command **77**
 debug platform udld command **80**
 debug platform vlan command **81**
 debug platform wireless-controller **107**
 debug pm command **82**
 debug port-security command **84**
 debug qos-manager command **85**
 debug spanning-tree backbonefast command **88**
 debug spanning-tree bpdu command **89**
 debug spanning-tree bpdu-opt command **90**
 debug spanning-tree command **86**
 debug spanning-tree mstp command **91**
 debug spanning-tree switch command **93**

- debug spanning-tree uplinkfast command **95**
 debug sw-vlan command **96**
 debug sw-vlan ifs command **98**
 debug sw-vlan notification command **100**
 debug sw-vlan vtp command **102**
 debug udld command **104**
 debug vqpc command **106**
 define interface-range command **107**
 delete (boot loader) command **6**
 delete command **109**
 deny (ARP access-list configuration) command **111**
 deny (IPv6) command **113**
 deny command **118**
 detect mechanism, causes **180**
DHCP snooping
 accepting untrusted packets from edge switch **228**
 enabling
 on a VLAN **235**
 option 82 **226, 228**
 trust on an interface **233**
 error recovery timer **186**
 rate limiting **232**
DHCP snooping binding database
 binding file, configuring **224**
 bindings
 adding **222**
 deleting **222**
 displaying **585**
 clearing database agent statistics **77**
 database agent, configuring **224**
 displaying
 binding entries **585**
 database agent status **588, 590**
 renewing **460**
 dir (boot loader) command **7**
 directories, deleting **109**
 domain name, VTP **909, 913**
 dot1x auth-fail max-attempts **130**
 dot1x auth-fail vlan **132**
 dot1x command **128**
 dot1x control-direction command **134**
 dot1x credentials (global configuration) command **136**
 dot1x critical global configuration command **137**
 dot1x critical interface configuration command **139**
 dot1x default command **141**
 dot1x fallback command **142**
 dot1x guest-vlan command **143**
 dot1x host-mode command **146**
 dot1x initialize command **148**
 dot1x mac-auth-bypass command **149**
 dot1x max-reauth-req command **151**
 dot1x max-req command **152**
 dot1x multiple-hosts command **153**
 dot1x pae command **154**
 dot1x port-control command **155**
 dot1x re-authenticate command **157**
 dot1x re-authentication command **158**
 dot1x reauthentication command **159**
 dot1x test eapol-capable command **160**
 dot1x test timeout command **161**
 dot1x timeout command **162**
 dot1x violation-mode command **166**
 dropping packets, with ACL matches **6**
 drop threshold, Layer 2 protocol tunneling **299**
 DSCP-to-CoS map **362**
 DSCP-to-DSCP-mutation map **362**
DTP **840**
DTP flap
 error detection for **180**
 error recovery timer **186**
 DTP negotiation **844**
 duplex command **168**
dynamic-access ports
 configuring **828**
 restrictions **829**

dynamic ARP inspection

ARP ACLs

apply to a VLAN **208**

define **20**

deny packets **111**

display **490**

permit packets **415**

clear

log buffer **75**

statistics **76**

display

ARP ACLs **490**

configuration and operating state **580**

log buffer **580**

statistics **580**

trust state and rate limit **580**

enable per VLAN

218

error detection for

180

error recovery timer

186

log buffer

clear **75**

configure **212**

display **580**

rate-limit incoming ARP packets

210

statistics

clear **76**

display **580**

trusted interface state

214

type of packet logged

219

validation checks

216

dynamic auto VLAN membership mode

839

dynamic desirable VLAN membership mode

839

Dynamic Host Configuration Protocol (DHCP)

See DHCP snooping

Dynamic Trunking Protocol

See DTP

E

EAP-request/identity frame

maximum number to send **152**

response time before retransmitting **162**

encapsulation methods **859**

energywise (global configuration) command **170, 172**

energywise domain command **174**

energywise query command **176**

environment variables, displaying **499**

errdisable detect cause command **180**

errdisable detect cause small-frame command **183**

errdisable recovery cause small-frame **185**

errdisable recovery command **186**

error conditions, displaying **551**

error disable detection **180**

error-disabled interfaces, displaying **565**

EtherChannel

assigning Ethernet interface to channel group **61**

creating port-channel logical interface **194**

debug EtherChannel/PAgP, display **12**

debug platform-specific events, display **43**

displaying **555**

enabling Layer 2 protocol tunneling for

LACP **300**

PAgP **300**

UDLD **300**

interface information, displaying **565**

LACP

clearing channel-group information **82**

debug messages, display **22**

displaying **627**

modes **61**

port priority for hot-standby ports **303**

restricting a protocol **65**

system priority **305**

load-distribution methods **433**

EtherChannel (continued)

PAgP

- aggregate-port learner [411](#)
- clearing channel-group information [87](#)
- debug messages, display [33](#)
- displaying [687](#)
- error detection for [180](#)
- error recovery timer [186](#)
- learn method [411](#)
- modes [61](#)
- physical-port learner [411](#)
- priority of interface for transmitted traffic [413](#)

Ethernet controller, internal register display [514](#)

Ethernet statistics, collecting [465](#)

exception crashinfo command [189](#)

exit command [898](#)

extended discovery of candidate switches [96](#)

extended-range VLANs

- and allowed VLAN list [859](#)
- and pruning-eligible list [859](#)
- configuring [883](#)

extended system ID for STP [768](#)

F

fallback profile command [190](#)

fallback profiles, displaying [558](#)

fan information, displaying [546](#)

file name, VTP [909](#)

files, deleting [109](#)

flash_init (boot loader) command [9](#)

flexible authentication ordering [33](#)

Flex Links

- configuring [832](#)
- configuring preferred VLAN [835](#)
- displaying [565](#)

flowcontrol command [192](#)

format (boot loader) command [10](#)

forwarding packets, with ACL matches [6](#)

forwarding results, display [6](#)

frame forwarding information, displaying [6](#)

front-end controller, counter and status information [8](#)

fsck (boot loader) command [11](#)

G

global configuration mode [2, 4](#)

H

hardware ACL statistics [486](#)

help (boot loader) command [12](#)

hierarchical policy maps [431](#)

hop-count limit for clusters [96](#)

host connection, port configuration [838](#)

host ports, private VLANs [842](#)

Hot Standby Router Protocol

See HSRP

HSRP

binding HSRP group to cluster [103](#)

standby group [103](#)

I

IEEE 802.1Q trunk ports and native VLANs [900](#)

IEEE 802.1Q tunnel ports

configuring [839](#)

displaying [531](#)

limitations [840](#)

IEEE 802.1x

and switchport modes [840](#)

violation error recovery [186](#)

See also port-based authentication

IEEE 802.1X Port Based Authentication

enabling guest VLAN supplicant [131, 142, 191](#)

- IGMP filters
 applying [238](#)
 debug messages, display [19](#)
- IGMP groups, setting maximum [240](#)
- IGMP maximum groups, debugging [20](#)
- IGMP profiles
 creating [242](#)
 displaying [593](#)
- IGMP snooping
 adding ports as a static member of a group [259](#)
 displaying [594, 599, 601](#)
 enabling [244](#)
 enabling the configurable-leave timer [246](#)
 enabling the Immediate-Leave feature [255](#)
 flooding query count [252](#)
 interface topology change notification behavior [254](#)
 multicast table [597](#)
 querier [248](#)
 query solicitation [252](#)
 report suppression [250](#)
 switch topology change notification behavior [252](#)
- images
 See software images
- Immediate-Leave feature, MVR [399](#)
- immediate-leave processing [255](#)
- Immediate-Leave processing, IPv6 [295](#)
- interface configuration mode [2, 4](#)
- interface port-channel command [194](#)
- interface range command [196](#)
- interface-range macros [107](#)
- interfaces
 assigning Ethernet interface to channel group [61](#)
 configuring [168](#)
 configuring multiple [196](#)
 creating port-channel logical [194](#)
 debug messages, display [15](#)
 disabling [743](#)
 displaying the MAC address table [648](#)
 restarting [743](#)
- interface speed, configuring [805](#)
- interface vlan command [198](#)
- internal registers, displaying [514, 524](#)
- Internet Group Management Protocol
 See IGMP
- invalid GBIC
 error detection for [180](#)
 error recovery timer [186](#)
- ip access-group command [200](#)
- ip address command [203](#)
- IP addresses, setting [203](#)
- IP address matching [349](#)
- ip admission command [205](#)
- ip admission name proxy http command [206](#)
- ip arp inspection filter vlan command [208](#)
- ip arp inspection limit command [210](#)
- ip arp inspection log-buffer command [212](#)
- ip arp inspection trust command [214](#)
- ip arp inspection validate command [216](#)
- ip arp inspection vlan command [218](#)
- ip arp inspection vlan logging command [219](#)
- IP DHCP snooping
 See DHCP snooping
- ip dhcp snooping binding command [222](#)
- ip dhcp snooping command [221](#)
- ip dhcp snooping database command [224](#)
- ip dhcp snooping information option allow-untrusted command [228](#)
- ip dhcp snooping information option command [226](#)
- ip dhcp snooping information option format remote-id command [230](#)
- ip dhcp snooping limit rate command [232](#)
- ip dhcp snooping trust command [233](#)
- ip dhcp snooping verify command [234](#)
- ip dhcp snooping vlan command [235](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [236](#)
- ip igmp filter command [238](#)
- ip igmp max-groups command [240, 266, 268](#)
- ip igmp profile command [242](#)

ip igmp snooping command **244**
 ip igmp snooping last-member-query-interval command **246**
 ip igmp snooping querier command **248**
 ip igmp snooping report-suppression command **250**
 ip igmp snooping tcn command **252**
 ip igmp snooping tcn flood command **254**
 ip igmp snooping vlan immediate-leave command **255**
 ip igmp snooping vlan mrouter command **257**
 ip igmp snooping vlan static command **259**
 IP multicast addresses **396**
 IP phones
 auto-QoS configuration **45**
 trusting packets sent from **388**
 IP-precedence-to-DSCP map **362**
 ip snap forwarding command **261**
 ip source binding command **262**
 IP source guard
 disabling **270**
 displaying
 binding entries **603**
 configuration **605**
 dynamic binding entries only **585**
 enabling **270**
 static IP source bindings **262**
 ip ssh command **264**
 IPv6 access list, deny conditions **113**
 ipv6 access-list command **271**
 ipv6 address dhcp command **274**
 ipv6 dhcp client request vendor command **275**
 ipv6 dhcp ping packets command **276**
 ipv6 dhcp pool command **278**
 ipv6 dhcp server command **281**
 ipv6 mld snooping command **283**
 ipv6 mld snooping last-listener-query count command **285**
 ipv6 mld snooping last-listener-query-interval command **287**
 ipv6 mld snooping listener-message-suppression command **289**

ipv6 mld snooping robustness-variable command **291**
 ipv6 mld snooping tcn command **293**
 ipv6 mld snooping vlan command **295**
 IPv6 SDM template **466**
 ipv6 traffic-filter command **297**
 ip verify source command **270**

J

jumbo frames
 See MTU

L

l2protocol-tunnel command **299**
 l2protocol-tunnel cos command **302**
 LACP
 See EtherChannel
 lacp port-priority command **303**
 lacp system-priority command **305**
 Layer 2 mode, enabling **826**
 Layer 2 protocol ports, displaying **624**
 Layer 2 protocol-tunnel
 error detection for **180**
 error recovery timer **186**
 Layer 2 protocol tunnel counters **81**
 Layer 2 protocol tunneling error recovery **300**
 Layer 2 traceroute
 IP addresses **874**
 MAC addresses **871**
 Layer 3 mode, enabling **826**
 line configuration mode **3, 5**
 Link Aggregation Control Protocol
 See EtherChannel
 link flap
 error detection for **180**
 error recovery timer **186**
 link state group command **311**

link state track command **313**
load-distribution methods for EtherChannel **433**
location (global configuration) command **307**
location (interface configuration) command **309**
logging event command **314**
logging event power-inline-status command **315**
logging file command **316**
logical interface **194**
loopback error
 detection for **180**
 recovery timer **186**
loop guard, for spanning tree **770, 774**

M

mac access-group command **318**
MAC access-groups, displaying **636**
MAC access list configuration mode **320**
mac access-list extended command **320**
MAC access lists **118**
MAC addresses
 disabling MAC address learning per VLAN **323**
 displaying
 aging time **642**
 all **640**
 dynamic **646**
 MAC address-table move updates **651**
 notification settings **650, 653**
 number of addresses in a VLAN **644**
 per interface **648**
 per VLAN **657**
 static **655**
 static and dynamic entries **638**
 dynamic
 aging time **322**
 deleting **83**
 displaying **646**
 enabling MAC address notification **327**
 enabling MAC address-table move update **325**

MAC addresses (continued)
 matching **349**
 persistent stack **813**
 static
 adding and removing **329**
 displaying **655**
 dropping on an interface **330**
 tables **640**
MAC address notification, debugging **24**
mac address-table aging-time **318, 349**
mac address-table aging-time command **322**
mac address-table learning command **323**
mac address-table move update command **325**
mac address-table notification command **327**
mac address-table static command **329**
mac address-table static drop command **330**
macro apply command **332**
macro auto execute command **335**
macro auto global processing command **340**
macro description command **342**
macro global command **343**
macro global description command **346**
macro name command **347**
macros
 adding a description **342**
 adding a global description **346**
 applying **343**
 creating **347**
 displaying **689**
 interface range **107, 196**
 specifying parameter values **343**
 tracing **343**

- maps
- QoS
 - defining **362**
 - displaying **667**
 - VLAN
 - creating **895**
 - defining **349**
 - displaying **732**
- match (access-map configuration) command **349**
- match (class-map configuration) command **351**
- maximum transmission unit
- See MTU
- mdix auto command **353**
- member switches
- See clusters
- memory (boot loader) command **13**
- mkdir (boot loader) command **15**
- MLD snooping
- configuring **289, 291**
 - configuring queries **285, 287**
 - configuring topology change notification **293**
 - displaying **614, 616, 618, 620**
 - enabling **283**
- MLD snooping on a VLAN, enabling **295**
- mls qos aggregate-policer command **356**
- mls qos command **354**
- mls qos cos command **358**
- mls qos dscp-mutation command **360**
- mls qos map command **362**
- mls qos queue-set output buffers command **366**
- mls qos queue-set output threshold command **368**
- mls qos rewrite ip dscp command **370**
- mls qos srr-queue input bandwidth command **372**
- mls qos srr-queue input buffers command **374**
- mls qos-srr-queue input cos-map command **376**
- mls qos srr-queue input dscp-map command **378**
- mls qos srr-queue input priority-queue command **380**
- mls qos srr-queue input threshold command **382**
- mls qos-srr-queue output cos-map command **384**
- mls qos srr-queue output dscp-map command **386**
- mls qos trust command **388**
- mls qos vlan-based command **390**
- mode, MVR **396**
- Mode button, and password recovery **470**
- modes, commands **2**
- monitor session command **391**
- more (boot loader) command **16**
- MSTP
- displaying **708, 709**
 - interoperability **91**
 - link type **772**
- MST region
- aborting changes **778**
 - applying changes **778**
 - configuration name **778**
 - configuration revision number **778**
 - current or pending display **778**
 - displaying **708, 709**
 - MST configuration mode **778**
 - VLANs-to-instance mapping **778**
- path cost **780**
- protocol mode **776**
- restart protocol migration process **91**
- root port
- loop guard **770**
 - preventing from becoming designated **770**
 - restricting which can be root **770**
 - root guard **770**
- root switch
- affects of extended system ID **768**
 - hello-time **783, 791**
 - interval between BDPU messages **784**
 - interval between hello BPDU messages **783, 791**
 - max-age **784**
 - maximum hop count before discarding BPDU **785**
 - port priority for selection of **787**

MSTP (continued)

 primary or secondary **791**

 switch priority **790**

state changes

 blocking to forwarding state **797**

 enabling BPDU filtering **760, 795**

 enabling BPDU guard **762, 795**

 enabling Port Fast **795, 797**

 forward-delay time **782**

 length of listening and learning states **782**

 rapid transition to forwarding **772**

 shutting down Port Fast-enabled ports **795**

state information display **707**

MTU

 configuring size **868**

 displaying global setting **721**

multicast group address, MVR **399**

multicast groups, MVR **397**

Multicast Listener Discovery

 See MLD

multicast router learning method **257**

multicast router ports, configuring **257**

multicast router ports, IPv6 **295**

multicast storm control **816**

multicast VLAN, MVR **396**

multicast VLAN registration

 See MVR

Multiple Spanning Tree Protocol

 See MSTP

MVR

 and address aliasing **397**

 configuring **396**

 configuring interfaces **399**

 debug messages, display **29**

 displaying **676**

 displaying interface information **678**

 members, displaying **680**

 mvr (global configuration) command **396**

 mvr (interface configuration) command **399**

mvr vlan group command **400**

N

native VLANs **859**

native VLAN tagging **900**

Network Admission Control Software Configuration Guide **205, 207**

network-policy (global configuration) command **403**

network-policy command **402**

network-policy profile (network-policy configuration) command **405**

nmsp attachment suppress command **409**

nmsp command **407**

nonegotiate, speed **805**

nonegotiating DTP messaging **844**

non-IP protocols

 denying **118**

 forwarding **423**

non-IP traffic access lists **320**

non-IP traffic forwarding

 denying **118**

 permitting **423**

non-stop forwarding **410**

normal-range VLANs **883, 889**

no vlan command **883, 893**

nsf command **410**

O

online diagnostics

 displaying

 configured boot-up coverage level **528**

 current scheduled tasks **528**

 event logs **528**

 supported test suites **528**

 test ID **528**

 test results **528**

 test statistics **528**

online diagnostics (continued)

- global configuration mode
 - clearing health monitoring diagnostic test schedule **75**
 - clearing test-based testing schedule **124**
 - setting health monitoring diagnostic testing **75**
 - setting test-based testing **124**
 - setting up health monitoring diagnostic test schedule **75**
 - setting up test-based testing **124**
- health monitoring diagnostic tests, configuring **121**
 - scheduled switchover
 - disabling **124**
 - enabling **124**
- scheduling
 - enabling **124**
 - removing **124**
- testing, starting **126**
- test interval, setting **124**

P**PAgP**

See EtherChannel

pagp learn-method command **411**

pagp port-priority command **413**

password, VTP **909, 913**

password-recovery mechanism, enabling and disabling **470**

permit (ARP access-list configuration) command **415**

permit (IPv6) command **417**

permit (MAC access-list configuration) command **423**

per-VLAN spanning-tree plus

See STP

physical-port learner **411**

PID, displaying **579**

PIM-DVMRP, as multicast router learning method **257**

PoE

configuring the power budget **438**

configuring the power management mode **435**

displaying controller register values **522**

displaying power management information **697**

logging of status **315**

police aggregate command **428**

police command **426**

policed-DSCP map **362**

policy-map command **430**

policy maps

applying to an interface **472, 479**

creating **430**

displaying **692**

hierarchical **431**

policers

displaying **660**

for a single class **426**

for multiple classes **356, 428**

policed-DSCP map **362**

traffic classification

defining the class **67**

defining trust states **876**

setting DSCP or IP precedence values **477**

Port Aggregation Protocol

See EtherChannel

port-based authentication

AAA method list **3**

configuring violation modes **166**

debug messages, display **8**

enabling IEEE 802.1x

globally **128**

per interface **155**

guest VLAN **143**

host modes **146**

IEEE 802.1x AAA accounting methods **1**

initialize an interface **148, 161**

MAC authentication bypass **149**

manual control of authorization state **155**

port-based authentication (continued)

PAE as authenticator **154**

periodic re-authentication

enabling **159**

time between attempts **162**

quiet period between failed authentication exchanges **162**

re-authenticating IEEE 802.1x-enabled ports **157**

resetting configurable IEEE 802.1x parameters **141**

switch-to-authentication server retransmission time **162**

switch-to-client frame-retransmission number **151 to 152**

switch-to-client retransmission time **162**

test for IEEE 802.1x readiness **160**

port-channel load-balance command **433**

Port Fast, for spanning tree **797**

port ranges, defining **107**

ports, debugging **82**

ports, protected **857**

port security

aging **851**

debug messages, display **84**

enabling **846**

violation error recovery **186**

port trust states for QoS **388**

port types, MVR **399**

power information, displaying **546**

power inline command **435**

power inline consumption command **438**

Power over Ethernet

See PoE

priority-queue command **440**

priority value, stack member **716, 821**

private-vlan command **442**

private-vlan mapping command **445**

private VLANs

association **855**

configuring **442**

configuring ports **842**

displaying **727**

host ports **842**

mapping

configuring **855**

displaying **565**

promiscuous ports **842**

privileged EXEC mode **2, 3**

product identification information, displaying **579**

promiscuous ports, private VLANs **842**

protected ports, displaying **570**

pruning

VLANs **859**

VTP

displaying interface information **565**

enabling **909, 913**

pruning-eligible VLAN list **861**

PVST+

See STP

Q

QoS

auto-QoS

configuring **45**

debug messages, display **2**

displaying **495**

class maps

creating **69**

defining the match criteria **351**

displaying **505**

defining the CoS value for an incoming packet **358**

displaying configuration information **495, 659**

DSCP transparency **370**

- QoS (continued)
- DSCP trusted ports
 - applying DSCP-to-DSCP-mutation map to [360](#)
 - defining DSCP-to-DSCP-mutation map [362](#)
 - egress queues
 - allocating buffers [366](#)
 - defining the CoS output queue threshold map [384](#)
 - defining the DSCP output queue threshold map [386](#)
 - displaying buffer allocations [663](#)
 - displaying CoS output queue threshold map [667](#)
 - displaying DSCP output queue threshold map [667](#)
 - displaying queueing strategy [663](#)
 - displaying queue-set settings [670](#)
 - enabling bandwidth shaping and scheduling [809](#)
 - enabling bandwidth sharing and scheduling [811](#)
 - limiting the maximum output on a port [807](#)
 - mapping a port to a queue-set [447](#)
 - mapping CoS values to a queue and threshold [384](#)
 - mapping DSCP values to a queue and threshold [386](#)
 - setting maximum and reserved memory allocations [368](#)
 - setting WTD thresholds [368](#)
 - enabling [354](#)
 - ingress queues
 - allocating buffers [374](#)
 - assigning SRR scheduling weights [372](#)
 - defining the CoS input queue threshold map [376](#)
 - defining the DSCP input queue threshold map [378](#)
 - displaying buffer allocations [663](#)
 - displaying CoS input queue threshold map [667](#)
 - displaying DSCP input queue threshold map [667](#)
 - displaying queueing strategy [663](#)
 - displaying settings for [661](#)
 - enabling the priority queue [380](#)
- QoS (continued)
- mapping CoS values to a queue and threshold [376](#)
 - mapping DSCP values to a queue and threshold [378](#)
 - setting WTD thresholds [382](#)
 - maps
 - defining [362, 376, 378, 384, 386](#)
 - displaying [667](#)
 - policy maps
 - applying an aggregate policer [428](#)
 - applying to an interface [472, 479](#)
 - creating [430](#)
 - defining policers [356, 426](#)
 - displaying policers [660](#)
 - displaying policy maps [692](#)
 - hierarchical [431](#)
 - policed-DSCP map [362](#)
 - setting DSCP or IP precedence values [477](#)
 - traffic classifications [67](#)
 - trust states [876](#)
 - port trust states [388](#)
 - queues, enabling the expedite [440](#)
 - statistics
 - in-profile and out-of-profile packets [663](#)
 - packets enqueued or dropped [663](#)
 - sent and received CoS values [663](#)
 - sent and received DSCP values [663](#)
 - trusted boundary for IP phones [388](#)
 - VLAN-based [390](#)
 - quality of service
 - See QoS
 - querytime, MVR [396](#)
 - queue-set command [447](#)
-
- R**
- radius-server dead-criteria command [448](#)
 - radius-server host command [450](#)

rapid per-VLAN spanning-tree plus
 See STP

rapid PVST+
 See STP

rcommand command **452**

re-authenticating IEEE 802.1x-enabled ports **157**

re-authentication
 periodic **159**
 time between attempts **162**
 receiver ports, MVR **399**
 receiving flow-control packets **192**
 recovery mechanism
 causes **186**
 display **74, 501, 549, 553**
 timer interval **187**
 redundancy for cluster switches **103**
 reload command **454**
 remote command **456**
 remote-span command **458**
 Remote Switched Port Analyzer
 See RSPAN

rename (boot loader) command **17**

renew ip dhcp snooping database command **460**

reset (boot loader) command **18**

reset command **898**

resource templates, displaying **700**

restricted VLAN
 See dot1x auth-fail vlan

rmdir (boot loader) command **19**

rmon collection stats command **465**

root guard, for spanning tree **770**

routed ports
 IP addresses on **204**
 number supported **204**

RSPAN

 configuring **391**
 displaying **673**
 filter RSPAN traffic **391**

RSPAN (continued)
 remote-span command **458**
 sessions
 displaying **673**

S

scheduled switchover
 disabling **124**
 enabling **124**

SDM mismatch mode **467, 717**

sdm prefer command **466**

SDM templates
 allowed resources **468**
 and stacking **467**
 displaying **700**
 dual IPv4 and IPv6 **466**

secure ports, limitations **848**

sending flow-control packets **192**

service password-recovery command **470**

service-policy command **472**

session command **475**

set (boot loader) command **20**

set command **477**

setup command **479**

setup express command **482**

shell trigger command **484**

show access-lists command **486**

show archive status command **489**

show arp access-list command **490**

show authentication command **491**

show auto qos command **495**

show boot command **499**

show cable-diagnostics tdr command **501**

show changes command **898**

show cisp command **504**

show class-map command **505**

show cluster candidates command **508**

show cluster command **506**

- show cluster members command **510**
 show controllers cpu-interface command **512**
 show controllers ethernet-controller command **514**
 show controllers power inline command **522**
 show controllers tcam command **524**
 show controller utilization command **526**
 show current command **898**
 show dot1q-tunnel command **531**
 show dot1x command **532**
 show dtp **537**
 show eap command **539**
 show energywise command **542**
 show env command **546**
 show errdisable detect command **549**
 show errdisable flap-values command **551**
 show errdisable recovery command **553**
 show etherchannel command **555**
 show fallback profile command **558**
 show flowcontrol command **560**
 show idprom command **562**
 show interfaces command **565**
 show interfaces counters command **576**
 show inventory command **579**
 show ip arp inspection command **580**
 show ipc command **607**
 show ip dhcp snooping binding command **585**
 show ip dhcp snooping command **584**
 show ip dhcp snooping database command **588, 590**
 show ip igmp profile command **593**
 show ip igmp snooping address command **616**
 show ip igmp snooping command **594, 614**
 show ip igmp snooping groups command **597**
 show ip igmp snooping mrouter command **599, 618**
 show ip igmp snooping querier command **601, 620**
 show ip source binding command **603**
 show ipv6 access-list command **611**
 show ipv6 dhcp conflict command **613**
 show ipv6 route updated **622**
 show ip verify source command **605**
 show l2protocol-tunnel command **624**
 show lacp command **627**
 show link state group command **634**
 show location **631**
 show mac access-group command **636**
 show mac address-table address command **640**
 show mac address-table aging time command **642**
 show mac address-table command **638**
 show mac address-table count command **644**
 show mac address-table dynamic command **646**
 show mac address-table interface command **648**
 show mac address-table learning command **650**
 show mac address-table move update command **651**
 show mac address-table notification command **85, 653, 26**
 show mac address-table static command **655**
 show mac address-table vlan command **657**
 show mls qos aggregate-policer command **660**
 show mls qos command **659**
 show mls qos input-queue command **661**
 show mls qos interface command **663**
 show mls qos maps command **667**
 show mls qos queue-set command **670**
 show mls qos vlan command **672**
 show monitor command **673**
 show mvr command **676**
 show mvr interface command **678**
 show mvr members command **680**
 show network-policy profile command **682**
 show nmsp command **684**
 show pagp command **687**
 show parser macro command **689**
 show platform acl command **2**
 show platform backup interface command **3**
 show platform configuration command **4**
 show platform etherchannel command **5**
 show platform forward command **6**
 show platform frontend-controller command **8**
 show platform igmp snooping command **9**
 show platform ipc trace command **17**

- show platform ip multicast command **11**
 show platform ip unicast command **12**
 show platform ipv6 unicast command **18**
 show platform ip wccp command **16**
 show platform layer4op command **20**
 show platform mac-address-table command **21**
 show platform messaging command **22**
 show platform monitor command **23**
 show platform mvr table command **24**
 show platform pm command **25**
 show platform port-asic command **26**
 show platform port-security command **31**
 show platform qos command **32**
 show platform resource-manager command **33**
 show platform snmp counters command **35**
 show platform spanning-tree command **36**
 show platform stack manager command **38**
 show platform stp-instance command **37**
 show platform tb command **42**
 show platform team command **44**
 show platform vlan command **47**
 show policy-map command **692**
 show port security command **694**
 show power inline command **697**
 show proposed command **898**
 show sdm prefer command **700**
 show setup express command **703**
 show shell command **704**
 show spanning-tree command **707**
 show storm-control command **714**
 show switch command **716**
 show system mtu command **721**
 show trust command **876**
 show udld command **722**
 show version command **725**
 show vlan access-map command **732**
 show vlan command **727**
 show vlan command, fields **729**
 show vlan filter command **734**
 show vmps command **735**
 show vtp command **738**
 shutdown command **743**
 shutdown threshold, Layer 2 protocol tunneling **299**
 shutdown vlan command **744**
 small violation-rate command **745**
 Smartports macros
 See macros
 SNMP host, specifying **752**
 SNMP informs, enabling the sending of **747**
 snmp-server enable traps command **747**
 snmp-server host command **752**
 snmp trap mac-notification command **757**
 SNMP traps
 enabling MAC address notification trap **757**
 enabling the MAC address notification feature **327**
 enabling the sending of **747**
 SoftPhone
 See Cisco SoftPhone
 software images
 copying **8**
 deleting **109**
 downloading **11**
 upgrading **8, 11**
 uploading **18**
 software version, displaying **725**
 source ports, MVR **399**
 SPAN
 configuring **391**
 debug messages, display **27**
 displaying **673**
 filter SPAN traffic **391**
 sessions
 add interfaces to **391**
 displaying **673**
 start new **391**
 spanning-tree backbonefast command **759**
 spanning-tree bpdufilter command **760**
 spanning-tree bpduguard command **762**

- spanning-tree cost command **764**
- spanning-tree etherchannel command **766**
- spanning-tree extend system-id command **768**
- spanning-tree guard command **770**
- spanning-tree link-type command **772**
- spanning-tree loopguard default command **774**
- spanning-tree mode command **776**
- spanning-tree mst configuration command **778**
- spanning-tree mst cost command **780**
- spanning-tree mst forward-time command **782**
- spanning-tree mst hello-time command **783**
- spanning-tree mst max-age command **784**
- spanning-tree mst max-hops command **785**
- spanning-tree mst port-priority command **787**
- spanning-tree mst pre-standard command **789**
- spanning-tree mst priority command **790**
- spanning-tree mst root command **791**
- spanning-tree portfast (global configuration) command **795**
- spanning-tree portfast (interface configuration) command **797**
- spanning-tree port-priority command **793**
- Spanning Tree Protocol
- See STP
- spanning-tree transmit hold-count command **799**
- spanning-tree uplinkfast command **800**
- spanning-tree vlan command **802**
- speed command **805**
- srr-queue bandwidth limit command **807**
- srr-queue bandwidth share command **811**
- SSH, configuring version **264**
- stack-mac persistent timer command **813**
- stack member
- access **475**
 - number **716, 824**
 - priority value **821**
 - provisioning **822**
 - reloading **454**
- stacks, switch
- disabling a member **819**
 - enabling a member **819**
 - MAC address **813**
 - provisioning a new member **822**
 - reloading **454**
 - stack member access **475**
 - stack member number **716, 824**
 - stack member priority value **716, 821**
 - static-access ports, configuring **828**
 - statistics, Ethernet group **465**
 - sticky learning, enabling **846**
 - storm-control command **816**
- STP
- BackboneFast **759**
 - counters, clearing **90**
 - debug messages, display
 - BackboneFast events **88**
 - MSTP **91**
 - optimized BPDUs handling **90**
 - spanning-tree activity **86**
 - switch shim **93**
 - transmitted and received BPDUs **89**
 - UplinkFast **95**
- detection of indirect link failures **759**
- enabling protocol tunneling for **299**
- EtherChannel misconfiguration **766**
- extended system ID **764**
- path cost **764**
- protocol modes **776**
- root port
- accelerating choice of new **800**
 - loop guard **770**
 - preventing from becoming designated **770**
 - restricting which can be root **770**
 - root guard **770**
 - UplinkFast **800**

- STP (continued)
- root switch
 - affects of extended system ID **768, 803**
 - hello-time **802**
 - interval between BDPU messages **802**
 - interval between hello BPDU messages **802**
 - max-age **802**
 - port priority for selection of **793**
 - primary or secondary **802**
 - switch priority **802**
 - state changes
 - blocking to forwarding state **797**
 - enabling BPDU filtering **760, 795**
 - enabling BPDU guard **762, 795**
 - enabling Port Fast **795, 797**
 - enabling timer to recover from error state **186**
 - forward-delay time **802**
 - length of listening and learning states **802**
 - shutting down Port Fast-enabled ports **795**
 - state information display **707**
 - VLAN options **790, 802**
 - SVIs, creating **198**
 - SVI status calculation **830**
 - Switched Port Analyzer
 - See SPAN
 - switching characteristics
 - modifying **826**
 - returning to interfaces **826**
 - switchport access command **828**
 - switchport autostate exclude command **830**
 - switchport backup interface command **832**
 - switchport block command **837**
 - switchport command **826**
 - switchport host command **838**
 - switchport mode command **839**
 - switchport mode private-vlan command **842**
 - switchport nonegotiate command **844**
 - switchport port-security aging command **851**
 - switchport port-security command **846**
 - switchport priority extend command **853**
 - switchport private-vlan command **855**
 - switchport protected command **857**
 - switchports, displaying **565**
 - switchport trunk command **859**
 - switchport voice vlan command **863, 864**
 - switch priority command **819, 821**
 - switch provision command **822**
 - switch renumber command **824**
 - system env temperature threshold yellow command **866**
 - system message logging **315**
 - system message logging, save message to flash **316**
 - system mtu command **868**
 - system resource templates **466**
-
- T**
- tar files, creating, listing, and extracting **15**
- TDR, running **870**
- Telnet, using to communicate to cluster switches **452**
- temperature information, displaying **546**
- templates, system resources **466**
- test cable-diagnostics tdr command **870**
- test relay **871**
- traceroute mac command **871**
- traceroute mac ip command **874**
- trunking, VLAN mode **839**
- trunk mode **839**
- trunk ports **839**
- trunks, to non-DTP device **840**
- trusted boundary for QoS **388**
- trusted port states for QoS **388**
- tunnel ports, Layer 2 protocol, displaying **624**
- type (boot loader) command **23**

U

UDLD

- aggressive mode **878, 880**
- debug messages, display **104**
- enable globally **878**
- enable per interface **880**
- error recovery timer **186**
- message timer **878**
- normal mode **878, 880**
- reset a shutdown interface **882**
- status **722**

udld command **878**udld port command **880**udld reset command **882**unicast storm control **816**

UniDirectional Link Detection

See UDLD

unknown multicast traffic, preventing **837**unknown unicast traffic, preventing **837**unset (boot loader) command **24**

upgrading

- software images
- copying **8**
- downloading **11**
- monitoring status of **489**

UplinkFast, for STP **800**user EXEC mode **2, 3****V**version (boot loader) command **26**version mismatch mode **717, 39**vlan (global configuration) command **883**vlan (VLAN configuration) command **889**vlan access-map command **895**VLAN access map configuration mode **895**

VLAN access maps

- actions **6**
- displaying **732**

VLAN-based QoS **390**

VLAN configuration

- rules **886, 891**
- saving **883, 893**

VLAN configuration mode

commands

VLAN **889**VTP **913**description **5**entering **897**summary **3**vlan database command **897**vlan dot1q tag native command **900**vlan filter command **902**VLAN filters, displaying **734**VLAN ID range **883, 889**

VLAN maps

applying **902**creating **895**defining **349**displaying **732**

VLAN Query Protocol

See VQP

VLANs

adding **883**configuring **883, 889**

debug messages, display

ISL **100**VLAN IOS file system error tests **98**VLAN manager activity **96**VTP **102**displaying configurations **727**enabling guest VLAN supplicant **131, 142, 191**extended-range **883**

VLANs (continued)

- MAC addresses
 - displaying **657**
 - number of **644**
- media types **886, 891**
- normal-range **883, 889**
- private **842**
 - configuring **442**
 - displaying **727**
- See also private VLANs
- restarting **744**
- saving the configuration **883**
- shutting down **744**
- SNMP traps for VTP **750, 754**
- suspending **744**
- variables **889**

VLAN Trunking Protocol

See VTP

VM mode **717, 39**

VMPS

- configuring servers **907**
- displaying **735**
- error recovery timer **187**
- reconfirming dynamic VLAN assignments **904**
- `vmps reconfirm` (global configuration) command **905**
- `vmps reconfirm` (privileged EXEC) command **904**
- `vmps retry` command **906**
- `vmps server` command **907**
- voice VLAN
 - configuring **863, 864**
 - setting port priority **853**

VQP

- and dynamic-access ports **829**
- clearing client statistics **92**
- displaying information **735**
- per-server retry count **906**
- reconfirmation interval **905**
- reconfirming dynamic VLAN assignments **904**

VTP

- changing characteristics **909**
- clearing pruning counters **93**
- configuring
 - domain name **909, 913**
 - file name **909**
 - mode **909, 913**
 - password **909, 913**
- counters display fields **739**
- displaying information **738**
- enabling
 - pruning **909, 913**
 - tunneling for **299**
 - Version 2 **909, 913**
- mode **909, 913**
- pruning **909, 913**
- saving the configuration **883, 893**
- statistics **738**
- status **738**
- status display fields **741**
- `vtp` (global configuration) command **909**
- `vtp` (VLAN configuration) command **913**

W

- wireless controller, accessing **475**
- wireless controller switch. **107**

X

- XENPAK module serial EEPROM information **518, 562**