show access-group mode interface

To display the ACL configuration on a Layer 2 interface, use the **show access-group mode interface** command.

show access-group mode interface [interface interface-number]

Syntax Description

interface	(Optional) Interface type; valid values are ethernet , fastethernet , gigabitethernet , tengigabitethernet , and port-channel .
interface-number	(Optional) Interface number.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The valid values for the port number depend on the chassis used.

Examples

This example shows how to display the ACL configuration on the Fast Ethernet interface 6/1:

Switch# show access-group mode interface fa6/1

Interface FastEthernet6/1:
 Access group mode is: merge
Switch#

Related Commands

access-group mode

show adjacency

To display information about the Layer 3 switching adjacency table, use the **show adjacency** command.

show adjacency [{interface interface-number} | {**null** interface-number} | {**port-channel** number} | {**vlan** vlan-id} | **detail** | **internal** | **summary**]

Syntax Description

interface	(Optional) Interface type; possible valid values are ethernet , fastethernet , gigabitethernet , tengigabitethernet , pos , ge-wan , and atm .
interface-number	(Optional) Module and port number; see the "Usage Guidelines" section for valid values.
null interface-number	(Optional) Specifies the null interface; the valid value is 0 .
port-channel number	(Optional) Specifies the channel interface; valid values are a maximum of 64 values ranging from 1 to 256.
vlan vlan-id	(Optional) Specifies the VLAN; valid values are from 1 to 4094.
detail	(Optional) Displays the information about the protocol detail and timer.
internal	(Optional) Displays the information about the internal data structure.
summary	(Optional) Displays a summary of CEF-adjacency information.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.2(25)EW	Extended to include the 10-Gigabit Ethernet interface.

Usage Guidelines

The *interface-number* argument designates the module and port number. Valid values for *interface-number* depend on the specified interface type and the chassis and module that are used. For example, if you specify a Gigabit Ethernet interface and have a 48-port 10/100BASE-T Ethernet module that is installed in a 13-slot chassis, valid values for the module number are from 1 to 13, and valid values for the port number are from 1 to 48.

Hardware Layer 3 switching adjacency statistics are updated every 60 seconds.

The following information is contained in the **show adjacency** command:

- Protocol interface.
- Type of routing protocol that is configured on the interface.
- Interface address.
- Method of adjacency that was learned.
- MAC address of the adjacent router.

• Time left before the adjacency rolls out of the adjacency table. After it rolls out, a packet must use the same next hop to the destination.

Examples

This example shows how to display adjacency information:

Switch# show adjacency

Protocol Interface Address

Switch#

This example shows how to display a summary of adjacency information:

Switch# show adjacency summary

Adjacency Table has 2 adjacencies

Interface Adjacency Count

FastEthernet2/3 2

Switch#

This example shows how to display protocol detail and timer information:

Switch# show adjacency detail

FastEthernet2/3

Protocol Interface Address

00000000FF9200003800000000000

ARP 03:58:12 172.20.52.22(11)

0 packets, 0 bytes
000000000FF9200003800000000000

ARP 03:58:06

Switch#

ΙP

This example shows how to display adjacency information for a specific interface:

Switch# show adjacency fastethernet2/3

Protocol Interface Address

Switch#

Related Commands

debug adjacency

show arp access-list

To display detailed information on an ARP access list, use the show arp command.

show arp access-list

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the ARP ACL information for a switch:

Switch# show arp access-list
ARP access list rose
 permit ip 10.101.1.1 0.0.0.255 mac any
 permit ip 20.3.1.0 0.0.0.255 mac any

Related Commands

access-group mode arp access-list ip arp inspection filter vlan

show auto install status

To display the status of an automatic installation, use the show auto install status command.

show auto install status

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.2(20)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the IP address of the TFTP server and to display whether or not the switch is currently acquiring the configuration file on the TFTP server:

Switch# show auto install status

Status : Downloading config file

DHCP Server : 20.0.0.1
TFTP Server : 30.0.0.3
Config File Fetched : Undetermined

The first IP address in the display indicates the server that is used for the automatic installation. The second IP address indicates the TFTP server that provided the configuration file.

show auto qos

To display the automatic quality of service (auto-QoS) configuration that is applied, use the **show auto qos** user EXEC command.

show auto qos [interface [interface-id]] [{begin | exclude | include}} expression]

Syntax Description

interface interface-id	(Optional) Displays auto-QoS information for the specified interface or for all interfaces. Valid interfaces include physical ports.
begin	(Optional) Begins with the line that matches the expression.
exclude	(Optional) Excludes lines that match the expression.
include	(Optional) Includes lines that match the specified expression.
expression	(Optional) Expression in the output to use as a reference point.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The **show auto qos interface** *interface-id* command displays the auto-QoS configuration; it does not display any user changes to the configuration that might be in effect.

To display information about the QoS configuration that might be affected by auto-QoS, use one of these commands:

- show qos
- show qos map
- show qos interface interface-id
- show running-config

Expressions are case sensitive. For example, if you enter **exclude output**, the lines that contain *output* do not appear, but the lines that contain *Output* appear.

Examples

This example shows output from the **show auto qos** command when auto-QoS is enabled:

```
Switch# show auto qos

00:00:55:qos

00:00:56:qos map cos 3 to dscp 26

00:00:57:qos map cos 5 to dscp 46

00:00:58:qos map dscp 16 to tx-queue 1

00:00:58:qos map dscp 32 to tx-queue 1

00:00:58:qos dbl

00:00:59:policy-map autoqos-voip-policy

00:00:59: class class-default

00:00:59: dbl

00:00:59:interface GigabitEthernet1/1
```

```
00:00:59: qos trust device cisco-phone

00:00:59: qos trust cos

00:00:59: tx-queue 3

00:00:59: priority high

00:00:59: shape percent 70

00:00:59: service-policy output autoqos-voip-policyend
```

This example shows output from the **show auto qos interface** command when the **auto qos voip cisco-phone** interface configuration command is entered:

```
Switch# show auto gos interface
Initial configuration applied by AutoQoS:
interface GigabitEthernet1/1
qos trust device cisco-phone
gos trust cos
tx-queue 3
priority high
shape percent 70
service-policy output autogos-voip-policy
interface GigabitEthernet1/2
qos trust device cisco-phone
qos trust cos
tx-queue 3
priority high
shape percent 70
service-policy output autoqos-voip-policy
```

This example shows output from the **show auto qos interface gigabitethernet1/1** command when the **auto qos voip cisco-phone** interface configuration command is entered:

```
Switch# show auto qos interface gigabitethernet1/1
Initial configuration applied by AutoQoS:
!
interface GigabitEthernet1/1
qos trust device cisco-phone
qos trust cos
tx-queue 3
priority high
shape percent 70
service-policy output autoqos-voip-policy
```

This example shows output from the **show auto qos** command when auto-QoS is disabled:

```
Switch# show auto qos
AutoQoS is disabled
```

Related Commands

auto gos voip

show bootflash:

To display information about the bootflash: file system, use the **show bootflash:** command.

show bootflash: [all | chips | filesys]

Syntax Description

all	(Optional) Displays all possible Flash information.
chips	(Optional) Displays Flash chip information.
filesys	(Optional) Displays file system information.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display file system status information:

Switch> show bootflash: filesys

```
----- FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: bootflash
 Magic Number
                     = 6887635 File System Vers = 10000
                                                          (1.0)
                     = 1000000 Sector Size = 40000
 Length
 Programming Algorithm = 39
                                Erased State
                                                = FFFFFFFF
 File System Offset = 40000
                                Length = F40000
 MONLIB Offset
                    = 100
                               Length = C628
 Bad Sector Map Offset = 3FFF8
                               Length = 8
 Squeeze Log Offset = F80000
                              Length = 40000
 Squeeze Buffer Offset = FC0000
                                Length = 40000
 Num Spare Sectors
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
              = 917CE8 Bytes Available = 628318
 Bytes Used
 Bad Sectors = 0
                        Spared Sectors = 0
 OK Files
              = 2
                        Bytes = 917BE8
 Deleted Files = 0
                        Bytes = 0
 Files w/Errors = 0
                        Bytes = 0
Switch>
```

This example shows how to display system image information:

```
Switch> show bootflash:
-# - ED --type-- --crc-- -seek- nlen -length- -----date/time----- name

1 .. image 8C5A393A 237E3C 14 2063804 Aug 23 1999 16:18:45 c4-boot-mz

2 .. image D86EE0AD 957CE8 9 7470636 Sep 20 1999 13:48:49 rp.halley
Switch>
```

This example shows how to display all bootflash information:

```
Switch> show bootflash: all
-# - ED --type-- --crc-- -seek-- nlen -length- ----date/time----- name
1 .. image
             8C5A393A 237E3C 14 2063804 Aug 23 1999 16:18:45 c4-boot-
2 .. image
             D86EE0AD 957CE8 9 7470636 Sep 20 1999 13:48:49 rp.halley
6456088 bytes available (9534696 bytes used)
------FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: bootflash
 Magic Number
                    = 6887635 File System Vers = 10000
                                                        (1.0)
                    = 1000000 Sector Size = 40000
 Programming Algorithm = 39 Erased State
                                               = FFFFFFFF
 File System Offset = 40000 Length = F40000
                    = 100 Length = C628
 MONLIB Offset
 Bad Sector Map Offset = 3FFF8
                                Length = 8
  Squeeze Log Offset = F80000
                                Length = 40000
 Squeeze Buffer Offset = FC0000 Length = 40000
 Num Spare Sectors
                   = 0
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
            = 917CE8 Bytes Available = 628318
 Bytes Used
 Bad Sectors = 0 Spared Sectors = 0
           = 2
                       Bytes = 917BE8
 OK Files
 Deleted Files = 0 Bytes = 0
Files w/Errors = 0 Bytes = 0
Switch>
```

show bootvar

To display BOOT environment variable information, use the show bootvar command.

show bootvar

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display BOOT environment variable information:

Switch# show bootvar
BOOT variable = sup:1;
CONFIG_FILE variable does not exist
BOOTLDR variable does not exist
Configuration register is 0x0
Switch#

show cdp neighbors

To display detailed information about the neighboring devices that are discovered through CDP, use the **show cdp neighbors** command.

show cdp neighbors [type number] [detail]

Syntax Description

type	(Optional) Interface type that is connected to the neighbors about which you want information; possible valid values are ethernet , fastethernet , gigabitethernet , tengigabitethernet , port-channel , and vlan .
number	(Optional) Interface number that is connected to the neighbors about which you want information.
detail	(Optional) Displays detailed information about a neighbor (or neighbors) including network address, enabled protocols, hold time, and software version.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.2(25)EW	Extended to include the 10-Gigabit Ethernet interface.

Usage Guidelines

The **vlan** keyword is supported in Catalyst 4500 series switches that are configured with a Supervisor Engine II.

The **port-channel** values are from 0 to 282; values from 257 to 282 are supported on the CSM and the FWSM only.

Examples

This example shows how to display the information about the CDP neighbors:

Switch# show cdp neighbors

Capability Codes	s: R - Router, T -	Trans Brid	lge, B - Sourc	e Route Br	idge
	S - Switch, H -	Host, I -	IGMP, r - Rep	eater, P -	Phone
Device ID	Local Intrfce	Holdtme	Capability	Platform	Port ID
lab-7206	Eth 0	157	R	7206VXR	Fas 0/0/0
lab-as5300-1	Eth 0	163	R	AS5300	Fas 0
lab-as5300-2	Eth 0	159	R	AS5300	Eth 0
lab-as5300-3	Eth 0	122	R	AS5300	Eth 0
lab-as5300-4	Eth 0	132	R	AS5300	Fas 0/0
lab-3621	Eth 0	140	R S	3631-telc	oFas 0/0
008024 2758E0	Eth 0	132	T	CAT3000	1/2
Switch#					

Table 2-13 describes the fields that are shown in the example.

Table 2-13 show cdp neighbors Field Descriptions

Field	Definition
Device ID	Configured ID (name), MAC address, or serial number of the neighbor device.
Local Intrfce	(Local Interface) The protocol that is used by the connectivity media.
Holdtme	(Holdtime) Remaining amount of time, in seconds, that the current device holds the CDP advertisement from a transmitting router before discarding it.
Capability	Capability code that is discovered on the device. This device type is listed in the CDP Neighbors table. Possible values are as follows:
	R—Router
	T—Transparent bridge
	B—Source-routing bridge
	S—Switch
	H—Host
	I—IGMP device
	r—Repeater
	P—Phone
Platform	Product number of the device.
Port ID	Protocol and port number of the device.

This example shows how to display detailed information about your CDP neighbors:

```
Switch# show cdp neighbors detail
_____
Device ID: lab-7206
Entry address(es):
 IP address: 172.19.169.83
Platform: cisco 7206VXR, Capabilities: Router
Interface: Ethernet0, Port ID (outgoing port): FastEthernet0/0/0
Holdtime: 123 sec
Version :
Cisco Internetwork Operating System Software
IOS (tm) 5800 Software (C5800-P4-M), Version 12.1(2)
Copyright (c) 1986-2002 by Cisco Systems, Inc.
advertisement version: 2
Duplex: half
Device ID: lab-as5300-1
Entry address(es):
 IP address: 172.19.169.87
Switch#
```

Table 2-14 describes the fields that are shown in the example.

Table 2-14 show cdp neighbors detail Field Descriptions

Field	Definition
Device ID	Name of the neighbor device and either the MAC address or the serial number of this device.
Entry address(es)	List of network addresses of neighbor devices.
[network protocol] address	Network address of the neighbor device. The address can be in IP, IPX, AppleTalk, DECnet, or CLNS protocol conventions.
Platform	Product name and number of the neighbor device.
Capabilities	Device type of the neighbor. This device can be a router, a bridge, a transparent bridge, a source-routing bridge, a switch, a host, an IGMP device, or a repeater.
Interface	Protocol and port number of the port on the current device.
Holdtime	Remaining amount of time, in seconds, that the current device holds the CDP advertisement from a transmitting router before discarding it.
Version:	Software version running on the neighbor device.
advertisement version:	Version of CDP that is being used for CDP advertisements.
Duplex:	Duplex state of connection between the current device and the neighbor device.

Related Commands

show cdp (refer to Cisco IOS documentation)
show cdp entry (refer to Cisco IOS documentation)
show cdp interface (refer to Cisco IOS documentation)
show cdp traffic (refer to Cisco IOS documentation)

show class-map

To display class map information, use the **show class-map** command.

show class-map class_name

Syntax Description

class_name	Name of	the	class	map.
------------	---------	-----	-------	------

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display class map information for all class maps:

```
Switch# show class-map Class Map match-any class-default (id 0)
```

Switch#

Match any
Class Map match-any class-simple (id 2)
Match any
Class Map match-all ipp5 (id 1)
Match ip precedence 5
Class Map match-all agg-2 (id 3)

This example shows how to display class map information for a specific class map:

```
Switch# show class-map ipp5
```

```
Class Map match-all ipp5 (id 1)
   Match ip precedence 5
Switch#
```

Related Commands

class-map show policy-map show policy-map interface

show diagnostic content

To display test information about the test ID, test attributes, and supported coverage test levels for each test and for all modules, use the **show diagnostic content** command.

show diagnostic content module {all | num}

Syntax Description

all	Displays all the modules on the chassis.
num	Module number

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.2(20)EWA	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the test suite, monitoring interval, and test attributes for all the modules of the chassis:

Switch# show diagnostic content module all

module 1:

```
Diagnostics test suite attributes:

B/* - Basic ondemand test / NA

P/V/* - Per port test / Per device test / NA

D/N/* - Disruptive test / Non-disruptive test / NA

S/* - Only applicable to standby unit / NA

X/* - Not a health monitoring test / NA

F/* - Fixed monitoring interval test / NA

E/* - Always enabled monitoring test / NA

A/I - Monitoring is active / Monitoring is inactive

m/* - Mandatory bootup test, can't be bypassed / NA

o/* - Ongoing test, always active / NA
```

			l'esting Interval
ID	Test Name	Attributes	(day hh:mm:ss.ms)
====		========	============
1)	supervisor-bootup>	**D****I**	not configured
2)	<pre>packet-memory-bootup></pre>	**D****I**	not configured
3)	<pre>packet-memory-ongoing></pre>	**N****I*o	not configured

```
module 6:
Diagnostics test suite attributes:
   B/* - Basic ondemand test / NA
  P/V/* - Per port test / Per device test / NA
  D/N/* - Disruptive test / Non-disruptive test / NA
    \ensuremath{\mathrm{S}/^*} - Only applicable to standby unit / NA
    X/* - Not a health monitoring test / NA
    F/* - Fixed monitoring interval test / NA
    E/* - Always enabled monitoring test / NA
    A/I - Monitoring is active / Monitoring is inactive
    \mbox{m/*} - Mandatory bootup test, can't be bypassed / NA
    o/* - Ongoing test, always active / NA
                                                       Testing Interval
                                                       (day hh:mm:ss.ms)
ID Test Name
                                            Attributes
1) linecard-online-diag -----> **D****I** not configured
Switch#
```

Related Commands

show diagnostic result module show diagnostic result module test 2 show diagnostic result module test 3

show diagnostic result module

To display the module-based diagnostic test results, use the show diagnostic result module command.

show diagnostic result module [slot-num | all] [test [test-id | test-id-range | all]] [detail]

Syntax Description

slot-num	(Optional) Specifies the slot on which diagnostics are displayed.
all	(Optional) Displays the diagnostics for all slots.
test	(Optional) Displays selected tests on the specified module.
test-id	(Optional) Specifies a single test ID.
test-id-range	(Optional) Specifies a range of test IDs.
all	(Optional) Displays the diagnostics for all tests.
detail	(Optional) Displays the complete test results.

Defaults

A summary of the test results for all modules in the chassis is displayed.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.2(18)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the summary results for all modules in the chassis:

Switch# show diagnostic result module

```
module 5:
  Overall diagnostic result: PASS
 Diagnostic level at card bootup: minimal
  Test results: (. = Pass, F = Fail, U = Untested)
   1) linecard-online-diag -----> .
module 6:
  Overall diagnostic result: PASS
 Diagnostic level at card bootup: minimal
 Test results: (. = Pass, F = Fail, U = Untested)
   1) linecard-online-diag -----> .
This example shows how to display the online diagnostics for module 1:
Switch# show diagnostic result module 1 detail
Current bootup diagnostic level: minimal
module 1:
Overall diagnostic result: PASS
Diagnostic level at card bootup: minimal
 Test results: (. = Pass, F = Fail, U = Untested)
  1) supervisor-bootup -----> .
        Error code -----> 0 (DIAG_SUCCESS)
        Total run count -----> 0
        Last test execution time ----> n/a
        First test failure time ----> n/a
        Last test failure time ----> n/a
        Last test pass time -----> n/a
        Total failure count ----> 0
        Consecutive failure count -----> 0
Power-On-Self-Test Results for ACTIVE Supervisor
Power-on-self-test for Module 1: WS-X4014
Port/Test Status: (. = Pass, F = Fail)
Reset Reason: PowerUp Software/User
Port Traffic: L2 Serdes Loopback ...
0: \ . \ 1: \ . \ 2: \ . \ 3: \ . \ 4: \ . \ 5: \ . \ 6: \ . \ 7: \ . \ 8: \ . \ 9: \ . \ 10: \ . \ 11: \ .
12: . 13: . 14: . 15: . 16: . 17: . 18: . 19: . 20: . 21: . 22: . 23: .
24: . 25: . 26: . 27: . 28: . 29: . 30: . 31: .
```

```
Port Traffic: L2 Asic Loopback ...
0: . 1: . 2: . 3: . 4: . 5: .
                                6: . 7: . 8: . 9: . 10: . 11: .
12: . 13: . 14: . 15: . 16: . 17: . 18: . 19: . 20: . 21: . 22: . 23: .
24: . 25: . 26: . 27: . 28: . 29: . 30: . 31: .
Port Traffic: L3 Asic Loopback ...
0: \ . \ 1: \ . \ 2: \ . \ 3: \ . \ 4: \ . \ 5: \ . \ 6: \ . \ 7: \ . \ 8: \ . \ 9: \ . \ 10: \ . \ 11: \ .
12: . 13: . 14: . 15: . 16: . 17: . 18: . 19: . 20: . 21: . 22: . 23: .
24: . 25: . 26: . 27: . 28: . 29: . 30: . 31: . au:
Switch Subsystem Memory ...
1: . 2: . 3: . 4: . 5: . 6: . 7: . 8: . 9: . 10: . 11: . 12: .
13: . 14: . 15: . 16: . 17: . 18: . 19: . 20: . 21: . 22: . 23: . 24: .
25: . 26: . 27: . 28: . 29: . 30: . 31: . 32: . 33: . 34: . 35: . 36: .
37: . 38: . 39: . 40: . 41: . 42: . 43: . 44: . 45: . 46: . 47: . 48: .
49: . 50: . 51: . 52: . 53: . 54: .
Module 1 Passed
  2) packet-memory-bootup -----> .
        Error code -----> 0 (DIAG_SUCCESS)
        Total run count -----> 0
        Last test execution time -----> n/a
        First test failure time -----> n/a
        Last test failure time -----> n/a
        Last test pass time ----> n/a
        Total failure count -----> 0
        Consecutive failure count -----> 0
packet buffers on free list: 64557 bad: 0 used for ongoing tests: 979
Number of errors found: 0
Cells with hard errors (failed two or more tests): 0
Cells with soft errors (failed one test, includes hard): 0
Suspect bad cells (uses a block that tested bad): 0
total buffers: 65536
bad buffers: 0 (0.0%)
good buffers: 65536 (100.0%)
Bootup test results:1
No errors.
  3) packet-memory-ongoing ----> U
        Error code -----> 0 (DIAG SUCCESS)
        Total run count -----> 0
        Last test execution time ----> n/a
        First test failure time -----> n/a
        Last test failure time -----> n/a
        Last test pass time -----> n/a
        Total failure count ----> 0
        Consecutive failure count -----> 0
packet buffers on free list: 64557 bad: 0 used for ongoing tests: 979
```

```
Packet memory errors: 0 0
Current alert level: green
Per 5 seconds in the last minute:
  0 0 0 0 0 0 0 0 0 0
  0 0
Per minute in the last hour:
  0 0 0 0 0 0 0 0 0
   0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0
Per hour in the last day:
   0 0 0 0 0 0 0 0 0 0
  0 0 0 0
Per day in the last 30 days:
  0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0
Direct memory test failures per minute in the last hour:
  0 0 0 0 0 0 0 0 0 0
   0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0 0
  0 0 0 0 0 0 0 0 0
    \  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0
Potential false positives: 0 0
 Ignored because of rx errors: 0 0
 Ignored because of cdm fifo overrun: 0 0
Ignored because of oir: 0 0
Ignored because isl frames received: 0 0
Ignored during boot: 0 0
 Ignored after writing hw stats: 0 0
Ignored on high gigaport: 0
Ongoing diag action mode: Normal
Last 1000 Memory Test Failures:
Last 1000 Packet Memory errors:
First 1000 Packet Memory errors:
```

Switch#

show diagnostic result module test 2

To display the results of the bootup packet memory test, use the **show diagnostic result module test 2** command. The output indicates whether the test passed, failed, or was not run.

show diagnostic result module N test 2 [detail]

Syntax Description

N	Specifies the module number.
detail	(Optional) Specifies the display of detailed information for analysis.

Defaults

Non-detailed results

Command Modes

EXEC mode

Command History

Release	Modification
12.2(18)EW	This command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The detail keyword is intended for use by Cisco support personnel when analyzing failures.

Examples

This example shows how to display the results of the bootup packet memory tests:

```
Switch# show diagnostic result module 1 test 2

Test results: (. = Pass, F = Fail, U = Untested)
```

2) packet-memory-bootup -----> .

This example shows how to display detailed results from the bootup packet memory tests:

Switch# show diagnostic result module 2 test 2 detail

```
Test results: (. = Pass, F = Fail, U = Untested)
```

```
Number of errors found: 0
Cells with hard errors (failed two or more tests): 0
Cells with soft errors (failed one test, includes hard): 0
Suspect bad cells (uses a block that tested bad): 0
total buffers: 65536
bad buffers: 0 (0.0%)
good buffers: 65536 (100.0%)
Bootup test results:
No errors.
```

Related Commands

diagnostic monitor action show diagnostic result module test 3

show diagnostic result module test 3

To display the results from the ongoing packet memory test, use the **show diagnostic result module test 3** command. The output indicates whether the test passed, failed, or was not run.

show diagnostic result module N test 3 [detail]

Syntax Description

N	Module number.
detail	(Optional) Specifies the display of detailed information for analysis.

Defaults

Non-detailed results

Command Modes

EXEC mode

Command History

Release	Modification
12.2(18)EW	This command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The detail keyword is intended for use by Cisco support personnel when analyzing failures.

Examples

This example shows how to display the results from the ongoing packet memory tests:

```
Switch# show diagnostic result module 1 test 3
Test results: (. = Pass, F = Fail, U = Untested)
```

```
3) packet-memory-ongoing -----> .
```

This example shows how to display the detailed results from the ongoing packet memory tests:

Switch# show diagnostic result module 1 test 3 detail

```
Test results: (. = Pass, F = Fail, U = Untested)
```

```
Packet memory errors: 0 0
Current alert level: green
Per 5 seconds in the last minute:
    0 0 0 0 0 0 0 0 0 0
   0 0
Per minute in the last hour:
   0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
Per hour in the last day:
     \  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0\  \, 0
    0 0 0 0 0 0 0 0 0 0
    0 0 0 0
Per day in the last 30 days:
    0 0 0 0 0 0 0 0 0 0
   0 0 0 0 0 0 0 0 0
Direct memory test failures per minute in the last hour:
   0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0
    0 0 0 0 0 0 0 0 0 0
Potential false positives: 0 0
  Ignored because of rx errors: 0 0
  Ignored because of cdm fifo overrun: 0 0
  Ignored because of oir: 0 0
  Ignored because isl frames received: 0 0
  Ignored during boot: 0 0
  Ignored after writing hw stats: 0 0
  Ignored on high gigaport: 0
Ongoing diag action mode: Normal
Last 1000 Memory Test Failures: v
Last 1000 Packet Memory errors:
First 1000 Packet Memory errors:
```

Related Commands

diagnostic monitor action show diagnostic result module test 2

show dot1x

To display the 802.1X statistics and operational status for the entire switch or for a specified interface, use the **show dot1x** command.

show dot1x [interface interface-id] | [statistics [interface interface-id]] | [all]

Syntax Description

interface interface-id	(Optional) Displays the 802.1X status for the specified port.				
statistics	(Optional) Displays 802.1X statistics for the switch or the specified interface.				
all	(Optional) Displays per-interface 802.1X configuration information for all interfaces with a non-default 802.1X configuration.				

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Display enhanced to show the guest-VLAN value.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.
12.2(25)EWA	Support for currently-assigned reauthentication timer (if the timer is configured to honor the Session-Timeout value) was added.

Usage Guidelines

If you do not specify an interface, the global parameters and a summary are displayed. If you specify an interface, the details for that interface are displayed.

If you specify the **statistics** keyword without the **interface** option, the statistics are displayed for all interfaces. If you specify the **statistics** keyword with the **interface** option, the statistics are displayed for the specified interface.

Expressions are case sensitive. For example, if you enter **exclude output**, the lines that contain *output* are not displayed, but the lines that contain *Output* are displayed.

The **show dot1x** command displays the currently-assigned reauthentication timer and time remaining before reauthentication, if reauthentication is enabled.

Examples

This example shows how to display the output from the **show dot1x** command:

Switch# show dot1x
Sysauthcontrol = Disabled
Dot1x Protocol Version = 1
Dot1x Oper Controlled Directions = Both
Dot1x Admin Controlled Directions = Both
Switch#

This example shows how to display the 802.1X statistics for a specific port:

```
Switch# show dot1x interface fa6/1
Supplicant MAC <Not Applicable>
  AuthSM State
                  = N/A
  BendSM State
                  = N/A
  ReAuthPeriod
                 = 3600 Seconds (Locally Configured)
  ReAuthAction = Reauthenticate
  TimeToNextReauth = N/A
PortStatus = N/A
                = 2.
MaxReq
MaxAuthReq
               = 2
HostMode
                = Single
           = Auto
= 60 Seconds
PortControl
QuietPeriod
Re-authentication = Enabled
               = 3600 Seconds
ReAuthPeriod
ServerTimeout
               = 30 Seconds
SuppTimeout
               = 30 Seconds
TxPeriod
               = 30 Seconds
Guest-Vlan
               = 0
Switch#
```



Table 2-15 provides a partial list of the displayed fields. The remaining fields in the display show internal state information. For a detailed description of these state machines and their settings, refer to the 802.1X specification.

Table 2-15 show dot1x interface Field Description

Field	Description
PortStatus	Status of the port (authorized or unauthorized). The status of a port is displayed as authorized if the dot1x port-control interface configuration command is set to auto and has successfully completed authentication.
Port Control	Setting of the dot1x port-control interface configuration command.
MultiHosts	Setting of the dot1x multiple-hosts interface configuration command (allowed or disallowed).

This is an example of output from the **show dot1x statistics interface gigabitethernet1/1** command. Table 2-16 describes the fields in the display.

Switch# show dot1x statistics interface gigabitethernet1/1

```
PortStatistics Parameters for Dot1x

TXReqId = 0   TxReq = 0  TxTotal = 0

RxStart = 0   RxLogoff = 0  RxRespId = 0  RxResp = 0

RxInvalid = 0  RxLenErr = 0  RxTotal = 0

RxVersion = 0  LastRxSrcMac 0000.0000.0000
```

Table 2-16 show dot1x statistics Field Descriptions

Field	Description
TxReq/TxReqId	Number of EAP-request/identity frames that have been sent.
TxTotal	Number of EAPOL frames of any type that have been sent.

Table 2-16 show dot1x statistics Field Descriptions (continued)

Field	Description					
RxStart	Number of valid EAPOL-start frames that have been received.					
RxLogoff	Number of EAPOL-logoff frames that have been received.					
RxRespId	Number of EAP-response/identity frames that have been received.					
RxResp	Number of valid EAP-response frames (other than response/identity frames) that have been received.					
RxInvalid	Number of EAPOL frames that have been received and have an unrecognized frame type.					
RxLenError	Number of EAPOL frames that have been received in which the packet body length field is invalid.					
RxTotal	Number of valid EAPOL frames of any type that have been received.					
RxVersion	Protocol version number carried in the most recently received EAPOL frame.					
LastRxSrcMac	Source MAC address carried in the most recently received EAPOL frame.					

Related Commands

dot1x guest-vlan dot1x max-reauth-req dot1x port-control

show environment

To display the environment alarm, operational status, and current reading for the chassis, use the **show environment** command.

show environment [alarm] | [status [chassis | fantray | powersupply | supervisor]] | [temperature]

Syntax Description

alarm	(Optional) Specifies the alarm status of the chassis.
status	(Optional) Specifies the operational status information.
chassis	(Optional) Specifies the operational status of the chassis.
fantray	(Optional) Specifies the status of the fan tray, and shows fan tray power consumption.
powersupply	(Optional) Specifies the status of the power supply.
supervisor	(Optional) Specifies the status of the supervisor engine.
temperature	(Optional) Specifies the current chassis temperature readings.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for the ability to display generic environment information with the show environment command was added.

Examples

This example shows how to display information about the environment alarms, operational status, and current temperature readings for the chassis:

Switch# show environment

no alarm

Chassis Temperature = 32 degrees Celsius Chassis Over Temperature Threshold = 75 degrees Celsius Chassis Critical Temperature Threshold = 95 degrees Celsius

Power				Fan	l	
Supply	Model No		Type	Sta	itus	Sensor
PS1	PWR-C45-1400AC		AC 1400W go		od	good
PS2	none					
Power Su	upply	Max	Min	Max	Min	Absolute
(Nos in	Watts)	Inline	Inline	System	System	Maximum
PS1		0	0	1360	1360	1400
PS2						

```
Power supplies needed by system : 1
Chassis Type : WS-C4507R
Supervisor Led Color : Green
Fantray : good
Power consumed by Fantray : 50 Watts
```

This example shows how to display information about the environment alarms:

```
Switch# show environment alarm no alarm Switch#
```

This example shows how to display information about the power supplies, chassis type, and fan trays:

Switch# show environment status						
		10			itus	
	PWR-C45-1400AC none					
(Nos in	Watts)	Inline	Inline	System	System	Absolute Maximum
PS1 PS2		0	0	1360		1400
Power supplies needed by system : 1						
Chassis Type : WS-C4507R						
Supervisor Led Color : Green						
Fantray : good						
Power consumed by Fantray : 50 Watts						

This example shows how to display information about the chassis:

```
Switch# show environment status chassis
Chassis Type :WS-C4006
Switch#
```

Switch#

This example shows how to display information about the fan tray:

```
Switch# show environment status fantray
Fantray : good
Power consumed by Fantray : 50 Watts
Switch#
```

This example shows how to display information about the power supply:

Switch#	show environment	status power	ersupply	
Power				Fan
Supply	Model No	Type	Status	Sensor
PS1	WS-X4008	AC 400W	good	good
PS2	WS-X4008	AC 400W	good	good
PS3	none			
Switch#				

This example shows how to display information about the supervisor engine:

```
Switch# show environment status supervisor
Supervisor Led Color :Green
Switch#
```

This example shows how to display information about the temperature of the chassis:

```
Switch# show environment temperature

Chassis Temperature = 2 32 degrees Celsius

Chassis Over Temperature Threshold = 75 degrees Celsius

Chassis Critical Temperature Threshold = 95 degrees Celsius

Switch#
```

show errdisable detect

To display the error disable detection status, use the show errdisable detect command.

show errdisable detect

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification	
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.	
12.1(19)EW	Display includes the status of storm control.	

Examples

This example shows how to display the error disable detection status:

Switch# show errdisable detect

ErrDisable Reason	Detection status
udld	Enabled
bpduguard	Enabled
security-violatio	Enabled
channel-misconfig	Disabled
psecure-violation	Enabled
vmps	Enabled
pagp-flap	Enabled
dtp-flap	Enabled
link-flap	Enabled
12ptguard	Enabled
gbic-invalid	Enabled
dhcp-rate-limit	Enabled
unicast-flood	Enabled
storm-control	Enabled
ilpower	Enabled
arp-inspection	Enabled
Switch#	

Related Commands

errdisable detect errdisable recovery show interfaces status

show errdisable recovery

To display error disable recovery timer information, use the **show errdisable recovery** command.

show errdisable recovery

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification	
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.	
12.1(19)EW	Display includes the status of storm control.	

Examples

This example shows how to display recovery timer information for error disable:

Switch# show errdisable recovery

ErrDisable Reason	Timer Status
udld	Disabled
bpduguard	Disabled
security-violatio	Disabled
channel-misconfig	Disabled
vmps	Disabled
pagp-flap	Disabled
dtp-flap	Disabled
link-flap	Disabled
12ptguard	Disabled
psecure-violation	Disabled
gbic-invalid	Disabled
dhcp-rate-limit	Disabled
unicast-flood	Disabled
storm-control	Disabled
arp-inspection	Disabled

Timer interval:30 seconds

Interfaces that will be enabled at the next timeout:

Interface	Errdisable reason	Time left(sec)
Fa7/32	arp-inspect	13

Related Commands

errdisable detect errdisable recovery show interfaces status

show etherchannel

To display EtherChannel information for a channel, use the show etherchannel command.

show etherchannel [channel-group] {port-channel | brief | detail | summary | port | load-balance | protocol}

Syntax Description

channel-group	(Optional) Number of the channel group; valid values are from 1 to 64.	
port-channel	ort-channel Displays port-channel information.	
brief	Displays a summary of EtherChannel information.	
detail	Displays detailed EtherChannel information.	
summary	Displays a one-line summary per channel group.	
port	Displays EtherChannel port information.	
load-balance	Displays load-balance information.	
protocol	Displays the enabled protocol.	

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification	
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.	
12.1(13)EW Support for LACP was added to this command.		

Usage Guidelines

If you do not specify a channel group, all channel groups are displayed.

In the output below, the Passive port list field is displayed for Layer 3 port channels only. This field means that the physical interface, which is still not up, is configured to be in the channel group (and indirectly is in the only port channel in the channel group).

Examples

This example shows how to display port-channel information for a specific group:

```
Ports in the Port-channel:
Index Load Port
------
Switch#
```

This example shows how to display load-balancing information:

```
Switch# show etherchannel load-balance
Source XOR Destination mac address
Switch#
```

Switch# show etherchannel 1 brief

Group state = L3

This example shows how to display a summary of information for a specific group:

```
Ports: 2 Maxports = 8
port-channels: 1 Max port-channels = 1
This example shows how to display detailed information for a specific group:
Switch# show etherchannel 1 detail
Group state = L3
Ports: 2 Maxports = 8
Port-channels: 1 Max Port-channels = 1
            Ports in the group:
Port: Fa5/4
          = EC-Enbld Down Not-in-Bndl Usr-Config
Port state
Port-channel = null
                                          Psudo-agport = Po1
                     Load = 0x00
Port indx = 0
Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
      A - Device is in Auto mode. P - Device learns on physical port.
Timers: H - Hello timer is running.
                                   Q - Quit timer is running.
      S - Switching timer is running. I - Interface timer is running.
Local information:
                           Hello
                                   Partner PAgP
                                                  Learning Group
        Flags State Timers Interval Count Priority Method Ifindex
Port
Fa5/4
        d U1/S1
                           1s
                                   0
                                          128
                                                    Any
Age of the port in the current state: 02h:33m:14s
Port: Fa5/5
Port state
          = EC-Enbld Down Not-in-Bndl Usr-Config
Gcchange = 0
                                         Psudo-agport = Po1
Port indx
          = 0
                      Load = 0x00
Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
     A - Device is in Auto mode. P - Device learns on physical port.
Timers: H - Hello timer is running.
                                   Q - Quit timer is running.
      S - Switching timer is running. I - Interface timer is running.
Local information:
                                   Partner PAgP
                           Hello
                                                  Learning Group
```

Flags State Timers Interval Count Priority Method Ifindex

128

Anv

0

1s

Port.

Fa5/5 d U1/S1

This example shows how to display a one-line summary per channel group:

```
Switch# show etherchannel summary
```

This example shows how to display EtherChannel port information for all ports and all groups:

```
Switch# show etherchannel port
```

```
Channel-group listing:
Group: 1
              Ports in the group:
               -----
Port: Fa5/4
Port state = EC-Enbld Down Not-in-Bndl Usr-Config
Channel group = 1 Mode = Desirable Gcchange = 0
Port-channel = null GC = 0x00000000 Psudo-agport = Pol
            = 0
                         Load = 0x00
Port indx
Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
       A - Device is in Auto mode. P - Device learns on physical port. H - Hello timer is running. Q - Quit timer is running.
Timers: H - Hello timer is running.
       S - Switching timer is running. I - Interface timer is running.
Local information:
                             Hello Partner PAgP Learning Group
Port
        Flags State Timers Interval Count Priority Method Ifindex
        d U1/S1
                              1s
                                  0
                                                        Any
Age of the port in the current state: 02h:40m:35s
Port: Fa5/5
Port state = EC-Enbld Down Not-in-Bndl Usr-Config
Channel group = 1 Mode = Desirable Gcchange = 0
Port-channel = null GC = 0x00000000 Psudo-agport = Pol Port indx = 0 Load - 0x00
Port indx = 0
                          Load = 0x00
```

```
Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is running.

<...output truncated...>

Switch#
```

This example shows how to display the protocol enabled:

```
Switch# show etherchannel protocol
```

```
Channel-group listing:
-------
Group: 12
------
Protocol: PAgP

Group: 24
-----
Protocol: - (Mode ON)
Switch#
```

Related Commands

channel-group interface port-channel

show flowcontrol

To display the per-interface status and statistics related to flow control, use the **show flowcontrol** command.

show flowcontrol [module slot | interface interface]

Syntax Description

module slot	(Optional) Limits the display to interfaces on a specific module.
interface interface	(Optional) Displays the status on a specific interface.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.

Usage Guidelines

Table 2-17 describes the fields in the **show flowcontrol** command output.

Table 2-17 show flowcontrol Command Output

Field	Description
Port	Module and port number.
Send-Flowcontrol-Admin	Flow-control administration. Possible settings: on indicates the local port sends flow control to the far end; off indicates the local port does not send flow control to the far end; desired indicates the local end sends flow control to the far end if the far end supports it.
Send-Flowcontrol-Oper	Flow-control operation. Possible setting: disagree indicates the two ports could not agree on a link protocol.
Receive-Flowcontrol-Admin	Flow-control administration. Possible settings: on indicates the local port requires the far end to send flow control; off indicates the local port does not allow the far end to send flow control; desired indicates the local end allows the far end to send flow control.
Receive-Flowcontrol-Oper	Flow-control operation. Possible setting: disagree indicates the two ports could not agree on a link protocol.
RxPause	Number of pause frames received.
TxPause	Number of pause frames transmitted.

Examples

This example shows how to display the flow control status on all the Gigabit Ethernet interfaces:

Switch# show flowcontrol

Port	Send Flo admin	wControl oper	Receive admin	FlowControl oper	RxPause	TxPause
Te1/1	off	off	on	off	0	0
Te1/2	off	off	on	off	0	0
Gi1/3	off	off	desired	on	0	0
Gi1/4	off	off	desired	on	0	0
Gi1/5	off	off	desired	on	0	0
Gi1/6	off	off	desired	on	0	0
Gi3/1	off	off	desired	off	0	0
Gi3/2	off	off	desired	off	0	0
Gi3/3	off	off	desired	off	0	0
Gi3/4	off	off	desired	off	0	0
Gi3/5	off	off	desired	off	0	0
Gi3/6	off	off	desired	off	0	0
Switch#						

This example shows how to display the flow control status on module 1:

Switch#	show flow	wcontrol r	module 1			
Port	Send Flow	wControl	Receive B	FlowControl	RxPause	TxPause
	admin	oper	admin	oper		
Gi1/1	desired	off	off	off	0	0
Gi1/2	on	disagree	on	on	0	0
Switch#						

This example shows how to display the flow control status on Gigabit Ethernet interface 3/4:

Switch# show flowcontrol interface gigabitethernet3/4

Port	Sena Flow	wcontrol	Receive F	TowControl	RXPause	TXPause
	admin	oper	admin	oper		
Gi3/4	off	off	on	on	0	0
Switch#						

This example shows how to display the flow control status on 10-Gigabit Ethernet interface 1/1:

Switch# show flowcontrol interface tengigabitethernet1/1

Port		wControl oper		FlowControl oper	RxPaus	e TxPause
Te1/1 Switch#	off	off	on	off	0	0

Related Commands

flowcontrol show interfaces status

show hw-module uplink

To display the current uplink mode, use the **show hw-module uplink** command.

show hw-module uplink

Defaults

None

Command Modes

Privileged EXEC

Command History

Release	Modification
12.2(25)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

If the active uplink mode is different than configured mode, the output displays the change.

By default, the current (operational) uplink selection is displayed.

Examples

This example shows the output displaying the current (active) uplinks:

Switch# show hw-module uplink

Active uplink configuration is TenGigabitEthernet

This example shows the output for redundant systems in SSO mode if the 10-Gigabit Ethernet uplinks are active, and the Gigabit Ethernet uplinks are selected:

Switch# show hw-module uplink

Active uplink configuration is TenGigabitEthernet
(will be GigabitEthernet after next reload)
A 'redundancy reload shelf' or power-cycle of chassis is required to
apply the new configuration

This example shows the output for redundant systems in RPR mode if the 10-Gigabit Ethernet uplinks are active, and the Gigabit Ethernet uplinks are selected:

Switch# show hw-module uplink

Active uplink configuration is TenGigabitEthernet (will be GigabitEthernet after next reload)
A reload of active supervisor is required to apply the new configuration.

Related Commands

hw-module uplink select

show idprom

To display the IDPROMs for the chassis, supervisor engine, module, power supplies, fan trays, clock module, and multiplexer (mux) buffer, use the **show idprom** command.

show idprom {all | chassis | module [mod] | interface int_name | supervisor | power-supply
number | fan-tray}

Syntax Description

all	Displays information for all IDPROMs.
chassis	Displays information for the chassis IDPROMs.
module	Displays information for the module IDPROMs.
mod	(Optional) Specifies the module name.
interface int_name	Displays information for the GBIC or SFP IDPROMs.
supervisor	Displays information for the supervisor engine IDPROMs.
power-supply number	Displays information for the power supply IDPROMs.
fan-tray	Displays information for the fan tray IDPROMs.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for the power-supply , fan-tray , clock-module , and mux-buffer keywords was added.
12.1(13)EW	Support for interface keyword was added.
12.2(18)EW	Enhanced the show idprom interface output to include the hexadecimal display of the GBIC/SFP SEEPROM contents.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.

Usage Guidelines

When you enter the **show idprom interface** command, the output lines for Calibration type and Rx (receive) power measurement may not be displayed for all GBICs.

Examples

This example shows how to display IDPROM information for module 4:

Switch# show idprom module 4
Module 4 Idprom:
Common Block Signature = 0xABAB
Common Block Version = 1
Common Block Length = 144

```
Common Block Checksum = 4199
Idprom Size = 256
Block Count = 2
FRU Major Type = 0x4201
FRU Minor Type = 303
OEM String = Cisco Systems, Inc.
Product Number = WS-X4306
Serial Number = 00000135
Part Number = <tbd>
Hardware Revision = 0.2
Manufacturing Bits = 0x0000
Engineering Bits = 0x0000
Snmp OID = 0.0.0.0.0.0.0.0
Power Consumption = 0
RMA Failure Code = 0 0 0 0
Linecard Block Signature = 0x4201
Linecard Block Version = 1
Linecard Block Length = 24
Linecard Block Checksum = 658
Feature Bits = 0x0000000000000000
Card Feature Index = 50
MAC Base = 0010.7bab.9830
MAC Count = 6
Switch#
```

This example shows how to display IDPROM information for the GBICs on the Gigabit Ethernet interface 1/2:

```
Switch# show idprom interface gigabitethernet1/2
GBIC Serial EEPROM Contents:
Common Block:
 Identifier
                  = GBIC [0x1]
 Extended Id
                 = Not specified/compliant with defined MOD_DEF [0x0]
 Connector
                  = SC connector [0x1]
 Transceiver
  Speed
                  = Not available [0x0]
  Media
                  = Not available [0x0]
                  = Not available [0x0]
  Technology
                  = Not available [0x0]
  Link Length
  GE Comp Codes = Not available [0x0]
  SONET Comp Codes = Not available [0x0]
 Encoding
                 = 8B10B [0x1]
 BR, Nominal
                  = 1300000000 MHz
 Length(9u) in km = GBIC does not support single mode fibre, or the length
                    must be determined from the transceiver technology.
 Length(9u)
                  = > 25.4 \text{ km}
 Length(50u)
                  = GBIC does not support 50 micron multi-mode fibre, or the
                    length must be determined from the transceiver technology.
                  = GBIC does not support 62.5 micron multi-mode fibre, or
 Length (62.5u)
                    the length must be determined from transceiver technology.
                  = GBIC does not support copper cables, or the length must
 Length (Copper)
                    be determined from the transceiver technology.
 Vendor name
                  = CTSCO-FINISAR
 Vendor OUI
                  = 36965
 Vendor Part No.
                  = FTR-0119-CSC
 Vendor Part Rev. = B
 Wavelength
                  = Not available
 CC_BASE
                  = 0x1A
Extended ID Fields
                  = Loss of Signal implemented TX_FAULT signal implemented TX_DISABLE is
 Options
implemented and disables the serial output [0x1A]
                  = Unspecified
 BR, max
```

= Unspecified

BR, min

```
Vendor Serial No. = K1273DH
Date code = 0.30409
Diag monitoring = Implemented
Calibration type = Internal
Rx pwr measuremnt = Optical Modulation Amplitude (OMA)
Address change = Required
CC_EXT
               = 0xB2
Vendor Specific ID Fields:
20944D30 29 00 02 80 22 33 38 3D C7 67 83 E8 DF 65 6A AF )..."38=Gg^Ch_ej/
SEEPROM contents (hex) size 128:
0x0000 01 00 01 00 00 00 00 00 00 00 01 0D 00 00 FF
0x0010 00 00 00 00 43 49 53 43 4F 2D 46 49 4E 49 53 41
                                                   ....CISCO-FINISA
0x0020 52 20 20 20 00 00 90 65 46 54 52 2D 30 31 31 39
                                                  R ..^PeFTR-0119
0x0030 2D 43 53 43 20 20 20 20 42 20 20 20 00 00 01 A
                                                   -CSC B
                                                   ....K1273DH
0x0040 00 1A 00 00 4B 31 32 37 33 44 48 20 20 20 20 20
0x0050 20 20 20 20 30 33 30 34 30 39 20 20 64 00 00 B2
                                                      030409 d..2
0x0060 29 00 02 80 22 33 38 3D C7 67 83 E8 DF 65 6A AF
                                                   )..^@"38=Gg^C._ej.
0x0070 1A 80 ED 00 00 00 00 00 00 00 00 38 23 3C 1B
                                                   .^@m.....8#<.
Switch#
```

This example shows how to display IDPROM information for the 10-Gigabit Ethernet interface 1/1:

```
Switch# show idprom interface tengigabitethernet1/1
```

```
X2 Serial EEPROM Contents:
Non-Volatile Register (NVR) Fields
X2 MSA Version supported
                                      : 0xA
NVR Size in bytes
                                      :0x100
Number of bytes used
                                      :0xD0
 Basic Field Address
                                      :0xB
Customer Field Address
                                      .0x77
                                      :0xA7
Vendor Field Address
Extended Vendor Field Address
                                      :0x100
Reserved
                                      :0x0
Transceiver type
                                      :0x2 = X2
Optical connector type
                                      :0x1 = SC
Bit encoding
                                      \cdot 0 \times 1 = NR7
Normal BitRate in multiple of 1M b/s :0x2848
 Protocol Type
Standards Compliance Codes :
10GbE Code Byte 0
                                      :0x2 =10GBASE-LR
10GbE Code Byte 1
                                      :0x0
SONET/SDH Code Byte 0
                                      :0x0
 SONET/SDH Code Byte 1
                                      :0x0
 SONET/SDH Code Byte 2
                                      :0x0
 SONET/SDH Code Byte 3
                                      : 0 \times 0
 10GFC Code Byte 0
                                      .0x0
 10GFC Code Byte 1
                                      :0x0
 10GFC Code Byte 2
                                      :0x0
10GFC Code Byte 3
                                      .0x0
Transmission range in 10m
                                      :0x3E8
Fibre Type :
Fibre Type Byte 0
                                      :0x40 =NDSF only
Fibre Type Byte 1
                                      :0x0 =Unspecified
Centre Optical Wavelength in 0.01nm steps - Channel 0 :0x1 0xFF 0xB8
 Centre Optical Wavelength in 0.01nm steps - Channel 1:0x0 0x0 0x0
Centre Optical Wavelength in 0.01nm steps - Channel 2 :0x0 0x0 0x0
Centre Optical Wavelength in 0.01nm steps - Channel 3 :0x0 0x0 0x0
 Package Identifier OUI :0xC09820
```

```
Transceiver Vendor OUI :0x3400800
Transceiver vendor name :CISCO-OPNEXT,INC
Part number provided by transceiver vendor
                                        ·TRT5021EN-SMC-W
Revision level of part number provided by vendor :00
Vendor serial number
                         :ONJ08290041
Vendor manufacturing date code :2004072000
Reserved1: 00 02 02 20 D1 00 00
Basic Field Checksum :0x10
Customer Writable Area:
 0x00: 58 32 2D 31 30 47 42 2D 4C 52 20 20 20 20 20 20
 0x10: 20 20 20 20 20 4F 4E 4A 30 38 32 39 30 30 34 31
 0x20: 31 30 2D 32 30 33 36 2D 30 31 20 20 41 30 31 20
Vendor Specific:
 0x30: 00 00 00 00 11 E2 69 A9 2F 95 C6 EE D2 DA B3 FD
 0x40: 9A 34 4A 24 CB 00 00 00 00 00 00 00 00 00 EF FC
 0x50: F4 AC 1A D7 11 08 01 36 00
Switch#
```

This example shows how to display IDPROM information for the supervisor engine:

```
Switch# show idprom supervisor
Supervisor Idprom:
Common Block Signature = 0xABAB
Common Block Version = 1
Common Block Length = 144
Common Block Checksum = 4153
Idprom Size = 256
Block Count = 2
FRU Major Type = 0x4101
FRU Minor Type = 333
OEM String = Cisco Systems, Inc.
Product Number = WS-X4014
Serial Number = JAB05320CCE
Part Number = 73-6854-04
Part Revision = 05
Manufacturing Deviation String = 0
Hardware Revision = 0.4
Manufacturing Bits = 0x0000
Engineering Bits = 0x0000
Snmp OID = 0.0.0.0.0.0.0.0
Power Consumption = 0
RMA Failure Code = 0 0 0 0
Supervisor Block Signature = 0x4101
Supervisor Block Version = 1
Supervisor Block Length = 24
Supervisor Block Checksum = 548
Feature Bits = 0x0000000000000000
Card Feature Index = 95
MAC Base = 0007.0ee5.2a44
MAC Count = 2
Switch#
```

This example shows how to display IDPROM information for the chassis:

```
Switch# show idprom chassis
Chassis Idprom:
  Common Block Signature = 0xABAB
  Common Block Version = 1
```

```
Common Block Length = 144
Common Block Checksum = 4285
Idprom Size = 256
Block Count = 2
FRU Major Type = 0x4001
FRU Minor Type = 24
OEM String = Cisco Systems, Inc.
Product Number = WS-C4006
 Serial Number = FOX04473737
 Part Number = 73-4289-02
Part Revision = 02
Manufacturing Deviation String = 0x00
Hardware Revision = 0.2
Manufacturing Bits = 0x0000
Engineering Bits = 0 \times 0000
Snmp OID = 0.0.0.0.0.0.0.0
Chassis Block Signature = 0x4001
Chassis Block Version = 1
Chassis Block Length = 22
Chassis Block Checksum = 421
Feature Bits = 0x0000000000000000
MAC Base = 0004.dd42.2600
MAC Count = 1024
Switch#
```

This example shows how to display IDPROM information for power supply 1:

```
Switch# show idprom power-supply 1
Power Supply 0 Idprom:
Common Block Signature = 0xABAB
Common Block Version = 1
Common Block Length = 144
 Common Block Checksum = 10207
 Idprom Size = 256
Block Count = 1
FRU Major Type = 0xAB01
FRU Minor Type = 8224
OEM String = Cisco Systems, Inc.
 Product Number = WS-CAC-1440W
 Serial Number = ACP05180002
 Part Number = 34-XXXX-01
 Part Revision = A0
Manufacturing Deviation String =
Hardware Revision = 1.1
Manufacturing Bits = 0x0000
Engineering Bits = 0x3031
 Snmp OID = 9.12.3.65535.65535.65535.65535
 Power Consumption = -1
 RMA Failure Code = 255 255 255 255
 Power Supply Block Signature = 0xFFFF
 PowerSupply Block Version = 255
 PowerSupply Block Length = 255
 PowerSupply Block Checksum = 65535
Feature Bits = 0x0000000FFFFFFFF
Current @ 110V = -1
Current @ 220V = -1
StackMIB OID = 65535
Switch#
```

This example shows how to display IDPROM information for the fan tray:

```
Switch# show idprom fan-tray
Fan Tray Idprom :
Common Block Signature = 0xABAB
Common Block Version = 1
Common Block Length = 144
Common Block Checksum = 19781
Idprom Size = 256
Block Count = 1
FRU Major Type = 0x4002
FRU Minor Type = 0
OEM String = "Cisco Systems"
 Product Number = WS-X4502-fan
 Serial Number =
Part Number =
Part Revision =
Manufacturing Deviation String =
Hardware Revision = 0.1
Manufacturing Bits = 0xFFFF
Engineering Bits = 0xFFFF
Snmp OID = 65535.65535.65535.65535.65535.65535.65535
Power Consumption = -1
RMA Failure Code = 255 255 255 255
Switch#
```

show interfaces

To display traffic on a specific interface, use the **show interfaces** command.

show interfaces [{{**fastethernet** mod/interface-number} | {**gigabitethernet** mod/interface-number} | {**tengigabitethernet** mod/interface-number} | {**null** interface-number} | **vlan** vlan_id} | **status**}]

Syntax Description

fastethernet mod/interface-number	(Optional) Specifies the Fast Ethernet module and interface.
gigabitethernet mod/interface-number	(Optional) Specifies the Gigabit Ethernet module and interface.
tengigabitethernet mod/interface-number	(Optional) Specifies the 10-Gigabit Ethernet module and interface.
null interface-number	(Optional) Specifies the null interface; the valid value is 0.
vlan vlan_id	(Optional) Specifies the VLAN; valid values are from 1 to 4094.
status	(Optional) Displays status information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for extended VLAN addresses was added.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The statistics are collected on a per-VLAN basis for Layer 2-switched packets and Layer 3-switched packets. The statistics are available for both unicast and multicast. The Layer 3-switched packet counts are available for both the ingress and egress directions. The per-VLAN statistics are updated every 5 seconds.

In some cases, you might see a difference in the duplex mode that is displayed between the **show interfaces** command and the **show running-config** commands. The duplex mode that is displayed in the **show interfaces** command is the actual duplex mode that the interface is running. The **show interfaces** command shows the operating mode for an interface, while the **show running-config** command shows the configured mode for an interface.

If you do not enter any keywords, all counters for all modules are displayed.

Examples

OL-6851-01

This example shows how to display traffic for a Gigabit Ethernet interface 2/5:

```
Switch# show interfaces gigabitethernet2/5
GigabitEthernet9/5 is up, line protocol is up
Hardware is C4k 1000Mb 802.3, address is 0001.64f8.3fa5 (bia 0001.64f8.3fa5)
Internet address is 172.20.20.20/24
MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 1000Mb/s
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:00, output never, output hang never
Last clearing of "show interface" counters never
Queueing strategy: fifo
Output queue 0/40, 0 drops; input queue 0/75, 0 drops
5 minute input rate 1000 bits/sec, 2 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
L2 Switched: ucast: 8199 pkt, 1362060 bytes - mcast: 6980 pkt, 371952 bytes
L3 in Switched: ucast: 0 pkt, 0 bytes - mcast: 0 pkt, 0 bytes mcast
L3 out Switched: ucast: 0 pkt, 0 bytes - mcast: 0 pkt, 0 bytes
300114 packets input, 27301436 bytes, 0 no buffer
Received 43458 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 input packets with dribble condition detected
15181 packets output, 1955836 bytes, 0 underruns
O output errors, O collisions, 3 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier
O output buffer failures, O output buffers swapped out
Switch#
```

This example shows how to display traffic for a 10-Gigabit Ethernet interface 1/1:

```
Switch# show interfaces tengigabitethernet1/1
```

```
TenGigabitEthernet1/1 is up, line protocol is up (connected)
  Hardware is Ten Gigabit Ethernet Port, address is 0004.dd46.7700 (bia 0004.dd46.7700)
  MTU 1500 bytes, BW 10000000 Kbit, DLY 10 usec,
     reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 10Gb/s, link type is auto, media type is 10GBaseL
  input flow-control is off, output flow-control is off
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/2000/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
     0 packets input, 0 bytes, 0 no buffer
     Received 0 broadcasts (0 multicast)
     0 runts, 0 giants, 0 throttles
     0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
     0 input packets with dribble condition detected
     0 packets output, 0 bytes, 0 underruns
     0 output errors, 0 collisions, 0 interface resets
     O babbles, O late collision, O deferred
     0 lost carrier, 0 no carrier
     0 output buffer failures, 0 output buffers swapped out
Switch#
```

This example shows how to display status information for Gigabit Ethernet interface 1/2:

Switch# show interfaces gigabitethernet1/2 status

Port	Name	Status	Vlan	Duplex	Speed Type
Gi1/2		notconnect	1	auto	1000 1000-XWDM-RXONLY
Switch#					

This example shows how to display status information for the interfaces on the supervisor engine:

Switch# show interfaces status

Port	Name	Status	Vlan	Duplex	Speed Type
Te1/1		connected	1	full	10G 10GBase-LR
Te1/2		connected	1	full	10G 10GBase-LR
Switch#					

show interfaces capabilities

To display the interface capabilities for an interface or for all the interfaces on a switch, use the **show interfaces capabilities** command.

show interfaces capabilities [{module mod}]

show interfaces [interface interface-number] capabilities

Syntax Description

module mod	(Optional) Display information for the specified module only.
interface	(Optional) Interface type; valid values are fastethernet , gigabitethernet , tengigabitethernet , and port-channel .
interface-number	(Optional) Port number.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Support for the 10-Gigabit Ethernet interface was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The *interface-number* argument designates the module and port number. Valid values for *interface-number* depend on the chassis and module used. For example, if you have a 48-port 10/100-Mbps Fast Ethernet RJ-21 (telco connector) switching module installed in a Catalyst 4507 chassis, valid values for the slot number are from 2 to 13 and valid values for the port number are 1 to 48.

Examples

This example shows how to display the interface capabilities for a module:

Switch# show interfaces capabilities module 1

GigabitEthernet1/1

Model: WS-X4516-Gbic
Type: Unsupported GBIC

Speed: 1000

Duplex: full

Trunk encap. type: 802.1Q,ISL

Trunk mode: on,off,desirable,nonegotiate

Channel: yes

Broadcast suppression:percentage(0-100), hw

Flowcontrol: rx-(off,on,desired),tx-(off,on,desired)

VLAN Membership: static, dynamic

Fast Start: yes

Queuing: rx-(N/A), tx-(4q1t, Sharing/Shaping)

```
CoS rewrite:
                      yes
 ToS rewrite:
                      yes
 Inline power:
                      no
 SPAN:
                      source/destination
 UDLD
                      yes
 Link Debounce:
                     no
 Link Debounce Time: no
 Port Security
                    yes
 Dot1x
                      yes
GigabitEthernet1/2
 Model:
                      WS-X4516-Gbic
 Type:
                      Unsupported GBIC
                     1000
 Speed:
 Duplex:
                     full
 Trunk encap. type: 802.1Q, ISL
 Trunk mode:
                     on, off, desirable, nonegotiate
 Channel:
                      yes
 Broadcast suppression:percentage(0-100), hw
                   rx-(off,on,desired),tx-(off,on,desired)
 Flowcontrol:
 VLAN Membership:
                      static, dynamic
 Fast Start:
                      yes
                      rx-(N/A), tx-(4q1t, Sharing/Shaping)
 Oueuing:
 CoS rewrite:
                     ves
 ToS rewrite:
                     yes
 Inline power:
                     no
 SPAN:
                     source/destination
 UDLD
                      yes
 Link Debounce:
                      no
 Link Debounce Time:
                      no
 Port Security
                      yes
 Dot1x
                       yes
Switch#
```

This example shows how to display the interface capabilities for the 10-Gigabit Ethernet interface 1/1:

```
Switch# show interfaces tengigabitethernet1/1 capabilities
TenGigabitEthernet1/1
```

```
TenGigabitEthernet1/1
 Model:
                       WS-X4517-X2
 Type:
                       10GBase-LR
                       10000
 Speed:
 Duplex:
                       full
                    802.1Q,ISL
 Trunk encap. type:
 Trunk mode:
                      on, off, desirable, nonegotiate
 Channel:
                       yes
 Broadcast suppression: percentage(0-100), hw
 Flowcontrol: rx-(off,on),tx-(off,on)
 VLAN Membership:
                    static, dynamic
 Fast Start:
                      yes
 Oueuing:
                      rx-(N/A), tx-(1p3q1t, Sharing/Shaping)
 CoS rewrite:
                      yes
                      yes
 ToS rewrite:
 Inline power:
                       no
 SPAN:
                       source/destination
 IIDI'D:
                       yes
 Link Debounce:
                      no
 Link Debounce Time: no
 Port Security:
                      yes
 Dot1x:
                      yes
 Maximum MTU:
                       9198 bytes (Jumbo Frames)
 Multiple Media Types: no
 Diagnostic Monitoring: N/A
Switch#
```

This example shows how to display the interface capabilities for Gigabit Ethernet interface 1/1:

```
Switch# show interfaces gigabitethernet1/1 capabilities
GigabitEthernet1/1
  Model:
                       WS-X4014-Gbic
                       No Ghic
  Type:
                       1000
  Speed:
                       full
 Duplex:
  Trunk encap. type: 802.1Q, ISL
  Trunk mode:
                    on, off, desirable, nonegotiate
  Channel:
                       yes
  Broadcast suppression:percentage(0-100), hw
                 rx-(off,on,desired),tx-(off,on,desired)
  Flowcontrol:
  VLAN Membership:
                       static, dynamic
  Fast Start:
                       yes
                       rx-(N/A), tx-(4q1t, Sharing/Shaping)
  Queuing:
  CoS rewrite:
                       ves
  ToS rewrite:
                       ves
  Inline power:
                       no
  SPAN:
                       source/destination
 UDDID:
                      yes
 Link Debounce:
                       no
  Link Debounce Time:
                       no
  Port Security:
                       ves
 Dot1x:
                       yes
 MTU Supported:
                       jumbo frames, baby giants
Switch#
```

This example shows how to display the interface capabilities for Fast Ethernet interface 3/1:

Switch# show interfaces fastethernet3/1 capabilities

```
FastEthernet3/1
 Model:
                       WS-X4148-RJ-RJ-45
                       10/100BaseTX
 Type:
                       10,100,auto
 Speed:
 Duplex:
                       half, full, auto
 Trunk encap. type:
                       802.1Q,ISL
 Trunk mode:
                       on, off, desirable, nonegotiate
 Channel:
                       yes
 Broadcast suppression:percentage(0-100), sw
 Flowcontrol:
                     rx-(none),tx-(none)
 VLAN Membership:
                     static, dynamic
 Fast Start:
                      yes
 Oueuing:
                       rx-(N/A), tx-(4q1t, Shaping)
 CoS rewrite:
                       yes
  ToS rewrite:
                       yes
  Inline power:
 SPAN:
                       source/destination
 UDLD:
                       ves
 Link Debounce:
                       no
 Link Debounce Time: no
 Port Security:
                      yes
 Dot1x:
                       yes
 MTU Supported:
                     no jumbo frames, baby giants
Switch#
```

Related Commands

show interfaces counters

show interfaces counters

To display the traffic on the physical interface, use the **show interfaces counters** command.

show interfaces counters [all | detail | errors | storm-control | trunk] [module mod]

Syntax Description

all	(Optional) Displays all the interface counters including errors, trunk, and detail.		
detail	(Optional) Displays the detailed interface counters.		
errors	(Optional) Displays the interface error counters.		
storm-control	(Optional) Displays the number of packets discarded due to suppression on the interface.		
trunk	(Optional) Displays the interface trunk counters.		
module mod	(Optional) Limits the display to interfaces on a specific module.		

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Support for storm control.
12.2(18)EW	Support for the display of total suppression discards.

Usage Guidelines

If you do not enter any keywords, all the counters for all modules are displayed.

The display for the **storm-control** keyword includes the suppressed multicast bytes.

Examples

This example shows how to display the error counters for a specific module:

 ${\tt Switch \#\ show\ interfaces\ counters\ errors\ module\ 1}$

Port	Align-Err	FCS-Err	Xmit-Err	Rcv-Err	UnderSize		
Gi1/1	0	0	0	0	0		
Gi1/2	0	0	0	0	0		
Port	Single-Col Mu	lti-Col La	ate-Col Exc	ess-Col Ca	rri-Sen	Runts	Giants
Gi1/1	0	0	0	0	0	0	0
Gi1/2	0	0	0	0	0	0	0
Switch#							

This example shows how to display the traffic that is seen by a specific module:

Switch# show interfaces counters module 1

Port	InOctets	InUcastPkts	InMcastPkts	InBcastPkts
Gi1/1	0	0	0	0
Gi1/2	0	0	0	0
Port	OutOctets	OutUcastPkts	OutMcastPkts	OutBcastPkts
Gi1/1	0	0	0	0
Gi1/2	0	0	0	0
Switch#				

This example shows how to display the trunk counters for a specific module:

Switch# show interfaces counters trunk module 1

Port	TrunkFramesTx	TrunkFramesRx	WrongEncap
Gi1/1	0	0	0
Gi1/2	0	0	0
Switch#			

This example shows how to display the number of packets that are discarded due to suppression:

Switch# show interfaces counters storm-control

Multicast Suppression : Enabled

Port	BcastSuppLevel	TotalSuppressionDiscards
Fa5/35	10.00%	6278550
Switch#		

Related Commands

show interfaces capabilities

show interfaces description

To display a description and status of an interface, use the show interfaces description command.

show interfaces [interface] description

•		_	-	
~ 1	/ntax	Heer	۱rın	tınn
•	viitua	DUST	, , , ,	uvi

interface ((Optional)	Type of	f interface.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display information for all interfaces:

Switch# show interfaces description

Interface	Status	Protocol	Description
PO0/0	admin down	down	First interface
PO0/1	admin down	down	
Gi1/1	up	up	GigE to server farm
Switch#			

Related Commands

description (refer to Cisco IOS documentation)

show interfaces link

To display how long a cable has been disconnected from an interface, use the **show interfaces link** command:

show interfaces link [module mod_num]

Syntax Description

modi	nΙσ	mad	num

(Optional) Limits the display to interfaces on a module.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.2(18)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

If the interface state is up, the command displays 0:00. If the interface state is down, the time (in hours, minutes, and seconds) is displayed.

Examples

This example shows how to display active link-level information:

Switch# show interfaces link

Port	Name	Down Time
Gi1/1		00:00:00
Gi1/2		00:00:00
Gi3/1		00:00:00
Gi3/2		00:00:00
Fa4/1		00:00:00
Fa4/2		00:00:00
Fa4/3		00:00:00
Fa4/4		00:00:00

This example shows how to display inactive link-level information:

Switch# show interfaces link

Port	Name	Do	own Time	9	
Gi3/4		1	minute	28	secs
Gi3/5		1	minute	28	secs
Gi3/6		1	minute	28	secs
Gi4/1		1	minute	28	secs

In this example, the cable has been disconnected from the port for 1 minute and 28 seconds.

show interfaces mtu

To display the maximum transmission unit (MTU) size of all the physical interfaces and SVIs on the switch, use the **show interfaces mtu** command.

show interfaces mtu [module mod]

Syntax Description	module mod	(Optional) Limits the display to interfaces on a specific module.

Defaults This command has no default settings.

Command Modes EXEC

Command History	Release	Modification
	12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples This example shows how to display the MTU size for all interfaces on module 1:

Switch> show interfaces mtu module 1

Port	Name	MTU
Gi1/1		1500
Gi1/2		1500
Switch	>	

Related Commands mi

show interfaces private-vlan mapping

To display PVLAN mapping information for VLAN SVIs, use the **show interfaces private-vlan mapping** command.

show interfaces private-vlan mapping [active]

•	_		
Syntax	Desc	ript	ion

active (Optional) Displays active interfac	ces only.
---	-----------

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

This command displays SVI information only.

Examples

This example shows how to display PVLAN mapping information:

Switch# show interfaces private-vlan mapping

Interface Secondary VLAN Type

vlan2	301	isolated
vlan2	302	isolated
Crititah#		

Switch#

Related Commands

private-vlan

private-vlan mapping

show interfaces status

To display the interface status or a list of interfaces in error-disabled state, use the **show interfaces status** command.

show interfaces status [err-disabled]

ntax			

err-disabled

(Optional) Displays interfaces in error-disabled state.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the status of all interfaces:

Switch# show interfaces status

Port	Name	Status	Vlan	Duplex	Speed	Type
Gi1/1		disabled	routed	full	1000	missing
Gi1/2		notconnect	1	full	1000	unknown (4)
Fa5/1		disabled	routed	auto	auto	10/100BaseTX
Fa5/2		disabled	routed	auto	auto	10/100BaseTX
Fa5/3		disabled	routed	auto	auto	10/100BaseTX
Fa5/4		disabled	routed	auto	auto	10/100BaseTX
Fa5/15		disabled	routed	auto	auto	10/100BaseTX
Fa5/16		disabled	routed	auto	auto	10/100BaseTX
Fa5/17		disabled	routed	auto	auto	10/100BaseTX
Switch#						

This example shows how to display the status of interfaces in an error-disabled state:

Switch# show interfaces status err-disabled

Port Name Status Reason Fa9/4 notconnect link-flap

informational error message when the timer expires on a cause

 $5d04h: PM-SP-4-ERR_RECOVER: Attempting to recover from link-flap err-disable state on Fa9/4 Switch#$

Related Commands

errdisable detect

show errdisable recovery

show interfaces switchport

To display the administrative and operational status of a switching (nonrouting) port, use the **show interfaces switchport** command.

show interfaces [interface-id] **switchport** [**module** mod]

Syntax Description

interface-id	(Optional) Interface ID for the physical port.
module mod	(Optional) Limits the display to interfaces on the specified module; valid values are from 1 to 6.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Support for per-interface display.
12.2(18)EW	Support for displaying the status of native VLAN tagging in the command output.

Examples

This example shows how to display switch-port information using the **begin** output modifier:

Switch# show interfaces switchport | include VLAN

Name: Fa5/6

Access Mode VLAN: 200 (VLAN0200)
Trunking Native Mode VLAN: 1 (default)

Trunking VLANs Enabled: ALL

Pruning VLANs Enabled: ALL

Switch#

This example shows how to display switch-port information for module 1:

Switch# show interfaces switchport module 1

Name:Gi1/1

Switchport: Enabled

Administrative Mode:dynamic auto

Operational Mode:down

Administrative Trunking Encapsulation:negotiate

Negotiation of Trunking:On Access Mode VLAN:1 (default)

Trunking Native Mode VLAN:1 (default)

Administrative private-vlan host-association:none

Administrative private-vlan mapping:none

Operational private-vlan:none

Trunking VLANs Enabled:ALL

Pruning VLANs Enabled:2-1001

Name:Gi1/2

Switchport:Enabled

```
Administrative Mode:dynamic auto
Operational Mode:down
Administrative Trunking Encapsulation:negotiate
Negotiation of Trunking:On
Access Mode VLAN:1 (default)
Trunking Native Mode VLAN:1 (default)
Administrative private-vlan host-association:none
Administrative private-vlan mapping:none
Operational private-vlan:none
Trunking VLANs Enabled:ALL
Pruning VLANs Enabled:2-1001
Switch#
```

This example shows how to display the status of native VLAN tagging on the port:

```
Switch# show interfaces g1/2 switchport
Name: Gi1/2
Switchport: Enabled
Administrative Mode: dynamic auto
Operational Mode: static access
Administrative Trunking Encapsulation: negotiate
Operational Trunking Encapsulation: native
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Native VLAN tagging: Disabled **
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Administrative private-vlan trunk Native VLAN tagging: Disabled
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
```

Related Commands

show interfaces capabilities show interfaces counters

show interfaces transceiver

To display diagnostic-monitoring data for all interfaces that have transceivers installed, use the **show interfaces transceiver** command.

show interfaces $\{\{[int_name] \text{ transceiver } \{[detail]\} \mid \{transceiver [module <math>mod]\}\}$

Syntax Description

int_name	(Optional) Interface.
detail	(Optional) Displays the calibrated values and the A2D readouts if the readout values differ from the calibrated values. Also displays the high-alarm, high-warning, low-warning, and low-alarm thresholds.
module mod	(Optional) Limits the display to interfaces on a specific module.

Defaults

The noninterface-specific versions of the show interfaces transceiver command are enabled by default.

The interface-specific versions of these commands are enabled by default if the specified interface has a transceiver (GBIC or SFP) that is configured for diagnostic monitoring, and the transceiver is in a module that supports diagnostic monitoring.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(20)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(18)EW	Support for the calibration keyword was withdrawn.

Usage Guidelines

The **show interfaces transceiver** command provides useful information under the following conditions:

- At least one transceiver is installed on a chassis that is configured for diagnostic monitoring.
- The transceiver is in a module that supports diagnostic monitoring.

If you notice that the alarm and warning flags have been set on a transceiver, reenter the command to confirm.

Examples

This example shows how to display diagnostic monitoring data for all interfaces with transceivers installed on the switch:

Switch# show interfaces transceiver

```
If device is externally calibrated, only calibrated values are printed.
++: high alarm, +: high warning, -: low warning, --: low alarm.

NA or N/A: not applicable, Tx: transmit, Rx: receive.

mA: milliamperes, dBm: decibels (milliwatts).

Optical Optical

Temperature Voltage Current Tx Power Rx Power

Port (Celsius) (Volts) (mA) (dBm) (dBm)
```

Gi1/1	48.1	3.30	0.0	8.1 ++	N/A
Gi1/2	33.0	3.30	1.8	-10.0	-36.9
Gi2/1	43.7	5.03	50.6 +	-16.7	N/A
Gi2/2	39.2	5.02	25.7	0.8	N/A
Switch#					



The value for the Optical Tx Power (in dBm) equals ten times log (Tx Power in mW). If the Tx Power value is 3 mW, then the Optical Tx Power value equals 10 * log (3), which equals 10 * .477 or 4.77 dBm. The Optical Rx Power value behaves similarly. If the Tx Power or the Rx Power is zero, then its dBm value is undefined and is shown as N/A (not applicable).

This example shows how to display detailed diagnostic monitoring data, including calibrated values, alarm and warning thresholds, A2D readouts, and alarm and warning flags. The A2D readouts are reported separately in parentheses only if they differ from the calibrated values:

Switch# show interfaces transceiver detail

mA: milliamperes, dBm: decibels (milliwatts), NA or N/A: not applicable. ++ : high alarm, + : high warning, - : low warning, -- : low alarm. A2D readouts (if they differ), are reported in parentheses. The threshold values are calibrated.

Port	Temperature (Celsius)	High Alarm Threshold (Celsius)	High Warn Threshold (Celsius)	Threshold	Low Alarm Threshold (Celsius)
Gi1/1	48.1	100.0	100.0	0.0	0.0
Gi1/2	34.9	100.0	100.0	0.0	0.0
Gi2/1	43.5	70.0	60.0	5.0	0.0
Gi2/2	39.1	70.0	60.0	5.0	0.0
	_	High Alarm	-		Low Alarm
	Voltage	Threshold	Threshold		Threshold
Port	(Volts)	(Volts)	(Volts)	(Volts)	(Volts)
Gi1/1	3.30	6.50	6.50	N/A	N/A
Gi1/2	3.30	6.50	6.50	N/A	N/A
Gi2/1	5.03	5.50	5.25	4.75	4.50
Gi2/2	5.02	5.50	5.25	4.75	4.50
	Current	High Alarm Threshold	High Warn Threshold	Low Warn Threshold	Low Alarm Threshold
Dowt	(milliamperes)				
Port	(MIIIIIamperes)	(mA) 	(mA) 	(mA) 	(mA)
Gi1/1	0.0	130.0	130.0	N/A	N/A
Gi1/2	1.7	130.0	130.0	N/A	N/A
Gi2/1	50.6 +	60.0	40.0	10.0	5.0
Gi2/2	25.8	60.0	40.0	10.0	5.0
	Optical	High Alarm	High Warn	Low Warn	Low Alarm
	Transmit Power	Threshold	Threshold	Threshold	Threshold
Port	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)
Gi1/1	8.1 ++	8.1	8.1	N/A	N/A
Gi1/2	-9.8	8.1	8.1	N/A	N/A
Gi2/1	-16.7 (-13.0)	3.4	3.2	-0.3	-0.5
Gi2/2	0.8 (5.1)	3.4	3.2	-0.3	-0.5
	Optical	High Alarm	High Warn	Low Warn	Low Alarm
	Receive Power	Threshold	Threshold	Threshold	Threshold
Port	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)

Gi1/1	N/A		8.1	8.1	N/A	N/A
Gi1/2	-30.9		8.1	8.1	N/A	N/A
Gi2/1	N/A	(-28.5)	5.9	-6.7	-28.5	-28.5
Gi2/2	N/A	(-19.5)	5.9	-6.7	-28.5	-28.5
Switch#						

This example shows how to display the monitoring data for the interfaces that have transceivers installed on module?

Switch# show interfaces transceiver module 2

If device is externally calibrated, only calibrated values are printed. ++ : high alarm, + : high warning, - : low warning, -- : low alarm. NA or N/A: not applicable, Tx: transmit, Rx: receive. mA: milliamperes, dBm: decibels (milliwatts).

				Optical	Optical
	Temperature	Voltage	Current	Tx Power	Rx Power
Port	(Celsius)	(Volts)	(mA)	(dBm)	(dBm)
Gi2/1	43.7	5.03	50.6 +	-16.7	N/A
Gi2/2	39.2	5.02	25.7	0.8	N/A
Switch#					

This example shows how to display the detailed monitoring data for the interfaces that have transceivers installed on module 2:

Switch# show interfaces transceiver detail module 2

mA: milliamperes, dBm: decibels (milliwatts), NA or N/A: not applicable. ++ : high alarm, + : high warning, - : low warning, -- : low alarm. A2D readouts (if they differ), are reported in parentheses. The threshold values are calibrated.

Port	Temperature (Celsius)	High Alarm Threshold (Celsius)	Threshold (Celsius)	Threshold (Celsius)	Threshold (Celsius)
	43.5 39.1	70.0	60.0	5.0 5.0	0.0
Port	Voltage (Volts)	High Alarm Threshold (Volts)	Threshold (Volts)	Threshold (Volts)	Threshold (Volts)
Gi2/1 Gi2/2	5.03 5.02		5.25	4.75 4.75	4.50
Port	Current (milliamperes)	(mA)	Threshold	Threshold (mA)	Threshold
Gi2/1	50.6 + 25.8		40.0	10.0	5.0
Port	Optical Transmit Power (dBm)	Threshold (dBm)	Threshold (dBm)	Threshold (dBm)	Threshold (dBm)
	-16.7 (-13.0) 0.8 (5.1)	3.4	3.2	-0.3	-0.5
Port	Optical Receive Power (dBm)	Threshold	Threshold	Threshold	Threshold

-							
G	Gi2/1	N/A	(-28.5)	5.9	-6.7	-28.5	-28.5
G	Gi2/2	N/A	(-19.5)	5.9	-6.7	-28.5	-28.5
Swite	¬h#						

This example shows how to display the monitoring data for the transceivers on interface Gi1/2:

```
Switch# show interfaces g1/2 transceiver
```

```
ITU Channel 23 (1558.98 nm),
Transceiver is externally calibrated.

If device is externally calibrated, only calibrated values are printed.
++ : high alarm, + : high warning, - : low warning, -- : low alarm.

NA or N/A: not applicable, Tx: transmit, Rx: receive.

mA: milliamperes, dBm: decibels (milliwatts).
```

	Temperature	Voltage	Current	Optical Tx Power	-
Port	(Celsius)	(Volts)	(mA)	(dBm)	(dBm)
Gi2/1 Switch#	43.7	5.03	50.6 +	-16.7	N/A

This example shows how to display detailed the monitoring data for the transceivers on interface Gi1/2:

Switch# show interfaces g1/2 transceiver detail

```
ITU Channel 23 (1558.98 nm),
Transceiver is externally calibrated.
mA: milliamperes, dBm: decibels (milliwatts), NA or N/A: not applicable.
++ : high alarm, + : high warning, - : low warning, -- : low alarm.
A2D readouts (if they differ), are reported in parentheses.
The threshold values are calibrated.
```

Port	Temperature (Celsius)	High Alarm Threshold (Celsius)	Threshold	Threshold	Threshold
Gi2/1	43.5	70.0	60.0	5.0	0.0
Port	Voltage (Volts)	High Alarm Threshold (Volts)	Threshold	Threshold	Threshold
Gi2/1	5.03	5.50	5.25	4.75	4.50
Port	Current (milliamperes)	High Alarm Threshold (mA)	Threshold	Threshold	Threshold
Gi2/1	50.6 +	60.0	40.0	10.0	5.0
Port	Optical Transmit Power (dBm)	-	Threshold	Threshold	Threshold
Gi2/1	-16.7 (-13.0)	3.4	3.2	-0.3	-0.5
Port	Optical Receive Power (dBm)		Threshold	Low Warn Threshold (dBm)	Threshold
Gi2/1 Ltch#	N/A (-28.5)	5.9	-6.7	-28.5	-28.5

Related Commands

show idprom

show interfaces status

show interfaces trunk

To display port and module interface-trunk information, use the **show interfaces trunk** command.

show interfaces trunk $[module \ mod]$

•		_		
~ 1	/ntax	11000	rin	tini

module mod	(Optional) Limits the display to interfaces on the specified module; valid values are
	from 1 to 6.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

If you do not specify a keyword, only information for trunking ports is displayed.

Examples

This example shows how to display interface-trunk information for module 5:

Switch# show interfaces trunk module 5

Port	Mode	Encapsulation	Status	Native vlan
Fa5/1	routed	negotiate	routed	1
Fa5/2	routed	negotiate	routed	1
Fa5/3	routed	negotiate	routed	1
Fa5/4	routed	negotiate	routed	1
Fa5/5	routed	negotiate	routed	1
Fa5/6	off	negotiate	not-trunking	10
Fa5/7	off	negotiate	not-trunking	10
Fa5/8	off	negotiate	not-trunking	1
Fa5/9	desirable	n-isl	trunking	1
Fa5/10	desirable	negotiate	not-trunking	1
Fa5/11	routed	negotiate	routed	1
Fa5/12	routed	negotiate	routed	1
Fa5/48	routed	negotiate	routed	1
Port	Vlans allowed	d on trunk		
Fa5/1	none			
Fa5/2	none			
Fa5/3	none			
Fa5/4	none			
Fa5/5	none			
Fa5/6	none			
Fa5/7	none			
Fa5/8	200			
Fa5/9	1-1005			

```
Fa5/10
         none
Fa5/11
         none
Fa5/12
         none
Fa5/48
         none
         Vlans allowed and active in management domain
Port
Fa5/1
         none
Fa5/2
         none
Fa5/3
         none
Fa5/4
         none
Fa5/5
         none
Fa5/6
         none
Fa5/7
         none
Fa5/8
         200
         Fa5/9
02,850,917,999,1002-1005
Fa5/10
        none
Fa5/11
         none
Fa5/12
         none
Fa5/48
         none
Port
         Vlans in spanning tree forwarding state and not pruned
Fa5/1
         none
Fa5/2
         none
Fa5/3
         none
Fa5/4
         none
Fa5/5
         none
Fa5/6
         none
Fa5/7
         none
Fa5/8
         1-6,10,20,50,100,152,200,300,303-305,349-351,400,500,521,524,570,801-8
Fa5/9
02,850,917,999,1002-1005
Fa5/10
        none
Fa5/11
         none
Fa5/48
         none
Switch#
```

This example shows how to display trunking information for active trunking ports:

Switch# show interfaces trunk

```
Port
      Mode
               Encapsulation Status
                                   Native vlan
Fa5/9
      desirable
               n-isl
                          trunking
                                   1
      Vlans allowed on trunk
Port.
Fa5/9
       1-1005
Port
      Vlans allowed and active in management domain
      Fa5/9
02,850,917,999,1002-1005
Port
      Vlans in spanning tree forwarding state and not pruned
Fa5/9
       02,850,917,999,1002-1005
Switch#
```

show ip arp inspection

To show the status of dynamic ARP inspection for a specific range of VLANs, use the **show ip arp inspection** command.

show ip arp inspection {[statistics] vlan vlan-range | interfaces [interface-name]}

Syntax Description

statistics	(Optional) Displays statistics for the following types of packets that have been processed by this feature: forwarded, dropped, MAC validation failure, and IP validation failure.
vlan vlan-range	(Optional) When used with the statistics keyword, displays the statistics for the selected range of VLANs. Without the statistics keyword, displays the configuration and operating state of DAI for the selected range of VLANs.
interfaces interface-name	(Optional) Displays the trust state and the rate limit of ARP packets for the provided interface. When the interface name is not specified, the command displays the trust state and rate limit for all applicable interfaces in the system.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the statistics of packets that have been processed by DAI for VLAN 3:

Switch# show ip arp inspection statistics vlan 3

Vlan	Forwarded		Dropped	DHCP Dro	ps	ACL Drop	s
3	31753		102407	1024	07		0
Vlan	DHCP Permits	ACL	Permits	Source MAC	Failur	res	
3	31753		0			0	
Vlan	Dest MAC Failu	res	IP Valid	ation Failure	es		
3		0)		
Switch#							

This example shows how to display the statistics of packets that have been processed by DAI for all active VLANs:

Switch# show ip arp inspection statistics

Vlan	Forwarded	Dropped	DHCP Drops	ACL Drops
1	0	0	0	0
2	0	0	0	0
3	68322	220356	220356	0
4	0	0	0	0
100	0	0	0	0
101	0	0	0	0
1006	0	0	0	0
1007	0	0	0	0
	DHCP Permits AC			
 1	0	0		0
2	0	0		0
3	68322	0		0
4	0	0		0
100	0	0		0
101	0	0		0
1006	0	0		0
1007	0	0		0
Vlan	Dest MAC Failures		ation Failures	
1	0		0	
2	0		0	
3	0		0	
4	0		0	
100	0		0	
101	0		0	
1006	0		0	
1007	0		0	
Switch#				

This example shows how to display the configuration and operating state of DAI for VLAN 1:

Switch# show ip arp inspection vlan 1
Source Mac Validation : Disabled
Destination Mac Validation : Disabled
IP Address Validation : Disabled

Vlan	Configuration	Operation ACL Match	Static ACL
1	Enabled	Active	
Vlan	ACL Logging	DHCP Logging	
1	Deny	Deny	
Switch#			

This example shows how to display the trust state of interface Fa6/3:

Switch# show ip arp inspection interfaces fastEthernet 6/3

DWICCIII DIION ID	arb rupbeceron	Incorraces rase.	
Interface	Trust State	Rate (pps)	Burst Interval
Fa6/1	Untrusted	20	5
Switch#			

This example shows how to display the trust state of the interfaces on the switch:

Switch#	show i	ip arp	inspection	interfa	ces
Interface		Tru	ıst State	Rate	(pps)
Gi1/1		Un	ntrusted		15
Gi1/2		Un	ntrusted		15
Gi3/1		Un	ntrusted		15
Gi3/2		Un	ntrusted		15
Fa3/3		Tr	rusted		None
Fa3/4		Un	ntrusted		15
Fa3/5		Un	ntrusted		15
Fa3/6		Un	ntrusted		15
Fa3/7		Un	ntrusted		15
Switch#					

Related Commands

arp access-list clear ip arp inspection log show ip arp inspection

show ip arp inspection log

To show the status of the log buffer, use the **show ip arp inspection log** command.

show ip arp inspection log

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the current contents of the log buffer before and after the buffers are cleared:

Switch# show ip arp inspection log Total Log Buffer Size : 10 Syslog rate : 0 entries per 10 seconds.

Interface	Vlan	Sender MAC	Sender IP	Num of Pkts
Fa6/3	1	0002.0002.0002	1.1.1.2	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.3	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.4	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.5	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.6	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.7	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.8	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.9	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.10	1(12:02:52 UTC Fri Apr 25 2003)
Fa6/3	1	0002.0002.0002	1.1.1.11	1(12:02:52 UTC Fri Apr 25 2003)
				5(12:02:52 UTC Fri Apr 25 2003)
Switch#				

This example shows how to clear the buffer with the **clear ip arp inspection log** command:

Switch# clear ip arp inspection log Switch# show ip arp inspection log Total Log Buffer Size : 10 Syslog rate : 0 entries per 10 seconds. No entries in log buffer. Switch#

Related Commands

arp access-list clear ip arp inspection log

show ip cef vlan

To view IP CEF VLAN interface status and configuration information and display the prefixes for a specific interface, use the **show ip cef vlan** command.

show ip cef vlan vlan_num [detail]

Syntax Description

vlan_num	Number of the VLAN.
detail	(Optional) Displays detailed information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the prefixes for a specific VLAN:

Switch# show ip c	ef vlan 1003	
Prefix	Next Hop	Interface
0.0.0.0/0	172.20.52.1	FastEthernet3/3
0.0.0.0/32	receive	
10.7.0.0/16	172.20.52.1	FastEthernet3/3
10.16.18.0/23	172.20.52.1	FastEthernet3/3
Curi + ah#		

This example shows how to display detailed IP CEF information for a specific VLAN:

Switch# show ip cef vlan 1003 detail

```
IP Distributed CEF with switching (Table Version 2364), flags=0x0 1383 routes, 0 reresolve, 0 unresolved (0 old, 0 new) 1383 leaves, 201 nodes, 380532 bytes, 2372 inserts, 989 invalidations 0 load sharing elements, 0 bytes, 0 references universal per-destination load sharing algorithm, id 9B6C9823 3 CEF resets, 0 revisions of existing leaves refcounts: 54276 leaf, 51712 node
```

Adjacency Table has 5 adjacencies Switch#

show ip dhcp snooping

To display the DHCP snooping configuration, use the **show ip dhcp snooping** command.

show ip dhcp snooping

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EWA	Support for option 82 on untrusted ports was added.

Examples

This example shows how to display the DHCP snooping configuration:

Switch# show ip dhcp snooping

Switch DHCP snooping is enabled

 $\ensuremath{\mathsf{DHCP}}$ snooping is configured on the following VLANs:

5 10

Insertion of option 82 is enabled

Option82 on untrusted port is not allowed

Verification of hwaddr field is enabled

Interface Trusted Rate limit (pps)
-----FastEthernet6/11 no 10
FastEthernet6/36 yes 50
Switch#

Related Commands

ip dhcp snooping

ip dhcp snooping information option

ip dhcp snooping limit rate

ip dhcp snooping trust

ip dhcp snooping vlan

show ip dhcp snooping binding

To display the DHCP snooping binding entries, use the show ip dhcp snooping binding command.

show ip dhcp snooping binding [ip-address] [mac-address] [**vlan** vlan_num] [**interface** interface_num]

Syntax Description

ip-address	(Optional) IP address for the binding entries.
mac-address	(Optional) MAC address for the binding entries.
vlan vlan_num	(Optional) Specifies a VLAN.
interface interface_num	(Optional) Specifies an interface.

Defaults

If no argument is specified, the switch will display the entire DHCP snooping binding table.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

DHCP snooping is enabled on a VLAN only if both the global snooping and the VLAN snooping are enabled.

To configure a range of VLANs, use the optional *last_vlan* argument to specify the end of the VLAN range.

Examples

This example shows how to display the DHCP snooping binding entries for a switch:

Switch# show ip dhcp snooping binding

MacAddress	IP Address	Lease (seconds)	Type	VLAN	Interface
0000.0100.0201	10.0.0.1	1600	dhcp-snooping	100	FastEthernet3/1
Switch#					

This example shows how to display an IP address for DHCP snooping binding entries:

Switch# show ip dhcp snooping binding 172.100.101.102

MacAddress	IP Address	Lease (seconds)	Type	VLAN	Interface
0000.0100.0201 Switch#	172.100.101.10	2 1600	dhcp-snooping	100	FastEthernet3/1

This example shows how to display the MAC address for the DHCP snooping binding entries:

Switch# show ip dhcp snooping binding 55.5.5.2 0002.b33f.3d5f

MacAddress	IpAddress	Lease(sec)	Type	VLAN Interface
00:02:B3:3F:3D:5F	55.5.5.2	492	dhcp-snooping	99 FastEthernet6/36
Switch#				

This example shows how to display the DHCP snooping binding entries' MAC address for a specific VLAN:

Switch# show ip dhcp snooping binding 55.5.5.2 0002.b33f.3d5f vlan 99

MacAddress	IpAddress	Lease(sec)	Туре	VLAN	Interface
00:02:B3:3F:3D:5F	55.5.5.2	479	dhcp-snooping	99	FastEthernet6/36
Switch#					

This example shows how to display the dynamic DHCP snooping binding entries:

Switch# show ip dhcp snooping binding dynamic

MacAddress	IP Address	Lease (seconds)	Type	VLAN	Interface
0000.0100.0201	10.0.0.1	1600	dhcp-snooping	100	FastEthernet3/1
Switch#					

This example shows how to display the DHCP snooping binding entries on VLAN 100:

Switch# show ip dhcp snooping binding vlan 100'

MacAddress	IP Address	Lease (seconds)	Туре	VLAN	Interface
0000.0100.0201	10.0.0.1	1600	dhcp-snooping	100	FastEthernet3/1
Switch#					

This example shows how to display the DHCP snooping binding entries on Ethernet interface 0/1:

Switch# show ip dhcp snooping binding interface fastethernet3/1

MacAddress	IP Address	Lease (seconds)	Туре	VLAN	Interface
0000.0100.0201 Switch#	10.0.0.1	1600	dhcp-snooping	100	FastEthernet3/1

Table 2-18 describes the fields in the **show ip dhcp snooping** command output.

Table 2-18 show ip dhcp snooping Command Output

Field	Description
Mac Address	Client hardware MAC address.
IP Address	Client IP address assigned from the DHCP server.
Lease (seconds)	IP address lease time.
Туре	Binding type; statically configured from CLI or dynamically learned.
VLAN	VLAN number of the client interface.
Interface	Interface that connects to the DHCP client host.

Related Commands

ip dhcp snooping information option

ip dhcp snooping limit rate

ip dhcp snooping trust

ip igmp snooping

ip igmp snooping vlan

show ip dhcp snooping database

To display the status of the DHCP snooping database agent, use the **show ip dhcp snooping database** command.

show ip dhcp snooping database [detail]

Syntax Description

detail	(Optional)	Provides additional	operating state and	statistics information.
--------	------------	---------------------	---------------------	-------------------------

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Added support of state and statistics information.

Examples

This example shows how to display the DHCP snooping database:

```
Switch# show ip dhcp snooping database
Agent URL :
Write delay Timer: 300 seconds
Abort Timer: 300 seconds
Agent Running : No
Delay Timer Expiry : Not Running
Abort Timer Expiry: Not Running
Last Succeded Time : None
Last Failed Time : None
Last Failed Reason : No failure recorded.
Total Attempts
                           0 Startup Failures:
Successful Transfers :
                          0 Failed Transfers :
                                                        0
Successful Reads :
                           O Failed Reads :
                                                        0
Successful Writes
                           0
                                Failed Writes
                 :
Media Failures
```

Switch#

This example shows how to view additional operating statistics:

```
Switch# show ip dhcp snooping database detail
Agent URL: tftp://10.1.1.1/directory/file
Write delay Timer: 300 seconds
Abort Timer: 300 seconds

Agent Running: No
Delay Timer Expiry: 7 (00:00:07)
Abort Timer Expiry: Not Running
```

```
Last Succeded Time : None
Last Failed Time: 17:14:25 UTC Sat Jul 7 2001
Last Failed Reason : Unable to access URL.
Total Attempts : 21 Startup Failures : Successful Transfers : 0 Failed Transfers : Successful Reads : 0 Failed Reads : Successful Writes : 0 Failed Writes : Media Failures : 0
                                                                        0
                                                                       2.1
                                                                        0
First successful access: Read
Last ignored bindings counters :
Binding Collisions : 0
                                         Expired leases
Invalid interfaces :
                                   0 Unsupported vlans :
Parse failures
                                    0
Last Ignored Time : None
Total ignored bindings counters:
Binding Collisions : 0 Expired leases : Invalid interfaces : 0 Unsupported vlans :
                                                                            0
Parse failures :
```

Related Commands

```
ip dhcp snooping
ip dhcp snooping database
ip dhcp snooping information option
ip dhcp snooping limit rate
ip dhcp snooping trust
ip dhcp snooping vlan
```

Switch#

show ip igmp interface

To view IP IGMP interface status and configuration information, use the **show ip igmp interface** command.

show ip igmp interface [fastethernet *slot/port* | **gigabitethernet** *slot/port* | **tengigabitethernet** *slot/port* | **null** *interface-number* | **vlan** *vlan_id*]

Syntax Description

fastethernet slot/port	(Optional) Specifies the Fast Ethernet interface and the number of the slot and port.
gigabitethernet slot/port	(Optional) Specifies the Gigabit Ethernet interface and the number of the slot and port; valid values are from 1 to 9.
tengigabitethernet slot/port	(Optional) Specifies the 10-Gigabit Ethernet interface and the number of the slot and port; valid values are from 1 to 2.
null interface-number	(Optional) Specifies the null interface and the number of the interface; the only valid value is 0 .
vlan vlan_id	(Optional) Specifies the VLAN and the number of the VLAN; valid values are from 1 to 4094.

Defaults

If you do not specify a VLAN, information for VLAN 1 is shown.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

If you omit the optional arguments, the **show ip igmp interface** command displays information about all interfaces.

Examples

This example shows how to view IGMP information for VLAN 200:

Switch# show ip igmp interface vlan 200
IGMP snooping is globally enabled
IGMP snooping is enabled on this Vlan
IGMP snooping immediate-leave is disabled on this Vlan
IGMP snooping mrouter learn mode is pim-dvmrp on this Vlan
IGMP snooping is running in IGMP-ONLY mode on this VLAN
Switch#

Related Commands

clear ip igmp group

show ip igmp snooping mrouter

show ip igmp profile

To view all configured IGMP profiles or a specified IGMP profile, use the **show ip igmp profile** privileged EXEC command.

show ip igmp profile [profile number]

Syntax Description

profile number	(Optional) IGMP profile number to be displayed; valid ranges are from
	1 to 4294967295.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(11b)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

If no profile number is entered, all IGMP profiles are displayed.

Examples

This example shows how to display IGMP profile 40:

```
Switch# show ip igmp profile 40
IGMP Profile 40
    permit
    range 233.1.1.1 233.255.255.255
Switch#
```

This example shows how to display all IGMP profiles:

```
Switch# show ip igmp profile
IGMP Profile 3
    range 230.9.9.0 230.9.9.0
IGMP Profile 4
    permit
    range 229.9.9.0 229.255.255.255
```

Related Commands

ip igmp profile

show ip igmp snooping

To display information on dynamically learned and manually configured VLAN switch interfaces, use the **show ip igmp snooping** command.

show ip igmp snooping [querier | groups | mrouter] [vlan vlan_id] a.b.c.d [summary | sources | hosts] [count]

Syntax Description

querier	(Optional) Specifies that the display will contain IP address and version information.			
groups	(Optional) Specifies that the display will list VLAN members sorted by group IP addresses.			
mrouter	(Optional) Specifies that the display will contain information on dynamically learned and manually configured multicast switch interfaces.			
vlan vlan_id	(Optional) Specifies a VLAN; valid values are from 1 to 1001 and from 1006 to 4094.			
a.b.c.d	Group or multicast IP address.			
summary	(Optional) Specifies a display of detailed information for a v2 or v3 group.			
sources	(Optional) Specifies a list of the source IPs for the specified group.			
hosts	(Optional) Specifies a list of the host IPs for the specified group.			
count	(Optional) Specifies a display of the total number of group addresses learned by the system on a global or per-VLAN basis.			

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Support for extended addressing was added.
12.1(20)EW	Added support to display configuration state for IGMPv3 explicit host tracking.

Usage Guidelines

You can also use the **show mac-address-table multicast** command to display the entries in the MAC address table for a VLAN that has IGMP snooping enabled.

You can display IGMP snooping information for VLAN interfaces by entering the **show ip igmp snooping** command.

Examples

This example shows how to display the global snooping information on the switch:

```
Switch# show ip igmp snooping
Global IGMP Snooping configuration:
IGMP snooping
                           : Enabled
IGMPv3 snooping
                           : Enabled
Report suppression
TCN solicit query
                          : Enabled
                           : Disabled
TCN flood query count
                           : 2
Vlan 1:
IGMP snooping
                                 : Enabled
IGMP snooping : Enabled
IGMPv2 immediate leave : Disabled
Explicit host tracking : Enabled
Multicast router learning mode : pim-dvmrp
CGMP interoperability mode : IGMP_ONLY
Vlan 2:
IGMP snooping
                                  : Enabled
IGMPv2 immediate leave : Disabled Explicit host tracking : Enabled
Multicast router learning mode : pim-dvmrp
CGMP interoperability mode : IGMP_ONLY
Switch>
```

This example shows how to display the snooping information on VLAN 2:

```
Switch# show ip igmp snooping vlan 2
Global IGMP Snooping configuration:
                         : Enabled
IGMP snooping
                        : Enabled
IGMPv3 snooping
Report suppression
TCN solicit query
                         : Enabled
                        : Disabled
TCN flood query count
                         : 2
Vlan 2:
IGMP snooping
                              : Enabled
                        : Disabled
: Enabled
IGMPv2 immediate leave
Explicit host tracking
Multicast router learning mode : pim-dvmrp
CGMP interoperability mode : IGMP_ONLY
Switch>
```

This example shows how to display IGMP querier information for all VLANs on a switch:

Switch#	show	ip i	gmp	snooping	querier	
Vlan	IP	Addr	ess	IGMP	Version	Port
2	10	.10.1	0.1	v2		Router
3	172	2.20.	50.2	2 v3		Fa3/15
Switch>						

This example shows how to display IGMP querier information for VLAN 5 when running IGMPv2:

Switch# show ip igmp snooping querier vlan 5

IP address :5.5.5.10
IGMP version :v2
Port :Fa3/1
Max response time :10s
Switch>

This example shows how to display IGMP querier information for VLAN 5 when running IGMPv3:

Switch# show ip igmp snooping querier vlan 5

IP address :5.5.5.10
IGMP version :v3
Port :Fa3/1
Max response time :10s
Query interval :60s
Robustness variable :2
Switch>

This example shows how to display snooping information for a specific group:

Switch# show ip igmp snooping group

Vlan	Group	Version	Ports
2	224.0.1.40	v3	Router
2	224.2.2.2	v3	Fa6/2
Switch>			

This example shows how to display the group's host types and ports in VLAN 1:

Switch# show ip igmp snooping group vlan 1 $\,$

Vlan	Group	Host Type	Ports	
1	229.2.3.4	v3	fa2/1 fa2/3	
1	224.2.2.2	v3	Fa6/2	
Switch>				

This example shows how to display the group's host types and ports in VLAN 1:

Switch# show ip igmp snooping group vlan 10 226.6.6.7

Vlan	Group	Version	Ports
10	226.6.6.7	v3	Fa7/13, Fa7/14
Switch>			

This example shows how to display the current state of a group with respect to a source IP address:

Switch# show ip igmp snooping group vlan 10 226.6.6.7 sources

Source information for group 226.6.6.7:

Timers: Expired sources are deleted on next IGMP General Query

SourceIP	Expires	Uptime	Inc	Hosts	Exc	Hosts
2.0.0.1	00:03:04	00:03:48	2		0	
2.0.0.2	00:03:04	00:02:07	2		0	
Switch>						

This example shows how to display the current state of a group with respect to a host MAC address:

```
Switch# show ip igmp snooping group vlan 10 226.6.6.7 hosts IGMPv3 host information for group 226.6.6.7 Timers: Expired hosts are deleted on next IGMP General Query
```

Host (MAC/IP)	Filter mode	Expires	Uptime	# Sources
175.1.0.29	INCLUDE	stopped	00:00:51	2
175.2.0.30	INCLUDE	stopped	00:04:14	2
Switch>				

This example shows how to display summary information for a v3 group:

```
Switch# show ip igmp snooping group vlan 10 226.6.6.7 summary Group Address (Vlan 10) : 226.6.6.7
Host type : v3
```

Member Ports : Fa7/13, Fa7/14
Filter mode : INCLUDE
Expires : stopped
Sources : 2

Reporters (Include/Exclude) : 2/0 Switch>

This example shows how to display multicast router information for VLAN 1:

```
Switch# show ip igmp snooping mrouter vlan 1
vlan ports

1 Gi1/1,Gi2/1,Fa3/48,Router
Switch#
```

This example shows how to display the total number of group addresses learned by the system globally:

```
Switch# show ip igmp snooping group count
Total number of groups: 54
Switch>
```

This example shows how to display the total number of group addresses learned on VLAN 5:

```
Switch# show ip igmp snooping group vlan 5 count Total number of groups: 30 Switch>
```

Related Commands

ip igmp snooping

ip igmp snooping vlan immediate-leave

ip igmp snooping vlan mrouter

ip igmp snooping vlan static

show ip igmp interface

show ip igmp snooping mrouter

show mac-address-table multicast

show ip igmp snooping membership

To display host membership information, use the show ip igmp snooping membership command.

show ip igmp snooping membership [interface *interface_num*] [**vlan** *vlan_id*] [**reporter** *a.b.c.d*] [**source** *a.b.c.d* **group** *a.b.c.d*]

Syntax Description

interface interface_num	(Optional) Displays IP address and version information of an interface.
vlan vlan_id	(Optional) Displays VLAN members sorted by group IP address of a VLAN; valid values are from 1 to 1001 and from 1006 to 4094.
reporter a.b.c.d	(Optional) Displays membership information for a specified reporter.
source a.b.c.d	(Optional) Specifies a reporter, source, or group IP address.
group a.b.c.d	(Optional) Displays all members of a channel (source, group), sorted by interface or VLAN.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(20)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

This command is valid only if explicit host tracking is enabled on the switch.

Examples

This example shows how to display host membership for the Gigabit Ethernet interface 4/1:

Switch# show ip igmp snooping membership interface gigabitethernet4/1
#channels: 5
#hosts : 1
Source/Group Interface Reporter Uptime Last-Join Last-Leave

40.40.40.2/224.10.10.10 Gi4/1 20.20.20.20 00:23:37 00:06:50 00:20:30
40.40.40.4/224.10.10.10Gi4/1 20.20.20.20 00:39:42 00:09:17 Switch#

This example shows how to display host membership for VLAN 20 and group 224.10.10.10:

Switch# show ip igmp snooping membership vlan 20 source 40.40.40.2 group 224.10.10.10 #channels: 5 #hosts : 1 Source/Group Interface Reporter Uptime Last-Join Last-Leave 40.40.40.2/224.10.10.10 Gi4/1 20.20.20.20 00:23:37 00:06:50 00:20:30 Switch#

This example shows how to display host membership information for VLAN 20 and to delete the explicit host tracking:

Switch# show ip igmp snooping membership vlan 20

Snooping Membership Summary for Vlan 20

Total number of channels:5
Total number of hosts :4

Source/Group	Interface	Reporter	Uptime Last-Join/	Last-Leave
40.0.0.1/224.1.1.1	Fa7/37	0002.4ba0.a4f6	00:00:04 00:00:04 /	
40.0.0.2/224.1.1.1	Fa7/37	0002.fd80.f770	00:00:17 00:00:17 /	
40.0.3/224.1.1.1	Fa7/36	20.20.20.20	00:00:04 00:00:04 /	
40.0.0.4/224.1.1.1	Fa7/35	20.20.20.210	00:00:17 00:00:17 /	
40.0.0.5/224.1.1.1	Fa7/37	0002.fd80.f770	00:00:17 00:00:17 /	_

Switch# clear ip igmp snooping membership vlan 20 Switch#

Related Commands

clear ip igmp snooping membership ip igmp snooping vlan explicit-tracking show ip igmp snooping vlan

OL-6851-01

show ip igmp snooping mrouter

To display information on the dynamically learned and manually configured multicast switch interfaces, use the **show ip igmp snooping mrouter** command.

show ip igmp snooping mrouter [{vlan vlan-id}]

Syntax Description

vlan vlan-id (Optional) Specifies a VLAN; valid values are from 1 to 1001 and from 1006 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(19)EW	Added support for extended VLAN addresses.

Usage Guidelines

You can also use the **show mac-address-table multicast** command to display entries in the MAC address table for a VLAN that has IGMP snooping enabled.

You can display IGMP snooping information for the VLAN interfaces by entering the **show ip igmp interface vlan** *vlan-num* command.

Examples

This example shows how to display snooping information for a specific VLAN:

Switch#	show	ip	igmp	snooping	mrouter	vlan	1
vlan			port	S			
+							
1		Gi1	1/1,G	i2/1,Fa3/	48,Switcl	n	
Switch#							

Related Commands

ip igmp snooping vlan mrouter show ip igmp interface show mac-address-table multicast

show ip igmp snooping vlan

To display information on the dynamically learned and manually configured VLAN switch interfaces, use the **show ip igmp snooping vlan** command.

show ip igmp snooping vlan vlan_num

Syntax Description

vlan num	Number of the VLAN; valid values are from 1 to 1001 and from 1006 to 4	1004
vlan num	Number of the VLAN, valid values are from 1 to 1001 and from 1000 to 2	+1194.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for extended addressing was added.

Usage Guidelines

You can also use the **show mac-address-table multicast** command to display the entries in the MAC address table for a VLAN that has IGMP snooping enabled.

Examples

This example shows how to display snooping information for a specific VLAN:

```
Switch# show ip igmp snooping vlan 2 vlan 2
```

IGMP snooping is globally enabled

IGMP snooping TCN solicit query is globally enabled

IGMP snooping global TCN flood query count is 2

IGMP snooping is enabled on this Vlan

IGMP snooping immediate-leave is disabled on this Vlan

IGMP snooping mrouter learn mode is pim-dvmrp on this Vlan

IGMP snooping is running in IGMP_ONLY mode on this Vlan

Switch#

Related Commands

ip igmp snooping

ip igmp snooping vlan immediate-leave

ip igmp snooping vlan mrouter

ip igmp snooping vlan static

show ip igmp interface

show ip igmp snooping mrouter

show mac-address-table multicast

show ip interface

To display the usability status of interfaces that are configured for IP, use the **show ip interface** command.

show ip interface [type number]

Syntax Description

type	(Optional) Interface type.
number	(Optional) Interface number.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.2(25)EW	Extended to include the 10-Gigabit Ethernet interface.

Usage Guidelines

The Cisco IOS software automatically enters a directly connected route in the routing table if the interface is usable. A usable interface is one through which the software can send and receive packets. If the software determines that an interface is not usable, it removes the directly connected routing entry from the routing table. Removing the entry allows the software to use dynamic routing protocols to determine backup routes to the network, if any.

If the interface can provide two-way communication, the line protocol is marked "up." If the interface hardware is usable, the interface is marked "up."

If you specify an optional interface type, you see information only on that specific interface.

If you specify no optional arguments, you see information on all the interfaces.

When an asynchronous interface is encapsulated with PPP or Serial Line Internet Protocol (SLIP), IP fast switching is enabled. The **show ip interface** command on an asynchronous interface that is encapsulated with PPP or SLIP displays a message indicating that IP fast switching is enabled.

Examples

This example shows how to display the usability status for a specific VLAN:

Switch# show ip interface vlan 1

```
Vlan1 is up, line protocol is up
Internet address is 10.6.58.4/24
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
```

```
Local Proxy ARP is disabled
 Security level is default
 Split horizon is enabled
 ICMP redirects are always sent
 ICMP unreachables are always sent
 ICMP mask replies are never sent
 IP fast switching is enabled
 IP fast switching on the same interface is disabled
  IP Flow switching is disabled
  IP CEF switching is enabled
 IP Fast switching turbo vector
 IP Normal CEF switching turbo vector
 IP multicast fast switching is enabled
 IP multicast distributed fast switching is disabled
 IP route-cache flags are Fast, CEF
 Router Discovery is disabled
 IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Probe proxy name replies are disabled
 Policy routing is disabled
 Network address translation is disabled
  WCCP Redirect outbound is disabled
 WCCP Redirect inbound is disabled
 WCCP Redirect exclude is disabled
 BGP Policy Mapping is disabled
  Sampled Netflow is disabled
  IP multicast multilayer switching is disabled
 Netflow Data Export (hardware) is enabled
Switch#
```

Table 2-19 describes the fields that are shown in the example.

Table 2-19 show ip interface Field Descriptions

Field	Description
Ethernet0 is up	If the interface hardware is usable, the interface is marked "up." For an interface to be usable, both the interface hardware and line protocol must be up.
line protocol is up	If the interface can provide two-way communication, the line protocol is marked "up." For an interface to be usable, both the interface hardware and line protocol must be up.
Internet address and subnet mask	IP address and subnet mask of the interface.
Broadcast address	Broadcast address.
Address determined by	Status of how the IP address of the interface was determined.
MTU	MTU value that is set on the interface.
Helper address	Helper address, if one has been set.
Secondary address	Secondary address, if one has been set.
Directed broadcast forwarding	Status of directed broadcast forwarding.
Multicast groups joined	Multicast groups to which this interface belongs.
Outgoing access list	Status of whether the interface has an outgoing access list set.
Inbound access list	Status of whether the interface has an incoming access list set.

Table 2-19 show ip interface Field Descriptions (continued)

Field	Description
Proxy ARP	Status of whether Proxy Address Resolution Protocol (ARP) is enabled for the interface.
Security level	IP Security Option (IPSO) security level set for this interface.
Split horizon	Status of split horizon.
ICMP redirects	Status of the redirect messages on this interface.
ICMP unreachables	Status of the unreachable messages on this interface.
ICMP mask replies	Status of the mask replies on this interface.
IP fast switching	Status of whether fast switching has been enabled for this interface. Fast switching is typically enabled on serial interfaces, such as this one.
IP SSE switching	Status of the IP silicon switching engine (SSE).
Router Discovery	Status of the discovery process for this interface. It is typically disabled on serial interfaces.
IP output packet accounting	Status of IP accounting for this interface and the threshold (maximum number of entries).
TCP/IP header compression	Status of compression.
Probe proxy name	Status of whether the HP Probe proxy name replies are generated.
WCCP Redirect outbound is enabled	Status of whether packets that are received on an interface are redirected to a cache engine.
WCCP Redirect exclude is disabled	Status of whether packets that are targeted for an interface are excluded from being redirected to a cache engine.
Netflow Data Export (hardware) is enabled	NDE hardware flow status on the interface.

show ip mfib

To display all active Multicast Forwarding Information Base (MFIB) routes, use the **show ip mfib** command.

show ip mfib [all | counters | log [n]]

Syntax Description

all	(Optional) Specifies all routes in the MFIB, including those routes that are used to accelerate fast switching but that are not necessarily in the upper-layer routing protocol table.
counters	(Optional) Specifies the counts of MFIB-related events. Only nonzero counters are shown.
log	(Optional) Specifies a log of the most recent number of MFIB-related events. The most recent event is first.
n	(Optional) Number of events.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The MFIB table contains a set of IP multicast routes; each route in the MFIB table contains several flags that associate to the route.

The route flags indicate how a packet that matches a route is forwarded. For example, the IC flag on an MFIB route indicates that some process on the switch needs to receive a copy of the packet. These flags are associated with MFIB routes:

- Internal Copy (IC) flag—Set on a route when a process on the switch needs to receive a copy of all packets matching the specified route.
- Signaling (S) flag—Set on a route when a switch process needs notification that a packet matching the route is received. In the expected behavior, the protocol code updates the MFIB state in response to having received a packet on a signaling interface.
- Connected (C) flag—When set on a route, the C flag has the same meaning as the S flag, except that the C flag indicates that only packets sent by directly connected hosts to the route should be signaled to a protocol process.

A route can also have a set of flags associated with one or more interfaces. For an (S,G) route, the flags on interface 1 indicate how the ingress packets should be treated and whether packets matching the route should be forwarded onto interface 1. These per-interface flags are associated with the MFIB routes:

• Accepting (A)—Set on the RPF interface when a packet that arrives on the interface and that is marked as Accepting (A) is forwarded to all Forwarding (F) interfaces.

- Forwarding (F)—Used with the A flag as described above. The set of forwarding interfaces together form a multicast olist or output interface list.
- Signaling (S)—Set on an interface when a multicast routing protocol process in Cisco IOS needs to be notified of ingress packets on that interface.
- Not Platform (NP) fast-switched—Used with the F flag. A forwarding interface is also marked as Not Platform fast-switched whenever that output interface cannot be fast-switched by the platform hardware and requires software forwarding.

For example, the Catalyst 4006 switch with Supervisor Engine III cannot switch tunnel interfaces in hardware so these interfaces are marked with the NP flag. When an NP interface is associated with a route, a copy of every ingress packet arriving on an Accepting interface is sent to the switch software forwarding path for software replication and then forwarded to the NP interface.

Examples

This example shows how to display all active MFIB routes:

```
Switch# show ip mfib
IP Multicast Forwarding Information Base
Entry Flags: C - Directly Connected, S - Signal,
             IC - Internal Copy
Interface Flags: A - Accept, F - Forward, NS - Signal,
            NP - Not platform switched
Packets: Fast/Partial/Slow Bytes: Fast/Partial/Slow:
(171.69.10.13, 224.0.1.40), flags (IC)
   Packets: 2292/2292/0, Bytes: 518803/0/518803
   Vlan7 (A)
   Vlan100 (F NS)
   Vlan105 (F NS)
(*, 224.0.1.60), flags ()
   Packets: 2292/0/0, Bytes: 518803/0/0
   Vlan7 (A NS)
(*, 224.0.1.75), flags ()
   Vlan7 (A NS)
(10.34.2.92, 239.192.128.80), flags ()
   Packets: 24579/100/0, 2113788/15000/0 bytes
   Vlan7 (F NS)
   Vlan100 (A)
(*, 239.193.100.70), flags ()
   Packets: 1/0/0, 1500/0/0 bytes
   Vlan7 (A)
Switch#
```

Related Commands

clear ip mfib counters

show ip mfib fastdrop

To show all currently active fast-drop entries and to show whether fast drop is enabled, use the **show ip mfib fastdrop** command.

show ip mfib fastdrop

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display all currently active fast-drop entries and whether fast drop is enabled.

Switch# show ip mfib fastdrop
MFIB fastdrop is enabled.
MFIB fast-dropped flows:
(10.0.0.1, 224.1.2.3, Vlan9) 00:01:32
(10.1.0.2, 224.1.2.3, Vlan9) 00:02:30
(1.2.3.4, 225.6.7.8, Vlan3) 00:01:50
Switch#

Related Commands

clear ip mfib fastdrop

show ip mroute

To display IP multicast routing table information, use the **show ip mroute** command.

show ip mroute [interface_type slot/port | host_name | host_address [source] | active [kbps |
interface_type num] | count | pruned | static | summary]

Syntax Description

interface_type slot/port	(Optional) Interface type and number of the slot and port; valid values for <i>interface type</i> are fastethernet , gigabitethernet , tengigabitethernet , null , and vlan .			
host_name	(Optional) Name or IP address as defined in the DNS hosts table.			
host_address source	(Optional) IP address or name of a multicast source.			
active	(Optional) Displays the rate that active sources are sending to multicast groups.			
kbps interface_type num	(Optional) Minimum rate at which active sources are sending to multicast groups; active sources sending at this rate or greater will be displayed. Valid values are from 1 to 4294967295 kbps.			
count	(Optional) Displays the route and packet count information.			
pruned	(Optional) Displays the pruned routes.			
static	(Optional) Displays the static multicast routes.			
summary	(Optional) Displays a one-line, abbreviated summary of each entry in the IP multicast routing table.			

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

If you omit all the optional arguments and keywords, the **show ip mroute** command displays all the entries in the IP multicast routing table.

The **show ip mroute active** *kbps* command displays all the sources sending at a rate greater than or equal to *kbps*.

The multicast routing table is populated by creating source, group (S,G) entries from star, group (*,G) entries. The star refers to all source addresses, the "S" refers to a single source address, and the "G" refers to the destination multicast group address. In creating (S,G) entries, the software uses the best path to that destination group found in the unicast routing table (through Reverse Path Forwarding (RPF).

Examples

This example shows how to display all the entries in the IP multicast routing table:

Switch# show ip mroute IP Multicast Routing Table Flags:D - Dense, S - Sparse, s - SSM Group, C - Connected, L - Local, P - Pruned, R - RP-bit set, F - Register flag, T - SPT-bit set, J - Join SPT, M - MSDP created entry, X - Proxy Join Timer Running A - Advertised via MSDP, U - URD, I - Received Source Specific Host Report. Outgoing interface flags:H - Hardware switched Timers: Uptime/Expires Interface state: Interface, Next-Hop or VCD, State/Mode (*, 230.13.13.1), 00:16:41/00:00:00, RP 10.15.1.20, flags:SJC Incoming interface:GigabitEthernet4/8, RPF nbr 10.15.1.20 Outgoing interface list: GigabitEthernet4/9, Forward/Sparse-Dense, 00:16:41/00:00:00, H (*, 230.13.13.2), 00:16:41/00:00:00, RP 10.15.1.20, flags:SJC Incoming interface: GigabitEthernet4/8, RPF nbr 10.15.1.20, RPF-MFD Outgoing interface list: GigabitEthernet4/9, Forward/Sparse-Dense, 00:16:41/00:00:00, H (10.20.1.15, 230.13.13.1), 00:14:31/00:01:40, flags:CJT Incoming interface: GigabitEthernet4/8, RPF nbr 10.15.1.20, RPF-MFD Outgoing interface list: GigabitEthernet4/9, Forward/Sparse-Dense, 00:14:31/00:00:00, H (132.206.72.28, 224.2.136.89), 00:14:31/00:01:40, flags:CJT Incoming interface: GigabitEthernet4/8, RPF nbr 10.15.1.20, RPF-MFD

This example shows how to display the rate that the active sources are sending to the multicast groups and to display only the active sources that are sending at greater than the default rate:

Switch# show ip mroute active

Outgoing interface list:Null

Switch#

```
Active IP Multicast Sources - sending > = 4 kbps

Group: 224.2.127.254, (sdr.cisco.com)
    Source: 146.137.28.69 (mbone.ipd.an1.gov)
    Rate: 1 pps/4 kbps(1sec), 4 kbps(last 1 secs), 4 kbps(life avg)

Group: 224.2.201.241, ACM 97
    Source: 130.129.52.160 (webcast3-e1.acm97.interop.net)
    Rate: 9 pps/93 kbps(1sec), 145 kbps(last 20 secs), 85 kbps(life avg)

Group: 224.2.207.215, ACM 97
    Source: 130.129.52.160 (webcast3-e1.acm97.interop.net)
    Rate: 3 pps/31 kbps(lsec), 63 kbps(last 19 secs), 65 kbps(life avg)

Switch#
```

This example shows how to display route and packet count information:

```
Switch# show ip mroute count

IP Multicast Statistics

56 routes using 28552 bytes of memory

13 groups, 3.30 average sources per group

Forwarding Counts:Pkt Count/Pkts per second/Avg Pkt Size/Kilobits per second
```

```
Other counts:Total/RPF failed/Other drops(OIF-null, rate-limit etc)

Group:224.2.136.89, Source count:1, Group pkt count:29051

Source:132.206.72.28/32, Forwarding:29051/-278/1186/0, Other:85724/8/56665
Switch#
```

This example shows how to display summary information:

```
Switch# show ip mroute summary

IP Multicast Routing Table

Flags: D - Dense, S - Sparse, s - SSM Group, C - Connected, L - Local,
        P - Pruned, R - RP-bit set, F - Register flag, T - SPT-bit set,
        J - Join SPT, M - MSDP created entry, X - Proxy Join Timer Running
        A - Advertised via MSDP, U - URD, I - Received Source Specific Host
        Report

Outgoing interface flags: H - Hardware switched

Timers: Uptime/Expires

Interface state: Interface, Next-Hop or VCD, State/Mode

Switch#
```

Table 2-20 describes the fields shown in the output.

Table 2-20 show ip mroute Field Descriptions

Field	Description			
Flags:	Information about the entry.			
D - Dense	Entry is operating in dense mode.			
S - Sparse	Entry is operating in sparse mode.			
s - SSM Group	Entry is a member of an SSM group.			
C - Connected	Member of the multicast group is present on the directly connected interface.			
L - Local	Switch is a member of the multicast group.			
P - Pruned	Route has been pruned. This information is retained in case a downstream member wants to join the source.			
R - Rp-bit set	Status of the (S,G) entry; is the (S,G) entry pointing toward the RP. The R - Rp-bit set is typically a prune state along the shared tree for a particular source.			
F - Register flag	Status of the software; indicates if the software is registered for a multicast source.			
T - SPT-bit set	Status of the packets; indicates if the packets been received on the shortest path source tree.			

Table 2-20 show ip mroute Field Descriptions (continued)

Field	Description				
J - Join SPT	For (*, G) entries, indicates that the rate of traffic flowing down the shared tree is exceeding the SPT-Threshold set for the group. (The default SPT-Threshold setting is 0 kbps.) When the J - Join SPT flag is set, the next (S,G) packet received down the shared tree triggers an (S,G) join in the direction of the source causing the switch to join the source tree.				
	For (S, G) entries, indicates that the entry was created because the SPT-Threshold for the group was exceeded. When the J - Join SPT flag is set for (S,G) entries, the switch monitors the traffic rate on the source tree and attempts to switch back to the shared tree for this source if the traffic rate on the source tree falls below the group's SPT-Threshold for more than one minute.				
	The switch measures the traffic rate on the shared tree and compares the measured rate to the group's SPT-Threshold once every second. If the traffic rate exceeds the SPT-Threshold, the J- Join SPT flag is set on the (*, G) entry until the next measurement of the traffic rate. The flag is cleared when the next packet arrives on the shared tree and a new measurement interval is started.				
	If the default SPT-Threshold value of 0 Kbps is used for the group, the J- Join SPT flag is always set on (*, G) entries and is never cleared. When the default SPT-Threshold value is used, the switch immediately switches to the shortest-path tree when traffic from a new source is received.				
Outgoing interface flag:	Information about the outgoing entry.				
H - Hardware switched	Entry is hardware switched.				
Timer:	Uptime/Expires.				
Interface state:	Interface, Next-Hop or VCD, State/Mode.				
(*, 224.0.255.1) (198.92.37.100/32, 224.0.255.1)	Entry in the IP multicast routing table. The entry consists of the IP address of the source switch followed by the IP address of the multicast group. An asterisk (*) in place of the source switch indicates all sources.				
	Entries in the first format are referred to as (*,G) or "star comma G" entries. Entries in the second format are referred to as (S,G) or "S comma G" entries. (*,G) entries are used to build (S,G) entries.				
uptime	How long (in hours, minutes, and seconds) the entry has been in the IP multicast routing table.				
expires How long (in hours, minutes, and seconds) until the entry removed from the IP multicast routing table on the outgointerface.					

Table 2-20 show ip mroute Field Descriptions (continued)

Field	Description			
RP	Address of the RP switch. For switches and access servers operating in sparse mode, this address is always 0.0.0.0.			
flags:	Information about the entry.			
Incoming interface	Expected interface for a multicast packet from the source. If the packet is not received on this interface, it is discarded.			
RPF neighbor	IP address of the upstream switch to the source. "Tunneling" indicates that this switch is sending data to the RP encapsulated in Register packets. The hexadecimal number in parentheses indicates to which RP it is registering. Each bit indicates a different RP if multiple RPs per group are used.			
DVMRP or Mroute	Status of whether the RPF information is obtained from the DVMRP routing table or the static mroutes configuration.			
Outgoing interface list	Interfaces through which packets are forwarded. When the ip pim nbma-mode command is enabled on the interface, the IP address of the PIM neighbor is also displayed.			
Ethernet0	Name and number of the outgoing interface.			
Next hop or VCD	Next hop specifies downstream neighbor's IP address. VCD specifies the virtual circuit descriptor number. VCD0 indicates that the group is using the static-map virtual circuit.			
Forward/Dense	Status of the packets; indicates if they are they forwarded on the interface if there are no restrictions due to access lists or the TTL threshold. Following the slash (/), mode in which the interface is operating (dense or sparse).			
Forward/Sparse	Sparse mode interface is in forward mode.			
time/time (uptime/expiration time)	Per interface, how long (in hours, minutes, and seconds) the entry has been in the IP multicast routing table. Following the slash (/), how long (in hours, minutes, and seconds) until the entry is removed from the IP multicast routing table.			

Related Commands

ip multicast-routing (refer to Cisco IOS documentation)
ip pim (refer to Cisco IOS documentation)

show ip source binding

To display IP source bindings that are configured on the system, use the **show ip source binding** EXEC command.

show ip source binding [ip-address] [mac-address] [**dhcp-snooping** | **static**] [**vlan** vlan-id] [**interface** interface-name]

Syntax Description

ip-address	(Optional) Binding IP address.
mac-address (Optional) Binding MAC address.	
dhcp-snooping	(Optional) DHCP-snooping type binding.
static	(Optional) Statically configured binding.
vlan vlan-id	(Optional) VLAN number.
interface interface-name	(Optional) Binding interface.

Defaults

Displays both static and DHCP snooping bindings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The optional parameters filter the display output result.

Examples

This example shows how to display the IP source bindings:

Switch#	show	ip	source	binding
---------	------	----	--------	---------

MacAddress	IpAddress	Lease(sec)	Туре	VLAN	Interface
00:00:00:0A:00:0B	11.0.0.1	infinite	static	10	FastEthernet6/10

Switch#

This example shows how to display the static IP binding entry of IP address 11.0.01:

Switch# show ip source binding 11.0.0.1 0000.000A.000B static vlan 10 interface Fa6/10

show ip source bin	nding 11.0.0.1	0000.000A.000B	static vlan	10 interfa	ice Fa6/10	
MacAddress	IpAddress	Lease(sec)	Type	VLAN	Interface	
00:00:00:0A:00:0B	11.0.0.1	infinite	static	10	FastEthernet6/10	
Switch#						

Related Commands

ip source binding

show ip verify source

To display the IP source guard configuration and filters on a particular interface, use the **show ip verify source** command.

show ip verify source [interface interface_num]

Syntax Description

interface *interface_num* (Optional) Specifies an interface.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

These examples show how to display the IP source guard configuration and filters on a particular interface with the **show ip verify source interface** command:

• This output appears when DHCP snooping is enabled on VLANs 10–20, interface fa6/1 has IP source filter mode that is configured as IP, and an existing IP address binding 10.0.0.1 is on VLAN 10:

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
fa6/1	ip	active	10.0.0.1		10
fa6/1	ip	active	deny-all		11-20



The second entry shows that a default PVACL (deny all IP traffic) is installed on the port for those snooping-enabled VLANs that do not have a valid IP source binding.

• This output appears when you enter the **show ip verify source interface fa6/2** command and DHCP snooping is enabled on VLANs 10–20, interface fa6/1 has IP source filter mode that is configured as IP, and there is an existing IP address binding 10.0.0.1 on VLAN 10:

```
Interface Filter-type Filter-mode IP-address Mac-address Vlan

fa6/2 ip inactive-trust-port
```

• This output appears when you enter the **show ip verify source interface fa6/3** command and the interface fa6/3 does not have a VLAN enabled for DHCP snooping:

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
fa6/3	ip	inactive-no-	snooping-vlan		

• This output appears when you enter the **show ip verify source interface fa6/4** command and the interface fa6/4 has an IP source filter mode that is configured as IP MAC and the existing IP MAC that binds 10.0.0.2/aaaa.bbbb.cccc on VLAN 10 and 11.0.0.1/aaaa.bbbb.cccd on VLAN 11:

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
fa6/4	ip-mac	active	10.0.0.2	aaaa.bbbb.cccc	10
fa6/4	ip-mac	active	11.0.0.1	aaaa.bbbb.cccd	11
fa6/4	ip-mac	active	deny-all	deny-all	12-20

• This output appears when you enter the **show ip verify source interface fa6/5** command and the interface fa6/5 has IP source filter mode that is configured as IP MAC and existing IP MAC binding 10.0.0.3/aaaa.bbbb.ccce on VLAN 10, but port security is not enabled on fa6/5:

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
fa6/5	ip-mac	active	10.0.0.3	permit-all	10
fa6/5	ip-mac	active	denv-all	permit-all	11-20



Enable port security first because the DHCP security MAC filter cannot apply to the port or VLAN.

• This output appears when you enter the **show ip verify source interface fa6/6** command and the interface fa6/6 does not have IP source filter mode that is configured:

DHCP security is not configured on the interface fa6/6.

This example shows how to display all the interfaces on the switch that have DHCP snooping security enabled with the **show ip verify source** command.

The output is an accumulation of per-interface show CLIs:

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
fa6/1	ip	active	10.0.0.1		10
fa6/1	ip	active	deny-all		11-20
fa6/2	ip	inactive-tru	st-port		
fa6/3	ip	inactive-no-	snooping-vlan		
fa6/4	ip-mac	active	10.0.0.2	aaaa.bbbb.cccc	10
fa6/4	ip-mac	active	11.0.0.1	aaaa.bbbb.cccd	11
fa6/4	ip-mac	active	deny-all	deny-all	12-20
fa6/5	ip-mac	active	10.0.0.3	permit-all	10
fa6/5	ip-mac	active	deny-all	permit-all	11-20

Related Commands

- ip dhcp snooping information option
- ip dhcp snooping limit rate
- ip dhcp snooping trust
- ip igmp snooping
- ip igmp snooping vlan
- ip source binding
- ip verify source vlan dhcp-snooping
- show ip source binding

show ipc

To display IPC information, use the **show ipc** command.

show ipc {nodes | ports | queue | status}

Syntax Description

nodes	Displays the participating nodes.
ports	Displays the local IPC ports.
queue	Displays the contents of the IPC retransmission queue.
status	Displays the status of the local IPC server.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the participating nodes:

Switch# show ipc nodes

There are 3 nodes in this IPC realm. TD Type Name Last Last Sent Heard 10000 Local IPC Master 0 0 2010000 Local GALIOS IPC:Card 1 0 0 GALIOS IPC:Card 2 2020000 Ethernet 12 26 Switch#

This example shows how to display the local IPC ports:

Switch# show ipc ports

There are 11 ports defined.

Port ID	Type	Name	(current	t/peak/total)	
10000.1	unicast	IPC Master:Zone	(-, F,	
10000.2	unicast	IPC Master:Echo			
10000.3	unicast	IPC Master:Control			
10000.4	unicast	Remote TTY Server Por	rt		
10000.5	unicast	GALIOS RF :Active			
index = 0	seat_id =	0x2020000 last sent	= 0	heard = 1635	0/1/1635
		GALIOS RED:Active 0x2020000 last sent	= 0	heard = 2	0/1/2
2020000.3 2020000.4 2020000.5 2020000.6 2020000.7	unicast unicast unicast unicast unicast	GALIOS IPC:Card 2:Cor GALIOS RFS :Standby Slave: Remote TTY Cl: GALIOS RF :Standby GALIOS RED:Standby		Ė	

```
RPC packets: current/peak/total 0/1/17 Switch#
```

This example shows how to display the contents of the IPC retransmission queue:

```
Switch# show ipc queue

There are 0 IPC messages waiting for acknowledgement in the transmit queue.

There are 0 IPC messages waiting for a response.

There are 0 IPC messages waiting for additional fragments.

There are 0 IPC messages currently on the IPC inboundQ.

There are 0 messages currently in use by the system.

Switch#
```

This example shows how to display the status of the local IPC server:

```
Switch# show ipc status
IPC System Status:
This processor is the IPC master server.
6000 IPC message headers in cache
3363 messages in, 1680 out, 1660 delivered to local port,
1686 acknowledgements received, 1675 sent,
0 NACKS received, 0 sent,
0 messages dropped on input, 0 messages dropped on output
0 no local port, 0 destination unknown, 0 no transport
O missing callback or queue, O duplicate ACKs, O retries,
0 message timeouts.
0 ipc_output failures, 0 mtu failures,
0 msg alloc failed, 0 emer msg alloc failed, 0 no origs for RPC replies
0 pak alloc failed, 0 memd alloc failed
0 no hwq, 1 failed opens, 0 hardware errors
No regular dropping of IPC output packets for test purposes
Switch#
```

show |2protocol-tunnel

To display information about the Layer 2 protocol tunnel ports, use the **show l2protocol-tunnel** command. This command displays information for the interfaces with protocol tunneling enabled.

show l2protocol-tunnel [interface *interface-id*] [[**summary**] | {**begin** | **exclude** | **include**} *expression*]

Syntax Description

interface interface-id	(Optional) Specifies the interface for which protocol tunneling information appears. Valid interfaces are physical ports and port channels; the port channel range is 1 to 64.
summary	(Optional) Displays only Layer 2 protocol summary information.
begin	(Optional) Displays information beginning with the line that matches the <i>expression</i> .
exclude	(Optional) Displays information that excludes lines that match the <i>expression</i> .
include	(Optional) Displays the lines that match the specified expression.
expression	(Optional) Expression in the output to use as a reference point.

Command Modes

User EXEC

Command History

Release	Modification		
12.2(18)EW	This command was first introduced on the Catalyst 4500 series switch.		
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.		

Usage Guidelines

After enabling Layer 2 protocol tunneling on an access or 802.1Q tunnel port with the **l2protocol-tunnel** command, you can configure some or all of these parameters:

- Protocol type to be tunneled
- · Shutdown threshold
- · Drop threshold

If you enter the **show l2protocol-tunnel** [**interface** *interface-id*] command, only information about the active ports on which all the parameters are configured appears.

If you enter the **show l2protocol-tunnel summary** command, only information about the active ports on which some or all of the parameters are configured appears.

Expressions are case sensitive. For example, if you enter | **exclude output**, the lines that contain *output* do not appear, but the lines that contain *Output* appear.

Examples

This is an example of output from the show l2protocol-tunnel command:

Switch> show 12protocol-tunnel
COS for Encapsulated Packets: 5

Port	Protocol		_	Encapsulation Counter	_	Drop Counter	
Fa0/10							
rau/10	stp			9847	1866	0	
	vtp				12	0	
	-				860	0	
	pagp				0	0	
	lacp udld			-	-	0	
D-0/11					211		
Fa0/11	cdp	1100			2350	0	
	stp				13	0	
	vtp	1100			67	0	
	pagp		900		5848	0	
	lacp		900	0	0	0	
	udld		900	0	0	0	
Fa0/12	cdp			2356	0	0	
	stp			11787	0	0	
	vtp			81	0	0	
	pagp			0	0	0	
	lacp			849	0	0	
	udld			0	0	0	
Fa0/13	cdp			2356	0	0	
	stp			11788	0	0	
	vtp			81	0	0	
	pagp			0	0	0	
	lacp			849	0	0	
	udld			0	0	0	
Switch#							

This is an example of output from the **show l2protocol-tunnel summary** command:

Switch> show 12protocol-tunnel summary COS for Encapsulated Packets: 5

Port	Protocol	Shutdown Threshold (cdp/stp/vtp) (pagp/lacp/udld)	Drop Threshold (cdp/stp/vtp) (pagp/lacp/udld)	Status			
Fa0/10	stp vtp	/	/	up			
		/	/	αp			
_		1100/1100/1100	/	up			
		/	900/ 900/ 900	- 1			
_		/	/	up			
pa	agp lacp udld	/	/	_			
Fa0/13	cdp stp vtp	/	/	up			
pa	agp lacp udld	/	/				
Fa0/14	cdp stp vtp	/	/	down			
pa	agp udld	/	/				
Fa0/15	cdp stp vtp	/	/	down			
pa	agp udld	/	/				
Fa0/16	cdp stp vtp	/	/	down			
pa	agp lacp udld	/	/				
		/	/	down			
pa							
Switch#							

Related Commands

clear I2protocol-tunnel counter (refer to Cisco IOS documentation)

12protocol-tunnel 12protocol-tunnel cos

show lacp

To display LACP information, use the **show lacp** command.

show lacp [channel-group] {counters | internal | neighbors | sys-id}

Syntax Description

channel-group	(Optional) Number of the channel group; valid values are from 1 to 64.
counters Displays the LACP statistical information.	
internal	Displays the internal information.
neighbors	Displays the neighbor information.
sys-id	Displays the LACP system identification.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switches.

Usage Guidelines

This command is not supported on systems that are configured with a Supervisor Engine I.

If you do not specify a *channel-group* value, all channel groups are displayed.

You can enter the optional *channel-group* value to specify a channel group for all keywords, except the **sys-id** keyword.

Examples

This example shows how to display LACP statistical information for a specific channel group:

Switch# show lacp 1 counters

	LA	CPDUs	Ma	rker	LACPDUs
Port	Sent	Recv	Sent	Recv	Pkts Err
Channel c	group: 1				
Fa4/1	8	15	0	0	3 0
Fa4/2	14	18	0	0	3 0
Fa4/3	14	18	0	0	0
Fa4/4	13	18	0	0	0
Switch#					

The output displays the following information:

- The LACPDUs Sent and Recv columns display the LACPDUs sent and received on each specific interface.
- The LACPDUs Pkts and Err columns display the marker protocol packets.

This example shows how to display internal information for the interfaces belonging to a specific channel:

```
Switch# show lacp 1 internal
Flags: S - Device sends PDUs at slow rate. F - Device sends PDUs at fast rate.
      A - Device is in Active mode.
                                     P - Device is in Passive mode.
Channel group 1
                       LACPDUs
                                LACP Port
                                           Admin Oper
                                                           Port
                                                                   Port
Port
       Flags
                State Interval Priority Key
                                                           Number
                                                                  State
                                                    Key
Fa4/1
     saC
                bndl 30s
                                 32768
                                            100
                                                    100
                                                           0xc1
                                                                   0x75
                                            100
Fa4/2
                bndl
                       30s
                                 32768
                                                    100
                                                           0xc2
                                                                   0x75
     saC
                                 32768
Fa4/3
       saC
                bndl
                       30s
                                             100
                                                    100
                                                           0xc3
                                                                   0x75
Fa4/4
        saC
                bndl
                       30s
                                  32768
                                             100
                                                    100
                                                           0xc4
                                                                   0x75
Switch#
```

Table 2-21 lists the output field definitions.

Table 2-21 show lacp internal Command Output Fields

Field	Description				
State	State of the specific port at the current moment is displayed; allowed values are as follows:				
	• <i>bndl</i> —Port is attached to an aggregator and bundled with other ports.				
	• <i>susp</i> —Port is in a suspended state; it is not attached to any aggregator.				
	• <i>indep</i> —Port is in an independent state (not bundled but able to switch data traffic. In this case, LACP is not running on the partner port).				
	• hot-sby—Port is in a Hot-standby state.				
	• down—Port is down.				
LACPDUs Interval	Interval setting.				
LACP Port Priority	Port priority setting.				
Admin Key	Administrative key.				
Oper Key	Operator key.				
Port Number	Port number.				
Port State	State variables for the port encoded as individual bits within a single octet with the following meaning [1]:				
	• bit0: LACP_Activity				
	• bit1: LACP_Timeout				
	• bit2: Aggregation				
	• bit3: Synchronization				
	• bit4: Collecting				
	• bit5: Distributing				
	• bit6: Defaulted				
	• bit7: Expired				

This example shows how to display LACP neighbors information for a specific port channel:

```
Switch# show lacp 1 neighbor
Flags: S - Device sends PDUs at slow rate. F - Device sends PDUs at fast rate.
        A - Device is in Active mode.
                                            P - Device is in Passive mode.
Channel group 1 neighbors
         Partner
                                  Partner
                                  Port Number
Port
         System ID
                                                   Age
                                                           Flags
Fa4/1
        8000,00b0.c23e.d84e
                                  0x81
                                                   29s
                                                            Ρ
                                                            Ρ
        8000,00b0.c23e.d84e
                                                   0s
Fa4/2
                                  0x82
Fa4/3
          8000,00b0.c23e.d84e
                                   0x83
                                                   0s
                                                            Ρ
Fa4/4
          8000,00b0.c23e.d84e
                                   0x84
                                                   0s
          Port
                        Admin
                                   Oper
                                             Port
          Priority
                        Key
                                   Key
                                             State
          32768
Fa4/1
                        2.00
                                   200
                                             0 \times 81
Fa4/2
          32768
                                   200
                        200
                                             0x81
Fa4/3
          32768
                        200
                                   200
                                             0x81
Fa4/4
          32768
                        200
                                   200
                                             0x81
Switch#
```

In the case where no PDUs have been received, the default administrative information is displayed in braces

This example shows how to display the LACP system identification:

```
Switch> show lacp sys-id 8000,AC-12-34-56-78-90 Switch>
```

The system identification is made up of the system priority and the system MAC address. The first two bytes are the system priority, and the last six bytes are the globally administered individual MAC address associated to the system.

Related Commands

lacp port-priority lacp system-priority

show mac access-group interface

To display the ACL configuration on a Layer 2 interface, use the **show mac access-group interface** command.

show mac access-group interface [interface interface-number]

Syntax Description

interface	(Optional) Specifies the interface type; valid values are ethernet , fastethernet , gigabitethernet , tengigabitethernet , pos , atm , port-channel , and ge-wan .
interface-number	(Optional) Specifies the port number.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The valid values for the port number depend on the chassis used.

Examples

This example shows how to display the ACL configuration on interface fast 6/1:

Switch# show mac access-group interface fast 6/1

Interface FastEthernet6/1:

Inbound access-list is simple-mac-acl
Outbound access-list is not set

Related Commands

access-group mode

show mac-address-table address

To display MAC address table information for a specific MAC address, use the **show mac-address-table address** command.

show mac-address-table address mac_addr [interface $type\ slot/port \mid protocol\ protocol\ vlan\ vlan_id$]

Syntax Description

mac_addr	48-bit MAC address; the valid format is H.H.H.
interface type slot/port	(Optional) Displays information for a specific interface; valid values for <i>type</i> are fastethernet , gigabitethernet , and tengigabitethernet .
protocol protocol	(Optional) Specifies a protocol. See the "Usage Guidelines" section for more information.
vlan vlan_id	(Optional) Displays entries for the specific VLAN only; valid values are from 1 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the internal VLAN number.

The keyword definitions for the protocol variable are as follows:

- ip specifies the IP protocol.
- ipx specifies the IPX protocols.
- assigned specifies the assigned protocol entries.
- other specifies the other protocol entries.

Examples

This example shows how to display MAC address table information for a specific MAC address:

Switch# show mac-address-table address 0030.94fc.0dff

vlan	Entries mac address	type	protocols	port	
1 Fa6/1	0030.94fc.0dff 0030.94fc.0dff 0030.94fc.0dff	static static	ip,ipx,assigned,other ip,ipx,assigned,other ip,ipx,assigned,other	Switch Switch	

Related Commands

show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table aging-time

To display the MAC address aging time, use the **show mac-address-table aging-time** command.

show mac-address-table aging-time [vlan vlan_id]

Syntax Description

vlan vlan id (Optional) Specifies a VLAN; valid values

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for extended addressing was added.

Examples

This example shows how to display the currently configured aging time for all VLANs:

Switch#	show mac-address-table aging-time
Vlan	Aging Time
100	300
200	1000

Switch#

This example shows how to display the currently configured aging time for a specific VLAN:

```
Switch# show mac-address-table aging-time vlan 100 Vlan Aging Time
---- 300 300
```

Switch#

Related Commands

show mac-address-table address show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table count

To display the number of entries currently in the MAC address table, use the **show mac-address-table count** command.

show mac-address-table count [vlan vlan_id]

Syntax Description

vlan vlan_id (Optional) Specifies a VLAN; valid values are from 1 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.

Examples

This example shows how to display the entry count for a specific VLAN:

Switch# show mac-address-table count vlan 1

MAC Entries for Vlan 1:

Dynamic Unicast Address Count: 0
Static Unicast Address (User-defined) Count: 0
Static Unicast Address (System-defined) Count: 1
Total Unicast MAC Addresses In Use: 1
Total Unicast MAC Addresses Available: 32768
Multicast MAC Address Count: 1
Total Multicast MAC Addresses Available: 16384
Switch#

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table dynamic

To display the dynamic MAC address table entries only, use the **show mac-address-table dynamic** command.

show mac-address-table dynamic [address mac_addr | **interface** type slot/port | **protocol** protocol | **vlan** vlan_id]

Syntax Description

address mac_addr	(Optional) Specifies a 48-bit MAC address; the valid format is H.H.H.	
interface type slot/port	(Optional) Specifies an interface to match; valid values for <i>type</i> are fastethernet , gigabitethernet , and tengigabitethernet .	
protocol protocol	(Optional) Specifies a protocol. See the "Usage Guidelines" section for more information.	
vlan vlan_id	(Optional) Displays entries for a specific VLAN; valid values are from 1 to 4094.	

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

The keyword definitions for the *protocol* argument are as follows:

- assigned specifies assigned protocol entries.
- **ip** specifies IP protocol.
- ipx specifies IPX protocols.
- other specifies other protocol entries.

The **show mac-address-table dynamic** command output for an EtherChannel interface changes the port number designation (such as, 5/7) to a port group number (such as, Po80).

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the internal VLAN number.

Examples

This example shows how to display all the dynamic MAC address entries:

Switch# show mac-address-table dynamic

vlan		type	protocols	port
+	+		-	-
1	0000.0000.0201	dynamic	ip	FastEthernet6/15
1	0000.0000.0202	dynamic	ip	FastEthernet6/15
1	0000.0000.0203	dynamic	ip,assigned	FastEthernet6/15
1	0000.0000.0204	dynamic	ip,assigned	FastEthernet6/15
1	0000.0000.0205	dynamic	ip,assigned	FastEthernet6/15
2	0000.0000.0101	dynamic	ip	FastEthernet6/16
2	0000.0000.0102	dynamic	ip	FastEthernet6/16
2	0000.0000.0103	dynamic	ip,assigned	FastEthernet6/16
2	0000.0000.0104	dynamic	ip,assigned	FastEthernet6/16
2	0000.0000.0105	dynamic	ip,assigned	FastEthernet6/16
Switch#				

This example shows how to display the dynamic MAC address entries with a specific protocol type (in this case, assigned):

Switch# show mac-address-table dynamic protocol assigned

vlan	Entries mac address +	type	protocols	port
1	0000.0000.0203	-	ip,assigned	FastEthernet6/15
1	0000.0000.0204	dynamic	ip,assigned	FastEthernet6/15
1	0000.0000.0205	dynamic	ip,assigned	FastEthernet6/15
2	0000.0000.0103	dynamic	ip,assigned	FastEthernet6/16
2	0000.0000.0104	dynamic	ip,assigned	FastEthernet6/16
2	0000.0000.0105	dynamic	ip,assigned	FastEthernet6/16
Switch#				

Related Commands

show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table interface

To display the MAC address table information for a specific interface, use the show mac-address-table interface command.

show mac-address-table interface type slot/port

Syntax Description

type	Interface type; valid values are ethernet , fastethernet , gigabitethernet , and tengigabitethernet .
slot/port	Number of the slot and port.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the internal VLAN number.

Examples

This example shows how to display MAC address table information for a specific interface:

Switch# show mac-address-table interface fastethernet6/16

Switch#	show mac-addres	s-table i	nterface fastetherr	et6/16
Unicast	Entries			
vlan	mac address	type	protocols	port
	+	+	+	+
2	0000.0000.0101	dynamic	other	FastEthernet6/16
2	0000.0000.0102	dynamic	other	FastEthernet6/16
2	0000.0000.0103	dynamic	other	FastEthernet6/16
2	0000.0000.0104	dynamic	other	FastEthernet6/16
2	0000.0000.0105	dynamic	other	FastEthernet6/16
2	0000.0000.0106	dynamic	other	FastEthernet6/16
Multica	st Entries			
vlan		type	-	
2 Switch#	ffff.ffff.ffff	system		

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table multicast show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table multicast

To display information about the multicast MAC address table, use the **show mac-address-table multicast** command.

show mac-address-table multicast [count | {igmp-snooping [count]} | { vlan $vlan_num$ }]

Syntax Description

count	(Optional) Displays the number of multicast entries.
igmp-snooping	(Optional) Displays only the addresses learned by IGMP snooping.
user	(Optional) Displays only the user-entered static addresses.
vlan vlan_num	(Optional) Displays information for a specific VLAN only; valid values are from 1 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.

Usage Guidelines

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the the internal VLAN number.

Examples

This example shows how to display multicast MAC address table information for a specific VLAN:

Switch# show mac-address-table multicast vlan 1

Multicast Entries
vlan mac address type ports

1 ffff.ffff.ffff system Switch,Fa6/15

Switch#

This example shows how to display the number of multicast MAC entries for all VLANs:

Switch# show mac-address-table multicast count
MAC Entries for all vlans:
Multicast MAC Address Count: 141
Total Multicast MAC Addresses Available: 16384
Switch#

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table protocol show mac-address-table static show mac-address-table vlan

show mac-address-table protocol

To display the MAC address table information that is based on the protocol, use the **show** mac-address-table protocol command.

show mac-address-table protocol {assigned | ip | ipx | other}

Syntax Description

assigned	Specifies the assigned protocol entries.
ip	Specifies the IP protocol entries.
ipx	Specifies the IPX protocol entries.
other	Specifies the other protocol entries.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the internal VLAN number.

Examples

This example shows how to display the MAC address table entries that have a specific protocol type (in this case, assigned):

Switch# show mac-address-table protocol assigned

vlan			-	-	ports
200	0050.3e8d.6400				
100	0050.3e8d.6400	static	assigned		Switch
5	0050.3e8d.6400	static	assigned		Switch
4092	0000.0000.0000	dynamic	assigned		Switch
1	0050.3e8d.6400	static	assigned		Switch
4	0050.3e8d.6400	static	assigned		Switch
4092	0050.f0ac.3058	static	assigned		Switch
4092	0050.f0ac.3059	dynamic	assigned		Switch
1	0010.7b3b.0978	dynamic	assigned		Fa5/9
Switc	h#				

This example shows the other output for the previous example:

Switch# show mac-address-table protocol other

	Entries			
vlan	mac address	type	protocols	port
1	0000.0000.0201	dynamic	•	FastEthernet6/15
1	0000.0000.0202	dynamic	other	FastEthernet6/15
1	0000.0000.0203	dynamic	other	FastEthernet6/15
1	0000.0000.0204	dynamic	other	FastEthernet6/15
1	0030.94fc.0dff	static	ip,ipx,assigned,other	Switch
2	0000.0000.0101	dynamic	other	FastEthernet6/16
2	0000.0000.0102	dynamic	other	FastEthernet6/16
2	0000.0000.0103	dynamic	other	FastEthernet6/16
2	0000.0000.0104	dynamic	other	FastEthernet6/16
Fa6/1	0030.94fc.0dff	static	ip,ipx,assigned,other	Switch
Fa6/2	0030.94fc.0dff	static	ip, ipx, assigned, other	Switch
Multica	st Entries			

vlan	mac address	type	ports
1	ffff.ffff.ffff		Switch,Fa6/15
2	ffff.ffff.ffff	system	Fa6/16
1002	ffff.ffff.ffff	system	
1003	ffff.ffff.ffff	system	
1004	ffff.ffff.ffff	system	
1005	ffff.ffff.ffff	system	
Fa6/1	ffff.ffff.ffff	system	Switch, Fa6/1
Fa6/2	ffff.ffff.ffff	system	Switch, Fa6/2
Switch#			

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table static show mac-address-table vlan

show mac-address-table static

To display the static MAC address table entries only, use the **show mac-address-table static** command.

show mac-address-table static [address mac_addr | interface type number | protocol protocol | vlan vlan_id]

Syntax Description

address mac_addr	(Optional) Specifies a 48-bit MAC address to match; the valid format is H.H.H.
interface type number	(Optional) Specifies an interface to match; valid values for <i>type</i> are fastethernet , gigabitethernet , and tengigabitethernet .
protocol protocol	(Optional) Specifies a protocol. See the "Usage Guidelines" section for more information.
vlan vlan_id	(Optional) Displays the entries for a specific VLAN; valid values are from 1 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

For the MAC address table entries that are used by the routed ports, the routed port name is displayed in the "vlan" column not the internal VLAN number.

The keyword definitions for the *protocol* argument are as follows:

- assigned specifies the assigned protocol entries.
- **ip** specifies the IP protocol.
- ipx specifies the IPX protocols.
- other specifies the other protocol entries.

Examples

This example shows how to display all the static MAC address entries:

```
Switch# show mac-address-table static
Unicast Entries
vlan mac address
                   type
                             protocols
                                                 port
 1 0030.94fc.0dff static ip,ipx,assigned,other Switch
Fa6/1 0030.94fc.0dff static ip,ipx,assigned,other Switch
Fa6/2 0030.94fc.0dff static ip,ipx,assigned,other Switch
Multicast Entries
     mac address type ports
vlan
______
     ffff.ffff.ffff system Switch,Fa6/15
      ffff.ffff.ffff system Fa6/16
1002
    ffff.ffff.ffff system
1003
    ffff.ffff.ffff system
     ffff.ffff.ffff system
1004
      ffff.ffff.ffff system
1005
Fa6/1
      ffff.ffff.ffff
                    system Switch, Fa6/1
Fa6/2
     ffff.ffff.ffff
                   system Switch, Fa6/2
Switch#
```

This example shows how to display the static MAC address entries with a specific protocol type (in this case, assigned):

Switch# show mac-address-table static protocol assigned Unicast Entries vlan mac address type port protocols 1 0030.94fc.0dff static ip, ipx, assigned, other Switch Fa6/1 0030.94fc.0dff static ip,ipx,assigned,other Switch Fa6/2 0030.94fc.0dff static ip, ipx, assigned, other Switch Multicast Entries vlan mac address type ports ______ ffff.ffff.ffff system Switch,Fa6/15 1 ffff.ffff.ffff system Fa6/16 2. 1002 ffff.ffff.ffff system 1003 ffff.ffff.ffff system 1004 ffff.ffff.ffff system ffff.ffff.ffff system 1005 ffff.ffff.ffff system Switch,Fa6/1 Fa6/1 Fa6/2 ffff.ffff.ffff system Switch,Fa6/2 Switch#

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table protocol show mac-address-table vlan

show mac-address-table vlan

To display information about the MAC address table for a specific VLAN, use the **show** mac-address-table vlan command.

show mac-address-table [vlan vlan_id] [protocol protocol]

Syntax Description

vlan vlan_id	(Optional) Displays the entries for a specific VLAN; valid values are from 1 to 4094.
protocol protocol	(Optional) Specifies a protocol. See the "Usage Guidelines" section for more information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for extended addressing was added.

Usage Guidelines

For the MAC address table entries used by the routed ports, the routed port name is displayed in the "vlan" column not the the internal VLAN number.

The keyword definitions for the *protocol* variable are as follows:

- assigned specifies the assigned protocol entries.
- **ip** specifies the IP protocol.
- ipx specifies the IPX protocols.
- other specifies the other protocol entries.

Examples

This example shows how to display information about the MAC address table for a specific VLAN:

Switch# show mac-address-table vlan 1

vlar		type	protocols	port
1	0000.0000.0201	dynamic		FastEthernet6/15
1	0000.0000.0202	dynamic	ip	FastEthernet6/15
1	0000.0000.0203	dynamic	other	FastEthernet6/15
1	0000.0000.0204	dynamic	other	FastEthernet6/15
1	0030.94fc.0dff	static	ip.ipx.assigned.other	Switch

```
Multicast Entries

vlan mac address type ports

------

1 ffff.ffff system Switch,Fa6/15

Switch#
```

This example shows how to display MAC address table information for a specific protocol type:

${\tt Switch\#}$ show mac-address-table vlan 100 protocol other

vlan	Entries mac address	type	protocols	port
1 1	0000.0000.0203 0000.0000.0204	dynamic dynamic	other other	FastEthernet6/15 FastEthernet6/15
1 Multica	0030.94fc.0dff st Entries	Static	ip,ipx,assigned,other	Switch
			ports	
1 Switch#	ffff.ffff.ffff	system :	Switch,Fa6/15	

Related Commands

show mac-address-table address show mac-address-table aging-time show mac-address-table count show mac-address-table dynamic show mac-address-table interface show mac-address-table multicast show mac-address-table protocol show mac-address-table static

show module

To display information about the module, use the **show module** command.

show module [mod | all]

Syntax Description

mod	(Optional) Number of the module; valid values vary from chassis to chassis.
all	(Optional) Displays information for all modules.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Enhanced the output of the show idprom interface command to include the 10-Gigabit Ethernet interface.

Usage Guidelines

In the Mod Sub-Module fields in the command output, the **show module** command displays the supervisor engine number but appends the uplink daughter card's module type and information.

If the PoE consumed by the module is more than 50 W above the administratively allocated PoE, the "Status" displays as "PwrOver." If the PoE consumed by the module is more than 50 W above the PoE module limit, the "Status" displays as "PwrFault."

Examples

This example shows how to display information for all the modules.

This example shows the **show module** command output for a system with inadequate power for all installed modules. The system does not have enough power for Module 5; the "Status" displays it as "PwrDeny."

Switch# show module all

		Card Type			Model	Serial No.
1 2 3 5	2 6 18	1000BaseX (GBIC) Superv 1000BaseX (GBIC) 1000BaseX (GBIC) Not enough power for mo 10/100BaseTX (RJ45)	visor(ad	ctive) V V V	VS-X4014 VS-X4306 VS-X4418 VS-X4148-FX-MT VS-X4148	JAB054109GH 00000110 JAB025104WK 00000000000 JAB023402RP
	IAC add	resses	Hw I		Sw +	Status
2 0	010.7b 050.73	1a.f9d0 to 005c.9d1a.f9d ab.9920 to 0010.7bab.992 56.2b36 to 0050.7356.2b fe.a930 to 0001.64fe.a9	25 0.2 47 1.0	12.1(11br)E	12.1(20020313:	00 Ok Ok Ok PwrDeny

6 0050.0f10.28b0 to 0050.0f10.28df 1.0 Ok Switch#

This example shows how to display information for a specific module:

This example shows how to display information for all the modules on the switch:

Switch# **show module** Chassis Type : WS-C4506

Power consumed by backplane : 0 Watts

Mod Ports Card Type		Model .	Serial No.
1 6 XG (X2), 1000BaseX (SFP) 3 6 1000BaseX (GBIC)	Supervisor(ac		00000110
M MAC addresses	Hw Fw	Sw	Status
1 0004.dd46.7700 to 0004.dd46.7705 3 0010.7bab.9920 to 0010.7bab.9925 Switch#	0.0 12.2(20r)	•	·

show monitor

To display information about the SPAN session, use the **show monitor** command.

show monitor [session] [range session-range | local | remote | all | session-number] [detail]

Syntax Description

session	(Optional) Displays the SPAN information for a session.
range	(Optional) Displays information for a range of sessions.
session-range (Optional) Specifies a range of sessions.	
local	(Optional) Displays all local SPAN sessions.
remote	(Optional) Displays the RSPAN source and destination sessions.
all	(Optional) Displays the SPAN and RSPAN sessions.
session-number	(Optional) Session number; valid values are from 1 to 6.
detail	(Optional) Displays the detailed SPAN information for a session.

Defaults

The **detail** keyword only displays lines with a nondefault configuration.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(13)EW	Added support for differing directions within a single user session.
12.1(19)EW	Output enhanced to display configuration status of SPAN enhancements.
12.1(20)EW	Added support to display configuration state for remote SPAN and learning.
12.2(20)EW	Added support to display ACLs that are applied to SPAN sessions.

Examples

This example shows how to display whether ACLs are applied to a given SPAN session on a Catalyst 4500 series switch:

Switch# show monitor

Session 1

Type : Local Session

Source Ports

Both : Fa6/1
Destination Ports : Fa6/2
Encapsulation : Native
Ingress : Disabled
Learning : Disabled

Filter VLANs : 1 IP Access-group : 10 This example shows how to display SPAN information for session 2:

```
Switch# show monitor session 2
Session 2
-----
Type : Remote Source Session
Source Ports:
    RX Only: Fa1/1-3
Dest RSPAN VLAN: 901
Ingress : Enabled, default VLAN=2
Learning : Disabled
Switch#
```

This example shows how to display the detailed SPAN information for session 1:

```
Switch# show monitor session 1 detail
Session 1
Type
                 : Local Session
Source Ports
   RX Only
                : None
   TX Only
                : None
   Both
                : Gi1/1, CPU
Source VLANs
   RX Only
                : None
   TX Only
                : None
   Both
                 : None
Source RSPAN VLAN : Fa6/1
Destination Ports : Fa6/1
   Encapsulation : DOT1Q
         Ingress : Enabled, default VLAN = 2
Filter VLANs : None
 Filter Types RX : Good
 Filter Types TX : None
Dest Rspan Vlan : 901
Ingress: Enabled, default VLAN=2
Learning : Disabled
IP Access-group : None
Switch#
```

This example shows how to display SPAN information for session 1 beginning with the line that starts with Destination:

```
Switch# show monitor session 1 | begin Destination
Destination Ports: None
Filter VLANs: None
Switch#
Switch#
```

Related Commands

monitor session

show pagp

To display information about the port channel, use the **show pagp** command.

show pagp [group-number] {counters | internal | neighbor}

Syntax Description

group-number	(Optional) Channel-group number; valid values are from 1 to 64.
counters Specifies the traffic counter information. internal Specifies the PAgP internal information.	Specifies the traffic counter information.
internal	Specifies the PAgP internal information.
neighbor	Specifies the PAgP neighbor information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

You can enter any **show pagp** command to display the active PAgP port-channel information. To display the nonactive information, enter the **show pagp** command with a group.

Examples

This example shows how to display information about the PAgP counter:

Switch# show pagp counters

	Inform	ation	Fli	ısh
Port	Sent	Recv	Sent	Recv
Channel	group: 1			
Fa5/4	2660	2452	0	0
Fa5/5	2676	2453	0	0
Channel	group: 2			
Fa5/6	289	261	0	0
Fa5/7	290	261	0	0
Switch#				

This example shows how to display internal PAgP information:

```
Switch# show pagp 1 internal
```

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running.

Q - Quit timer is running.

I - Interface timer is running.

Channel group 1

				петто	Par ther	PAGP	Learning	
Port	Flags	State	Timers	Interval	Count	Priority	Method	IfIndx
Fa5/4	SC	U6/S7		30s	1	128	Any	129
Fa5/5	SC	U6/S7		30s	1	128	Any	129
Switch#								

This example shows how to display PAgP neighbor information for all neighbors:

Switch# show pagp neighbor

Flags: S - Device is sending Slow hello. C - Device is in Consistent state. A - Device is in Auto mode. P - Device learns on physical port.

Channel group 1 neighbors

	Partner	Partner	Partner		Partner	Group
Port	Name	Device ID	Port	Age	Flags	Cap.
Fa5/4	JAB031301	0050.0f10.230c	2/45	2s	SAC	2D
Fa5/5	JAB031301	0050.0f10.230c	2/46	27s	SAC	2D

Channel group 2 neighbors

	Partner	Partner	Partner		Partner	Group
Port	Name	Device ID	Port	Age	Flags	Cap.
Fa5/6	JAB031301	0050.0f10.230c	2/47	10s	SAC	2F
Fa5/7	JAB031301	0050.0f10.230c	2/48	11s	SAC	2F

Switch#

Related Commands

pagp learn-method pagp port-priority

show policy-map

To display information about the policy map, use the **show policy-map** command.

show policy-map [policy_map_name]

Syntax Description

policy	man	name	(O_1	n

(Optional) Name of the policy map.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display information for all the policy maps:

```
Switch# show policy-map
Policy Map ipp5-policy
class ipp5
set ip precedence 6
Switch#
```

This example shows how to display information for a specific policy map:

```
Switch# show policy ipp5-policy
Policy Map ipp5-policy
class ipp5
set ip precedence 6
Switch#
```

Related Commands

class-map policy-map show class-map show policy-map interface

show policy-map interface

To display the statistics and configurations of the input and output policies that are attached to an interface, use the **show policy-map interface** command.

show policy-map interface [{fastethernet interface-number} | {gigabitethernet interface-number} | {port-channel number} | {vlan vlan_id}] [input | output]

Syntax Description

(Optional) Specifies the Fast Ethernet 802.3 interface.
(Optional) Specifies the Gigabit Ethernet 802.3z interface.
(Optional) Specifies the port channel.
(Optional) Specifies the VLAN ID; valid values are from 1 to 4094.
(Optional) Specifies input policies only.
(Optional) Specifies output policies only.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.

Examples

This example shows how to display the statistics and configurations of all input and output policies attached to an interface:

Switch# show policy-map interface

```
FastEthernet6/1

service-policy input:ipp5-policy

class-map:ipp5 (match-all)
    0 packets
    match:ip precedence 5
    set:
        ip precedence 6

class-map:class-default (match-any)
    0 packets
    match:any
    0 packets
```

service-policy output:ipp5-policy

```
class-map:ipp5 (match-all)
    0 packets
    match:ip precedence 5
    set:
        ip precedence 6

class-map:class-default (match-any)
    0 packets
    match:any
    0 packets
Switch#
```

This example shows how to display the input policy statistics and configurations for a specific interface:

```
Switch# show policy-map interface fastethernet 5/36 input
service-policy input:ipp5-policy

class-map:ipp5 (match-all)
    0 packets
    match:ip precedence 5
    set:
        ip precedence 6

class-map:class-default (match-any)
    0 packets
    match:any
    0 packets
Switch#
```

Related Commands

class-map policy-map show class-map show qos

show policy-map interface vlan

To show the QoS policy-map information applied to a specific VLAN on an interface, use the **show policy-map interface vlan** command.

show policy-map interface vlan interface-id vlan vlan-id

Syntax Description

interface interface-id	(Optional) Displays QoS policy-map information for a specific interface.
vlan vlan-id	(Optional) Displays QoS policy-map information for a specific VLAN.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

Take the following configuration as an example:

```
interface GigabitEthernet3/1
vlan-range 20,400
  service-policy input p1
vlan-range 300-301
  service-policy output p2
```

This example shows how to display policy-map statistics on VLAN 20 on the Gigabit Ethernet 6/1 interface:

```
Switch# show policy-map interface gigabitEthernet 3/1 vlan 20
GigabitEthernet3/1 vlan 20
Service-policy input: p1
Class-map: class-default (match-any)
0 packets
Match: any
0 packets
police: Per-interface
```

Conform: 0 bytes Exceed: 0 bytes

Related Commands

service-policy show policy-map interface

show port-security

To display the port security settings for an interface or for the switch, use the **show port-security** command.

show port-security [address] [interface *interface-id*] [vlan vlan-id]

Syntax Description

address	(Optional) Displays all secure MAC addresses for all ports or for a specific port.
interface interface-id	(Optional) Displays port security settings for a specific interface.
vlan vlan-id	(Optional) Displays port security settings for a specific VLAN.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(18)EW	Support was enhanced to display sticky MAC addresses.
12.2(25)EWA	Support was enhanced to display setting on a per-VLAN basis.

Usage Guidelines

If you enter the command without keywords, the output includes the administrative and operational status of all secure ports on the switch.

If you enter the *interface-id* value, the **show port-security** command displays port security settings for the interface.

If you enter the **address** keyword, the **show port-security address** command displays the secure MAC addresses for all interfaces and the aging information for each secure address.

If you enter the *interface-id* value and the **address** keyword, the **show port-security address interface** command displays all the MAC addresses for the interface with aging information for each secure address. You can also use this command to display all the MAC addresses for an interface even if you have not enabled port security on it.

Examples

This example shows how to display port security settings for the entire switch:

	<pre>port-security MaxSecureAddr</pre>	CurrentAddr (Count)	SecurityViolation (Count)	Security Action
Fa3/1	2	2	0	Restrict
Fa3/2	2	2	0	Restrict
Fa3/3	2	2	0	Shutdown
Fa3/4	2	2	0	Shutdown
Fa3/5	2	2	0	Shutdown
Fa3/6	2	2	0	Shutdown

Fa3/7	2	2	0	Shutdown
Fa3/8	2	2	0	Shutdown
Fa3/10	1	0	0	Shutdown
Fa3/11	1	0	0	Shutdown
Fa3/12	1	0	0	Restrict
Fa3/13	1	0	0	Shutdown
Fa3/14	1	0	0	Shutdown
Fa3/15	1	0	0	Shutdown
Fa3/16	1	0	0	Shutdown

Total Addresses in System (excluding one mac per port) :8
Max Addresses limit in System (excluding one mac per port) :1024

Global SNMP trap control for port-security :20 (traps per second)

This example shows how to display port security settings for interface Fast Ethernet 5/1:

Switch# show port-security interface fastethernet 5/1

Port Security : Enabled
Port Status : Secure-up
Violation Mode : Shutdown
Aging Time : 0 mins
Aging Type : Absolute
SecureStatic Address Aging : Disabled
Maximum MAC Addresses : 1
Total MAC Addresses : 1

Configured MAC Addresses : 0 Sticky MAC Addresses : 1

Last Source Address : 0000.0001.001a

Security Violation Count : 0

This example shows how to display all secure MAC addresses configured on all switch interfaces:

Switch# show port-security address

Secure Mac Address Table

Vlan	Mac Address	Туре	Ports	Remaining Age (mins)
1	0000.0001.0000	SecureConfigure	d Fa3/1	15 (I)
1	0000.0001.0001	SecureConfigure	d Fa3/1	14 (I)
1	0000.0001.0100	SecureConfigure	d Fa3/2	=
1	0000.0001.0101	SecureConfigure	d Fa3/2	=
1	0000.0001.0200	SecureConfigure	d Fa3/3	=
1	0000.0001.0201	SecureConfigure	d Fa3/3	_
1	0000.0001.0300	SecureConfigure	d Fa3/4	_
1	0000.0001.0301	SecureConfigure	d Fa3/4	=
1	0000.0001.1000	SecureDynamic	Fa3/5	-
1	0000.0001.1001	SecureDynamic	Fa3/5	-
1	0000.0001.1100	SecureDynamic	Fa3/6	-
1	0000.0001.1101	SecureDynamic	Fa3/6	-
1	0000.0001.1200	SecureSticky	Fa3/7	-
1	0000.0001.1201	SecureSticky	Fa3/7	-
1	0000.0001.1300	SecureSticky	Fa3/8	-
1	0000.0001.1301	SecureSticky	Fa3/8	-

Total Addresses in System (excluding one mac per port) :8
Max Addresses limit in System (excluding one mac per port) :3072

This example shows how to display the maximum allowed number of secure MAC addresses and the current number of secure MAC addresses on interface Gigabitethernet1/1:

Switch# show port-security interface gigabitethernet1/1 vlan

Defau.	lt maxımur	n:	22	
VLAN	Maximum		Current	
2	2	22		3
3	2	22		3
4	2	22		3
5	2	22		1
6	2	22		2

This example shows how to display the port security settings on interface Gigabitethernet1/1 for VLANs 2 and 3:

Switch# show port-security interface gigabitethernet1/1 vlan 2-3

Default maximum:		22		
VLAN Maximum			Current	
2		22		3
3		22		3

This example shows how to display all secure MAC addresses configured on interface Gigabitethernet1/1 with aging information for each address.

Switch# show port-security interface gigabitethernet1/1 address

Secure Mac Address Table

Vlan	Mac Address	Туре	Ports Remaining Age(mins)
2	0001.0001.0001	SecureConfigured	Gi1/1 -
2	0001.0001.0002	SecureSticky	Gi1/1 -
3	0001.0001.0001	SecureConfigured	Gi1/1 -
3	0001.0001.0002	SecureSticky	Gi1/1 -
3	0001.0001.0003	SecureSticky	Gi1/1 -
4	0001.0001.0001	SecureConfigured	Gi1/1 -
4	0001.0001.0003	SecureSticky	Gi1/1 -
6	0001.0001.0001	SecureConfigured	Gi1/1 -
6	0001.0001.0002	SecureConfigured	Gi1/1 -

Total Addresses: 12

This example shows how to display all secure MAC addresses configured on VLANs 2 and 3 on interface Gigabitethernet1/1 with aging information for each address:

Switch# show port-security interface gigabitethernet1/1 address vlan 2-3

	Secure Mac Ac	dress Table		
Vlan	Mac Address	Туре	Ports	Remaining Age(n

Vlan	Mac Address	Туре	Ports	Remaining Age(mins)
2	0001.0001.0001	SecureConfigured	Gi1/1	_
2	0001.0001.0002	SecureSticky	Gi1/1	_
2	0001.0001.0003	SecureSticky	Gi1/1	_
3	0001.0001.0001	SecureConfigured	Gi1/1	_
3	0001.0001.0002	SecureSticky	Gi1/1	_
3	0001.0001.0003	SecureSticky	Gi1/1	=

Total Addresses: 12

Switch#

Related Commands

switchport port-security

show power

To display information about the power status, use the **show power** command.

show power [available | capabilities | detail | inline {[interface] | consumption default | module | mod} | module | status | supplies]

Syntax Description

available	(Optional) Displays the available system power.
capabilities	(Optional) Displays the individual power supply capabilities.
detail	(Optional) Displays detailed information on power resources.
inline	(Optional) Displays the PoE status.
interface	(Optional) Type of interface; the only valid value is fastethernet.
consumption default	(Optional) Displays the PoE consumption.
module mod	(Optional) Displays the PoE consumption for the specified module.
module	(Optional) Displays the power consumption for each module.
status	(Optional) Displays the power supply status.
supplies	(Optional) Displays the number of power supplies needed by the system.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

If a powered device is connected to an interface with external power, the switch does not recognize the powered device. The Device column in the output of the **show power inline** command displays as unknown.

If your port is not capable of supporting Power over Ethernet, you will receive this message:

Power over Ethernet not supported on interface Admin

The **show power in-line** *interface* | *module* command displays the amount of power that is used to operate a Cisco 7960 IP Phone. To view the amount of power requested, use the **show cdp neighbors** command.

Because of the PoE consumed by FPGAs and other hardware components on the module the operating PoE consumption for an 802.3af-compliant module can be nonzero, even when there are no powered devices attached to the module. The operating PoE can vary by as much as 20 W because of fluctuations in the PoE that is consumed by the hardware components.

Examples

This example shows how to display information about the general power supply:

Switch# show power

Power				Fan	Inline
Supply	Model No	Туре	Status	Sensor	Status
PS1	PWR-C45-2800AC	AC 2800W	good	good	good
PS2	PWR-C45-1000AC	AC 1000W	err-disable	good	n.a.

*** Power Supplies of different type have been detected***

Power supplies needed by system :1 Power supplies currently available :1

Power Summary (in Watts)	Used	Maximum Available			
System Power (12V) Inline Power (-50V) Backplane Power (3.3V)	328 0 10	1360 1400 40			
Total Used Switch#	338	(not to exceed	Total Maximum	Available =	750)

This example shows how to display the amount of available system power:

Switch# show power available

Power Summary

(in Watts)	Available	Used	Remaining
System Power	1360	280	1080
Inline Power	1400	0	1400
Maximum Power	2800	280	2520
Switch#			

This example shows how to display the detailed information for system power.

Switch# show power detail

Power Supply	Model No	Туре	Status	Fan Sensor	Inline Status
PS1	PWR-C45-1300ACV	AC 1300W	good	good	good
PS2	none				

Power supplies needed by system :1 Power supplies currently available :1

Power Summary		Maximum
(in Watts)	Used	Availabl
System Power (12V)	518	1000
Inline Power (-50V)	24	742
Backplane Power (3.3V)	40	40

Total Used 582 (not to exceed Total Maximum Available = 1300)

		Watts Used	d of System Po	wer (12V)
Mod	Model	currently	out of reset	in reset
1	WS-X4013+	110	110	110
3	WS-X4448-GB-LX	90	90	50
4	WS-X4418	80	80	50
5	WS-X4248-RJ45V	65	65	25

6 7 	WS-X4248-RJ45V WS-4548-GB-RJ45 Fan Tray	65 58 50	65 58 		25 15 	
	Total	518	468		275	
Mod	Model	Inline Power	r Admin I evice	Inline PS	-	Efficiency
1 3 4 5	WS-X4013+ WS-X4448-GB-LX WS-X4418 WS-X4248-RJ45V WS-X4248-RJ45V	- - - 24 0	- - - 22 0	- - - 22 22	- - 20 20	- - 89 89
7 	WS-4548-GB-RJ45	_ 	-		-	-

22



Total

The "Inline Power Oper" displays the PoE consumed by the powered devices attached to the module in addition to the PoE consumed by the FPGAs and other hardware components on the module. The "Inline Power Admin" displays only the PoE allocated by the powered devices attached to the module.

44

40

This example shows how to display the power status information:

24

Switch# show power status											
Power			Fan	Inline							
Supply	Model N	0	Type	St	tatus	Sensor	Status				
PS1	PWR-C45-2800AC		AC 2800W		ood	good	good				
PS2 PWR-C45		-2800AC	AC 28	00W gd	ood	good	good				
Power S	upply	Max	Min	Max	Min	Absolute					
(Nos in	Watts)	Inline	Inline	System	System	Maximum					
PS1		1400	1400	1360	1360	2800					
PS2		1400	1400	1360	1360	2800					
Switch#											

This example shows how to verify the PoE consumption for the switch:

```
Switch# show power inline consumption default Default PD consumption : 5000 mW Switch#
```

This example shows how to display the status of inline power:

Switch# show power inline Available:677(w) Used:117(w) Remaining:560(w)

Interface Admin		Oper	Powe	r(Watts)	Device	Class
			From PS	To Device		
Fa3/1	auto	on	17.3	15.4	Ieee PD	0
Fa3/2	auto	on	4.5	4.0	Ieee PD	1
Fa3/3	auto	on	7.1	6.3	Cisco IP Phone 7960	0
Fa3/4	auto	on	7.1	6.3	Cisco IP Phone 7960	n/a
Fa3/5	auto	on	17.3	15.4	Ieee PD	0
Fa3/6	auto	on	17.3	15.4	Ieee PD	0
Fa3/7	auto	on	4.5	4.0	Ieee PD	1
Fa3/8	auto	on	7.9	7.0	Ieee PD	2
Fa3/9	auto	on	17.3	15.4	Ieee PD	3
Fa3/10	auto	on	17.3	15.4	Ieee PD	4

Fa3/11	auto	off		0	0	n/a	n/a
Fa3/12	auto	off		0	0	n/a	n/a
Fa3/13	auto	off		0	0	n/a	n/a
Fa3/14	auto	off		0	0	n/a	n/a
Fa3/15	auto	off		0	0	n/a	n/a
Fa3/16	auto	off		0	0	n/a	n/a
Fa3/17	auto	off		0	0	n/a	n/a
Fa3/18	auto	off		0	0	n/a	n/a
Totals:		10	on	117.5	104.6		
Switch#							

This example shows how to display the number of power supplies needed by the system:

```
Switch# show power supplies
Power supplies needed by system = 2
Switch#
```

Switch# show power inline fa3/1

This example shows how to display the PoE status for Fast Ethernet interface 3/1:

```
Available:677(w) Used:11(w) Remaining:666(w)

Interface Admin Oper Power(Watts) Device Class
From PS To Device
------
Fa3/1 auto on 11.2 10.0 Ieee PD 0

Interface AdminPowerMax AdminConsumption
(Watts) (Watts)
```

Fa3/1 15.4 10.0 Switch#

Related Commands

power dc input power inline power inline consumption power redundancy-mode power supplies required

show qos

To display QoS information, use the **show qos** command.

show qos

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows the output that might be displayed if you do not enter any keywords:

Switch# **show qos** QoS is enabled globally
Switch#

Related Commands

qos (global configuration mode) qos (interface configuration mode)

show qos aggregate policer

To display QoS aggregate policer information, use the show qos aggregate policer command.

show qos aggregate policer [aggregate_name]

•	-			
Syntax	Hacr	`rii	ntın	n
JVIIIAA	DESL	, I I I	บแบ	ш

aggregate_name	(Optional)	Named	aggregate	policer.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The aggregate policer name is case sensitive.

Examples

This example shows the output if you do not enter any keywords:

Switch# show qos aggregate policer

Policer aggr-1

Rate(bps):10000000 Normal-Burst(bytes):1000000

 $\verb|conform-action:transmit| exceed-action:policed-dscp-transmit|$

Policymaps using this policer: ipp5-policy

Switch#

Related Commands

qos aggregate-policer

show qos dbl

To display global Dynamic Buffer Limiting (DBL) information, use the show qos dbl command.

show qos dbl

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display global DBL information:

Switch# show qos dbl DBL is enabled globally

DBL flow includes vlan

DBL flow includes 14-ports

DBL does not use ecn to indicate congestion

DBL exceed-action mark probability:15%

DBL max credits:15

DBL aggressive credit limit:10

DBL aggressive buffer limit:2 packets

Switch#

Related Commands

qos (global configuration mode) qos dbl

show qos interface

To display queueing information, use the **show qos interface** command.

show qos interface {fastethernet interface-number | gigabitethernet interface-number} | [vlan vlan_id | port-channel number]

Syntax Description

fastethernet interface-number	Specifies the Fast Ethernet 802.3 interface.
gigabitethernet interface-number	Specifies the Gigabit Ethernet 802.3z interface.
vlan vlan_id	(Optional) Specifies the VLAN ID; valid values are from 1 to 4094.
port-channel number	(Optional) Specifies the port channel; valid ranges are from 1 to 64.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(13)EW	Added support for extended VLAN addresses.
12.1(19)EW	Display changed to include the Port Trust Device.

Examples

This example shows how to display queueing information:

Switch# show gos interface fastethernet 6/1

QoS is enabled globally Port QoS is enabled

Administrative Port Trust State: 'dscp' Operational Port Trust State: 'untrusted'

Port Trust Device: 'cisco-phone' Default DSCP:0 Default CoS:0

Tx-Queue	Bandwidth	ShapeRate	Priority	QueueSize
	(bps)	(bps)		(packets)
1	31250000	disabled	N/A	240
2	31250000	disabled	N/A	240
3	31250000	disabled	normal	240
4	31250000	disabled	N/A	240
Switch#				

Related Commands

qos map cos show qos tx-queue

show qos maps

To display QoS map information, use the show qos maps command.

show qos maps [cos | dscp [policed | tx-queue]]

Syntax Description

cos	(Optional) Displays CoS map information.
dscp	(Optional) Displays DSCP map information.
policed	(Optional) Displays policed map information.
tx-queue	(Optional) Displays tx-queue map information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display QoS map settings:

```
Switch# show qos maps
DSCP-TxQueue Mapping Table (dscp = d1d2)
d1 :d2 0 1 2 3 4 5 6 7 8 9
     01 01 01 01 01 01 01 01 01 01
 1:
      01 01 01 01 01 01 02 02 02 02
      02 02 02 02 02 02 02 02 02 02
      02 02 03 03 03 03 03 03 03 03
      03 03 03 03 03 03 03 04 04
      04 04 04 04 04 04 04 04 04 04
      04 04 04 04
Policed DSCP Mapping Table (dscp = d1d2)
d1:d2 0 1 2 3 4 5 6 7 8 9
      00 01 02 03 04 05 06 07 08 09
      10 11 12 13 14 15 16 17 18 19
1:
      20 21 22 23 24 25 26 27 28 29
      30 31 32 33 34 35 36 37 38 39
      40 41 42 43 44 45 46 47 48 49
      50 51 52 53 54 55 56 57 58 59
```

60 61 62 63

Related Commands

qos (global configuration mode) qos (interface configuration mode)

show redundancy

To display redundancy facility information, use the **show redundancy** command.

show redundancy {clients | counters | history | states}

Syntax Description

clients	(Optional) Displays information about the redundancy facility client.
counters	(Optional) Displays information about the redundancy facility counter.
history	(Optional) Displays a log of past status and related information for the redundancy facility.
states	(Optional) Displays information about the redundancy facility state.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1.(13)EW	Support for this command was introduced on the Catalyst 4500 series switch
	(Catalyst 4507R only).

Examples

This example shows how to display information about the redundancy facility:

```
Switch# show redundancy
4507r-demo#show redundancy
Redundant System Information :
      Available system uptime = 2 days, 2 hours, 39 minutes
Switchovers system experienced = 0
              Standby failures = 0
        Last switchover reason = none
                 Hardware Mode = Duplex
    Configured Redundancy Mode = Stateful Switchover
     Operating Redundancy Mode = Stateful Switchover
             Maintenance Mode = Disabled
                Communications = Up
Current Processor Information :
              Active Location = slot 1
        Current Software state = ACTIVE
       Uptime in current state = 2 days, 2 hours, 39 minutes
                 Image Version = Cisco Internetwork Operating System Software
IOS (tm) Catalyst 4000 L3 Switch Software (cat4000-I5S-M), Version 12.2(20)EWA(3
.92), CISCO INTERNAL USE ONLY ENHANCED PRODUCTION VERSION
Copyright (c) 1986-2004 by cisco Systems, Inc.
Compiled Wed 14-Jul-04 04:42 by esi
                          BOOT = bootflash:cat4000-i5s-mz.122_20_EWA_392,1
        Configuration register = 0x2002
```

```
Peer Processor Information:

Standby Location = slot 2

Current Software state = STANDBY HOT

Uptime in current state = 2 days, 2 hours, 39 minutes

Image Version = Cisco Internetwork Operating System Software

IOS (tm) Catalyst 4000 L3 Switch Software (cat4000-I5S-M), Version 12.2(20)EWA(3.92), CISCO INTERNAL USE ONLY ENHANCED PRODUCTION VERSION

Copyright (c) 1986-2004 by cisco Systems, Inc.

Compiled Wed 14-Jul-04 0

BOOT = bootflash:cat4000-i5s-mz.122_20_EWA_392,1

Configuration register = 0x2002
```

Switch#

This example shows how to display redundancy facility client information:

The output displays the following information:

- clientID displays the client's ID number.
- clientSeq displays the client's notification sequence number.
- Current redundancy facility state.

This example shows how to display the redundancy facility counter information:

```
Switch# show redundancy counters
Redundancy Facility OMs
              comm link up = 1
        comm link down down = 0
          invalid client tx = 0
          null tx by client = 0
               tx failures = 0
      tx msg length invalid = 0
      client not rxing msgs = 0
 rx peer msg routing errors = 0
          null peer msg rx = 0
        errored peer msg rx = 0
                 buffers tx = 1535
     tx buffers unavailable = 0
                 buffers rx = 1530
      buffer release errors = 0
 duplicate client registers = 0
  failed to register client = 0
       Invalid client syncs = 0
```

This example shows how to display redundancy facility history information:

```
Switch# show redundancy history
00:00:01 client added: RF_INTERNAL_MSG(0) seq=0
00:00:01 client added: RF_LAST_CLIENT(65000) seq=65000
00:00:01 client added: GALIOS_CONFIG_SYNC(28) seq=330
00:00:03 client added: Redundancy Mode RF(30) seq=135
```

```
00:00:03 *my state = INITIALIZATION(2) *peer state = DISABLED(1)
00:00:03 RF_PROG_INITIALIZATION(100) RF_INTERNAL_MSG(0) op=0 rc=11
00:00:03 RF_PROG_INITIALIZATION(100) Redundancy Mode RF(30) op=0 rc=11
00:00:03 RF_PROG_INITIALIZATION(100) GALIOS_CONFIG_SYNC(28) op=0 rc=11
00:00:03 RF_PROG_INITIALIZATION(100) RF_LAST_CLIENT(65000) op=0 rc=11
00:00:03 *my state = NEGOTIATION(3) peer state = DISABLED(1)
00:00:25 RF_EVENT_GO_ACTIVE(511) op=0
00:00:25 *my state = ACTIVE-FAST(9) peer state = DISABLED(1)
00:00:25 RF_STATUS_MAINTENANCE_ENABLE(403) Redundancy Mode RF(30) op=0
00:00:25 RF_STATUS_MAINTENANCE_ENABLE(403) GALIOS_CONFIG_SYNC(28) op=0
00:00:25 RF_PROG_ACTIVE_FAST(200) RF_INTERNAL_MSG(0) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_FAST(200) Redundancy Mode RF(30) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_FAST(200) GALIOS_CONFIG_SYNC(28) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_FAST(200) RF_LAST_CLIENT(65000) op=0 rc=11
00:00:25 *my state = ACTIVE-DRAIN(10) peer state = DISABLED(1)
00:00:25 RF_PROG_ACTIVE_DRAIN(201) RF_INTERNAL_MSG(0) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_DRAIN(201) Redundancy Mode RF(30) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_DRAIN(201) GALIOS_CONFIG_SYNC(28) op=0 rc=11
00:00:25 RF_PROG_ACTIVE_DRAIN(201) RF_LAST_CLIENT(65000) op=0 rc=11
---cut---cut---cut---
---cut---cut---cut---
00:01:34 RF_PROG_PLATFORM_SYNC(300) RF_INTERNAL_MSG(0) op=0 rc=11
00:01:34 RF_PROG_PLATFORM_SYNC(300) Redundancy Mode RF(30) op=0 rc=11
00:01:34 RF_PROG_PLATFORM_SYNC(300) GALIOS_CONFIG_SYNC(28) op=0 rc=0
00:01:34 RF_EVENT_CLIENT_PROGRESSION(503) GALIOS_CONFIG_SYNC(28) op=1 rc=0
00:01:36 RF_EVENT_PEER_PROG_DONE(506) GALIOS_CONFIG_SYNC(28) op=300
00:01:36 RF_PROG_PLATFORM_SYNC(300) RF_LAST_CLIENT(65000) op=0 rc=0
00:01:36 RF_EVENT_CLIENT_PROGRESSION(503) RF_LAST_CLIENT(65000) op=1 rc=0
00:01:36 RF_EVENT_PEER_PROG_DONE(506) RF_LAST_CLIENT(65000) op=300
00:01:38 *my state = ACTIVE(13) *peer state = STANDBY COLD(4)
```

This example shows how to display information about the redundancy facility state:

Related Commands

redundancy redundancy force-switchover

Switch#

keep_alive count = 0
keep_alive threshold = 18

RF debug mask = 0x0

Switch# show redundancy states

my state = 13 -ACTIVE

show running-config

To display the module status and configuration, use the **show running-config** command.

show running-config [module slot]

Syntax Description

module slot	(Optional	Specifies the module slot number; valid values are from 1 to	6.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

In some cases, you might see a difference in the duplex mode displayed when you enter the **show interfaces** command and the **show running-config** command. If you do see a difference, the duplex mode displayed in the **show interfaces** command is the actual duplex mode that the interface is running. The **show interfaces** command shows the operating mode for an interface, while the **show running-config** command shows the configured mode for an interface.

The **show running-config** command output for an interface may display a duplex mode configuration but no configuration for the speed. When no speed is displayed in the output, it indicates that the interface speed is configured to be auto and that the duplex mode shown becomes the operational setting once the speed is configured to something other than auto. With this configuration, it is possible that the operating duplex mode for that interface does not match the duplex mode shown with the **show running-config** command.

Examples

This example shows how to display the module and status configuration for all modules:

```
Switch# show running-config
03:23:36:%SYS-5-CONFIG_I:Configured from console by consolesh runn
Building configuration...

Current configuration:3268 bytes
!
version 12.1
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname Switch
!
!
power supplies required 1
ip subnet-zero
```

```
!
!
interface FastEthernet1
no ip address
shutdown
duplex auto
speed auto
Switch#
```

This example shows the output for the **show running-config** command when you have enabled the **switchport voice vlan** command:

```
Switch# show running-config int fastethernet 6/1
Building configuration...

Current configuration:133 bytes
!
interface FastEthernet6/1
switchport voice vlan 2
no snmp trap link-status
spanning-tree portfast
channel-group 1 mode on
end

Switch#
```

show slavebootflash:

To display information about the standby bootflash file system, use the show slavebootflash: command.

show slavebootflash: [all | chips | filesys]

Syntax Description

all	(Optional) Displays all possible Flash information.
chips	(Optional) Displays Flash chip information.
filesys	(Optional) Displays file system information.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display file system status information:

Switch# show slavebootflash: filesys

```
----- FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: bootflash
 Magic Number
                    = 6887635 File System Vers = 10000
                                                         (1.0)
                     = 1000000 Sector Size = 40000
 Length
 Programming Algorithm = 39
                               Erased State
                                               = FFFFFFFF
 File System Offset = 40000
                               Length = F40000
 MONLIB Offset
                    = 100
                              Length = C628
 Bad Sector Map Offset = 3FFF8
                               Length = 8
 Squeeze Log Offset = F80000 Length = 40000
 Squeeze Buffer Offset = FC0000
                                Length = 40000
 Num Spare Sectors
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
              = 917CE8 Bytes Available = 628318
 Bytes Used
 Bad Sectors = 0
                   Spared Sectors = 0
 OK Files
              = 2
                        Bytes = 917BE8
 Deleted Files = 0
                       Bytes = 0
 Files w/Errors = 0
                       Bytes = 0
Switch>
```

This example shows how to display system image information:

```
Switch# show slavebootflash:
-# - ED --type-- --crc-- -seek-- nlen -length- -----date/time----- name

1 .. image 8C5A393A 237E3C 14 2063804 Aug 23 1999 16:18:45 c4-boot-mz

2 .. image D86EE0AD 957CE8 9 7470636 Sep 20 1999 13:48:49 rp.halley
Switch>
```

This example shows how to display all bootflash information:

```
Switch# show slavebootflash: all
-# - ED --type-- --crc-- -seek-- nlen -length- ----date/time---- name
1 .. image
            8C5A393A 237E3C 14 2063804 Aug 23 1999 16:18:45 c4-boot-
2 .. image
            D86EE0AD 957CE8 9 7470636 Sep 20 1999 13:48:49 rp.halley
6456088 bytes available (9534696 bytes used)
----- FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: bootflash
 Magic Number
                    = 6887635 File System Vers = 10000
                    = 1000000 Sector Size = 40000
                               Erased State
 Programming Algorithm = 39
                                               = FFFFFFFF
 File System Offset = 40000 Length = F40000
                               Length = C628
 MONLIB Offset
                     = 100
 Bad Sector Map Offset = 3FFF8
                                Length = 8
 Squeeze Log Offset = F80000
                                Length = 40000
 Squeeze Buffer Offset = FC0000 Length = 40000
 Num Spare Sectors
                    = 0
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
              = 917CE8 Bytes Available = 628318
 Bytes Used
 Bad Sectors = 0 Spared Sectors = 0
          = 2
                       Bytes = 917BE8
 OK Files
 Deleted Files = 0 Bytes = 0
Files w/Errors = 0 Bytes = 0
Switch>
```

show slaveslot0:

To display information about the file system on the standby supervisor engine, use the **show slaveslot0:** command.

show slot0: [all | chips | filesys]

Syntax Description

all	(Optional) Displays all Flash information including the output from the show slot0: chips and show slot0: filesys commands.
chips	(Optional) Displays Flash chip register information.
filesys	(Optional) Displays file system status information.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display a summary of the file system:

```
Switch# show slaveslot0:
-# - ED --type-- --crc-- -seek-- nlen -length- -----date/time----- name
1 .. image 6375DBB7 A4F144 6 10678468 Nov 09 1999 10:50:42 halley
5705404 bytes available (10678596 bytes used)
Switch>
```

This example shows how to display Flash chip information:

```
Switch# show slaveslot0: chips
******* Intel Series 2+ Status/Register Dump *******
ATTRIBUTE MEMORY REGISTERS:
 Config Option Reg (4000): 2
 Config Status Reg (4002): 0
 Card Status Reg (4100): 1
 Write Protect Reg (4104): 4
 Voltage Cntrl Reg (410C): 0
 Rdy/Busy Mode Reg (4140): 2
COMMON MEMORY REGISTERS: Bank 0
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
         Status Reg: B0B0
  Block Status Regs:
    0 : B0B0 B0B0 B0B0 B0B0
                                B0B0 B0B0
                                           B0B0
                                                 B0B0
   8 : B0B0 B0B0 B0B0 B0B0
                                B0B0 B0B0 B0B0
                                                 B0B0
   16 : B0B0 B0B0 B0B0 B0B0
                                B0B0 B0B0 B0B0
                                                 B0B0
   24 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
                                                 B0B0
```

```
COMMON MEMORY REGISTERS: Bank 1
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
         Status Reg: B0B0
 Block Status Regs:
   0 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
   8 : B0B0 B0B0 B0B0 B0B0
                           B0B0 B0B0 B0B0
                                         B0B0
   16 : B0B0 B0B0 B0B0 B0B0
                           B0B0 B0B0 B0B0
                                         B0B0
   24 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
                                         B0B0
COMMON MEMORY REGISTERS: Bank 2
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
        Status Reg: B0B0
 Block Status Regs:
   8 : B0B0 B0B0 B0B0 B0B0
                           B0B0
                               вово вово
                                         B0B0
            B0B0
                 B0B0
                      B0B0
   16:
       B0B0
                           B0B0
                               B0B0
                                    B0B0
   24 : B0B0 B0B0 B0B0 B0B0
                          B0B0 B0B0 B0B0 B0B0
COMMON MEMORY REGISTERS: Bank 3
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
       Status Reg: B0B0
 Block Status Regs:
   8 : B0B0 B0B0 B0B0 B0B0
                          B0B0 B0B0 B0B0
   16:
       B0B0 B0B0 B0B0 B0B0
                           B0B0
                               B0B0
                                    B0B0
                                         B0B0
   COMMON MEMORY REGISTERS: Bank 4
 Intelligent ID Code : FFFFFFF
   IID Not Intel -- assuming bank not populated
```

This example shows how to display file system information:

```
Switch# show slaveslot0: filesys
-----FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: slot0
 Magic Number = 6887635 File System Vers = 10000
                    = 1000000 Sector Size = 20000
 Length
 Programming Algorithm = 4
                               Erased State
                                               = FFFFFFFF
 File System Offset = 20000 Length = FA0000
 MONLIB Offset = 100
                              Length = F568
 Bad Sector Map Offset = 1FFF0
                              Length = 10
 Squeeze Log Offset = FC0000
                              Length = 20000
 Squeeze Buffer Offset = FE0000
                               Length = 20000
 Num Spare Sectors = 0
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
              = 9F365C Bytes Available = 5AC9A4
 Bytes Used
             = 0
 Bad Sectors
                        Spared Sectors = 0
              = 1
                        Bytes = 9F35DC
 OK Files
 Deleted Files = 0
                       Bytes = 0
 Files w/Errors = 0
                       Bytes =
Switch>
```

show slot0:

To display information about the slot0: file system, use the **show slot0:** command.

show slot0: [all | chips | filesys]

Syntax Description

all	(Optional) Displays all Flash information including the output from the show slot0: chips and show slot0: filesys commands.
chips	(Optional) Displays Flash chip register information.
filesys	(Optional) Displays file system status information.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display a summary of the file system:

```
Switch# show slot0:
-# - ED --type-- --crc-- -seek-- nlen -length- -----date/time----- name
1 .. image 6375DBB7 A4F144 6 10678468 Nov 09 1999 10:50:42 halley
5705404 bytes available (10678596 bytes used)
Switch>
```

This example shows how to display Flash chip information:

```
Switch# show slot0: chips
****** Intel Series 2+ Status/Register Dump ******
ATTRIBUTE MEMORY REGISTERS:
 Config Option Reg (4000): 2
 Config Status Reg (4002): 0
 Card Status Reg (4100): 1
 Write Protect Reg (4104): 4
 Voltage Cntrl Reg (410C): 0
 Rdy/Busy Mode Reg (4140): 2
COMMON MEMORY REGISTERS: Bank 0
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
          Status Reg: B0B0
 Block Status Regs:
   0 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
                                             B0B0
   8 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
                                             B0B0
   16 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
                                             B0B0
```

COMMON MEMORY REGISTERS: Bank 1

```
Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
        Status Reg: B0B0
 Block Status Regs:
   0 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
   8 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
   16 : B0B0 B0B0 B0B0 B0B0
                             B0B0 B0B0 B0B0 B0B0
   COMMON MEMORY REGISTERS: Bank 2
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
         Status Reg: B0B0
 Block Status Regs:
   8 : B0B0 B0B0 B0B0 B0B0 B0B0 B0B0 B0B0
   16 : B0B0 B0B0 B0B0 B0B0
                             B0B0
                                  B0B0 B0B0
                                            B0B0
   24 : B0B0
             вово вово
                        B0B0
                             B0B0
                                  B0B0 B0B0
COMMON MEMORY REGISTERS: Bank 3
 Intelligent ID Code : 8989A0A0
 Compatible Status Reg: 8080
 Global
         Status Reg: B0B0
 Block Status Regs:
   8 : B0B0 B0B0 B0B0 B0B0
                             B0B0 B0B0 B0B0
                                            B0B0
   16 : B0B0 B0B0 B0B0 B0B0
                             B0B0 B0B0 B0B0
   24 : B0B0 B0B0 B0B0 B0B0
                             B0B0 B0B0 B0B0 B0B0
COMMON MEMORY REGISTERS: Bank 4
 Intelligent ID Code : FFFFFFF
   IID Not Intel -- assuming bank not populated
This example shows how to display file system information:
Switch# show slot0: filesys
-----FILE SYSTEM STATUS-----
 Device Number = 0
DEVICE INFO BLOCK: slot0
 \texttt{Magic Number} \qquad \qquad \texttt{= 6887635} \qquad \texttt{File System Vers = 10000}
                    = 1000000 Sector Size
 Length
                                           = 20000
 Programming Algorithm = 4
                              Erased State
                                             = FFFFFFFF
 File System Offset = 20000
                             Length = FA0000
 MONLIB Offset
                   = 100
                             Length = F568
 Bad Sector Map Offset = 1FFF0
                             Length = 10
 Squeeze Log Offset = FC0000
                             Length = 20000
 Squeeze Buffer Offset = FE0000
                              Length = 20000
 Num Spare Sectors = 0
   Spares:
STATUS INFO:
 Writable
 NO File Open for Write
 Complete Stats
 No Unrecovered Errors
 No Squeeze in progress
USAGE INFO:
              = 9F365C Bytes Available = 5AC9A4
 Bytes Used
            = 0
 Bad Sectors
                       Spared Sectors = 0
              = 1
                       Bytes = 9F35DC
 OK Files
 Deleted Files = 0
                      Bytes = 0
 Files w/Errors = 0
                      Bvtes = 0
Switch>
```

show spanning-tree

To display spanning-tree state information, use the **show spanning-tree** command.

show spanning-tree [bridge_group | active | backbonefast | bridge [id] | inconsistentports | interface type | root | summary [total] | uplinkfast | vlan vlan_id | pathcost method | detail]

Syntax Description

Defaults

Interface information summary is displayed.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Support for extended addressing was added.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Examples

This example shows how to display spanning-tree information on the active interfaces only:

Switch# show spanning-tree active UplinkFast is disabled

BackboneFast is disabled

VLAN1 is executing the ieee compatible Spanning Tree protocol Bridge Identifier has priority 32768, address 0050.3e8d.6401 Configured hello time 2, max age 20, forward delay 15

```
Current root has priority 16384, address 0060.704c.7000
  Root port is 265 (FastEthernet5/9), cost of root path is 38
  Topology change flag not set, detected flag not set
  Number of topology changes 0 last change occurred 18:13:54 ago
  Times: hold 1, topology change 24, notification 2
         hello 2, max age 14, forward delay 10
 Timers: hello 0, topology change 0, notification 0
 Port 265 (FastEthernet5/9) of VLAN1 is forwarding
   Port path cost 19, Port priority 128, Port Identifier 129.9.
  Designated root has priority 16384, address 0060.704c.7000
  Designated bridge has priority 32768, address 00e0.4fac.b000
  Designated port id is 128.2, designated path cost 19
  Timers: message age 3, forward delay 0, hold 0
  Number of transitions to forwarding state: 1
  BPDU: sent 3, received 32852
Switch#
```

This example shows how to display the spanning-tree BackboneFast status:

Switch# show spanning-tree backbonefast

```
BackboneFast is enabled

BackboneFast statistics
------

Number of transition via backboneFast (all VLANs) : 0

Number of inferior BPDUs received (all VLANs) : 0

Number of RLQ request PDUs received (all VLANs) : 0

Number of RLQ response PDUs received (all VLANs) : 0

Number of RLQ request PDUs sent (all VLANs) : 0

Number of RLQ response PDUs sent (all VLANs) : 0

Switch#
```

This example shows how to display spanning-tree information for the bridge:

Switch# show spanning-tree bridge

```
VLAN1
 Bridge ID Priority
                       32768
                      0050.3e8d.6401
            Address
            Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Bridge ID Priority 32768
            Address
                      0050.3e8d.6402
            Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
VLAN3
 Bridge ID Priority
                       32768
                       0050.3e8d.6403
            Address
            Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Switch#
```

This example shows how to display a summary of interface information:

Switch# show spanning-tree

```
VLAN1

Spanning tree enabled protocol ieee
Root ID Priority 32768
Address 0030.94fc.0a00
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 32768
Address 0030.94fc.0a00
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300
```

```
Interface
                                           Designated
                    Port ID Prio Cost Sts
                                           Cost Bridge ID
                                                                  Port ID
Name
                    _____ ___
                                           ____ _____
                    129.79 128 19 FWD
FastEthernet6/15
                                            0 32768 0030.94fc.0a00 129.79
VIJAN2
 Spanning tree enabled protocol ieee
           Priority 32768
Address 0030.94fc.0a01
 Root ID
           This bridge is the root
           Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Bridge ID Priority
                     32768
           Address 0030.94fc.0a01
            \mbox{Hello Time} \mbox{ 2 sec} \mbox{ Max Age 20 sec} \mbox{ Forward Delay 15 sec} 
           Aging Time 300
Interface
                                           Designated
Name
                    Port ID Prio Cost Sts
                                          Cost Bridge ID
                                                                 Port ID
                    ______
                                           ---- ------
FastEthernet6/16
                   129.80 128
                                 19 FWD
                                              0 32768 0030.94fc.0a01 129.80
```

This example shows how to display spanning-tree information for Fast Ethernet interface 5/9:

Switch# show spanning-tree interface fastethernet5/9 Interface Fa0/10 (port 23) in Spanning tree 1 is ROOT-INCONSISTENT Port path cost 100, Port priority 128 Designated root has priority 8192, address 0090.0c71.a400 Designated bridge has priority 32768, address 00e0.1e9f.8940 Designated port is 23, path cost 115 Timers: message age 0, forward delay 0, hold 0 BPDU: sent 0, received 0 The port is in the portfast mode Switch#

This example shows how to display spanning-tree information for a specific VLAN:

```
Switch# show spanning-tree vlan 1
VLAN1 is executing the ieee compatible Spanning Tree protocol
 Bridge Identifier has priority 32768, address 0030.94fc.0a00
 Configured hello time 2, max age 20, forward delay 15
 We are the root of the spanning tree
  Topology change flag not set, detected flag not set
  Number of topology changes 5 last change occurred 01:50:47 ago
         from FastEthernet6/16
  Times: hold 1, topology change 35, notification 2
         hello 2, max age 20, forward delay 15
  Timers:hello 0, topology change 0, notification 0, aging 300
 Port 335 (FastEthernet6/15) of VLAN1 is forwarding
  Port path cost 19, Port priority 128, Port Identifier 129.79.
   Designated root has priority 32768, address 0030.94fc.0a00
  Designated bridge has priority 32768, address 0030.94fc.0a00
  Designated port id is 129.79, designated path cost 0
  Timers:message age 0, forward delay 0, hold 0
  Number of transitions to forwarding state:1
  BPDU:sent 6127, received 0
Switch#
```

This example shows how to display spanning-tree information for a specific bridge group:

```
Switch# show spanning-tree vlan 1
UplinkFast is disabled
BackboneFast is disabled
Switch#
```

This example shows how to display a summary of port states:

Switch# show spanning-tree summary

Root bridge for:VLAN1, VLAN2.
PortFast BPDU Guard is disabled
EtherChannel misconfiguration guard is enabled
UplinkFast is disabled
BackboneFast is disabled
Default pathcost method used is short

Name		Blocking	g Listenin	g Learning	g Forwarding	g STP Active
VLAN1		0	0	0	1	1
VLAN2		0	0	0	1	1
	2 VLANs	0 ()	0 2	2 2	2
Switch#						

This example shows how to display the total lines of the spanning-tree state section:

Switch# show spanning-tree summary totals

Root bridge for:VLAN1, VLAN2.
PortFast BPDU Guard is disabled
EtherChannel misconfiguration guard is enabled
UplinkFast is disabled
BackboneFast is disabled
Default pathcost method used is short

Name			Blocki	ng	Listenin	ıg	Learning	Forwarding	STP	Active
	2	VLANs	0	0		0	2	2		
Switch#										

This example shows how to determine whether any ports are in root inconsistent state:

Switch# show spanning-tree inconsistentports

Name	Interface	Inconsistency
VLAN1	FastEthernet3/1	Root Inconsistent
Number of Switch#	inconsistent ports (segments)	in the system:1

Related Commands

```
spanning-tree backbonefast
spanning-tree cost
spanning-tree guard
spanning-tree pathcost method
spanning-tree portfast default
spanning-tree portfast (interface configuration mode)
spanning-tree port-priority
spanning-tree uplinkfast
spanning-tree vlan
```

show spanning-tree mst

To display MST protocol information, use the show spanning-tree mst command.

show spanning-tree mst [configuration]

show spanning-tree mst [instance-id] [detail]

show spanning-tree mst [instance-id] interface interface [detail]

Syntax Description

configuration	(Optional) Displays region configuration information.
instance-id	(Optional) Instance identification number; valid values are from 0 to 15.
detail	(Optional) Displays detailed MST protocol information.
interface interface	(Optional) Interface type and number; valid values for type are fastethernet , gigabitethernet , tengigabitethernet , port-channel , and vlan . See the "Usage Guidelines" section for more information.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

This command is not supported on systems that are configured with a Supervisor Engine I.

In the output display of the **show spanning-tree mst configuration** command, a warning message might display. This message appears if you do not map secondary VLANs to the same instance as the associated primary VLAN. The display includes a list of the secondary VLANs that are not mapped to the same instance as the associated primary VLAN. The warning message is as follows:

See the **show spanning-tree** command for output definitions.

Examples

This example shows how to display region configuration information:

Switch# show spanning-tree mst configuration

Name [leo] Revision 2702

Instance Vlans mapped

0 1-9,11-19,21-29,31-39,41-4094

1 10,20,30,40

G. 15 - 2. II

Switch#

This example shows how to display additional MST protocol values:

```
Switch# show spanning-tree mst 3 detail
# # # # # # MST03 vlans mapped: 3,3000-3999
Bridge address 0002.172c.f400 priority 32771 (32768 sysid 3)
Root this switch for MST03
GigabitEthernet1/1 of MST03 is boundary forwarding
Port info port id 128.1 priority 128
cost 20000
Designated root address 0002.172c.f400 priority 32771
Designated bridge address 0002.172c.f400 priority 32771 port
id 128.1
Timers: message expires in 0 sec, forward delay 0, forward transitions 1
Bpdus (MRecords) sent 4, received 0
FastEthernet4/2 of MST03 is backup blocking
Port info port id 128.194 priority 128 cost
200000
Designated root address 0002.172c.f400 priority 32771
cost 0
Designated bridge address 0002.172c.f400 priority 32771 port id
Timers: message expires in 2 sec, forward delay 0, forward transitions 1
Bpdus (MRecords) sent 3, received 252
Switch#
```

This example shows how to display MST information for a specific interface:

```
Switch# show spanning-tree mst 0 interface fastethernet4/1 detail
Edge port: no (trunk) port guard : none
(default)
Link type: point-to-point (point-to-point) bpdu filter: disable
(default)
Boundary : internal bpdu guard : disable
(default)
FastEthernet4/1 of MST00 is designated forwarding
Vlans mapped to MST00 1-2,4-2999,4000-4094
Port info port id 128.193 priority 128 cost
200000
Designated root address 0050.3e66.d000 priority 8193
cost 20004
Designated ist master address 0002.172c.f400 priority 49152
cost 0
Designated bridge address 0002.172c.f400 priority 49152 port id
Timers: message expires in 0 sec, forward delay 0, forward transitions 1
Bpdus sent 492, received 3
Switch#
```

Related Commands

spanning-tree mst spanning-tree mst forward-time spanning-tree mst hello-time spanning-tree mst max-hops spanning-tree mst root

show storm-control

To display the broadcast storm control settings on the switch or on the specified interface, use the **show storm-control** command.

show storm-control [interface-id | **broadcast**]

Syntax Description

interface-id	(Optional) Specifies the interface ID for the physical port.
broadcast	(Optional) Displays the broadcast storm threshold setting.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.

Usage Guidelines

When you enter an interface ID, the storm control thresholds are displayed for the specified interface.

If you do not enter an interface ID, the settings are displayed for the broadcast traffic type for all ports on the switch.

Examples

This is an example of output from the **show storm-control** command when no keywords are entered. Because no traffic type keyword was entered, the broadcast storm control settings are displayed.

Switch# show storm-control

Interface	Filter State	Upper	Lower	Current
Gi2/1	Forwarding	30.00%	30.00%	N/A
Gi4/1	Forwarding	30.00%	30.00%	N/A
Gi4/3	Forwarding	30.00%	30.00%	N/A
Switch#				

50.00%

This is an example of output from the **show storm-control** command for a specified interface. Because no traffic type keyword was entered, the broadcast storm control settings are displayed.

0.00%

Switch#	show	stor	n-contro	l fasteth	ernet2/17
Interfac	ce F	ilter	State	Level	Current

Forwarding

Fa2/17 Switch# This is an example of output from the **show storm-control** command for a specified interface and traffic type, where no storm control threshold has been set for that traffic type on the specified interface.

Switch# show storm-control gigabitethernet2/1 broadcast

```
Interface Filter State Level Current
------Gi2/1 forwarding 100.00% N/A
<output truncated>
Switch#
```

Table 2-22 describes the fields in the **show storm-control** display.

Table 2-22 show storm-control Field Descriptions

Field	Description			
Interface	Displays the ID of the interface.			
Filter State	Displays the status of the filter:			
	Blocking—Storm control is enabled, and a storm has occurred.			
	• Forwarding—Storm control is enabled, and no storms have occurred.			
	• Inactive—Storm control is disabled.			
Level	Displays the threshold level set on the interface for broadcast traffic.			
Current	Displays the bandwidth utilization of broadcast traffic as a percentage of total available bandwidth. This field is valid only when storm control is enabled.			
	Note N/A is displayed for interfaces that do storm control in the hardware.			

Related Commands

storm-control show interfaces counters show running-config

show system mtu

To display the global MTU setting, use the **show system mtu** command.

show system mtu

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the global MTU setting:

Switch# show system mtu

Global Ethernet MTU is 1550 bytes.

Switch#

Related Commands

system mtu

show tech-support

To display troubleshooting information for TAC, use the **show tech-support** command.

show tech-support [bridging | cef | ipmulticast | isis | password [page] | page]

Syntax Description

bridging	(Optional) Specifies bridging-related information.
cef	(Optional) Specifies CEF-related information.
ipmulticast	(Optional) Specifies IP multicast-related information.
isis	(Optional) Specifies CLNS and ISIS-related information.
password	(Optional) Includes passwords and other security information in the output.
page	(Optional) Displays one page of information at a time in the output.

Defaults

The defaults are as follows:

- Outputs are displayed without page breaks.
- Passwords and other security information are removed from the output.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

Press the **Return** key to display the next line of output, or press the **Space** bar to display the next page of information. If you do not enter the **page** keyword, the output scrolls. It does not stop for page breaks.

If you enter the **password** keyword, password encryption is enabled, but only the encrypted form appears in the output.

If you do not enter the **password** keyword, the passwords and other security-sensitive information in the output are replaced in the output with the word "removed."

The **show tech-support** commands are a compilation of several **show** commands and the output can be quite lengthy. For a sample display of the output of the **show tech-support** command, see the individual **show** command listed.

If you enter the **show tech-support** command without arguments, the output displays the equivalent of these **show** commands:

- show version
- show running-config
- show stacks
- show interfaces
- show controllers

- · show process memory
- · show process cpu
- show buffers
- · show logging
- show module
- show power
- show environment
- show interfaces switchport
- show interfaces trunk
- · show vlan

If you enter the **ipmulticast** keyword, the output displays the equivalent of these **show** commands:

- show ip pim interface
- show ip pim interface count
- show ip pim neighbor
- show ip pim rp
- show ip igmp groups
- show ip igmp interface
- show ip mroute count
- show ip mroute
- · show ip mcache
- show ip dvmrp route

Examples

For a sample display of the **show tech-support** command output, see the commands listed in the "Usage Guidelines" section for more information.

Related Commands

See the "Usage Guidelines" section.

show udld

To display the administrative and operational UDLD status, use the **show udld** command.

show udld interface-id

Syntax Description

<i>interface-id</i> Name of the interface.
--

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release Modification						
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.					
12.2(25)EW	Added support for the 10-Gigabit Ethernet interface.					

Usage Guidelines

If you do not enter an interface ID value, the administrative and operational UDLD status for all interfaces is displayed.

Examples

This example shows how to display the UDLD state for Gigabit Ethernet interface 2/2:

```
Switch# show udld gigabitethernet2/2
Interface Gi2/2
Port enable administrative configuration setting: Follows device default
Port enable operational state: Enabled
Current bidirectional state: Bidirectional
Current operational state: Advertisement
Message interval: 60
Time out interval: 5
No multiple neighbors detected
   Entry 1
    Expiration time: 146
    Device ID: 1
   Current neighbor state: Bidirectional
    Device name: 0050e2826000
    Port ID: 2/1
   Neighbor echo 1 device: SAD03160954
   Neighbor echo 1 port: Gi1/1
   Message interval: 5
   CDP Device name: 066527791
Switch#
```

Related Commands

udld (global configuration mode)
udld (interface configuration mode)

show vlan

To display VLAN information, use the show vlan command.

show vlan [brief | id vlan_id | name name]

show vlan private-vlan [type]

Syntax Description

brief	(Optional) Displays only a single line for each VLAN, naming the VLAN, status, and
	ports.
id vlan_id	(Optional) Displays information about a single VLAN identified by VLAN ID number; valid values are from 1 to 4094.
name name	(Optional) Displays information about a single VLAN identified by VLAN name; valid values are an ASCII string from 1 to 32 characters.
private-vlan	Displays private VLAN information.
type	(Optional) Private VLAN type.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.1(12c)EW	Added support for extended VLAN addresses.

Examples

This example shows how to display the VLAN parameters for all VLANs within the administrative domain:

Switch# show vlan

VLAN	Name	Status	Ports
1	default	active	Fa5/9
2	VLAN0002	active	Fa5/9
3	VLAN0003	active	Fa5/9
4	VLAN0004	active	Fa5/9
5	VLAN0005	active	Fa5/9
6	VLAN0006	active	Fa5/9
10	VLAN0010	active	Fa5/9
20	VLAN0020	active	Fa5/9

<...Output truncated...>

917 999 1002 1003 1004	trcrf- fddin	917			act: act: act:	ive 1 ive 1 ive 1 ive 1	Fa5/9 Fa5/9 Fa5/9 Fa5/9 Fa5/9 Fa5/9			
VLAN	Туре	SAID	MTU	Parent	RingNo	Bridge	No Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	_	_	_		_	0	0
2	enet	100001	1500	_	_	_	_	_	0	0
3	enet	100003	1500	_	_	_	_	_	303	0
4	enet	100004	1500	_	_	_	_	_	304	0
5	enet	100005	1500	_	_	_	_	_	305	0
6	enet	100006	1500	_	_	_	_	_	0	0
10	enet	100010	1500	_	_	_	_	_	0	0
20	enet	100020	1500	_	_	_	_	_	0	0
50	enet	100050	1500	-	-	-	-	-	0	0
<(Output	truncated.	>							
850	enet	100850	1500	_	_	_	_	_	0	0
917	enet	100917	1500	-	-	_	-	_	0	0
999	enet	100999	1500	-	-	_	-	_	0	0
1002	fddi	101002	1500	-	0	-	_	_	0	0
1003	trcrf	101003	4472	1005	3276	-	-	srb	0	0
1004	fdnet	101004	1500	-	-	-	ieee	_	0	0
1005	trbrf	101005	4472	_	_	15	ibm	_	0	0
VLAN	AREHor	ps STEHops	Backup	CRF						
802	0	0	off							
1003		7	off							
Swite	ch#									

This example shows how to display the VLAN name, status, and associated ports only:

Switch# show vlan brief

VLAN	Name	Status	Ports
1	default	active	Fa5/9
2	VLAN0002	active	Fa5/9
3	VLAN0003	active	Fa5/9
4	VLAN0004	active	Fa5/9
5	VLAN0005	active	Fa5/9
10	VLAN0010	active	Fa5/9
•			
999	VLAN0999	active	Fa5/9
1002	fddi-default	active	Fa5/9
1003	trcrf-default	active	Fa5/9
1004	fddinet-default	active	Fa5/9
1005	trbrf-default	active	Fa5/9
Swit	ch#		

This example shows how to display the VLAN parameters for VLAN 3 only:

Switch# show vlan id 3

VLAN	Name				Stat	tus	Ports				
3	VLAN0	003			acti	ive	Fa5/9				
VLAN	Туре	SAID	MTU	Parent	RingNo	Bridge	No Stp	BrdgMode	Trans1	Trans2	
3	enet	100003	1500	-	-	-	-	-	303	0	

Table 2-23 describes the fields in the **show vlan** command output.

Table 2-23 show vlan Command Output Fields

Field	Description				
VLAN	VLAN number.				
Name	Name, if configured, of the VLAN.				
Status	Status of the VLAN (active or suspend).				
Ports	Ports that belong to the VLAN.				
Туре	Media type of the VLAN.				
SAID	Security Association Identifier value for the VLAN.				
MTU	Maximum transmission unit size for the VLAN.				
Parent	Parent VLAN, if one exists.				
RingNo	Ring number for the VLAN, if applicable.				
BrdgNo	Bridge number for the VLAN, if applicable.				
Stp	Spanning Tree Protocol type used on the VLAN.				

Related Commands

vlan database vlan (VLAN Database mode)

vtp (global configuration mode)

show vlan access-map

To display the contents of a VLAN access map, use the show vlan access-map command.

show vlan access-map [map-name]

•		_	_							
61	m	tax	, II	0	er	rı	n	tı	n	n
U	,,,	ιaz	L	, ,	Ju		N	u	u	ш

map-name (Optional) Name of the VLAN access ma
--

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(12c)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This command shows how to display the contents of a VLAN access map:

Switch# show vlan access-map mordred

Vlan access-map "mordred" 1
match: ip address 13
action: forward capture

Switch#

Related Commands

vlan access-map

show vlan counters

To display the software-cached counter values, use the **show vlan counters** command.

show vlan [id vlanid] counters

Syntax Description

id vlanid	(Optional)	Displays th	he software-cached	counter values	for a specific	VLAN.
-----------	------------	-------------	--------------------	----------------	----------------	-------

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switches.

Usage Guidelines

If you enter the **show vlan counters** command without specifying the VLAN ID, the software-cached counter values for all VLANs are displayed.

Examples

This example shows how to display the software-cached counter values for a specific VLAN:

Switch# show vlan counters

* Multicast counters include broadcast packets

Vlan Id	:	1
L2 Unicast Packets	:	0
L2 Unicast Octets	:	0
L3 Input Unicast Packets	:	0
L3 Input Unicast Octets	:	0
L3 Output Unicast Packets	:	0
L3 Output Unicast Octets	:	0
L3 Output Multicast Packets	:	0
L3 Output Multicast Octets	:	0
L3 Input Multicast Packets	:	0
L3 Input Multicast Octets	:	0
L2 Multicast Packets	:	1
L2 Multicast Octets	:	94
Switch>		

Related Commands

clear vlan counters

show vlan dot1q tag native

To display all the ports on the switch that are eligible for native VLAN tagging as well as their current native VLAN tagging status, use the **show vlan dot1q tag native** command.

show vlan dot1q tag native

Syntax Description

This command has no arguments or keywords.

Command Modes

User EXEC

Command History

Release	Modification
12.1(18)EW	This command was introduced on the Catalyst 4500 series switch.

Examples

This is an example of output from the show vlan dot1q tag native command:

Switch# show vlan dot1q tag native

dot1q native vlan tagging is disabled globally

Per Port Native Vlan Tagging State

Port	Operational	Native VLAN		
	Mode	Tagging State		
f3/2	trunk	enabled		
f3/16	PVLAN trunk	disabled		
f3/16	trunk	enabled		

Related Commands

switchport mode

vlan (global configuration) (refer to Cisco IOS documentation)vlan (VLAN configuration) (refer to Cisco IOS documentation)

show vlan internal usage

Use the show vlan internal usage command to display information about the internal VLAN allocation.

show vlan [id vlan-id] internal usage

Syntax Description

id vlan-id	(Optional) Displays internal VLAN allocation information for the specified VLAN;
	valid values are from 1 to 4094.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(19)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display information about the current internal VLAN allocation:

Switch# show vlan internal usage

This example shows how to display information about the internal VLAN allocation for a specific VLAN:

Switch# show vlan id 1030 internal usage

VLAN Usage
---1030 GigabitEthernet1/2

Related Commands

vlan internal allocation policy

show vlan mtu

To display the minimum and maximum transmission unit (MTU) sizes of each VLAN, use the **show vlan mtu** command.

show vlan mtu

Syntax Description

This command has no arguments or keywords

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Usage Guidelines

The MTU_Mismatch column in the command output indicates whether all the ports in the VLAN have the same MTU. When "yes" is displayed in the MTU_Mismatch column, it means that the VLAN has a port with different MTUs, and packets might be dropped that are switched from a port with a larger MTU to a port with a smaller MTU. If the VLAN does not have an SVI, the hyphen (-) symbol is displayed in the SVI_MTU column.

For a VLAN, if the MTU-Mismatch column displays yes, the names of the port with the MinMTU and the port with the MaxMTU are displayed. For a VLAN, if the SVI_MTU is bigger than the MinMTU, "TooBig" is displayed after the SVI_MTU.

Examples

This is an example of output from the **show vlan mtu** command:

Switch# show vlan mtu

VLAN SVI_MTU	MINMIO (DOLC)	MaxMTU(port)	MTU_Mismatch
1. 1.00	1500	1500	
1 1500 Switch>	1500	1500	No

Related Commands

mtu

show vlan private-vlan

To display private VLAN information, use the show vlan private-vlan command.

show vlan private-vlan [type]

Syntax Description

type	(Optional) Displays the private VLAN type; valid types are isolated, primary,
	community, nonoperational, and normal.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.
12.2(20)EW	Support for community VLAN was added.

Usage Guidelines

When the **show vlan private-vlan type** command displays a VLAN type as normal, it indicates that a regular VLAN has been used in the private VLAN configuration. When normal is displayed, this indicates that two VLANs have been associated before the type was set, and the private VLAN is not operational. This information is useful for debugging purposes.

Examples

This example shows how to display information about all currently configured private VLANs:

Switch# show vlan private-vlan

Primary	Secondary	Type	Ports
2	301	community	Fa5/3, Fa5/25
2	302	community	
	10	community	
100	101	isolated	
150	151	non-operational	
	202	community	
	303	community	
401	402	non-operational	
Switch#			



A blank Primary value indicates that no association exists.

This example shows how to display information about all currently configured private VLAN types:

Switch# show vlan private-vlan type

Table 2-24 describes the fields in the show vlan private-vlan command output.

Table 2-24 show vlan private-vlan Command Output Fields

Field	Description		
Primary	Number of the primary VLAN.		
Secondary	Number of the secondary VLAN.		
Secondary-Type	Secondary VLAN type is isolated or community.		
Ports	Indicates the ports within a VLAN.		
Туре	Type of VLAN; possible values are primary , isolated , community, nonoperational, or normal .		

Related Commands

private-vlan private-vlan mapping

show vlan remote-span

To display a list of Remote SPAN (RSPAN) VLANs, use the show vlan remote-span command.

show vlan remote-span

Syntax Description

This command has no arguments or keywords.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification			
12.1(12)EW	This command was introduced on the Catalyst 4500 series switches.			

Examples

This example shows how to display a list of RSPAN VLANs:

Router# show vlan remote-span

Remote SPAN VLANs

2,20

Related Commands

remote-span

vlan (VLAN Database mode)

show vmps

To display the VLAN Query Protocol (VQP) version, reconfirmation interval, retry count, VLAN Membership Policy Server (VMPS) IP addresses, current servers, and primary servers, use the **show vmps** command.

show vmps [statistics]

Syntax Description

statistics	O	ptional)	Dis	plavs	the	client	-side	statistics.

Defaults

This command has no default settings.

Command Modes

EXEC

Command History

Release	Modification
12.1(13)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This is an example of output from the **show vmps** command:

```
Switch# show vmps

VQP Client Status:
------

VMPS VQP Version: 1

Reconfirm Interval: 60 min

Server Retry Count: 3

VMPS domain server: 172.20.50.120 (primary, current)

Reconfirmation status
------

VMPS Action: No Dynamic Port

Switch#
```

This is an example of output from the **show vmps statistics** command:

Switch# **show vmps statistics** VMPS Client Statistics

```
______
VQP Queries:
                        0
VQP Responses:
                        0
VMPS Changes:
VQP Shutdowns:
                        0
VQP Denied:
                        0
                        0
VQP Wrong Domain:
VQP Wrong Version:
                        0
VQP Insufficient Resource: 0
Switch#
```

Related Commands

vmps reconfirm (privileged EXEC)

show vtp

To display VTP statistics and domain information, use the **show vtp** command.

show vtp {counters | status}

Syntax Description

counters	Specifies the VTP statistics.
status	Specifies the VTP domain status.

Defaults

This command has no default settings.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.1(8a)EW	Support for this command was introduced on the Catalyst 4500 series switch.

Examples

This example shows how to display the VTP statistics:

```
Switch# show vtp counters VTP statistics:
```

```
Summary advertisements received : 1
Subset advertisements received : 1
Request advertisements received : 0
Summary advertisements transmitted : 31
Subset advertisements transmitted : 1
Request advertisements transmitted : 0
Number of config revision errors : 0
Number of config digest errors : 0
Number of V1 summary errors : 0
```

VTP pruning statistics:

Trunk	Join Transmitted Jo	oin Received	Summary advts received from non-pruning-capable device
Fa5/9 Switch#	1555	1564	0

This example shows how to display the VTP domain status:

Switch# show vtp status

```
VTP Version : 2
Configuration Revision : 250
Maximum VLANs supported locally : 1005
Number of existing VLANs : 33
VTP Operating Mode : Server
VTP Domain Name : Lab_Network
VTP Pruning Mode : Enabled
VTP V2 Mode : Enabled
VTP Traps Generation : Disabled
```

```
MD5 digest : 0xE6\ 0xF8\ 0x3E\ 0xDD\ 0xA4\ 0xF5\ 0xC2\ 0x0E Configuration last modified by 172.20.52.18 at 9-22-99 11:18:20 Local updater ID is 172.20.52.18 on interface Vl1 (lowest numbered VLAN interface found) Switch#
```

This example shows how to display only those lines in the **show vtp** output that contain the word Summary:

```
Switch# show vtp counters | include Summary

Summary advertisements received : 1

Summary advertisements transmitted : 32

Trunk Join Transmitted Join Received Summary advts received from Switch#
```

Table 2-25 describes the fields in the **show vtp** command output.

Table 2-25 show vtp Command Output Fields

Field	Description
Summary advertisements received	Total number of summary advertisements received.
Subset advertisements received	Total number of subset advertisements received.
Request advertisements received	Total number of request advertisements received.
Summary advertisements transmitted	Total number of summary advertisements transmitted.
Subset advertisements transmitted	Total number of subset advertisements transmitted.
Request advertisements transmitted	Total number of request advertisements transmitted.
Number of config revision errors	Number of config revision errors.
Number of config digest errors	Number of config revision digest errors.
Number of V1 summary errors	Number of V1 summary errors.
Trunk	Trunk port participating in VTP pruning.
Join Transmitted	Number of VTP-Pruning Joins transmitted.
Join Received	Number of VTP-Pruning Joins received.
Summary advts received from non-pruning-capable device	Number of Summary advertisements received from nonpruning-capable devices.
Number of existing VLANs	Total number of VLANs in the domain.
Configuration Revision	VTP revision number used to exchange VLAN information.
Maximum VLANs supported locally	Maximum number of VLANs allowed on the device.
Number of existing VLANs	Number of existing VLANs.
VTP Operating Mode	Indicates whether VTP is enabled or disabled.
VTP Domain Name	Name of the VTP domain.
VTP Pruning Mode	Indicates whether VTP pruning is enabled or disabled.
VTP V2 Mode	Indicates the VTP V2 mode as server, client, or transparent.
VTP Traps Generation	Indicates whether VTP trap generation mode is enabled or disabled.
MD5 digest	Checksum values.

Related Commands

vtp (global configuration mode)

vtp client

vtp domain

vtp password

vtp pruning

vtp server

vtp transparent

vtp v2-mode