



INDEX

A

aaa accounting dot1x command **2-1**
aaa authentication dot1x command **2-3**
AAA methods **2-3**
access control entries
 See ACEs
access control lists
 See ACLs
access groups
 IP **2-84**
 MAC, displaying **2-303**
 matching for QoS classification **2-154**
 access mode **2-441**
 access ports **2-441**
 ACEs **2-55, 2-181**
 ACLs
 as match criteria for QoS classes **2-154**
 deny **2-53**
 displaying **2-231**
 for non-IP protocols **2-136**
 IP **2-84**
 on Layer 2 interfaces **2-84**
 permit **2-179**
 action command **2-5**
 address aliasing **2-170**
 aggregate policers
 applying **2-186**
 creating **2-188**
 displaying **2-335**
 QoS **2-189**
 aggregate-port learner **2-175**
 allowed VLANs **2-456**

archive download-sw command **2-7**
archive tar command **2-10**
archive upload-sw command **2-13**
attaching policy maps to interfaces **2-214**
audience **xv**
authorization state of controlled port **2-61**
autonegotiation of duplex mode **2-69**

B

bandwidth, configuring for QoS **2-15**
bandwidth command **2-15**
boot (boot loader) command **A-2**
boot boothlp command **2-18**
boot config-file command **2-19**
boot enable-break command **2-20**
boot helper command **2-21**
boot helper-config file command **2-22**
booting
 Cisco IOS image **2-25**
 displaying environment variables **2-235**
 interrupting **2-20**
 manually **2-23**
boot loader
 accessing **A-1**
 booting
 Cisco IOS image **A-2**
 helper image **2-21**
directories
 creating **A-15**
 displaying a list of **A-7**
 removing **A-19**

boot loader (continued)

displaying
 available commands **A-12**
 memory heap utilization **A-14**
 version **A-26**

environment variables
 described **A-20**
 displaying settings **A-20**
 location of **A-21**
 setting **A-20**
 unsetting **A-24**

files
 copying **A-5**
 deleting **A-6**
 displaying a list of **A-7**
 displaying the contents of **A-4, A-16, A-23**
 renaming **A-17**

file system
 formatting **A-10**
 initializing flash **A-9**
 running a consistency check **A-11**

loading helper images **A-13**

prompt **A-1**

resetting the system **A-18**

boot manual command **2-23**

boot private-config-file command **2-24**

boot system command **2-25**

BPDUs filtering, for spanning tree **2-384, 2-422**

BPDUs guard, for spanning tree **2-386, 2-422**

broadcast storm control **2-431**

burst bytes, in QoS policers **2-182, 2-188**

C

cat (boot loader) command **A-4**

caution, description **xvi**

CBWFQ, configuring **2-15**

channel-group command **2-26**

channel-protocol command **2-30**

child policy maps **2-216**

class-based traffic shaping **2-229**

class-based weighted fair queuing
 See CBWFQ

class command **2-32**

class-map command **2-34**

class-map configuration mode **2-35**

class maps
 creating **2-34**
 defining the match criteria **2-155**
 displaying **2-239**
 matching in **2-34**

class of service
 See CoS

clear lacp command **2-38**

clear mac address-table command **2-39**

clear pagp command **2-40**

clear policer cpu uni counters command **2-41**

clear port-security command **2-42**

clear spanning-tree counters command **2-44**

clear spanning-tree detected-protocols command **2-45**

clear vmps statistics command **2-47**

command modes defined **1-1**

committed information rate in QoS policers **2-182, 2-188**

configuration, initial
 See also getting started guide and hardware installation guide

configuration files
 password recovery disable considerations **A-1**
 specifying the name **2-19, 2-24**

configuring multiple interfaces **2-80**

conform-action command **2-48**

control-plane policer **2-41**

control-plane policer information, displaying **2-336**

control-plane security **2-191**

control plane statistics, clearing **2-41**

- conventions
 command [xv](#)
 for examples [xvi](#)
 publication [xv](#)
 text [xv](#)
- copy (boot loader) command [A-5](#)
- CoS
 as match criteria for QoS groups [2-155](#)
 for QoS classification [2-218](#)
 setting value in policy maps [2-218](#)
- CPU ASIC statistics, displaying [2-240](#)
- CPU protection policers, displaying [C-16](#)
-
- D**
- debug dot1x command [B-2](#)
 debug etherchannel command [B-3](#)
 debug interface command [B-5](#)
 debug ip dhcp snooping command [B-4](#)
 debug ip igmp filter command [B-6](#)
 debug ip igmp max-groups command [B-7](#)
 debug ip igmp snooping command [B-8](#)
 debug lacp command [B-9](#)
 debug mac-notification command [B-10](#)
 debug matm command [B-11](#)
 debug monitor command [B-12](#)
 debug mvrdbg command [B-13](#)
 debug nvram command [B-14](#)
 debug pagp command [B-15](#)
 debug platform acl command [B-16](#)
 debug platform cpu-queues command [B-17](#)
 debug platform dot1x command [B-19](#)
 debug platform etherchannel command [B-20](#)
 debug platform forw-tcam command [B-21](#)
 debug platform ip dhcp command [B-22](#)
 debug platform ip igmp snooping command [B-23](#)
 debug platform led command [B-25](#)
 debug platform matm command [B-26](#)
 debug platform messaging application command [B-27](#)
- debug platform phy command [B-28](#)
 debug platform pm command [B-30](#)
 debug platform policer cpu uni command [B-32](#)
 debug platform port-asic command [B-33](#)
 debug platform port-security command [B-34](#)
 debug platform qos-acl-tcam command [B-35](#)
 debug platform remote-commands command [B-36](#)
 debug platform resource-manager command [B-37](#)
 debug platform snmp command [B-38](#)
 debug platform span command [B-39](#)
 debug platform supervisor-asic command [B-40](#)
 debug platform sw-bridge command [B-41](#)
 debug platform tcam command [B-42](#)
 debug platform udld command [B-44](#)
 debug platform vlan command [B-45](#)
 debug pm command [B-46](#)
 debug port-security command [B-48](#)
 debug qos-manager command [B-49](#)
 debug spanning-tree bpdu command [B-52](#)
 debug spanning-tree bpdu-opt command [B-53](#)
 debug spanning-tree command [B-50](#)
 debug spanning-tree mstp command [B-54](#)
 debug spanning-tree switch command [B-56](#)
 debug sw-vlan command [B-58](#)
 debug sw-vlan ifs command [B-60](#)
 debug sw-vlan notification command [B-61](#)
 debug udld command [B-63](#)
 debug vqpc command [B-65](#)
 default policer configuration
 NNIs [C-18](#)
 UNIs [C-17](#)
- define interface-range command [2-50](#)
 delete (boot loader) command [A-6](#)
 delete command [2-52](#)
 deny command [2-53](#)
 detect mechanism, causes [2-70](#)

DHCP snooping
 accepting untrusted packets from edge switch **2-95**
 enabling
 on a VLAN **2-101**
 option 82 **2-93, 2-95**
 trust on an interface **2-99**
 error recovery timer **2-72**
 rate limiting **2-98**

DHCP snooping binding database
 binding file, configuring **2-91**

bindings
 adding **2-89**
 deleting **2-89**
 displaying **2-283**

clearing database agent statistics **2-36**

database agent, configuring **2-91**

displaying
 binding entries **2-283**
 database agent status **2-285, 2-287**

renewing **2-210**

differentiated service code point
 See DSCP

dir (boot loader) command **A-7**

directories, deleting **2-52**

documentation, related **xvi**

document conventions **xv**

dot1x default command **2-56**

dot1x host-mode command **2-57**

dot1x initialize command **2-58**

dot1x max-req command **2-59, 2-60**

dot1x port-control command **2-61**

dot1x re-authenticate command **2-63**

dot1x reauthentication command **2-64**

dot1x system-auth-control command **2-65**

dot1x timeout command **2-66**

dropping packets, with ACL matches **2-5**

DSCP
 as match criteria for QoS groups **2-156**
 for QoS traffic marking **2-220**
 setting in policy maps **2-220**
 duplex command **2-68**
 dynamic-access ports
 configuring **2-436**
 restrictions **2-437**

Dynamic Host Configuration Protocol (DHCP)
 See DHCP snooping

E

EAP-request/identity frame
 maximum number to send **2-60**
 response time before retransmitting **2-66**

environment variables, displaying **2-235**

errdisable detect cause command **2-70**

errdisable recovery command **2-72**

error conditions, displaying **2-259**

error disable detection **2-70**

error-disabled interfaces, displaying **2-270**

EtherChannel
 assigning Ethernet interface to channel group **2-26**
 creating port-channel logical interface **2-78**
 debug EtherChannel/PAgP, display **B-3**
 debug platform-specific events, display **B-20**
 displaying **2-263**
 interface information, displaying **2-270**

LACP
 clearing channel-group information **2-38**
 debug messages, display **B-9**
 displaying **2-299**
 modes **2-26**
 port priority for hot-standby ports **2-127**
 restricting a protocol **2-30**
 system priority **2-129**

load-distribution methods **2-195**

EtherChannel (continued)

PAgP

- aggregate-port learner [2-175](#)
- clearing channel-group information [2-40](#)
- debug messages, display [B-15](#)
- displaying [2-331](#)
- error detection for [2-70](#)
- error recovery timer [2-72](#)
- learn method [2-175](#)
- modes [2-26](#)
- physical-port learner [2-175](#)
- priority of interface for transmitted traffic [2-177](#)

Ethernet controller, internal register display [2-242](#)

Ethernet statistics, collecting [2-211](#)

examples, conventions for [xvi](#)

exceed-action command [2-74](#)

extended-range VLANs

- and allowed VLAN list [2-456](#)

- configuring [2-475](#)

extended system ID for STP [2-392](#)

F

fan information, displaying [2-256](#)

files, deleting [2-52](#)

flash_init (boot loader) command [A-9](#)

flowcontrol command [2-76](#)

format (boot loader) command [A-10](#)

forwarding packets, with ACL matches [2-5](#)

forwarding results, display [C-5](#)

frame forwarding information, displaying [C-5](#)

fsck (boot loader) command [A-11](#)

G

global configuration mode [1-2, 1-3](#)

H

hardware ACL statistics [2-231](#)

help (boot loader) command [A-12](#)

host connection, port configuration [2-440](#)

host ports, private VLANs [2-443](#)

I

IEEE 802.1x

- and switchport modes [2-441](#)

- violation error recovery [2-72](#)

See also port-based authentication

IGMP filters

- applying [2-104](#)

- debug messages, display [B-6](#)

IGMP groups, setting maximum [2-106](#)

IGMP maximum groups, debugging [B-7](#)

IGMP profiles

- creating [2-108](#)

- displaying [2-290](#)

IGMP snooping

- adding ports as a static member of a group [2-123](#)

- displaying [2-291, 2-295, 2-297](#)

- enabling [2-110](#)

- enabling the configurable-leave timer [2-112](#)

- enabling the Immediate-Leave feature [2-120](#)

- flooding query count [2-118](#)

- interface topology change notification behavior [2-119](#)

- multicast table [2-293](#)

- querier [2-114](#)

- query solicitation [2-118](#)

- report suppression [2-116](#)

- switch topology change notification behavior [2-118](#)

images

- See software images

Immediate-Leave feature, MVR [2-172](#)

immediate-leave processing [2-120](#)

- initial configuration
See also getting started guide and hardware installation guide
- input policy maps
and ACL classification **2-154**
and aggregate policers **2-189**
commands not supported in **2-193**
configuration guidelines **2-193**
- interface command **2-83**
interface configuration mode **1-2, 1-4**
interface port-channel command **2-78**
interface range command **2-80**
interface-range macros **2-50**
- interfaces
assigning Ethernet interface to channel group **2-26**
configuring **2-68**
configuring multiple **2-80**
creating port-channel logical **2-78**
debug messages, display **B-5**
disabling **2-373**
displaying the MAC address table **2-315**
restarting **2-373**
- interface speed, configuring **2-429**
internal registers, displaying **2-242, 2-249**
- Internet Group Management Protocol
See IGMP
- invalid GBIC
error detection for **2-70**
error recovery timer **2-72**
- ip address command **2-86**
IP addresses, setting **2-86**
IP address matching **2-152**
- IP DHCP snooping
See DHCP snooping
- ip dhcp snooping binding command **2-89**
ip dhcp snooping command **2-88**
ip dhcp snooping database command **2-91**
ip dhcp snooping information option allow-untrusted command **2-95**
- ip dhcp snooping information option command **2-93**
ip dhcp snooping information option format remote-id command **2-97**
ip dhcp snooping limit rate command **2-98**
ip dhcp snooping trust command **2-99**
ip dhcp snooping verify command **2-100**
ip dhcp snooping vlan command **2-101**
ip dhcp snooping vlan information option format-type circuit-id string command **2-102**
ip igmp filter command **2-104**
ip igmp max-groups command **2-106**
ip igmp profile command **2-108**
ip igmp snooping command **2-110**
ip igmp snooping last-member-query-interval command **2-112**
ip igmp snooping querier command **2-114**
ip igmp snooping report-suppression command **2-116**
ip igmp snooping tcn command **2-118**
ip igmp snooping tcn flood command **2-119**
ip igmp snooping vlan immediate-leave command **2-120**
ip igmp snooping vlan mrouter command **2-121**
ip igmp snooping vlan static command **2-123**
IP multicast addresses **2-169**
IP precedence, as match criteria for QoS groups **2-158**
IP source guard, displaying dynamic binding entries **2-283**
ip ssh command **2-125**
-
- J**
- jumbo frames
See MTU
-
- L**
- LACP
See EtherChannel
- lacp port-priority command **2-127**
lacp system-priority command **2-129**

Layer 2 traceroute
 IP addresses **2-466**
 MAC addresses **2-463**
 line configuration mode **1-2, 1-4**
 Link Aggregation Control Protocol
 See EtherChannel
 link flap
 error detection for **2-70**
 error recovery timer **2-72**
 load_helper (boot loader) command **A-13**
 load-distribution methods for EtherChannel **2-195**
 logging event command **2-131**
 logging file command **2-132**
 logical interface **2-78**
 loopback error
 detection for **2-70**
 recovery timer **2-72**
 loop guard, for spanning tree **2-394, 2-398**

M

mac access-group command **2-134**
 MAC access-groups, displaying **2-303**
 MAC access list configuration mode **2-136**
 mac access-list extended command **2-136**
 MAC access lists **2-53**
 MAC addresses
 displaying
 aging time **2-309**
 all **2-307**
 dynamic **2-313**
 notification settings **2-317**
 number of addresses in a VLAN **2-311**
 per interface **2-315**
 per VLAN **2-321**
 static **2-319**
 static and dynamic entries **2-305**

MAC addresses (continued)
 dynamic
 aging time **2-138**
 deleting **2-39**
 displaying **2-313**
 enabling MAC address notification **2-139**
 matching **2-152**
 static
 adding and removing **2-141**
 displaying **2-319**
 dropping on an interface **2-142**
 tables **2-307**
 MAC address notification, debugging **B-10**
 mac address-table aging-time **2-134, 2-152**
 mac address-table aging-time command **2-138**
 mac address-table notification command **2-139**
 mac address-table static command **2-141**
 mac address-table static drop command **2-142**
 macro description command **2-146**
 macro global command **2-147**
 macro global description command **2-149**
 macro name command **2-150**
 macros
 adding a description **2-146**
 adding a global description **2-149**
 applying **2-147**
 creating **2-150**
 displaying **2-333**
 interface range **2-50, 2-80**
 specifying parameter values **2-147**
 tracing **2-147**
 manual
 audience **xv**
 purpose of **xv**
 mapping tables, QoS **2-460**

maps
 class
 creating **2-34**
 VLAN
 creating **2-478**
 defining **2-152**
 displaying **2-369**
 match access-group command **2-154**
 match cos command **2-155**
 match ip dscp command **2-156**
 match ip precedence command **2-158**
 match qos-group command **2-160**
 maximum transmission unit
 See MTU
 mdix auto command **2-162**
 memory (boot loader) command **A-14**
 mkdir (boot loader) command **A-15**
 mode, MVR **2-169**
 modes, commands **1-1**
 monitor session command **2-164**
 more (boot loader) command **A-16**
 MSTP
 displaying **2-350**
 interoperability **2-45**
 link type **2-396**
 MST region
 aborting changes **2-402**
 applying changes **2-402**
 configuration name **2-402**
 configuration revision number **2-402**
 current or pending display **2-402**
 displaying **2-350**
 MST configuration mode **2-402**
 VLANs-to-instance mapping **2-402**
 path cost **2-404**
 protocol mode **2-400**
 restart protocol migration process **2-45**

MSTP (continued)
 root port
 loop guard **2-394**
 preventing from becoming designated **2-394**
 restricting which can be root **2-394**
 root guard **2-394**
 root switch
 affects of extended system ID **2-392**
 hello-time **2-407, 2-418**
 interval between BDPU messages **2-409**
 interval between hello BPDU messages **2-407, 2-418**
 max-age **2-409**
 maximum hop count before discarding BPDU **2-411**
 port priority for selection of **2-413**
 primary or secondary **2-418**
 switch priority **2-416**
 state changes
 blocking to forwarding state **2-424**
 enabling BPDU filtering **2-384, 2-422**
 enabling BPDU guard **2-386, 2-422**
 enabling Port Fast **2-422, 2-424**
 forward-delay time **2-406**
 length of listening and learning states **2-406**
 rapid transition to forwarding **2-396**
 shutting down Port Fast-enabled ports **2-422**
 state information display **2-349**
 MTU
 configuring size **2-458**
 displaying global setting **2-357**
 multicast group address, MVR **2-172**
 multicast groups, MVR **2-170**
 multicast router learning method **2-121**
 multicast router ports, configuring **2-121**
 multicast storm control **2-431**
 multicast VLAN, MVR **2-169**
 multicast VLAN registration
 See MVR

multiple hosts on authorized port **2-57**

Multiple Spanning Tree Protocol

 See MSTP

MVR

 and address aliasing **2-170**

 configuring **2-169**

 configuring interfaces **2-172**

 debug messages, display **B-13**

 displaying **2-325**

 displaying interface information **2-327**

 members, displaying **2-329**

mvr (global configuration) command **2-169**

mvr (interface configuration) command **2-172**

mvr vlan group command **2-173**

N

native VLANs **2-456**

network node interface **2-197**

nonegotiate, speed **2-429, 2-430**

non-IP protocols

 denying **2-53**

 forwarding **2-179**

non-IP traffic access lists **2-136**

non-IP traffic forwarding

 denying **2-53**

 permitting **2-179**

normal-range VLANs **2-475**

note, description **xvi**

no vlan command **2-475**

O

output policy maps

 and QoS group classification **2-160**

 and traffic shaping **2-229**

 commands not supported in **2-193**

 configuration guidelines **2-193**

output policy maps (continued)

 priority in **2-200**

 queue limit in **2-205**

P

PAgP

 See EtherChannel

pagp learn-method command **2-175**

pagp port-priority command **2-177**

parent policy maps **2-216**

password-recovery mechanism, enabling and disabling **2-212**

permit command **2-179**

per-VLAN spanning-tree plus

 See STP

physical-port learner **2-175**

PID, displaying **2-280**

PIM-DVMRP, as multicast router learning method **2-121**

police

 multiple conform actions for a class **2-48**

 multiple exceed actions for a class **2-74**

 with priority **2-182**

 police aggregate command **2-186**

 police command **2-182**

 policer aggregate command **2-188**

 policer configuration

 default for NNIs **C-18**

 default for UNIs **C-17**

 policer cpu uni command **2-191**

 policers

 aggregate **2-186, 2-188**

 for CPU protection **2-191**

 individual **2-182**

 policy-map class, configuring multiple actions **2-48, 2-74**

 policy-map class configuration mode **2-32**

 policy-map class police configuration mode **2-48, 2-184**

 policy-map command **2-192**

 policy-map configuration mode **2-192**

- policy maps
- and CoS classification **2-155**
 - and DSCP classification **2-156**
 - and IP precedence classification **2-158**
 - and policing **2-184**
 - applying **2-214**
 - applying to an interface **2-193, 2-214, 2-226**
 - child **2-216**
 - creating **2-192**
 - displaying **2-338**
 - hierarchical **2-216**
 - parent **2-216**
 - policers
 - for a single class **2-182**
 - for multiple classes **2-186, 2-188, 2-191, 2-216**
 - setting priority **2-199**
 - setting QoS group identifier **2-224**
 - traffic classification, defining **2-32**
 - traffic marking
 - setting CoS values **2-218**
 - setting DSCP values **2-220**
 - setting IP precedence values **2-222**
- Port Aggregation Protocol
- See EtherChannel
- port-based authentication
- AAA method list **2-3**
 - debug messages, display **B-2**
 - enabling 802.1x
 - globally **2-65**
 - per interface **2-61**
 - host modes **2-57**
 - IEEE 802.1x AAA accounting methods **2-1**
 - initialize an interface **2-58**
 - manual control of authorization state **2-61**
 - multiple hosts on authorized port **2-57**
 - periodic re-authentication
 - enabling **2-64**
 - time between attempts **2-66**
- port-based authentication (continued)**
- quiet period between failed authentication exchanges **2-66**
 - re-authenticating 802.1x-enabled ports **2-63**
 - resetting configurable 802.1x parameters **2-56**
 - switch-to-authentication server retransmission time **2-66**
 - switch-to-client frame-retransmission number **2-59 to 2-60**
 - switch-to-client retransmission time **2-66**
 - port-channel load-balance command **2-195**
 - Port Fast, for spanning tree **2-424**
 - port ranges, defining **2-50**
 - ports, debugging **B-46**
 - ports, protected **2-454**
 - port security
 - aging **2-450**
 - debug messages, display **B-48**
 - enabling **2-446**
 - violation error recovery **2-72**
 - port shaping **2-230**
 - port-type command **2-197**
 - port types, MVR **2-172**
 - power information, displaying **2-256**
 - precedence
 - for QoS traffic marking **2-222**
 - setting in policy maps **2-222**
 - priority command **2-199**
 - priority queuing, QoS **2-199**
 - priority with police, QoS **2-199**
 - private-vlan command **2-202**
 - private VLANs
 - association **2-452**
 - configuring **2-202**
 - configuring ports **2-443**
 - displaying **2-364**
 - host ports **2-443**
 - mapping
 - configuring **2-452**
 - promiscuous ports **2-443**

privileged EXEC mode **1-2, 1-3**
 product identification information, displaying **2-280**
 promiscuous ports, private VLANs **2-443**
 PVST+
 See STP

Q

QoS
 aggregate policers
 applying **2-186**
 creating **2-188**
 displaying **2-335**
 class maps
 creating **2-34**
 defining the match criteria **2-155**
 displaying **2-239**
 displaying statistics for **2-338, C-24**
 policy maps
 applying an aggregate policer **2-186, 2-188, 2-191, 2-216**
 applying to an interface **2-214, 2-226**
 creating **2-192**
 defining policers **2-182**
 displaying policy maps **2-338**
 setting CoS values **2-218**
 setting DSCP values **2-220**
 setting IP precedence values **2-222**
 setting QoS group identifier **2-224**
 traffic classifications **2-32**
 table maps
 configuring **2-460**
 displaying **2-358**
 QoS groups
 as match criteria **2-160**
 for QoS traffic classification **2-224**
 setting in policy maps **2-224**

QoS match criteria
 ACLs **2-154**
 CoS value **2-155**
 DSCP value **2-156**
 precedence value **2-158**
 QoS group number **2-160**
 quality of service
 See QoS
 querytime, MVR **2-169**
 queue-limit command **2-205**

R

rapid per-VLAN spanning-tree plus
 See STP
 rapid PVST+
 See STP
 re-authenticating 802.1x-enabled ports **2-63**
 re-authentication
 periodic **2-64**
 time between attempts **2-66**
 receiver ports, MVR **2-172**
 receiving flow-control packets **2-76**
 recovery mechanism
 causes **2-72**
 display **2-237, 2-257, 2-261**
 timer interval **2-72**
 remote-span command **2-208**
 Remote Switched Port Analyzer
 See RSPAN
 rename (boot loader) command **A-17**
 renew ip dhcp snooping database command **2-210**
 reset (boot loader) command **A-18**
 rmdir (boot loader) command **A-19**
 rmon collection stats command **2-211**
 root guard, for spanning tree **2-394**

RSPAN

- configuring [2-164](#)
- displaying [2-323](#)
- filter RSPAN traffic [2-164](#)
- remote-span command [2-208](#)
- sessions
 - add interfaces to [2-164](#)
 - displaying [2-323](#)
 - start new [2-164](#)

S

SDM templates

- displaying [2-347](#)
- secure ports, limitations [2-448](#)
- sending flow-control packets [2-76](#)
- service password-recovery command [2-212](#)
- service policy (policy-map class configuration) command [2-216](#)
- service-policy interface configuration command [2-214](#)
- service-policy policy-map class configuration command [2-216](#)
- set (boot loader) command [A-20](#)
- set cos command [2-218](#)
- set dscp command [2-220](#)
- set precedence command [2-222](#)
- set qos-group command [2-224](#)
- setup command [2-226](#)

SFPs, displaying information about [2-280](#)

- shape average command [2-229](#)
- show access-lists command [2-231](#)
- show aggregate-policer command [2-358](#)
- show archive status command [2-234](#)
- show boot command [2-235](#)
- show class-map command [2-239](#)
- show controllers cpu-interface command [2-240](#)
- show controllers ethernet-controller command [2-242](#)
- show controllers team command [2-249](#)
- show controllers utilization command [2-251](#)

- show controller utilization command [2-251](#)
- show dot1x command [2-253](#)
- show env command [2-256](#)
- show errdisable detect command [2-257](#)
- show errdisable flap-values command [2-259](#)
- show errdisable recovery command [2-261](#)
- show etherchannel command [2-263](#)
- show flowcontrol command [2-266](#)
- show idprom command [2-268](#)
- show interfaces command [2-270](#)
- show interfaces counters command [2-278](#)
- show inventory command [2-280](#)
- show ip dhcp snooping binding command [2-283](#)
- show ip dhcp snooping command [2-282](#)
- show ip dhcp snooping database command [2-285, 2-287](#)
- show ip igmp profile command [2-290](#)
- show ip igmp snooping command [2-291](#)
- show ip igmp snooping command querier detail [2-297](#)
- show ip igmp snooping groups command [2-293](#)
- show ip igmp snooping mrouter command [2-295](#)
- show ip igmp snooping querier command [2-297](#)
- show ip igmp snooping querier detail command [2-297](#)
- show lacp command [2-299](#)
- show mac access-group command [2-303](#)
- show mac address-table address command [2-307](#)
- show mac address-table aging time command [2-309](#)
- show mac address-table command [2-305](#)
- show mac address-table count command [2-311](#)
- show mac address-table dynamic command [2-313](#)
- show mac address-table interface command [2-315](#)
- show mac address-table notification command [2-317](#)
- show mac address-table static command [2-319](#)
- show mac address-table vlan command [2-321](#)
- show monitor command [2-323](#)
- show mvr command [2-325](#)
- show mvr interface command [2-327](#)
- show mvr members command [2-329](#)
- show pagp command [2-331](#)
- show parser macro command [2-333](#)

- show platform acl command **C-2**
 show platform configuration command **C-3**
 show platform etherchannel command **C-4**
 show platform forward command **C-5**
 show platform igmp snooping command **C-7**
 show platform layer4op command **C-9**
 show platform mac-address-table command **C-10**
 show platform messaging command **C-11**
 show platform monitor command **C-12**
 show platform mvr table command **C-13**
 show platform pm command **C-14**
 show platform policer cpu command **C-16**
 show platform port-asic command **C-19**
 show platform port-security command **C-23**
 show platform qos command **C-24**
 show platform resource-manager command **C-27**
 show platform snmp counters command **C-29**
 show platform spanning-tree synchronization command **C-30**
 show platform stp-instance command **C-31**
 show platform tcam command **C-32**
 show platform vlan command **C-35**
 show policer aggregate command **2-335**
 show policer cpu uni command **2-336**
 show policy-map command **2-338**
 show policy-map interface output fields **2-341**
 show port security command **2-342**
 show port-type command **2-345**
 show sdm prefer command **2-347**
 show spanning-tree command **2-349**
 show storm-control command **2-355**
 show system mtu command **2-357**
 show udld command **2-360**
 show version command **2-362**
 show vlan access-map command **2-369**
 show vlan command **2-364**
 show vlan command, fields **2-366**
 show vlan filter command **2-370**
 show vmps command **2-371**
 shutdown command **2-373**
 shutdown vlan command **2-374**
 SNMP host, specifying **2-378**
 SNMP informs, enabling the sending of **2-375**
 snmp-server enable traps command **2-375**
 snmp-server host command **2-378**
 snmp trap mac-notification command **2-382**
 SNMP traps
 enabling MAC address notification trap **2-382**
 enabling the MAC address notification feature **2-139**
 enabling the sending of **2-375**
 software images
 deleting **2-52**
 downloading **2-7**
 upgrading **2-7**
 uploading **2-13**
 software version, displaying **2-362**
 source ports, MVR **2-172**
 SPAN
 configuring **2-164**
 debug messages, display **B-12**
 displaying **2-323**
 filter SPAN traffic **2-164**
 sessions
 add interfaces to **2-164**
 displaying **2-323**
 start new **2-164**
 spanning-tree bpdufilter command **2-384**
 spanning-tree bpduguard command **2-386**
 spanning-tree cost command **2-388**
 spanning-tree etherchannel command **2-390**
 spanning-tree extend system-id command **2-392**
 spanning-tree guard command **2-394**
 spanning-tree link-type command **2-396**
 spanning-tree loopguard default command **2-398**
 spanning-tree mode command **2-400**
 spanning-tree mst configuration command **2-402**
 spanning-tree mst cost command **2-404**
 spanning-tree mst forward-time command **2-406**

spanning-tree mst hello-time command **2-407**
 spanning-tree mst max-age command **2-409**
 spanning-tree mst max-hops command **2-411**
 spanning-tree mst port-priority command **2-413**
 spanning-tree mst pre-standard command **2-415**
 spanning-tree mst priority command **2-416**
 spanning-tree mst root command **2-418**
 spanning-tree portfast (global configuration) command **2-422**
 spanning-tree portfast (interface configuration) command **2-424**
 spanning-tree port-priority command **2-420**
Spanning Tree Protocol
 See STP
 spanning-tree vlan command **2-426**
 speed command **2-429**
 SSH, configuring version **2-125**
 static-access ports, configuring **2-436**
 statistics, Ethernet group **2-211**
 sticky learning, enabling **2-446**
 storm-control command **2-431**
STP
 counters, clearing **2-44**
 debug messages, display
 MSTP **B-54**
 optimized BPDUs handling **B-53**
 spanning-tree activity **B-50**
 switch shim **B-56**
 transmitted and received BPDUs **B-52**
 EtherChannel misconfiguration **2-390**
 extended system ID **2-392**
 path cost **2-388**
 protocol modes **2-400**
 root port
 loop guard **2-394**
 preventing from becoming designated **2-394**
 restricting which can be root **2-394**
 root guard **2-394**

STP (continued)
 root switch
 affects of extended system ID **2-392, 2-427**
 hello-time **2-426**
 interval between BDPU messages **2-426**
 interval between hello BPDU messages **2-426**
 max-age **2-426**
 port priority for selection of primary or secondary **2-426**
 switch priority **2-426**
 state changes
 blocking to forwarding state **2-424**
 enabling BPDU filtering **2-384, 2-422**
 enabling BPDU guard **2-386, 2-422**
 enabling Port Fast **2-422, 2-424**
 enabling timer to recover from error state **2-72**
 forward-delay time **2-426**
 length of listening and learning states **2-426**
 shutting down Port Fast-enabled ports **2-422**
 state information display **2-349**
 VLAN options **2-416, 2-426**
Switched Port Analyzer
 See SPAN
switching characteristics
 modifying **2-434**
 returning to interfaces **2-434**
 switchport access command **2-436**
 switchport block command **2-438**
 switchport command **2-434**
 switchport host command **2-440**
 switchport mode command **2-441**
 switchport mode private-vlan command **2-443**
 switchport port-security aging command **2-450**
 switchport port-security command **2-446**
 switchport private-vlan command **2-452**
 switchport protected command **2-454**
 switchports, displaying **2-270**
 switchport trunk command **2-456**

system message logging, save message to flash **2-132**
 system mtu command **2-458**

T

table-map command **2-460**
 table-map configuration mode **2-460**
 table maps
 configuring **2-460**
 displaying **2-358**
 QoS **2-460**
 tar files, creating, listing, and extracting **2-10**
 TDR, running **2-462**
 temperature information, displaying **2-256**
 test cable-diagnostics tdr command **2-462**
 traceroute mac command **2-463**
 traceroute mac ip command **2-466**
 traffic shaping, QoS **2-229**
 trunking, VLAN mode **2-441**
 trunk mode **2-441**
 trunk ports **2-441**
 type (boot loader) command **A-23**

U

UDLD
 aggressive mode **2-468, 2-470**
 debug messages, display **B-63**
 enable globally **2-468**
 enable per interface **2-470**
 error recovery timer **2-72**
 message timer **2-468**
 normal mode **2-468, 2-470**
 reset a shutdown interface **2-472**
 status **2-360**
 udld command **2-468**
 udld port command **2-470**
 udld reset command **2-472**

unicast storm control **2-431**
 UniDirectional Link Detection
 See UDLD
 uni-vlan command **2-473**
 unknown multicast traffic, preventing **2-438**
 unknown unicast traffic, preventing **2-438**
 unset (boot loader) command **A-24**
 upgrading
 software images **2-7**
 monitoring status of **2-234**
 upgrading information
 See release notes
 user EXEC mode **1-2**
 user network interface **2-197**

V

version (boot loader) command **A-26**
 vlan access-map command **2-478**
 VLAN access map configuration mode **2-478**
 VLAN access maps
 actions **2-5**
 displaying **2-369**
 vlan command **2-475**
 VLAN configuration mode
 commands **2-475**
 description **1-4**
 entering **2-475**
 summary **1-2**
 vlan filter command **2-480**
 VLAN filters, displaying **2-370**
 VLAN ID range **2-475**
 VLAN maps
 applying **2-480**
 creating **2-478**
 defining **2-152**
 displaying **2-369**
 VLAN Query Protocol
 See VQP

VLANs

- adding [2-475](#)
- configuring [2-475](#)
- debug messages, display
 - activation of [B-61](#)
 - VLAN IOS file system error tests [B-60](#)
 - VLAN manager activity [B-58](#)
- displaying configurations [2-364](#)
- extended-range [2-475](#)
- MAC addresses
 - displaying [2-321](#)
 - number of [2-311](#)
- normal-range [2-475](#)
- private [2-443](#)
 - configuring [2-202](#)
 - displaying [2-364](#)
- See also private VLANs
- restarting [2-374](#)
- saving the configuration [2-475](#)
- shutting down [2-374](#)
- suspending [2-374](#)

VMPS

- configuring servers [2-485](#)
- displaying [2-371](#)
- error recovery timer [2-72](#)
- reconfirming dynamic VLAN assignments [2-482](#)
- `vmps reconfirm` (global configuration) command [2-483](#)
- `vmps reconfirm` (privileged EXEC) command [2-482](#)
- `vmps retry` command [2-484](#)
- `vmps server` command [2-485](#)

VQP

- and dynamic-access ports [2-437](#)
- clearing client statistics [2-47](#)
- displaying information [2-371](#)
- per-server retry count [2-484](#)
- reconfirmation interval [2-483](#)
- reconfirming dynamic VLAN assignments [2-482](#)

W

- Weighted Tail Drop
 See WTD
`WTD, queue-limit` command [2-205](#)