



## INDEX

---

## A

aaa accounting dot1x command **2-1**  
aaa authentication dot1x command **2-3**  
AAA methods **2-3**  
access control entries  
    See ACEs  
access control lists  
    See ACLs  
access groups  
    IP **2-100**  
        MAC, displaying **2-387**  
        matching for QoS classification **2-198**  
access mode **2-532**  
access ports **2-532**  
ACEs **2-63, 2-233**  
ACLS  
    as match criteria for QoS classes **2-198**  
    deny **2-61**  
    displaying **2-292**  
    for non-IP protocols **2-176**  
    IP **2-100**  
    on Layer 2 interfaces **2-100**  
    permit **2-231**  
action command **2-5**  
address aliasing **2-219**  
aggregate policers  
    applying **2-238**  
    creating **2-240**  
    displaying **2-422**  
    QoS **2-241**  
aggregate-port learner **2-225**  
allowed VLANs **2-548**

archive download-sw command **2-7**  
archive tar command **2-10**  
archive upload-sw command **2-13**  
arp access-list command **2-15**  
attaching policy maps to interfaces **2-274**  
audience **xvii**  
authorization state of controlled port **2-69**  
autonegotiation of duplex mode **2-77**

---

## B

backup interfaces  
    configuring **2-526**  
    displaying **2-342**  
bandwidth, configuring for QoS **2-17**  
bandwidth command **2-17**  
boot (boot loader) command **A-2**  
boot bootlpr command **2-20**  
boot config-file command **2-21**  
boot enable-break command **2-22**  
boot helper command **2-23**  
boot helper-config file command **2-24**  
booting  
    Cisco IOS image **2-27**  
    displaying environment variables **2-297**  
    interrupting **2-22**  
    manually **2-25**

- boot loader  
 accessing [A-1](#)  
 booting  
   Cisco IOS image [A-2](#)  
   helper image [2-23](#)  
 directories  
   creating [A-15](#)  
   displaying a list of [A-7](#)  
   removing [A-19](#)  
 displaying  
   available commands [A-12](#)  
   memory heap utilization [A-14](#)  
   version [A-26](#)  
 environment variables  
   described [A-20](#)  
   displaying settings [A-20](#)  
   location of [A-21](#)  
   setting [A-20](#)  
   unsettting [A-24](#)  
 files  
   copying [A-5](#)  
   deleting [A-6](#)  
   displaying a list of [A-7](#)  
   displaying the contents of [A-4, A-16, A-23](#)  
   renaming [A-17](#)  
 file system  
   formatting [A-10](#)  
   initializing flash [A-9](#)  
   running a consistency check [A-11](#)  
 loading helper images [A-13](#)  
 prompt [A-1](#)  
 resetting the system [A-18](#)  
 boot manual command [2-25](#)  
 boot private-config-file command [2-26](#)  
 boot system command [2-27](#)  
 BPDU filtering, for spanning tree [2-472, 2-510](#)  
 BPDU guard, for spanning tree [2-474, 2-510](#)  
 broadcast storm control [2-519](#)  
 bundling characteristics, UNI [2-83](#)  
 burst bytes, in QoS policers [2-234, 2-240](#)
- 
- C**
- cat (boot loader) command [A-4](#)  
 caution, description [xviii](#)  
 CBWFQ, configuring [2-17](#)  
 CDP, enabling protocol tunneling for [2-160](#)  
 CFM [2-224](#)  
 CFM as OAM protocol [2-224](#)  
 channel-group command [2-28](#)  
 channel-protocol command [2-32](#)  
 child policy maps [2-276](#)  
 class-based traffic shaping [2-290](#)  
 class-based weighted fair queuing  
   See CBWFQ  
 class command [2-34](#)  
 class-map command [2-36](#)  
 class-map configuration mode [2-37](#)  
 class maps  
   creating [2-36](#)  
   defining the match criteria [2-199](#)  
   displaying [2-301](#)  
   matching in [2-36](#)  
 class of service  
   See CoS  
 clear ip arp inspection log command [2-38](#)  
 clear ip arp inspection statistics command [2-39](#)  
 clear ipc command [2-41](#)  
 clear ip dhcp snooping database statistics command [2-40](#)  
 clear l2protocol-tunnel counters command [2-42](#)  
 clear lacp command [2-43](#)  
 clear mac address-table command [2-44, 2-45](#)  
 clear pagp command [2-46](#)  
 clear policer cpu uni counters command [2-47](#)  
 clear port-security command [2-48](#)  
 clear spanning-tree counters command [2-50](#)  
 clear spanning-tree detected-protocols command [2-51](#)  
 clear vmps statistics command [2-53](#)

command modes defined **1-1**  
 committed information rate in QoS policers **2-234, 2-240**  
 configuration, initial  
   See also getting started guide and hardware installation guide  
 configuration files  
   password recovery disable considerations **A-1**  
   specifying the name **2-21, 2-26**  
 configuring multiple interfaces **2-96**  
 conform-action command **2-54**  
 control-plane policer **2-47**  
 control-plane policer information, displaying **2-423**  
 control-plane security **2-243**  
 control plane statistics, clearing **2-47**  
 conventions  
   command **xviii**  
   for examples **xviii**  
   publication **xviii**  
   text **xviii**  
 copy (boot loader) command **A-5**  
 CoS  
   as match criteria for QoS groups **2-199**  
   for QoS classification **2-279**  
   setting value in policy maps **2-279**  
 CoS value, assigning to Layer 2 protocol packets **2-163**  
 CPU ASIC statistics, displaying **2-302**  
 CPU protection policers, displaying **C-21**

**D**

debug backup command **B-2**  
 debug dot1x command **B-3**  
 debug etherchannel command **B-4**  
 debug interface command **B-10**  
 debug ip dhcp snooping command **B-8**  
 debug ip igmp filter command **B-11**  
 debug ip igmp max-groups command **B-12**  
 debug ip igmp snooping command **B-13**  
 debug ip verify source packet command **B-9**

debug lacp command **B-14**  
 debug mac-notification command **B-15**  
 debug matm command **B-16**  
 debug matm move update command **B-17**  
 debug monitor command **B-18**  
 debug mvrdbg command **B-19**  
 debug nvram command **B-20**  
 debug pagp command **B-21**  
 debug platform acl command **B-22**  
 debug platform backup interface command **B-24**  
 debug platform cfm command **B-23**  
 debug platform cpu-queues command **B-25**  
 debug platform dot1x command **B-27**  
 debug platform etherchannel command **B-28**  
 debug platform forw-tcam command **B-29**  
 debug platform ip arp inspection command **B-30**  
 debug platform ipc command **B-38**  
 debug platform ip dhcp command **B-31**  
 debug platform ip igmp snooping command **B-32**  
 debug platform ip multicast command **B-34**  
 debug platform led command **B-39**  
 debug platform matm command **B-40**  
 debug platform messaging application command **B-41**  
 debug platform phy command **B-42**  
 debug platform pm command **B-44**  
 debug platform policer cpu uni command **B-46**  
 debug platform port-asic command **B-47**  
 debug platform port-security command **B-48**  
 debug platform qos-acl-tcam command **B-49**  
 debug platform remote-commands command **B-50**  
 debug platform resource-manager command **B-51**  
 debug platform snmp command **B-52**  
 debug platform span command **B-53**  
 debug platform supervisor-asic command **B-54**  
 debug platform sw-bridge command **B-55**  
 debug platform tcam command **B-56**  
 debug platform udld command **B-58**  
 debug platform vlan command **B-59**  
 debug pm command **B-60**

- debug port-security command **B-62**  
 debug qos-manager command **B-63**  
 debug spanning-tree bpdu command **B-66**  
 debug spanning-tree bpdu-opt command **B-67**  
 debug spanning-tree command **B-64**  
 debug spanning-tree mstp command **B-68**  
 debug spanning-tree switch command **B-70**  
 debug sw-vlan command **B-72**  
 debug sw-vlan ifs command **B-74**  
 debug sw-vlan notification command **B-75**  
 debug udld command **B-77**  
 debug vqpc command **B-79**  
 default  
 policer configuration  
 NNIs **C-23**  
 UNIs **C-22**  
 define interface-range command **2-56**  
 delete (boot loader) command **A-6**  
 delete command **2-58**  
 deny (ARP access-list configuration) command **2-59**  
 deny command **2-61**  
 detect mechanism, causes **2-78**  
 DHCP snooping  
 accepting untrusted packets from edge switch **2-125**  
 enabling  
 on a VLAN **2-131**  
 option 82 **2-123, 2-125**  
 trust on an interface **2-129**  
 error recovery timer **2-80**  
 rate limiting **2-128**  
 DHCP snooping binding database  
 binding file, configuring **2-121**  
 bindings  
 adding **2-119**  
 deleting **2-119**  
 displaying **2-358**  
 clearing database agent statistics **2-40**
- DHCP snooping binding database (continued)**  
 database agent, configuring **2-121**  
 displaying  
 binding entries **2-358**  
 database agent status **2-360**  
 renewing **2-266**  
 differentiated service code point  
 See DSCP  
 dir (boot loader) command **A-7**  
 directories, deleting **2-58**  
 documentation, related **xviii**  
 document conventions **xviii**  
 domains, CFM **2-224**  
 dot1x default command **2-64**  
 dot1x host-mode command **2-65**  
 dot1x initialize command **2-66**  
 dot1x max-req command **2-67, 2-68**  
 dot1x port-control command **2-69**  
 dot1x re-authenticate command **2-71**  
 dot1x reauthentication command **2-72**  
 dot1x system-auth-control command **2-73**  
 dot1x timeout command **2-74**  
 dropping packets, with ACL matches **2-5**  
 drop threshold, Layer 2 protocol tunneling **2-160**  
 DSCP  
 as match criteria for QoS groups **2-200, 2-206**  
 for QoS traffic marking **2-281**  
 setting in policy maps **2-281**  
 dual-purpose uplink ports  
 selecting the type **2-211**  
 duplex command **2-76**  
 dynamic-access ports  
 configuring **2-524**  
 restrictions **2-525**

dynamic ARP inspection  
 ARP ACLs  
   apply to a VLAN **2-105**  
   define **2-15**  
   deny packets **2-59**  
   display **2-296**  
   permit packets **2-229**  
 clear  
   log buffer **2-38**  
   statistics **2-39**  
 display  
   ARP ACLs **2-296**  
   configuration and operating state **2-354**  
   log buffer **2-354**  
   statistics **2-354**  
   trust state and rate limit **2-354**  
 enable per VLAN **2-115**  
 error detection for **2-78**  
 error recovery timer **2-80**  
 log buffer  
   clear **2-38**  
   configure **2-109**  
   display **2-354**  
 rate-limit incoming ARP packets **2-107**  
 statistics  
   clear **2-39**  
   display **2-354**  
 trusted interface state **2-111**  
 type of packet logged **2-116**  
 validation checks **2-113**  
 Dynamic Host Configuration Protocol (DHCP)  
   See DHCP snooping

---

**E**

EAP-request/identity frame  
 maximum number to send **2-68**  
 response time before retransmitting **2-74**  
 E-LMI mapping **2-83**  
 environment variables, displaying **2-297**  
 errdisable detect cause command **2-78**  
 errdisable recovery command **2-80**  
 error conditions, displaying **2-325**  
 error disable detection **2-78**  
 error-disabled interfaces, displaying **2-342**  
 EtherChannel  
   assigning Ethernet interface to channel group **2-28**  
   creating port-channel logical interface **2-94**  
   debug EtherChannel/PAgP, display **B-4**  
   debug platform-specific events, display **B-28**  
   displaying **2-329**  
   enabling Layer 2 protocol tunneling for  
     LACP **2-161**  
     PAgP **2-161**  
     UDLD **2-161**  
   interface information, displaying **2-342**  
   LACP  
     clearing channel-group information **2-43**  
     debug messages, display **B-14**  
     displaying **2-381**  
     modes **2-28**  
     port priority for hot-standby ports **2-164**  
     restricting a protocol **2-32**  
     system priority **2-166**  
   load-distribution methods **2-247**  
   PAgP  
     aggregate-port learner **2-225**  
     clearing channel-group information **2-46**  
     debug messages, display **B-21**  
     displaying **2-418**  
     error detection for **2-78**  
     error recovery timer **2-80**  
     learn method **2-225**  
     modes **2-28**  
     physical-port learner **2-225**  
     priority of interface for transmitted traffic **2-227**  
   Ethernet controller, internal register display **2-304**  
   ethernet evc command **2-82**

ethernet lmi ce-vlan map command [2-83, 2-85](#)

Ethernet Local Management Interface

See E-LMI

Ethernet service

debugging [B-6](#)

displaying [2-332](#)

Ethernet service instance [2-270](#)

Ethernet service interfaces [2-336](#)

Ethernet statistics, collecting [2-267](#)

Ethernet UNI configuration [2-87](#)

ethernet uni id command [2-89](#)

Ethernet virtual connections

See EVCs

EVC configuration mode [2-82](#)

EVCs [2-82](#)

and VLANs [2-87](#)

service instances [2-270](#)

UNI counts [2-569](#)

EVC service

point-to-multipoint [2-569](#)

point-to-point [2-569](#)

examples, conventions for [xviii](#)

exceed-action command [2-90](#)

extended-range VLANs

and allowed VLAN list [2-548](#)

configuring [2-573](#)

extended system ID for STP [2-480](#)

## F

fan information, displaying [2-320](#)

files, deleting [2-58](#)

flash\_init (boot loader) command [A-9](#)

Flex Links

configuring [2-526](#)

displaying [2-342](#)

flowcontrol command [2-92](#)

format (boot loader) command [A-10](#)

forwarding packets, with ACL matches [2-5](#)

forwarding results, display [C-6](#)

frame forwarding information, displaying [C-6](#)

fsck (boot loader) command [A-11](#)

## G

global configuration mode [1-2, 1-3](#)

## H

hardware ACL statistics [2-292](#)

help (boot loader) command [A-12](#)

host connection, port configuration [2-531](#)

host ports, private VLANs [2-535](#)

## I

IEEE 802.1ag Connectivity Fault Management

See CFM

IEEE 802.1Q trunk ports and native VLANs [2-578](#)

IEEE 802.1Q tunnel ports

configuring [2-532](#)

displaying [2-315](#)

limitations [2-533](#)

IEEE 802.1x

and switchport modes [2-533](#)

violation error recovery [2-80](#)

See also port-based authentication

IGMP filters

applying [2-134](#)

debug messages, display [B-11](#)

IGMP groups, setting maximum [2-135](#)

IGMP maximum groups, debugging [B-12](#)

IGMP profiles

creating [2-137](#)

displaying [2-362](#)

- IGMP snooping  
 adding ports as a static member of a group **2-152**  
 displaying **2-363, 2-367, 2-369**  
 enabling **2-139**  
 enabling the configurable-leave timer **2-141**  
 enabling the Immediate-Leave feature **2-149**  
 flooding query count **2-147**  
 interface topology change notification behavior **2-148**  
 multicast table **2-365**  
 querier **2-143**  
 query solicitation **2-147**  
 report suppression **2-145**  
 switch topology change notification behavior **2-147**
- images  
 See software images
- Immediate-Leave feature, MVR **2-221**
- immediate-leave processing **2-149**
- initial configuration  
 See also getting started guide and hardware installation guide
- input policy maps  
 and ACL classification **2-198**  
 and aggregate policers **2-241**  
 commands not supported in **2-245**  
 configuration guidelines **2-245**
- interface command **2-98**
- interface configuration mode **1-2, 1-4**
- interface port-channel command **2-94**
- interface range command **2-96**
- interface-range macros **2-56**
- interfaces  
 assigning Ethernet interface to channel group **2-28**  
 configuring **2-76**  
 configuring multiple **2-96**  
 creating port-channel logical **2-94**  
 debug messages, display **B-10**  
 disabling **2-461**  
 displaying the MAC address table **2-399**  
 restarting **2-461**
- interface speed, configuring **2-517**
- internal registers, displaying **2-304, 2-311**
- Internet Group Management Protocol  
 See IGMP
- invalid GBIC  
 error detection for **2-78**  
 error recovery timer **2-80**
- ip address command **2-103**
- IP addresses, setting **2-103**
- IP address matching **2-196**
- ip arp inspection filter vlan command **2-105**
- ip arp inspection limit command **2-107**
- ip arp inspection log-buffer command **2-109**
- ip arp inspection trust command **2-111**
- ip arp inspection validate command **2-113**
- ip arp inspection vlan command **2-115**
- ip arp inspection vlan logging command **2-116**
- IP DHCP snooping  
 See DHCP snooping
- ip dhcp snooping binding command **2-119**
- ip dhcp snooping command **2-118**
- ip dhcp snooping database command **2-121**
- ip dhcp snooping information option allow-untrusted command **2-125**
- ip dhcp snooping information option command **2-123**
- ip dhcp snooping information option format remote-id command **2-127**
- ip dhcp snooping limit rate command **2-128**
- ip dhcp snooping trust command **2-129**
- ip dhcp snooping verify command **2-130**
- ip dhcp snooping vlan command **2-131**
- ip dhcp snooping vlan information option format-type circuit-id string command **2-132**
- ip igmp filter command **2-134**
- ip igmp max-groups command **2-135**
- ip igmp profile command **2-137**
- ip igmp snooping command **2-139**
- ip igmp snooping last-member-query-interval command **2-141**
- ip igmp snooping querier command **2-143**

- ip igmp snooping report-suppression command **2-145**  
 ip igmp snooping tcn command **2-147**  
 ip igmp snooping tcn flood command **2-148**  
 ip igmp snooping vlan immediate-leave command **2-149**  
 ip igmp snooping vlan mrouter command **2-150**  
 ip igmp snooping vlan static command **2-152**  
 IP multicast addresses **2-218**  
 IP precedence, as match criteria for QoS groups **2-202**  
 ip source binding command **2-154**  
 IP source guard  
   disabling **2-158**  
   displaying  
     binding entries **2-371**  
     configuration **2-373**  
   enabling **2-158**  
   static IP source bindings **2-154**  
 IP source guard, displaying  
   dynamic binding entries **2-358**  
 ip ssh command **2-156**  
 ip verify source command **2-158**

**J**

- jumbo frames  
 See MTU

**L**

- l2protocol-tunnel command **2-160**  
 l2protocol-tunnel cos command **2-163**  
 LACP  
   See EtherChannel  
 lacp port-priority command **2-164**  
 lacp system-priority command **2-166**  
 Layer 2 mode, enabling **2-522**  
 Layer 2 protocol ports, displaying **2-379**

- Layer 2 protocol-tunnel  
   error detection for **2-78**  
   error recovery timer **2-80**  
 Layer 2 protocol tunnel counters **2-42**  
 Layer 2 protocol tunneling error recovery **2-161**  
 Layer 2 traceroute  
   IP addresses **2-562**  
   MAC addresses **2-559**  
 Layer 3 mode, enabling **2-522**  
 line configuration mode **1-2, 1-4**  
 Link Aggregation Control Protocol  
   See EtherChannel  
 link flap  
   error detection for **2-78**  
   error recovery timer **2-80**  
 link state group command **2-168**  
 link state track command **2-170**  
 load\_helper (boot loader) command **A-13**  
 load-distribution methods for EtherChannel **2-247**  
 logging event command **2-171**  
 logging file command **2-172**  
 logical interface **2-94**  
 loopback error  
   detection for **2-78**  
   recovery timer **2-80**  
 loop guard, for spanning tree **2-482, 2-486**

**M**

- mac access-group command **2-174**  
 MAC access-groups, displaying **2-387**  
 MAC access list configuration mode **2-176**  
 mac access-list extended command **2-176**  
 MAC access lists **2-61**

- MAC addresses
- disabling MAC address learning per VLAN **2-179**
  - displaying
    - aging time **2-393**
    - all **2-391**
    - dynamic **2-397**
    - MAC address-table move updates **2-402**
    - notification settings **2-401, 2-404**
    - number of addresses in a VLAN **2-395**
    - per interface **2-399**
    - per VLAN **2-408**
    - static **2-406**
    - static and dynamic entries **2-389**
  - dynamic
    - aging time **2-178**
    - deleting **2-44**
    - displaying **2-397**
  - enabling MAC address notification **2-183**
  - enabling MAC address-table move update **2-181**
  - matching **2-196**
  - static
    - adding and removing **2-185**
    - displaying **2-406**
    - dropping on an interface **2-186**
  - tables **2-391**
- MAC address notification, debugging **B-15**
- mac address-table aging-time **2-174, 2-196**
- mac address-table aging-time command **2-178**
- mac address-table learning command **2-179**
- mac address-table move update command **2-181**
- mac address-table notification command **2-183**
- mac address-table static command **2-185**
- mac address-table static drop command **2-186**
- macro description command **2-190**
- macro global command **2-191**
- macro global description command **2-193**
- macro name command **2-194**
- macros
- adding a description **2-190**
  - adding a global description **2-193**
  - applying **2-191**
  - creating **2-194**
  - displaying **2-420**
  - interface range **2-56, 2-96**
  - specifying parameter values **2-191**
  - tracing **2-191**
- maintenance end points **2-569**
- manual
- audience **xvii**
  - purpose of **xvii**
- mapping tables, QoS **2-555**
- maps
- class
    - creating **2-36**
- VLAN
- creating **2-576**
  - defining **2-196**
  - displaying **2-456**
- match access-group command **2-198**
- match cos command **2-199**
- match ip dscp command **2-200**
- match ip precedence command **2-202**
- match qos-group command **2-204**
- match vlan command **2-206**
- maximum transmission unit
- See MTU
- mdix auto command **2-209**
- media-type command **2-211**
- memory (boot loader) command **A-14**
- mkdir (boot loader) command **A-15**
- mode, MVR **2-218**
- modes, commands **1-1**
- monitor session command **2-213**
- more (boot loader) command **A-16**

## MSTP

displaying [2-437](#)  
 interoperability [2-51](#)  
 link type [2-484](#)  
 MST region  
   aborting changes [2-490](#)  
   applying changes [2-490](#)  
   configuration name [2-490](#)  
   configuration revision number [2-490](#)  
   current or pending display [2-490](#)  
   displaying [2-437](#)  
   MST configuration mode [2-490](#)  
   VLANs-to-instance mapping [2-490](#)  
 path cost [2-492](#)  
 protocol mode [2-488](#)  
 restart protocol migration process [2-51](#)  
 root port  
   loop guard [2-482](#)  
   preventing from becoming designated [2-482](#)  
   restricting which can be root [2-482](#)  
 root guard [2-482](#)  
 root switch  
   affects of extended system ID [2-480](#)  
   hello-time [2-495, 2-506](#)  
   interval between BPDU messages [2-497](#)  
   interval between hello BPDU messages [2-495, 2-506](#)  
   max-age [2-497](#)  
   maximum hop count before discarding BPDU [2-499](#)  
   port priority for selection of [2-501](#)  
   primary or secondary [2-506](#)  
   switch priority [2-504](#)

## MSTP (continued)

state changes  
   blocking to forwarding state [2-512](#)  
   enabling BPDU filtering [2-472, 2-510](#)  
   enabling BPDU guard [2-474, 2-510](#)  
   enabling Port Fast [2-510, 2-512](#)  
   forward-delay time [2-494](#)  
   length of listening and learning states [2-494](#)  
   rapid transition to forwarding [2-484](#)  
   shutting down Port Fast-enabled ports [2-510](#)  
   state information display [2-436](#)  
 MTU  
   configuring size [2-552](#)  
   displaying global setting [2-444](#)  
 multicast group address, MVR [2-221](#)  
 multicast groups, MVR [2-219](#)  
 multicast router learning method [2-150](#)  
 multicast router ports, configuring [2-150](#)  
 multicast storm control [2-519](#)  
 multicast VLAN, MVR [2-218](#)  
 multicast VLAN registration  
   See MVR  
 multiple hosts on authorized port [2-65](#)  
 Multiple Spanning Tree Protocol  
   See MSTP  
 multiplexing, UNI [2-87](#)  
 MVR  
   and address aliasing [2-219](#)  
   configuring [2-218](#)  
   configuring interfaces [2-221](#)  
   debug messages, display [B-19](#)  
   displaying [2-412](#)  
   displaying interface information [2-414](#)  
   members, displaying [2-416](#)  
   mvr (global configuration) command [2-218](#)  
   mvr (interface configuration) command [2-221](#)  
   mvr vlan group command [2-222](#)

**N**

native VLANs **2-548**  
 native VLAN tagging **2-578**  
 network node interface **2-249**  
 nonegotiate, speed **2-517, 2-518**  
 non-IP protocols  
   denying **2-61**  
   forwarding **2-231**  
 non-IP traffic access lists **2-176**  
 non-IP traffic forwarding  
   denying **2-61**  
   permitting **2-231**  
 normal-range VLANs **2-573**  
 note, description **xviii**  
 no vlan command **2-573**

**O**

OAM protocol **2-224**  
 oam protocol cfm svlan command **2-224**  
 operation, administration, and maintenance protocol  
   See OAM  
 output policy maps  
   and QoS group classification **2-204**  
   and traffic shaping **2-290**  
   commands not supported in **2-245**  
   configuration guidelines **2-245**  
   priority in **2-254**  
   queue limit in **2-261**

**P**

PAgP  
   See EtherChannel  
 pagp learn-method command **2-225**  
 pagp port-priority command **2-227**  
 parent policy maps **2-277**

password-recovery mechanism, enabling and disabling **2-272**  
 permit (ARP access-list configuration) command **2-229**  
 permit command **2-231**  
 per-VLAN spanning-tree plus  
   See STP  
 physical-port learner **2-225**  
 PID, displaying **2-352**  
 PIM-DVMRP, as multicast router learning method **2-150**  
 police  
   multiple conform actions for a class **2-54**  
   multiple exceed actions for a class **2-90**  
   with priority **2-234**  
 police aggregate command **2-238**  
 police command **2-234**  
 policer aggregate command **2-240**  
 policer configuration  
   default for NNIs **C-23**  
   default for UNIs **C-22**  
 policer cpu uni command **2-243**  
 policers  
   aggregate **2-238, 2-240**  
   for CPU protection **2-243**  
   individual **2-234**  
 policy-map class, configuring multiple actions **2-54, 2-90**  
 policy-map class configuration mode **2-34**  
 policy-map class police configuration mode **2-54, 2-236**  
 policy-map command **2-244**  
 policy-map configuration mode **2-244**  
 policy maps  
   and CoS classification **2-199**  
   and DSCP classification **2-200**  
   and IP precedence classification **2-202**  
   and policing **2-236**  
   applying **2-274**  
   applying to an interface **2-245, 2-274, 2-287**  
   child **2-276**  
   creating **2-244**  
   displaying **2-425**

**policy maps (continued)**

hierarchical **2-276**  
 parent **2-277**  
 policers  
   for a single class **2-234**  
   for multiple classes **2-238, 2-240, 2-243, 2-276**  
 setting priority **2-253**  
 setting QoS group identifier **2-285**  
 traffic classification, defining **2-34**  
 traffic marking  
   setting CoS values **2-279**  
   setting DSCP values **2-281**  
   setting IP precedence values **2-283**  
**Port Aggregation Protocol**  
 See EtherChannel  
 port-based authentication  
   AAA method list **2-3**  
   debug messages, display **B-3**  
   enabling 802.1x  
     globally **2-73**  
     per interface **2-69**  
   host modes **2-65**  
   IEEE 802.1x AAA accounting methods **2-1**  
   initialize an interface **2-66**  
   manual control of authorization state **2-69**  
   multiple hosts on authorized port **2-65**  
   periodic re-authentication  
     enabling **2-72**  
     time between attempts **2-74**  
   quiet period between failed authentication exchanges **2-74**  
   re-authenticating 802.1x-enabled ports **2-71**  
   resetting configurable 802.1x parameters **2-64**  
   switch-to-authentication server retransmission time **2-74**  
   switch-to-client frame-retransmission number **2-67 to 2-68**  
   switch-to-client retransmission time **2-74**  
   port-channel load-balance command **2-247**  
**Port Fast**, for spanning tree **2-512**

port ranges, defining **2-56**  
 ports, debugging **B-60**  
 ports, protected **2-546**  
 port security  
   aging **2-542**  
   debug messages, display **B-62**  
   enabling **2-538**  
   violation error recovery **2-80**  
 port shaping **2-291**  
 port-type command **2-249**  
 port types, MVR **2-221**  
 power information, displaying **2-320**  
 power-supply dual command **2-251**  
 precedence  
   for QoS traffic marking **2-283**  
   setting in policy maps **2-283**  
 priority command **2-253**  
 priority queuing, QoS **2-253**  
 priority with police, QoS **2-253**  
 private-vlan command **2-256**  
 private-vlan mapping command **2-259**  
 private VLANs  
   association **2-544**  
   configuring **2-256**  
   configuring ports **2-535**  
   displaying **2-451**  
   host ports **2-535**  
   mapping  
     configuring **2-544**  
     displaying **2-342**  
     promiscuous ports **2-535**  
 privileged EXEC mode **1-2, 1-3**  
 product identification information, displaying **2-352**  
 promiscuous ports, private VLANs **2-535**  
**PVST+**  
 See STP

**Q****QoS**

aggregate policers

    applying **2-238**    creating **2-240**    displaying **2-422**

class maps

    creating **2-36**    defining the match criteria **2-199**    displaying **2-301**displaying statistics for **2-425, C-29**

policy maps

    applying an aggregate policer **2-238, 2-240, 2-243, 2-276**    applying to an interface **2-274, 2-287**    creating **2-244**    defining policers **2-234**    displaying policy maps **2-425**    setting CoS values **2-279**    setting DSCP values **2-281**    setting IP precedence values **2-283**    setting QoS group identifier **2-285**    traffic classifications **2-34**

table maps

    configuring **2-555**    displaying **2-445****QoS groups**as match criteria **2-204**for QoS traffic classification **2-285**setting in policy maps **2-285****QoS match criteria**ACLs **2-198**CoS value **2-199**DSCP value **2-200, 2-206**precedence value **2-202**QoS group number **2-204****quality of service**

See QoS

querytime, MVR **2-218**queue-limit command **2-261****R**

rapid per-VLAN spanning-tree plus

See STP

rapid PVST+

See STP

re-authenticating 802.1x-enabled ports **2-71**

re-authentication

    periodic **2-72**    time between attempts **2-74**receiver ports, MVR **2-221**receiving flow-control packets **2-92**

recovery mechanism

    causes **2-80**    display **2-299, 2-323, 2-327**    timer interval **2-80**remote-span command **2-264**

Remote Switched Port Analyzer

See RSPAN

rename (boot loader) command **A-17**renew ip dhcp snooping database command **2-266**reset (boot loader) command **A-18**resource templates, displaying **2-434**rmdir (boot loader) command **A-19**rmon collection stats command **2-267**root guard, for spanning tree **2-482**

routed ports

    IP addresses on **2-104**    number supported **2-104**

RSPAN

    configuring **2-213**    displaying **2-410**    filter RSPAN traffic **2-213**    remote-span command **2-264**

**RSPAN (continued)**

sessions  
 add interfaces to **2-213**  
 displaying **2-410**  
 start new **2-213**

---

**S**

sdm prefer command **2-268**  
 SDM templates  
 allowed resources **2-269**  
 displaying **2-434**  
 secure ports, limitations **2-540**  
 sending flow-control packets **2-92**  
 service instance command **2-270**  
 service instances, displaying **2-334**  
 service password-recovery command **2-272**  
 service policy (policy-map class configuration) command **2-276**  
 service-policy interface configuration command **2-274**  
 service-policy policy-map class configuration command **2-276**  
 set (boot loader) command **A-20**  
 set cos command **2-279**  
 set dscp command **2-281**  
 set precedence command **2-283**  
 set qos-group command **2-285**  
 setup command **2-287**  
 SFPs, displaying information about **2-352**  
 shape average command **2-290**  
 show access-lists command **2-292**  
 show aggregate-policer command **2-445**  
 show archive status command **2-295**  
 show arp access-list command **2-296**  
 show boot command **2-297**  
 show class-map command **2-301**  
 show controllers cpu-interface command **2-302**  
 show controllers ethernet-controller command **2-304**  
 show controllers tcam command **2-311**

show controllers utilization command **2-313**  
 show controller utilization command **2-313**  
 show dot1q-tunnel command **2-315**  
 show dot1x command **2-317**  
 show env command **2-320**  
 show errdisable detect command **2-323**  
 show errdisable flap-values command **2-325**  
 show errdisable recovery command **2-327**  
 show etherchannel command **2-329**  
 show ethernet service evc command **2-332**  
 show ethernet service instance command **2-334**  
 show ethernet service interface command **2-336**  
 show flowcontrol command **2-338**  
 show idprom command **2-340**  
 show interfaces command **2-342**  
 show interfaces counters command **2-350**  
 show inventory command **2-352**  
 show ip arp inspection command **2-354**  
 show ipc command **2-375**  
 show ip dhcp snooping binding command **2-358**  
 show ip dhcp snooping command **2-357**  
 show ip dhcp snooping database command **2-360**  
 show ip igmp profile command **2-362**  
 show ip igmp snooping command **2-363**  
 show ip igmp snooping command querier detail **2-369**  
 show ip igmp snooping groups command **2-365**  
 show ip igmp snooping mrouter command **2-367**  
 show ip igmp snooping querier command **2-369**  
 show ip igmp snooping querier detail command **2-369**  
 show ip source binding command **2-371**  
 show ip verify source command **2-373**  
 show l2protocol-tunnel command **2-379**  
 show lacp command **2-381**  
 show link state group command **2-385**  
 show mac access-group command **2-387**  
 show mac address-table address command **2-391**  
 show mac address-table aging time command **2-393**  
 show mac address-table command **2-389**  
 show mac address-table count command **2-395**

- show mac address-table dynamic command **2-397**  
 show mac address-table interface command **2-399**  
 show mac address-table learning command **2-401**  
 show mac address-table move update command **2-402**  
 show mac address-table notification command **2-45, 2-404, B-17**  
 show mac address-table static command **2-406**  
 show mac address-table vlan command **2-408**  
 show monitor command **2-410**  
 show mvr command **2-412**  
 show mvr interface command **2-414**  
 show mvr members command **2-416**  
 show pagp command **2-418**  
 show parser macro command **2-420**  
 show platform acl command **C-2**  
 show platform cfm command **C-3**  
 show platform configuration command **C-4**  
 show platform etherchannel command **C-5**  
 show platform forward command **C-6**  
 show platform igmp snooping command **C-8**  
 show platform ipc trace command **C-13**  
 show platform ip multicast command **C-10**  
 show platform ip unicast command **C-11**  
 show platform layer4op command **C-14**  
 show platform mac-address-table command **C-15**  
 show platform messaging command **C-16**  
 show platform monitor command **C-17**  
 show platform mvr table command **C-18**  
 show platform pm command **C-19**  
 show platform policer cpu command **C-21**  
 show platform port-asic command **C-24**  
 show platform port-security command **C-28**  
 show platform qos command **C-29**  
 show platform resource-manager command **C-32**  
 show platform snmp counters command **C-34**  
 show platform spanning-tree synchronization command **C-35**  
 show platform stp-instance command **C-36**  
 show platform tcam command **C-37**  
 show platform vlan command **C-40**  
 show policer aggregate command **2-422**  
 show policer cpu uni command **2-423**  
 show policy-map command **2-425**  
 show policy-map interface output fields **2-428**  
 show port security command **2-429**  
 show port-type command **2-432**  
 show sdm prefer command **2-434**  
 show spanning-tree command **2-436**  
 show storm-control command **2-442**  
 show system mtu command **2-444**  
 show udld command **2-447**  
 show version command **2-449**  
 show vlan access-map command **2-456**  
 show vlan command **2-451**  
 show vlan command, fields **2-453**  
 show vlan filter command **2-457**  
 show vmpls command **2-458**  
 shutdown command **2-461**  
 shutdown threshold, Layer 2 protocol tunneling **2-160**  
 shutdown vlan command **2-462**  
 SNMP host, specifying **2-466**  
 SNMP informs, enabling the sending of **2-463**  
 snmp-server enable traps command **2-463**  
 snmp-server host command **2-466**  
 snmp trap mac-notification command **2-470**  
 SNMP traps  
     enabling MAC address notification trap **2-470**  
     enabling the MAC address notification feature **2-183**  
     enabling the sending of **2-463**  
 software images  
     deleting **2-58**  
     downloading **2-7**  
     upgrading **2-7**  
     uploading **2-13**  
 software version, displaying **2-449**  
 source ports, MVR **2-221**

- SPAN
- configuring **2-213**
  - debug messages, display **B-18**
  - displaying **2-410**
  - filter SPAN traffic **2-213**
  - sessions
    - add interfaces to **2-213**
    - displaying **2-410**
    - start new **2-213**
  - spanning-tree bpdufilter command **2-472**
  - spanning-tree bpduguard command **2-474**
  - spanning-tree cost command **2-476**
  - spanning-tree etherchannel command **2-478**
  - spanning-tree extend system-id command **2-480**
  - spanning-tree guard command **2-482**
  - spanning-tree link-type command **2-484**
  - spanning-tree loopguard default command **2-486**
  - spanning-tree mode command **2-488**
  - spanning-tree mst configuration command **2-490**
  - spanning-tree mst cost command **2-492**
  - spanning-tree mst forward-time command **2-494**
  - spanning-tree mst hello-time command **2-495**
  - spanning-tree mst max-age command **2-497**
  - spanning-tree mst max-hops command **2-499**
  - spanning-tree mst port-priority command **2-501**
  - spanning-tree mst pre-standard command **2-503**
  - spanning-tree mst priority command **2-504**
  - spanning-tree mst root command **2-506**
  - spanning-tree portfast (global configuration) command **2-510**
  - spanning-tree portfast (interface configuration) command **2-512**
  - spanning-tree port-priority command **2-508**
- Spanning Tree Protocol
- See STP
- spanning-tree vlan command **2-514**
- speed command **2-517**
- SSH, configuring version **2-156**
- static-access ports, configuring **2-524**
- statistics, Ethernet group **2-267**
- sticky learning, enabling **2-538**
- storm-control command **2-519**
- STP
- counters, clearing **2-50**
  - debug messages, display
    - MSTP **B-68**
    - optimized BPDUs handling **B-67**
    - spanning-tree activity **B-64**
    - switch shim **B-70**
    - transmitted and received BPDUs **B-66**
  - enabling protocol tunneling for **2-160**
  - EtherChannel misconfiguration **2-478**
  - extended system ID **2-480**
  - path cost **2-476**
  - protocol modes **2-488**
  - root port
    - loop guard **2-482**
    - preventing from becoming designated **2-482**
    - restricting which can be root **2-482**
    - root guard **2-482**
  - root switch
    - affects of extended system ID **2-480, 2-515**
    - hello-time **2-514**
    - interval between BPDU messages **2-514**
    - interval between hello BPDU messages **2-514**
    - max-age **2-514**
    - port priority for selection of **2-508**
    - primary or secondary **2-514**
    - switch priority **2-514**

**STP (continued)**

state changes  
     blocking to forwarding state **2-512**  
     enabling BPDU filtering **2-472, 2-510**  
     enabling BPDU guard **2-474, 2-510**  
     enabling Port Fast **2-510, 2-512**  
     enabling timer to recover from error state **2-80**  
     forward-delay time **2-514**  
     length of listening and learning states **2-514**  
     shutting down Port Fast-enabled ports **2-510**  
     state information display **2-436**  
     VLAN options **2-504, 2-514**  
 SVIs, creating **2-98**  
 Switched Port Analyzer  
     See SPAN  
 switching characteristics  
     modifying **2-522**  
     returning to interfaces **2-522**  
 switchport access command **2-524**  
 switchport backup interface command **2-526**  
 switchport block command **2-529**  
 switchport command **2-522**  
 switchport host command **2-531**  
 switchport mode command **2-532**  
 switchport mode private-vlan command **2-535**  
 switchport port-security aging command **2-542**  
 switchport port-security command **2-538**  
 switchport private-vlan command **2-544**  
 switchport protected command **2-546**  
 switchports, displaying **2-342**  
 switchport trunk command **2-548**  
 system env temperature threshold yellow command **2-550**  
 system message logging, save message to flash **2-172**  
 system mtu command **2-552**  
 system resource templates **2-268**

**T**

table-map command **2-555**

table-map configuration mode **2-555**  
 table maps  
     configuring **2-555**  
     displaying **2-445**  
     QoS **2-555**  
     tar files, creating, listing, and extracting **2-10**  
     TDR, running **2-557**  
     temperature information, displaying **2-320**  
     templates, system resources **2-268**  
     test cable-diagnostics tdr command **2-557**  
     traceroute mac command **2-559**  
     traceroute mac ip command **2-562**  
     traffic shaping, QoS **2-290**  
     trunking, VLAN mode **2-532**  
     trunk mode **2-532**  
     trunk ports **2-532**  
     tunnel ports, Layer 2 protocol, displaying **2-379**  
     type (boot loader) command **A-23**

**U**

UDLD  
     aggressive mode **2-564, 2-566**  
     debug messages, display **B-77**  
     enable globally **2-564**  
     enable per interface **2-566**  
     error recovery timer **2-80**  
     message timer **2-564**  
     normal mode **2-564, 2-566**  
     reset a shutdown interface **2-568**  
     status **2-447**  
     udld command **2-564**  
     udld port command **2-566**  
     udld reset command **2-568**  
 UNI  
     bundling and multiplexing **2-87**  
     Ethernet **2-87**  
     unicast storm control **2-519**  
     uni count command **2-569**

UniDirectional Link Detection  
See UDLD

UNI ID, Ethernet **2-89**

uni-vlan command **2-571**

unknown multicast traffic, preventing **2-529**

unknown unicast traffic, preventing **2-529**

unset (boot loader) command **A-24**

upgrading  
  software images **2-7**  
  monitoring status of **2-295**

upgrading information  
  See release notes

user EXEC mode **1-2**

user network interface **2-249**

VLAN Query Protocol  
  See VQP

VLANs  
  adding **2-573**  
  configuring **2-573**  
  debug messages, display  
  activation of **B-75**  
  VLAN IOS file system error tests **B-74**

  VLAN manager activity **B-72**

  displaying configurations **2-451**

  extended-range **2-573**

  MAC addresses

    displaying **2-408**

    number of **2-395**

  normal-range **2-573**

  private **2-535**

    configuring **2-256**

    displaying **2-451**

    See also private VLANs

  restarting **2-462**

  saving the configuration **2-573**

  shutting down **2-462**

  suspending **2-462**

VMPS

  configuring servers **2-585**

  displaying **2-458**

  error recovery timer **2-80**

  reconfirming dynamic VLAN assignments **2-582**

  vmps reconfirm (global configuration) command **2-583**

  vmps reconfirm (privileged EXEC) command **2-582**

  vmps retry command **2-584**

  vmps server command **2-585**

VQP

  and dynamic-access ports **2-525**

  clearing client statistics **2-53**

  displaying information **2-458**

  per-server retry count **2-584**

  reconfirmation interval **2-583**

  reconfirming dynamic VLAN assignments **2-582**

## V

version (boot loader) command **A-26**

vlan access-map command **2-576**

VLAN access map configuration mode **2-576**

VLAN access maps  
  actions **2-5**  
  displaying **2-456**

vlan command **2-573**

VLAN configuration mode  
  commands **2-573**  
  description **1-4**  
  entering **2-573**  
  summary **1-2**

vlan dot1q tag native command **2-578**

vlan filter command **2-580**

VLAN filters, displaying **2-457**

VLAN ID range **2-573**

VLAN maps  
  applying **2-580**  
  creating **2-576**  
  defining **2-196**  
  displaying **2-456**

VTP, enabling tunneling for [2-160](#)

---

**W**

Weighted Tail Drop

See WTD

WTD, queue-limit command [2-261](#)

