



CHAPTER 4

Delete Commands

First Published: October 26, 2010, OL-23878-01

This chapter contains the following commands:

- [delete account](#)
- [delete dns](#)
- [delete process](#)

delete account

delete account *account-name*

Syntax Description

<i>account-name</i>	Represents the IP address of the DNS server that you want to delete.
---------------------	--

Command Modes

Admin

Command privilege level: 4

Allowed during upgrade: No

Command History

Release	Modifications
1.2	This command was first documented.

Usage Guidelines

Use this command to delete an administrator account.

Examples

admin:**delete account admin**

delete dns

delete dns *ip-address*

Syntax Description

<i>ip-address</i>	Represents the IP address of the DNS server that you want to delete.
-------------------	--

Command Modes

Admin
Command privilege level: 1
Allowed during upgrade: No

Command History

Release	Modifications
1.2	This command was first documented.

Usage Guidelines

The system asks whether you want to continue to execute this command.



Caution

If you continue, this command causes a temporary loss of network connectivity.

Examples

```
admin:delete dns 192.0.2.0
```

delete process

delete process *process-id* [**force** | **terminate** | **crash**]

Syntax Description

<i>process-id</i>	Represents the process ID number.
-------------------	-----------------------------------

Command Modes

Admin

Command privilege level: 1

Allowed during upgrade: Yes

Options

- **force**—Tells the process to stop.
- **terminate**—Tells the operating system to terminate the process.
- **crash**—Crashes the process and produces a crash dump.

Command History

Release	Modifications
1.2	This command was first documented.

Usage Guidelines

Usage Guidelines



Note

Use the **force** option only if the command alone does not delete the process and use the **terminate** option only if **force** does not delete the process.

Examples

```
admin:delete process 192.0.2.0
```