

CHAPTER 8

Unset Commands

First Published: October 31, 2011, OL-23878-01

This chapter contains the following **unset** commands:

- [unset network dns](#)
- [unset network domain](#)

unset network dns

unset network dns options [timeout] [attempts] [rotate]

Syntax Description

timeout	Sets the wait time before the system considers a DNS query as failed to the default.
attempts	Sets the number of DNS attempts to make before failing to the default.
rotate	Sets the method for selecting a nameserver to the default. This affects how loads are distributed across nameservers.

Command Modes

Admin
Command privilege level: 1

Command History

Release	Modifications
1.2	This command was first documented.

Usage Guidelines

This command unsets DNS options.
The system asks whether you want to continue to execute this command.



If you continue, the system will temporarily lose network connectivity.

Examples

```
admin:unset network dns options 55
***  W A R N I N G  ***
This will cause the system to temporarily lose network connectivity

Continue (y/n)?y

Executed command unsuccessfully
```

unset network domain


unset network domain

Syntax Description	None
---------------------------	------

Command Modes	Admin Command privilege level: 1
----------------------	-------------------------------------

Command History	Release	Modifications
	1.8	This command was first documented.

Usage Guidelines	This command unsets the domain name. The system asks whether you want to continue to execute this command.
-------------------------	---

 Caution	If you continue, the system will restart.
---	---

Examples	admin: unset network domain Continue (y/n)?y
-----------------	--

■ unset network domain