

TANDBERG			2000-09-27	Page 1 of 1
X21 Cable for Codec			Version 1.1	D1230101
	DATE	SIGN	REVISIONS	
PREP				
TECH				
APP				

Partnumber: 111935

X21 Cable for Codec

Valid for : TANDBERG 7000/6000/2500/800

- Connector on cable at Codec end : Female 26 pin high-density DSUB
- Connector on cable at X.21-adapter end : Male 15 pin DSUB, pinout according to ISO4903 “Data Communication - 15 pin DTE/DCE interface connector and pin assignments”.
- Cable length : 3m
- Cable type : Shielded
- Connector housing : Metal, with cable shield connected to metal housing at both ends

Signal Name	Female 26pin DSUB Pin number	Male 15pin DSUB Pin number	Comments
Frame Ground	1	1	May or may not be twisted pair
Signal ground	19	8	
T(A), transmit data	11	2	Twisted pair
T(B)	12	9	
C(A), command	20	3	Twisted pair
C(B)	21	10	
R(A), receive data	13	4	Twisted pair
R(B)	14	11	
I(A), indication	22	5	Twisted pair
I(B)	23	12	
S(A), clock	15	6	Twisted pair
S(B)	16	13	
Cable Marking	NET	X21	Place text near connectors