



# Hardware and Software Interoperability Matrix

This document provides interoperability matrices for Cisco Unified Computing System components and configurations that have been tested and validated by Cisco, by Cisco partners, or both. Use this document as a reference for supported hardware and software.

This document contains the following sections:

- [Audience](#)
- [Operating System Interoperability Matrix](#)
- [VM-FEX Software Interoperability Matrix](#)
- [Converged Network Adapter Interoperability Matrix](#)
- [Network Interface Card Interoperability Matrix](#)
- [RAID Controller on Motherboard Interoperability Matrix](#)
- [UCS Storage Accelerator Interoperability Matrix](#)
- [Storage Array Interoperability Matrix](#)
- [Enterprise Backup Interoperability Matrix](#)
- [Switch Interoperability Matrix](#)
- [Related Documentation](#)
- [Obtaining Documentation and Submitting a Service Request](#)

For C-Series servers managed by UCSM, *unless otherwise indicated in this document*, the supported firmware and drivers are those listed in the 1.4(7) and 1.4(8) C-Series Compatibility guide, located at [http://www.cisco.com/en/US/products/ps10477/prod\\_technical\\_reference\\_list.html](http://www.cisco.com/en/US/products/ps10477/prod_technical_reference_list.html).

For information about compatibility with different infrastructure bundles, please refer to the Release Note for the desired infrastructure bundle release.

## Audience

This document is designed for use by Cisco TAC, sales, support engineers, professional service partners, and systems administrators responsible for the design and deployment of the Unified Computing System in the data center environment.

This document applies to the B Series Servers in Cisco Unified Computing System Release 2.1(2). The content of this document is updated on a regular basis. The current version was created on 2013-11-16.

### **Operating System Interoperability Matrix**

Table 1 lists the operating systems that the Unified Computing System B Series Servers support.

**Table 1: Operating System**

| <b>UCS Blade Server</b>                               | <b>Vendor</b> | <b>Operating System Version</b>     | <b>Notes</b> |
|---|---------------|-------------------------------------|--------------|
| B200, B250, B230, B440 M2 and B200, B22, B420 M3      | Citrix        | XenServer 6.0.2                     |              |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3      | Citrix        | XenServer 6.1                       |              |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3      | Citrix        | XenServer 6.2                       |              |
| B200, B250, B230, B440 M1 & M2 and B22, B200 M3       | Microsoft     | Windows Server 2008 SP2 x64         | 18           |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3 | Microsoft     | Windows Server 2008 R2 SP1 x64      | 18           |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3      | Microsoft     | Windows Server 2012                 | 18           |
| B230, B440 M2 and B200, B22, B420 M3                  | Oracle        | OL 6.3 64bit with UEK 2.6.39-200    | 22           |
| B230, B440 M2 and B200, B22, B420 M3                  | Oracle        | OVM 3.1.1 64bit with UEK 2.6.39-200 |              |
| B200, B250, B230, B440 M2                             | Oracle        | Solaris 10 09/10 (U9)               |              |
| B200, B250, B230, B440 M2                             | Oracle        | Solaris 10 08/11 (U10)              |              |
| B200, B250, B230, B440 M2                             | Oracle        | Solaris 10 01/13 (U11)              |              |
| B200, B22, B420 M3                                    | Oracle        | Solaris 11 10/12 (U1)               |              |

| <b>UCS Blade Server</b>                                     | <b>Vendor</b> | <b>Operating System Version</b>         | <b>Notes</b> |
|---|---------------|---|--------------|
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | Red Hat       | Red Hat Enterprise Linux 5.7 64bit      |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | Red Hat       | Red Hat Enterprise Linux 5.8 64bit      |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | Red Hat       | Red Hat Enterprise Linux 5.9 64bit      |              |
| B200, B250 M2 and B230, B440 M1 & M2 and B200, B22, B420 M3 | Red Hat       | Red Hat Enterprise Linux 6.2 64bit      |              |
| B200, B250 M2 and B230, B440 M1 & M2 and B200, B22, B420 M3 | Red Hat       | Red Hat Enterprise Linux 6.3 64bit      |              |
| B200, B250 M2 and B230, B440 M1 & M2 and B200, B22, B420 M3 | Red Hat       | Red Hat Enterprise Linux 6.4 64bit      |              |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3            | SuSE          | SUSE Linux Enterprise Server 11.2 64bit |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | VMware        | vSphere 4.1 U2                          |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | VMware        | vSphere 4.1i U2                         |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | VMware        | vSphere 4.1i U3                         |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | VMware        | vSphere 4.1i U3                         |              |
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3       | VMware        | vSphere 5.0 U1                          |              |

| <b>UCS Blade Server</b>   | <b>Vendor</b> | <b>Operating System Version</b> | <b>Notes</b> |
|---|---------------|---------------------------------|--------------|
| B200, B250, B230, B440 M1 & M2 and B200, B22, B420 M3   | VMware        | vSphere 5.0 U2                  |              |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3  | VMware        | vSphere 5.1                     |              |
| B200, B250, B230, B440 M2 and B200, B22, B420 M3  | VMware        | vSphere 5.1 U1                  |              |
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3           | Citrix        | XenServer 6.0.2                 | 20           |
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3           | Citrix        | XenServer 6.1                   | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | Microsoft     | Windows Server 2008 R2 x64      | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | Microsoft     | Windows Server 2008 SP2 x64     | 20           |
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3           | Microsoft     | Windows Server 2012             | 20           |

| <b>UCS Blade Server</b>  | <b>Vendor</b> | <b>Operating System Version</b>        | <b>Notes</b> |
|--|---------------|--|--------------|
| C200/C210 M1 & M2,<br>C200 M2(SFF), C250 M1<br>& M2, C260 M2, C460<br>M1 & M2, C220/C240<br>M3(SFF/LFF), C22/C24<br>M3(SFF), C420 M3 | Oracle        | OL 6.3 64bit with UEK<br>2.6.39-200    | 20           |
| C200/C210 M2, C200<br>M2(SFF), C250 M2,<br>C260 M2, C460 M1 &<br>M2, C220/C240 M3(SFF/<br>LFF), C22/C24 M3(SFF),<br>C420 M3          | Oracle        | OVM 3.1.1 64bit with<br>UEK 2.6.39-200 | 20           |
| C200/C210 M2, C200<br>M2(SFF), C250 M2,<br>C260 M2, C460 M1 &<br>M2, C220/C240 M3(SFF/<br>LFF), C22/C24 M3(SFF),<br>C420 M3          | Oracle        | Solaris 10 08/11 (U10)                 | 20           |
| C200/C210 M1 & M2,<br>C200 M2(SFF), C250 M1<br>& M2, C260 M2, C460<br>M1 & M2, C220/C240<br>M3(SFF/LFF), C22/C24<br>M3(SFF), C420 M3 | Red Hat       | Red Hat Enterprise Linux<br>5.7 64bit  | 20           |
| C200/C210 M1 & M2,<br>C200 M2(SFF), C250 M1<br>& M2, C260 M2, C460<br>M1 & M2, C220/C240<br>M3(SFF/LFF), C22/C24<br>M3(SFF), C420 M3 | Red Hat       | Red Hat Enterprise Linux<br>5.8 64bit  | 20           |
| C200/C210 M1 & M2,<br>C200 M2(SFF), C250 M1<br>& M2, C260 M2, C460<br>M1 & M2, C220/C240<br>M3(SFF/LFF), C22/C24<br>M3(SFF), C420 M3 | Red Hat       | Red Hat Enterprise Linux<br>6.2 64bit  | 20           |
| C260 M2, C460 M2,<br>C220/C240 M3(SFF/<br>LFF), C22/C24 M3(SFF)  | Red Hat       | Red Hat Enterprise Linux<br>6.3 64bit  | 20           |

| <b>UCS Blade Server</b>   | <b>Vendor</b> | <b>Operating System Version</b>         | <b>Notes</b> |
|---|---------------|---|--------------|
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | SuSE          | SUSE Linux Enterprise Server 11.2 64bit | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | VMware        | vSphere 4.1 U2                          | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2,   | VMware        | vSphere 4.1i U2                         | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | VMware        | vSphere 4.1 U3                          | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2,   | VMware        | vSphere 4.1i U3                         | 20           |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | VMware        | vSphere 5.0 U1                          | 20           |
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3           | VMware        | vSphere 5.1                             | 20           |

### **VM-FEX Software Interoperability Matrix**

Table 2 lists the VM-FEX software that the Unified Computing System B Series Servers support.

**Table 2: VM-FEX Software**

| <b>Software Type</b> | <b>Software Version</b>           | <b>Operating System</b>            | <b>Driver</b>                                |
|----------------------|-----------------------------------|------------------------------------|--|
| VM-FEX               | VEM410-201108406                  | vSphere 4.1 U2                     | v132-4.2.1.1.4.1.0-2.0.4                     |
| VM-FEX               | VEM410-201108406                  | vSphere 4.1i U2                    | v132-4.2.1.1.4.1.0-2.0.4                     |
| VM-FEX               | VEM410-201108406                  | vSphere 4.1 U3                     | v132-4.2.1.1.4.1.0-2.0.4                     |
| VM-FEX               | VEM410-201108406                  | vSphere 4.1i U3                    | v132-4.2.1.1.4.1.0-2.0.4                     |
| VM-FEX               | VEM500-20110825132140- BG-release | vSphere 5.0 U1                     | v132-4.2.1.1.4.1.0-3.0.4                     |
| VM-FEX               | VEM500-20110825132140- BG-release | vSphere 5.0 U2                     | v132-4.2.1.1.4.1.0-3.0.4                     |
| VM-FEX               | cisco-vem-v151-5.1-1.1.1          | vSphere 5.1                        | cisco-vem-v151-5.1-1.1.1                     |
| VM-FEX               | cisco-vem-v151-5.1-1.1.1          | vSphere 5.1 U1                     | cisco-vem-v151-5.1-1.1.1                     |
| VM-FEX               |                                   | Red Hat Enterprise Linux 6.2 64bit | 2.1.1.41 (enic)                              |
| VM-FEX               |                                   | Red Hat Enterprise Linux 6.3 64bit | 2.1.1.41 (enic)                              |
| VM-FEX               |                                   | Red Hat Enterprise Linux 6.4 64bit | 2.1.1.42 (enic)                              |
| VM-FEX               |                                   | Windows Server 2012                | 2.3.0.4 (PF, VF enic) / 2.2.0.11 (vmfex_ext) |

**Converged Network Adapter Interoperability Matrix**

Table 3 lists the converged network adapters that the Unified Computing System B Series Servers support.

**Table 3: Converged Network Adapters**

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                                   | <b>Operating System</b>          | <b>Adapter Driver</b>            | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|--|----------------------------------|----------------------------------|-------------------------|--------------|
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | OL 6.3 64bit with UEK 2.6.39-200 | 1.5.0.45 (FNIC) / 2.1.1.24 (NIC) | 2.1(2)                  | 14, 22       |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                                   | <b>Operating System</b>                 | <b>Adapter Driver</b>              | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|--|---|------------------------------------|-------------------------|--------------|
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | OVM 3.1.1 with UEK 2.6.39-200           | 1.5.0.45 (FNIC) / 2.1.1.24 (NIC)   | 2.1(2)                  | 14, 23, 28   |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 5.7 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 5.8 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 5.9 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14, 27   |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 6.2 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 6.3 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | Red Hat Enterprise Linux 6.4 64bit      | 1.5.0.45 (FNIC) / 2.1.1.42 (ENIC)  | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | SUSE Linux Enterprise Server 11.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 14           |
| B200, B22, B420 M3      | UCS 1240 Virtual Interface Card and Port Expander Card | vSphere 4.1 U2                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 14, 31   |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>  | <b>Operating System</b>              | <b>Adapter Driver</b>  | <b>Adapter Firmware</b> | <b>Notes</b>          |
|-------------------------|---|--------------------------------------|--|-------------------------|-----------------------|
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 4.1i U2                      | 1.4.0.223 (FNIC) /<br>2.1.2.38 (ENIC)                                    | 2.1(2)                  | 10, 12, 14,<br>19, 31 |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 4.1 U3                       | 1.4.0.223 (FNIC) /<br>2.1.2.38 (ENIC)                                    | 2.1(2)                  | 11, 14, 31            |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 4.1i U3                      | 1.4.0.223 (FNIC) /<br>2.1.2.38 (ENIC)                                    | 2.1(2)                  | 10, 12, 14,<br>19, 31 |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 5.0 U1                       | 1.5.0.45 (FNIC) /<br>2.1.2.38 (ENIC)                                     | 2.1(2)                  | 11, 12, 14,<br>19, 31 |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 5.0 U2                       | 1.5.0.45 (FNIC) /<br>2.1.2.38 (ENIC)                                     | 2.1(2)                  | 11, 12, 14,<br>19, 31 |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 5.1                          | 1.5.0.45 (FNIC) /<br>2.1.2.38 (ENIC)                                     | 2.1(2)                  | 11, 12, 14,<br>19, 31 |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | vSphere 5.1 U1                       | 1.5.0.45 (FNIC) /<br>2.1.2.38 (ENIC)                                     | 2.1(2)                  | 11, 12, 14,<br>19, 31 |
| B200, B22 M3            | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | Windows<br>Server 2008<br>SP2 x64    | 2.1.0.25 (FNIC) /<br>2.3.0.4 (ENIC) /<br>2.1.0.9 (NIC<br>Teaming Driver) | 2.1(2)                  | 12, 14, 17, 25        |
| B200, B22,<br>B420 M3   | UCS 1240<br>Virtual Interface<br>Card and Port<br>Expander Card | Windows<br>Server 2008 R2<br>SP1 x64 | 2.1.0.25 (FNIC) /<br>2.3.0.4 (ENIC) /<br>2.1.0.9 (NIC<br>Teaming Driver) | 2.1(2)                  | 12, 14, 25            |

| <b>UCS Blade Server</b>                    | <b>Adapter Model</b>                                   | <b>Operating System</b>            | <b>Adapter Driver</b>               | <b>Adapter Firmware</b> | <b>Notes</b> |
|--|--|------------------------------------|-------------------------------------|-------------------------|--------------|
| B200, B22, B420 M3                         | UCS 1240 Virtual Interface Card and Port Expander Card | Windows Server 2012                | 2.3.0.12 (FNIC) / 2.3.0.4 (ENIC)    | 2.1(2)                  | 12, 14       |
| B200, B22, B420 M3                         | UCS 1240 Virtual Interface Card and Port Expander Card | XenServer 6.0.2                    | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)   | 2.1(2)                  | 14           |
| B200, B22, B420 M3                         | UCS 1240 Virtual Interface Card and Port Expander Card | XenServer 6.1                      | 1.5.0.20 (FNIC) / 2.1.1.39-1 (ENIC) | 2.1(2)                  | 4, 14, 29    |
| B200, B22, B420 M3                         | UCS 1240 Virtual Interface Card and Port Expander Card | XenServer 6.2                      | 1.5.0.45 (FNIC) / 2.1.1.39-1 (ENIC) | 2.1(2)                  | 4, 14        |
| B230, B440 M2 and B200, B22, B420 M3       | UCS 1280 Virtual Interface Card                        | OL 6.3 64bit with UEK 2.6.39-200   | 1.5.0.45 (FNIC) / 2.1.1.24 (NIC)    | 2.1(2)                  | 14, 22       |
| B230, B440 M2 and B200, B22, B420 M3       | UCS 1280 Virtual Interface Card                        | OVM 3.1.1 with UEK 2.6.39-200      | 1.5.0.45 (FNIC) / 2.1.1.24 (NIC)    | 2.1(2)                  | 14, 23, 28   |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card                        | Red Hat Enterprise Linux 5.7 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)   | 2.1(2)                  | 12, 14       |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card                        | Red Hat Enterprise Linux 5.8 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)   | 2.1(2)                  | 12, 14       |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card                        | Red Hat Enterprise Linux 5.9 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)   | 2.1(2)                  | 12, 14, 27   |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card                        | Red Hat Enterprise Linux 6.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)   | 2.1(2)                  | 12, 14       |

| <b>UCS Blade Server</b>                    | <b>Adapter Model</b>            | <b>Operating System</b>                 | <b>Adapter Driver</b>              | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|---------------------------------|---|------------------------------------|-------------------------|--------------------|
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | Red Hat Enterprise Linux 6.3 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 14             |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | Red Hat Enterprise Linux 6.4 64bit      | 1.5.0.45 (FNIC) / 2.1.1.42 (ENIC)  | 2.1(2)                  | 12, 14             |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | SUSE Linux Enterprise Server 11.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 14                 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 4.1 U2                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 14, 31         |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 4.1i U2                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 10, 12, 14, 19, 31 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 4.1 U3                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 14, 31         |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 4.1i U3                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 10, 12, 14, 19, 31 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 5.0 U1                          | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)  | 2.1(2)                  | 11, 12, 14, 19, 31 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card | vSphere 5.0 U2                          | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)  | 2.1(2)                  | 11, 12, 14, 19, 31 |

| <b>UCS Blade Server</b>                    | <b>Adapter Model</b>             | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|----------------------------------|------------------------------------|---|-------------------------|--------------------|
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | vSphere 5.1                        | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 12, 14, 19, 31 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | vSphere 5.1 U1                     | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 12, 14, 19, 31 |
| B200, B230, B440 M2 and B200, B22 M3       | UCS 1280 Virtual Interface Card  | Windows Server 2008 SP2 x64        | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 12, 14, 17, 25     |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | Windows Server 2008 R2 SP1 x64     | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 12, 14, 25         |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | Windows Server 2012                | 2.3.0.12 (FNIC) / 2.3.0.4 (ENIC)                                | 2.1(2)                  | 12, 14             |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | XenServer 6.0.2                    | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 14                 |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | XenServer 6.1                      | 1.5.0.20 (FNIC) / 2.1.1.39-1 (ENIC)                             | 2.1(2)                  | 4, 14, 29          |
| B200, B230, B440 M2 and B200, B22, B420 M3 | UCS 1280 Virtual Interface Card  | XenServer 6.2                      | 1.5.0.45 (FNIC) / 2.1.1.39-1 (ENIC)                             | 2.1(2)                  | 4, 14              |
| B200, B250, B230, B440 M1 and M2           | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 5.7 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 12                 |
| B200, B250, B230, B440 M1 and M2           | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 5.8 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 12                 |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>             | <b>Operating System</b>                 | <b>Adapter Driver</b>              | <b>Adapter Firmware</b> | <b>Notes</b>   |
|--------------------------------------|----------------------------------|---|------------------------------------|-------------------------|----------------|
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 5.9 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12, 27         |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 6.2 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12             |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 6.3 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 12             |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M81KR Virtual Interface Card | Red Hat Enterprise Linux 6.4 64bit      | 1.5.0.45 (FNIC) / 2.1.1.42 (ENIC)  | 2.1(2)                  | 12             |
| B200, B250, B230, B440 M2            | UCS M81KR Virtual Interface Card | SUSE Linux Enterprise Server 11.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  |                |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 4.1 U2                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 31         |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 4.1i U2                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 10, 12, 19, 31 |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 4.1 U3                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 31         |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 4.1i U3                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 10, 12, 19, 31 |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 5.0 U1                          | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)  | 2.1(2)                  | 11, 12, 19, 31 |
| B200, B250, B230, B440 M1 and M2     | UCS M81KR Virtual Interface Card | vSphere 5.0 U2                          | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)  | 2.1(2)                  | 11, 12, 19, 31 |
| B200, B250, B230, B440 M2            | UCS M81KR Virtual Interface Card | vSphere 5.1                             | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)  | 2.1(2)                  | 11, 12, 19, 31 |

| <b>UCS Blade Server</b>   | <b>Adapter Model</b>                 | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b>   |
|---|--------------------------------------|------------------------------------|---|-------------------------|----------------|
| B200, B250, B230, B440 M2   | UCS M81KR Virtual Interface Card     | vSphere 5.1 U1                     | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 12, 19, 31 |
| B200, B250, B230, B440 M1 & M2                                    | UCS M81KR Virtual Interface Card     | Windows Server 2008 SP2 x64        | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 12, 17, 25     |
| B200, B250, B230, B440 M1 and M2                                  | UCS M81KR Virtual Interface Card     | Windows Server 2008 R2 SP1 x64     | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 12, 25         |
| B200, B250, B230, B440 M2   | UCS M81KR Virtual Interface Card     | Windows Server 2012                | 2.3.0.12 (FNIC) / 2.3.0.4 (ENIC)                                | 2.1(2)                  | 12             |
| B200, B250, B230, B440 M2   | UCS M81KR Virtual Interface Card     | XenServer 6.0.2                    | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  |                |
| B200, B250, B230, B440 M2   | UCS M81KR Virtual Interface Card     | XenServer 6.1                      | 1.5.0.20 (FNIC) / 2.1.1.39-1 (ENIC)                             | 2.1(2)                  | 4, 29          |
| B200, B250, B230, B440 M2   | UCS M81KR Virtual Interface Card     | XenServer 6.2                      | 1.5.0.45 (FNIC) / 2.1.1.39-1 (ENIC)                             | 2.1(2)                  | 4              |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | Red Hat Enterprise Linux 5.7 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 20, 21         |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF), C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | Red Hat Enterprise Linux 5.8 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 20, 21         |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>                 | <b>Operating System</b>                 | <b>Adapter Driver</b>              | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|--------------------------------------|---|------------------------------------|-------------------------|--------------------|
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | Red Hat Enterprise Linux 6.2 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 20, 21             |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | Red Hat Enterprise Linux 6.3 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 20, 21             |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | SUSE Linux Enterprise Server 11.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)  | 2.1(2)                  | 20, 21             |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | vSphere 4.1 U2                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | vSphere 4.1i U2                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | vSphere 4.1 U3                          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3 | UCS VIC 1225 10-Gbps 2 port CNA SFP+ | vSphere 4.1i U3                         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>   | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|--|------------------------------------|---|-------------------------|--------------------|
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3   | UCS VIC 1225 10-Gbps 2 port CNA SFP+                           | vSphere 5.0 U1                     | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3   | UCS VIC 1225 10-Gbps 2 port CNA SFP+                           | vSphere 5.1                        | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3   | UCS VIC 1225 10-Gbps 2 port CNA SFP+                           | Windows Server 2008 SP2 x64        | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 20, 21, 25         |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3   | UCS VIC 1225 10-Gbps 2 port CNA SFP+                           | Windows Server 2008 R2 SP1 x64     | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 20, 21, 25         |
| C260 M2, C460 M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF),C420 M3   | UCS VIC 1225 10-Gbps 2 port CNA SFP+                           | Windows Server 2012                | 2.3.0.12 (FNIC) / 2.3.0.4 (ENIC)                                | 2.1(2)                  | 20, 21             |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Red Hat Enterprise Linux 5.7 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC)                               | 2.1(2)                  | 20, 21             |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>   | <b>Operating System</b>                 | <b>Adapter Driver</b>             | <b>Adapter Firmware</b> | <b>Notes</b> |
|--|--|---|-----------------------------------|-------------------------|--------------|
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Red Hat Enterprise Linux 5.8 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC) | 2.1(2)                  | 20, 21       |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Red Hat Enterprise Linux 6.2 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC) | 2.1(2)                  | 20, 21       |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Red Hat Enterprise Linux 6.3 64bit      | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC) | 2.1(2)                  | 20, 21       |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | SUSE Linux Enterprise Server 11.2 64bit | 1.5.0.45 (FNIC) / 2.1.1.41 (ENIC) | 2.1(2)                  | 20, 21       |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>   | <b>Operating System</b> | <b>Adapter Driver</b>              | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|--|-------------------------|------------------------------------|-------------------------|--------------------|
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 4.1 U2          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 4.1i U2         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 4.1 U3          | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 4.1i U3         | 1.4.0.223 (FNIC) / 2.1.2.38 (ENIC) | 2.1(2)                  | 11, 19, 20, 21, 31 |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>   | <b>Operating System</b>        | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b>       |
|--|--|--------------------------------|---|-------------------------|--------------------|
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 5.0 U1                 | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF)           | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | vSphere 5.1                    | 1.5.0.45 (FNIC) / 2.1.2.38 (ENIC)                               | 2.1(2)                  | 11, 19, 20, 21, 31 |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Windows Server 2008 SP2 x64    | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 20, 21, 25         |
| C200/C210 M1 & M2, C200 M2(SFF), C250 M1 & M2, C260 M2, C460 M1 & M2, C220/C240 M3(SFF/LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Windows Server 2008 R2 SP1 x64 | 2.1.0.25 (FNIC) / 2.3.0.4 (ENIC) / 2.1.0.9 (NIC Teaming Driver) | 2.1(2)                  | 20, 21, 25         |

| <b>UCS Blade Server</b>  | <b>Adapter Model</b>   | <b>Operating System</b>            | <b>Adapter Driver</b>                  | <b>Adapter Firmware</b> | <b>Notes</b> |
|--|--|------------------------------------|--|-------------------------|--------------|
| C200/C210 M2, C200 M2(SFF), C250 M2, C260 M2, C460 M1 & M2, C220/ C240 M3(SFF/ LFF), C22/C24 M3(SFF) | P81E Dual Port 10-Gbps Ethernet to PCIe Virtual Interface Card | Windows Server 2012                | 2.3.0.12 (FNIC) / 2.3.0.4 (ENIC)       | 2.1(2)                  | 20, 21       |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 5.7 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 5.8 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 5.9 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 6.2 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 6.3 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Red Hat Enterprise Linux 6.4 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)        | 4.6.209.2               | 8            |
| B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | Solaris 11 10/12 (U1)              | 20120210-2.70i (FC) / 4.1.369.1S (ETH) | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3   | UCS M73KR-E Converged Network Adapter                          | vSphere 4.1 U2                     | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH)   | 4.6.209.2               | 8            |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>        | <b>Adapter Driver</b>  | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|--------------------------------|--|-------------------------|--------------|
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 4.1i U2                | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 4.1 U3                 | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 4.1i U3                | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 5.0 U1                 | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 5.0 U2                 | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 5.1                    | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | vSphere 5.1 U1                 | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | Windows Server 2008 R2 SP1 x64 | 2.74.014.001 (FC) / 4.6.142.8 (ETH), 8.01.002.051 (NIC Teaming Driver) | 4.6.209.2               | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-E Converged Network Adapter | Windows Server 2012            | 2.74.014.001 (FC) / 4.6.142.8 (ETH)                                    | 4.6.209.2               | 8            |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>                | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|------------------------------------|--------------------------------------|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.7 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.8 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.9 64bit | 8.2.2.15 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 6.2 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 6.3 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | Red Hat Enterprise Linux 6.4 64bit | 8.3.7.18 (FC) / 4.6.142.5 (ETH)      | 4.6.209.2               | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | vSphere 4.1 U3                     | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH) | 4.6.209.2               | 8, 11        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | vSphere 4.1i U3                    | 8.2.1.151.65 (FC) / 4.6.142.10 (ETH) | 4.6.209.2               | 8, 19        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-E Converged Network Adapter | vSphere 5.0 U1                     | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH) | 4.6.209.2               | 8, 11, 19    |

| <b>UCS Blade Server</b>        | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>  | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------|---------------------------------------|------------------------------------|--|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | vSphere 5.0 U2                     | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8, 11, 19    |
| B200, B250, B230, B440 M2      | UCS M72KR-E Converged Network Adapter | vSphere 5.1                        | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8, 11, 19    |
| B200, B250, B230, B440 M2      | UCS M72KR-E Converged Network Adapter | vSphere 5.1 U1                     | 8.2.4.151.65 (FC) / 4.6.142.10 (ETH)                                   | 4.6.209.2               | 8, 11, 19    |
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | Windows Server 2008 SP2 x64        | 2.74.014.001 (FC) / 4.6.142.8 (ETH), 8.01.002.051 (NIC Teaming Driver) | 4.6.209.2               | 8            |
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-E Converged Network Adapter | Windows Server 2008 R2 SP1 x64     | 2.74.014.001 (FC) / 4.6.142.8 (ETH), 8.01.002.051 (NIC Teaming Driver) | 4.6.209.2               | 8            |
| B200, B250, B230, B440 M2      | UCS M72KR-E Converged Network Adapter | Windows Server 2012                | 2.74.014.001 (FC) / 4.6.142.8 (ETH)                                    | 4.6.209.2               | 8            |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.7 64bit | 8.2.0.96.2p (FC)   | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.8 64bit | 8.2.0.108.4p (FC)  | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-E Converged Network Adapter | Red Hat Enterprise Linux 5.9 64bit | 8.2.0.128.3p (FC)  | 2.1(2)                  | 8, 13        |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>                  | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|------------------------------------|--|-------------------------|--------------|
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | vSphere 4.1 U2                     | 8.2.1.30.1-58vmw (FC)                  | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | vSphere 4.1i U2                    | 8.2.1.30.1-58vmw (FC)                  | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | vSphere 4.1 U3                     | 8.2.1.30.1-58vmw (FC)                  | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | vSphere 4.1i U3                    | 8.2.1.30.1-58vmw (FC)                  | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | Windows Server 2008 SP2 x64        | 7.2.41.002 (FC)                        | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1       | UCS M71KR-E Converged Network Adapter | Windows Server 2008 R2 SP1 x64     | 7.2.41.002 (FC)                        | 2.1(2)                  | 8, 13        |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.7 64bit | 8.04.00.06.5.6-k (FC) / 5.0.29.2 (ETH) | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.8 64bit | 8.04.00.06.5.6-k (FC) / 5.0.29.2 (ETH) | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.9 64bit | 8.03.07.15.05.09-k (FC) / 5.0.29 (ETH) | 1.10.84                 | 8            |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>                   | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|------------------------------------|---|-------------------------|--------------|
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.2 64bit | 8.04.00.06.06.0-k (FC) / 5.0.29.2 (ETH) | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.3 64bit | 8.04.00.06.06.0-k (FC) / 5.0.29.2 (ETH) | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.4 64bit | 8.04.00.08.06.4-k (FC) / 5.0.29 (ETH)   | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 4.1 U2                     | 841.k1.48.1-1vmw (FC) / 4.0.744 (ETH)   | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 4.1i U2                    | 841.k1.48.1-1vmw (FC) / 4.0.744 (ETH)   | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 4.1 U3                     | 841.k1.48.1-1vmw (FC) / 4.0.744 (ETH)   | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 4.1i U3                    | 841.k1.48.1-1vmw (FC) / 4.0.744 (ETH)   | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 5.0 U1                     | 934.5.4.0-1vmw (FC) / 5.0.750 (ETH)     | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 5.0 U2                     | 934.5.4.0-1vmw (FC) / 5.0.750 (ETH)     | 1.10.84                 | 8            |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|------------------------------------|---|-------------------------|--------------|
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 5.1                        | 934.5.4.0-1vmw (FC) / 5.0.750 (ETH)                                 | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | vSphere 5.1 U1                     | 934.5.4.0-1vmw (FC) / 5.0.750 (ETH)                                 | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Windows Server 2008 R2 SP1 x64     | 9.1.10.15 (FC) / 4.7.16.0907 (ETH), 4.6.6.1213 (NIC Teaming Driver) | 1.10.84                 | 8            |
| B230, B440 M2 and B200, B22, B420 M3 | UCS M73KR-Q Converged Network Adapter | Windows Server 2012                | 9.1.10.15 (FC) / 4.7.16.0907 (ETH)                                  | 1.10.84                 | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.7 64bit | 8.03.07.03.05.07-k (FC) / 1.0.00.25 (ETH)                           | 2.00.77                 | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.8 64bit | 8.03.07.09.05.08-k (FC) / 1.0.00.29 (ETH)                           | 2.00.77                 | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.9 64bit | 8.0.3.07.15.05.09-k (FC) / 1.0.00.30 (ETH)                          | 2.00.77                 | 8            |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.2 64bit | 8.03.07.05.06.2-k (FC) / 1.00.00.29 (ETH)                           | 2.00.77                 | 8            |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.3 64bit | 8.04.00.04.06.3-k (FC) / 1.00.00.30 (ETH)                           | 2.00.77                 | 8            |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>                     | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---------------------------------------|------------------------------------|---|-------------------------|--------------|
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | Red Hat Enterprise Linux 6.4 64bit | 8.04.00.08.06.4-k (FC) / 1.00.00.31 (ETH) | 2.00.77                 | 8            |
| B200, B250, B230, B440 M2            | UCS M72KR-Q Converged Network Adapter | Solaris 10 09/10 (U9)              | 20100301-3.00 (FC) / 100429-v1.05 (ETH)   | 2.00.77                 | 8            |
| B200, B250, B230, B440 M2            | UCS M72KR-Q Converged Network Adapter | Solaris 10 08/11 (U10)             | 3.06 (FC) / 1.10 (ETH)                    | 2.00.77                 | 8            |
| B200, B250, B230, B440 M2            | UCS M72KR-Q Converged Network Adapter | Solaris 10 01/13 (U11)             | 20120717-4.01 (FC) / 101203-v1.10 (ETH)   | 2.00.77                 | 8            |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | vSphere 4.1 U2                     | 841.k1.48.1-1vmw (FC) / 1.0.0.53 (ETH)    | 2.00.77                 | 8, 11        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | vSphere 4.1i U2                    | 841.k1.48.1-1vmw (FC) / 1.0.0.53 (ETH)    | 2.00.77                 | 8, 19        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | vSphere 4.1 U3                     | 841.k1.48.1-1vmw (FC) / 1.0.0.53 (ETH)    | 2.00.77                 | 8, 11        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | vSphere 4.1i U3                    | 841.k1.48.1-1vmw (FC) / 1.0.0.53 (ETH)    | 2.00.77                 | 8, 19        |
| B200, B250, B230, B440 M1 & M2       | UCS M72KR-Q Converged Network Adapter | vSphere 5.0 U1                     | 934.5.4.0-1vmw (FC) / 2.0.0.54 (ETH)      | 2.00.77                 | 8, 11, 19    |

| <b>UCS Blade Server</b>        | <b>Adapter Model</b>                  | <b>Operating System</b>            | <b>Adapter Driver</b>                | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------|---------------------------------------|------------------------------------|--------------------------------------|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | vSphere 5.0 U2                     | 934.5.4.0-1vmw (FC) / 2.0.0.54 (ETH) | 2.00.77                 | 8, 11, 19    |
| B200, B250, B230, B440 M2      | UCS M72KR-Q Converged Network Adapter | vSphere 5.1                        | 934.5.4.0-1vmw (FC) / 2.0.0.54 (ETH) | 2.00.77                 | 8, 11, 19    |
| B200, B250, B230, B440 M2      | UCS M72KR-Q Converged Network Adapter | vSphere 5.1 U1                     | 934.5.4.0-1vmw (FC) / 2.0.0.54 (ETH) | 2.00.77                 | 8, 11, 19    |
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | Windows Server 2008 SP2 x64        | 9.1.8.27 (FC) / 1.0.1.12 (ETH)       | 2.00.77                 | 8            |
| B200, B250, B230, B440 M1 & M2 | UCS M72KR-Q Converged Network Adapter | Windows Server 2008 R2 SP1 x64     | 9.1.8.27 (FC) / 1.0.1.12 (ETH)       | 2.00.77                 | 8            |
| B200, B250, B230, B440 M2      | UCS M72KR-Q Converged Network Adapter | Windows Server 2012                | 9.1.10.15 (FC) / 1.0.1.15 (ETH)      | 2.00.77                 | 8            |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.7 64bit | 8.03.07.03.05.07-k (FC)              | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.8 64bit | 8.03.07.09.05.08-k (FC)              | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | Red Hat Enterprise Linux 5.9 64bit | 8.03.07.15.05.09-k (FC)              | 2.1(2)                  | 8, 13        |

| <b>UCS Blade Server</b>        | <b>Adapter Model</b>                  | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------|---------------------------------------|--------------------------------|-----------------------|-------------------------|--------------|
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | vSphere 4.1 U2                 | 831.k1.28.1-1vmw (FC) | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | vSphere 4.1i U2                | 831.k1.28.1-1vmw (FC) | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | vSphere 4.1 U3                 | 831.k1.28.1-1vmw (FC) | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | vSphere 4.1i U3                | 831.k1.28.1-1vmw (FC) | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | Windows Server 2008 SP2 x64    | 9.1.8.27 (FC)         | 2.1(2)                  | 8, 13        |
| B200, B250 M1 & M2 and B440 M1 | UCS M71KR-Q Converged Network Adapter | Windows Server 2008 R2 SP1 x64 | 9.1.8.27 (FC)         | 2.1(2)                  | 8, 13        |

### Network Interface Card Interoperability Matrix

Table 4 lists the network interface cards that the Unified Computing System B Series Servers support.

**Table 4: Network Interface Cards**

| <b>UCS Blade Server</b>        | <b>Adapter Model</b>                    | <b>Operating System</b>            | <b>Adapter Driver</b>            | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------|---|------------------------------------|----------------------------------|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2 | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.7 64bit | 1.62.00-6 (ETH) / 2.1.3b (iSCSI) | 6.2.15.23.7.1           |              |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                    | <b>Operating System</b>            | <b>Adapter Driver</b>                    | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---|------------------------------------|--|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.8 64bit | 1.70.00-0 (ETH)                          | 6.2.15.23.7.1           |              |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.9 64bit | 7.2.51-0 (ETH)                           | 6.2.15.23.7.1           |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.2 64bit | 1.62.00-6 (ETH)                          | 6.2.15.23.7.1           |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.3 64bit | 1.70.00-0 (ETH)                          | 6.2.15.23.7.1           |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M51KR-B 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.4 64bit | 1.72.51-0 (ETH)                          | 6.2.15.23.7.1           |              |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | vSphere 4.1 U2                     | 1.62.15.v41 (ETH) / 1.9.1t.v41.2 (iSCSI) | 6.2.15.23.7.1           | 11           |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | vSphere 4.1i U2                    | 1.62.15.v41 (ETH) / 1.9.1t.v41.2 (iSCSI) | 6.2.15.23.7.1           | 12, 19       |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | vSphere 5.0 U1                     | 1.61.15.v50.1 (ETH)                      | 6.2.15.23.7.1           |              |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | vSphere 5.0 U2                     | 1.61.15.v50.1 (ETH)                      | 6.2.15.23.7.1           |              |

| <b>UCS Blade Server</b>              | <b>Adapter Model</b>                    | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------------|---|------------------------------------|---|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | Windows Server 2008 SP2 x64        | 6.2.9.0 (ETH) / 6.2.7.0 (iSCSI) / 1.4.10.0 (NIC Teaming Driver) | 6.2.15.23.7.1           |              |
| B200, B250, B230, B440 M1 & M2       | UCS M51KR-B 10-Gigabit Ethernet Adapter | Windows Server 2008 R2 SP1 x64     | 6.2.9.0 (ETH) / 6.2.7.0 (iSCSI) / 1.4.10.0 (NIC Teaming Driver) | 6.2.15.23.7.1           | 12, 17       |
| B200, B250, B230, B440 M1 & M2       | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.7 64bit | 3.2.9 (ETH)   | 2.1.60.1.1              |              |
| B200, B250, B230, B440 M1 & M2       | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.8 64bit | 3.4.8-k (ETH)   | 2.1.60.1.1              |              |
| B200, B250, B230, B440 M1 & M2       | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.9 64bit | 3.4.8-k (ETH)   | 2.1.60.1.1              |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.2 64bit | 3.3.9 (ETH)   | 2.1.60.1.1              |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.3 64bit | 3.4.8-k (ETH)   | 2.1.60.1.1              |              |
| B200, B250 M2 and B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 6.4 64bit | 3.9.15-k (ETH)  | 2.1.60.1.1              |              |
| B200, B250, B230, B440 M1 & M2       | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 4.1 U2                     | 3.1.17.1 (ETH)  | 2.1.60.1.1              | 11           |

| <b>UCS Blade Server</b>        | <b>Adapter Model</b>                    | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|--------------------------------|---|--------------------------------|-----------------------|-------------------------|--------------|
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 4.1i U2                | 3.1.17.1 (ETH)        | 2.1.60.1.1              | 19           |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 4.1 U3                 | 3.1.17.1 (ETH)        | 2.1.60.1.1              | 11           |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 4.1i U3                | 3.1.17.1 (ETH)        | 2.1.60.1.1              | 19           |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 5.0 U1                 | 3.7.13 (ETH)          | 2.1.60.1.1              | 11, 19       |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 5.0 U2                 | 3.7.13 (ETH)          | 2.1.60.1.1              | 11, 19       |
| B200, B250, B230, B440 M2      | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 5.1                    | 3.7.13 (ETH)          | 2.1.60.1.1              | 11, 19       |
| B200, B250, B230, B440 M2      | UCS M61KR-I 10-Gigabit Ethernet Adapter | vSphere 5.1 U1                 | 3.7.13 (ETH)          | 2.1.60.1.1              | 11, 19       |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | Windows Server 2008 SP2 x64    | 2.7.28.0 (ETH)        | 2.1.60.1.1              |              |
| B200, B250, B230, B440 M1 & M2 | UCS M61KR-I 10-Gigabit Ethernet Adapter | Windows Server 2008 R2 SP1 x64 | 2.7.28.0 (ETH)        | 2.1.60.1.1              |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                       | <b>Operating System</b>            | <b>Adapter Driver</b>   | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|--|------------------------------------|-------------------------|-------------------------|--------------|
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.7 64bit | 3.2.9 (ETH)             | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.8 64bit | 3.4.8-k (ETH)           | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | Red Hat Enterprise Linux 5.9 64bit | 3.4.8-k (ETH)           | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | vSphere 4.1 U2                     | 2.0.38.2.5.1-1vmw (ETH) | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | vSphere 4.1i U2                    | 2.0.38.2.5.1-1vmw (ETH) | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | vSphere 4.1 U3                     | 2.0.38.2.5.1-1vmw (ETH) | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | vSphere 4.1i U3                    | 2.0.38.2.5.1-1vmw (ETH) | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | Windows Server 2008 SP2 x64        | 2.4.29.1 (ETH)          | 2.1.11 (pxe)            |              |
| B200, B250 M1 & M2      | UCS 82598KR-CI 10-Gigabit Ethernet Adapter | Windows Server 2008 R2 SP1 x64     | 2.4.29.1 (ETH)          | 2.1.11 (pxe)            |              |

### RAID Controller on Motherboard Interoperability Matrix

Table 5 lists the RAID controllers on motherboard that the Unified Computing System B Series Servers support.

**Table 5: RAID Controller on Motherboard**

| UCS Blade Server   | Adapter Model                             | Operating System                   | Adapter Driver | Adapter Firmware | Notes |
|--------------------|---|------------------------------------|----------------|------------------|-------|
| B200, B250 M1 & M2 | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 5.7 64bit | 3.0.4.18rh     | 1.32.09.00       |       |
| B200, B250 M1 & M2 | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 5.8 64bit | 3.0.4.20rh     | 1.32.09.00       |       |
| B200, B250 M1 & M2 | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 5.9 64bit | 3.04.20rh1     | 1.32.09.00       |       |
| B200, B250 M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 6.2 64bit | 3.04.19        | 1.32.09.00       |       |
| B200, B250 M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 6.3 64bit | 3.04.20        | 1.32.09.00       |       |
| B200, B250 M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Red Hat Enterprise Linux 6.4 64bit | 3.04.20        | 1.32.09.00       |       |
| B200, B250 M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Solaris 10 09/10 (U9)              | 1.100          | 1.32.09.00       |       |
| B200, B250 M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Solaris 10 08/11 (U10)             | 1.109          | 1.32.09.00       |       |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                      | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|---|---|-----------------------|-------------------------|--------------|
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | Solaris 10 01/13 (U11)                  | 1.114                 | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | SUSE Linux Enterprise Server 11.2 64bit | 4.28.00.00            | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 4.1 U2                          | 4.21.00.01.1-5vmw     | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 4.1i U2                         | 4.21.00.01.1-5vmw     | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 4.1 U3                          | 4.21.00.01.1-5vmw     | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 4.1i U3                         | 4.21.00.01.1-5vmw     | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 5.0 U1                          | 4.23.01.00-5          | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 5.0 U2                          | 4.23.01.00-5          | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 5.1                             | 4.23.01.00-5          | 1.32.09.00              |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                      | <b>Operating System</b>            | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|---|------------------------------------|-----------------------|-------------------------|--------------|
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | vSphere 5.1 U1                     | 4.23.01.00-5          | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Windows Server 2008 SP2 x64        | 1.34.02.00            | 1.32.09.00              |              |
| B200, B250 M1 & M2      | LSI Logic SAS1064E PCI-Express Fusion-MPT | Windows Server 2008 R2 SP1 x64     | 1.34.02.00            | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | Windows Server 2012                | 1.34.2.6              | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | XenServer 6.0.2                    | 4.22                  | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | XenServer 6.1                      | 4.28.00.00            | 1.32.09.00              |              |
| B200, B250 M2           | LSI Logic SAS1064E PCI-Express Fusion-MPT | XenServer 6.2                      | 4.28.00.00            | 1.32.09.00              |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240)             | OL 6.3 64bit with UEK 2.6.39-200   | 00.00.05.40           | 20.10.1-0100            | 22           |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240)             | OVM 3.1.1 with UEK 2.6.39-200      | 00.00.05.40           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240)             | Red Hat Enterprise Linux 5.7 64bit | 6.506.00.00           | 20.10.1-0100            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>          | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------------|---|-----------------------|-------------------------|--------------|
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Red Hat Enterprise Linux 5.8 64bit      | 6.506.00.00           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Red Hat Enterprise Linux 5.9 64bit      | 00.00.06.15-rh        | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Red Hat Enterprise Linux 6.2 64bit      | 6.506.00.00           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Red Hat Enterprise Linux 6.3 64bit      | 6.506.00.00           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Red Hat Enterprise Linux 6.4 64bit      | 6.504.01.00-rh1       | 20.10.1-0100            |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | Solaris 10 09/10 (U9)                   | 03.03.00              | 20.10.1-0100            | 3            |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | Solaris 10 08/11 (U10)                  | 03.03.00              | 20.10.1-0100            | 3            |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | Solaris 10 01/13 (U11)                  | 03.03.00              | 20.10.1-0100            | 3            |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | SUSE Linux Enterprise Server 11.2 64bit | 6.506.00.00           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 4.1 U2                          | 6.506.01.00.1         | 20.10.1-0100            | 11           |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 4.1i U2                         | 6.506.01.00.1         | 20.10.1-0100            | 19           |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 4.1 U3                          | 6.506.01.00.1         | 20.10.1-0100            | 11           |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>          | <b>Operating System</b>          | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------------|----------------------------------|-----------------------|-------------------------|--------------|
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 4.1i U3                  | 6.506.01.00.1         | 20.10.1-0100            | 19           |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 5.0 U1                   | 6.506.51.00.1         | 20.10.1-0100            | 11, 19       |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | vSphere 5.0 U2                   | 6.506.51.00.1         | 20.10.1-0100            | 11, 19       |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | vSphere 5.1                      | 6.506.51.00.1         | 20.10.1-0100            | 11, 19       |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | vSphere 5.1 U1                   | 6.506.51.00.1         | 20.10.1-0100            | 11, 19       |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Windows Server 2008 SP2 x64      | 6.506.01.00           | 20.10.1-0100            |              |
| B230 M1 & M2            | LSI Logic MegaSAS 2008 (9240) | Windows Server 2008 R2 SP1 x64   | 6.506.01.00           | 20.10.1-0100            |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | Windows Server 2012              | 6.506.02.00           | 20.10.1-0100            |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | XenServer 6.0.2                  | 5.41                  | 20.10.1-0100            |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | XenServer 6.1                    | 6.15                  | 20.10.1-0100            |              |
| B230 M2                 | LSI Logic MegaSAS 2008 (9240) | XenServer 6.2                    | 6.5060000000000002    | 20.10.1-0100            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | OL 6.3 64bit with UEK 2.6.39-200 | 00.00.05.40           | 12.12.0-0050            | 22           |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>          | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------------|---|-----------------------|-------------------------|--------------|
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | OVM 3.1.1 with UEK 2.6.39-200           | 00.00.05.40           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 5.7 64bit      | 6.506.00.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 5.8 64bit      | 6.506.00.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 5.9 64bit      | 00.00.06.15-rh        | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 6.2 64bit      | 6.506.00.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 6.3 64bit      | 6.506.00.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Red Hat Enterprise Linux 6.4 64bit      | 6.504.01.00-rh1       | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | Solaris 10 09/10 (U9)                   | 2.4                   | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | Solaris 10 08/11 (U10)                  | 2.9                   | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | Solaris 10 01/13 (U11)                  | 3.0                   | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | SUSE Linux Enterprise Server 11.2 64bit | 6.506.00.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 4.1 U2                          | 6.506.01.00.1         | 12.12.0-0050            | 11           |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>          | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------------|--------------------------------|-----------------------|-------------------------|--------------|
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 4.1i U2                | 6.506.01.00.1         | 12.12.0-0050            | 19           |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 4.1 U3                 | 6.506.01.00.1         | 12.12.0-0050            | 11           |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 4.1i U3                | 6.506.01.00.1         | 12.12.0-0050            | 19           |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 5.0 U1                 | 6.506.51.00.1         | 12.12.0-0050            | 11, 19       |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | vSphere 5.0 U2                 | 6.506.51.00.1         | 12.12.0-0050            | 11, 19       |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | vSphere 5.1                    | 6.506.51.00.1         | 12.12.0-0050            | 11, 19       |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | vSphere 5.1 U1                 | 6.506.51.00.1         | 12.12.0-0050            | 11, 19       |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Windows Server 2008 SP2 x64    | 6.506.01.00           | 12.12.0-0050            |              |
| B440 M1 & M2            | LSI Logic MegaSAS 2108 (9260) | Windows Server 2008 R2 SP1 x64 | 6.506.01.00           | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | Windows Server 2012            | 6.506.02.00           | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | XenServer 6.0.2                | 5.41                  | 12.12.0-0050            |              |
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | XenServer 6.1                  | 6.15                  | 12.12.0-0050            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>          | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------------|---|-----------------------|-------------------------|--------------|
| B440 M2                 | LSI Logic MegaSAS 2108 (9260) | XenServer 6.2                           | 6.5060000000000002    | 12.12.0-0050            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | OL 6.3 64bit with UEK 2.6.39-200        | 00.00.05.40           | 20.11.1-0135            | 22           |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | OVM 3.1.1 with UEK 2.6.39-200           | 00.00.05.40           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 5.7 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 5.8 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 5.9 64bit      | 00.00.06.15-rh        | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 6.2 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 6.3 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Red Hat Enterprise Linux 6.4 64bit      | 06.504.01.00-rh1      | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | Solaris 11 10/12 (U1)                   | 03.03.00              | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | SUSE Linux Enterprise Server 11.2 64bit | 6.506.00.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004   | vSphere 4.1 U2                          | 6.506.01.00.1         | 20.11.1-0135            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>        | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-----------------------------|--------------------------------|-----------------------|-------------------------|--------------|
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 4.1i U2                | 6.506.01.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 4.1 U3                 | 6.506.01.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 4.1i U3                | 6.506.01.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 5.0 U1                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 5.0 U2                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 5.1                    | 6.506.51.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | vSphere 5.1 U1                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | Windows Server 2008 SP2 x64    | 6.506.01.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | Windows Server 2008 R2 SP1 x64 | 6.506.01.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | Windows Server 2012            | 6.506.02.00           | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | XenServer 6.0.2                | 5.41                  | 20.11.1-0135            |              |
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | XenServer 6.1                  | 6.15                  | 20.11.1-0135            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>        | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-----------------------------|---|-----------------------|-------------------------|--------------|
| B200 M3                 | LSI Logic MegaRAID SAS 2004 | XenServer 6.2                           | 6.5060000000000002    | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | OL 6.3 64bit with UEK 2.6.39-200        | 00.00.05.40           | 20.11.1-0135            | 22           |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | OVM 3.1.1 with UEK 2.6.39-200           | 00.00.05.40           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 5.7 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 5.8 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 5.9 64bit      | 00.00.06.15-rh        | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 6.2 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 6.3 64bit      | 6.506.00.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Red Hat Enterprise Linux 6.4 64bit      | 6.504.01.00-rh1       | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | SUSE Linux Enterprise Server 11.2 64bit | 6.506.00.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Solaris 11 10/12 (U1)                   | 03.03.00              | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 4.1 U2                          | 6.506.01.00.1         | 20.11.1-0135            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>        | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-----------------------------|--------------------------------|-----------------------|-------------------------|--------------|
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 4.1i U2                | 6.506.01.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 4.1 U3                 | 6.506.01.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 4.1i U3                | 6.506.01.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 5.0 U1                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 5.0 U2                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 5.1                    | 6.506.51.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | vSphere 5.1 U1                 | 6.506.51.00.1         | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Windows Server 2008 SP2 x64    | 6.506.01.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Windows Server 2008 R2 SP1 x64 | 6.506.01.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | Windows Server 2012            | 6.506.02.00           | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | XenServer 6.0.2                | 5.41                  | 20.11.1-0135            |              |
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | XenServer 6.1                  | 6.15                  | 20.11.1-0135            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>        | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-----------------------------|---|-----------------------|-------------------------|--------------|
| B22 M3                  | LSI Logic MegaRAID SAS 2002 | XenServer 6.2                           | 6.5060000000000002    | 20.11.1-0135            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | OL 6.3 64bit with UEK 2.6.39-200        | 00.00.05.40           | 23.12.0-0014            | 22           |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | OVM 3.1.1 with UEK 2.6.39-200           | 00.00.05.40           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 5.7 64bit      | 6.506.00.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 5.8 64bit      | 6.506.00.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 5.9 64bit      | 00.00.06.15-rh        | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 6.2 64bit      | 6.506.00.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 6.3 64bit      | 6.506.00.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Red Hat Enterprise Linux 6.4 64bit      | 6.504.01.00-rh1       | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | SUSE Linux Enterprise Server 11.2 64bit | 6.506.00.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Solaris 11 10/12 (U1)                   | 3.0                   | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 4.1 U2                          | 6.506.01.00.1         | 23.12.0-0014            |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>        | <b>Operating System</b>        | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-----------------------------|--------------------------------|-----------------------|-------------------------|--------------|
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 4.1i U2                | 6.506.01.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 4.1 U3                 | 6.506.01.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 4.1i U3                | 6.506.01.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 5.0 U1                 | 6.506.51.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 5.0 U2                 | 6.506.51.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 5.1                    | 6.506.51.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | vSphere 5.1 U1                 | 6.506.51.00.1         | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Windows Server 2008 R2 SP1 x64 | 6.506.01.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | Windows Server 2012            | 6.506.02.00           | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | XenServer 6.0.2                | 5.41                  | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | XenServer 6.1                  | 6.15                  | 23.12.0-0014            |              |
| B420 M3                 | LSI Logic MegaRAID SAS 2208 | XenServer 6.2                  | 6.5060000000000002    | 23.12.0-0014            |              |

**UCS Storage Accelerator Interoperability Matrix**

Table 6 lists the UCS storage accelerators that are supported with this version of the Unified Computing System.

***Table 6: UCS Storage Accelerators***

| <b>UCS Blade Server</b> | <b>Adapter Model</b>    | <b>Operating System</b>                 | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|-------------------------|---|-----------------------|-------------------------|--------------|
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | Red Hat Enterprise Linux 5.7 64bit      | 14.00.00.00           | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | Red Hat Enterprise Linux 5.8 64bit      | 14.00.00.00           | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | Red Hat Enterprise Linux 6.2 64bit      | 14.00.00.00           | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | Red Hat Enterprise Linux 6.3 64bit      | 14.00.00.00           | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | SUSE Linux Enterprise Server 11.2 64bit | 14.00.00.00           | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | vSphere 4.1i U3                         | 14.00.00.00.1         | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | vSphere 5.0 U1                          | 14.00.00.00.1         | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | vSphere 5.0 U2                          | 14.00.00.00.1         | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | vSphere 5.1                             | 14.00.00.00.1         | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | vSphere 5.1 U1                          | 14.00.00.00.1         | 08.65.02.00             |              |
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive | Windows Server 2008 R2 SP1 x64          | 2.10.58.00            | 08.65.02.00             |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>             | <b>Operating System</b>                 | <b>Adapter Driver</b>     | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|----------------------------------|---|---------------------------|-------------------------|--------------|
| B200, B22, B420 M3      | LSI 400GB SLC WarpDrive          | Windows Server 2012                     | 2.10.58.00                | 08.65.02.00             |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 5.7 64bit      | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 5.8 64bit      | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 6.2 64bit      | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 6.3 64bit      | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | SUSE Linux Enterprise Server 11.2 64bit | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | vSphere 4.1i U3                         | 3.2.4.1108 (Block)        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | vSphere 5.0 U1                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | vSphere 5.0 U2                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | vSphere 5.1                             | 3.2.4.1108 (Block / SCSI) | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | vSphere 5.1 U1                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Windows Server 2008 R2 SP1 x64          | 3.2.2.869 (Block )        | 7.1.13                  |              |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>             | <b>Operating System</b>                 | <b>Adapter Driver</b>     | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|----------------------------------|---|---------------------------|-------------------------|--------------|
| B200, B22, B420 M3      | UCS 365GB MLC Fusion-io ioDrive2 | Windows Server 2012                     | 3.2.2.869 (Block )        | 7.1.13                  |              |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 5.7 64bit      | 3.2.2.869 (Block )        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 5.8 64bit      | 3.2.2.869 (Block )        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 6.2 64bit      | 3.2.2.869 (Block )        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | Red Hat Enterprise Linux 6.3 64bit      | 3.2.2.869 (Block )        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | SUSE Linux Enterprise Server 11.2 64bit | 3.2.2.869 (Block )        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | vSphere 4.1i U3                         | 3.2.4.1108 (Block)        | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | vSphere 5.0 U1                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | vSphere 5.0 U2                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | vSphere 5.1                             | 3.2.4.1108 (Block / SCSI) | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | vSphere 5.1 U1                          | 3.2.4.1108 (Block / SCSI) | 7.1.13                  | 34           |
| B200, B22, B420 M3      | UCS 785GB MLC Fusion-io ioDrive2 | Windows Server 2008 R2 SP1 x64          | 3.2.2.869 (Block )        | 7.1.13                  | 34           |

| <b>UCS Blade Server</b> | <b>Adapter Model</b>                   | <b>Operating System</b> | <b>Adapter Driver</b> | <b>Adapter Firmware</b> | <b>Notes</b> |
|-------------------------|--|-------------------------|-----------------------|-------------------------|--------------|
| B200, B22,<br>B420 M3   | UCS 785GB<br>MLC Fusion-io<br>ioDrive2 | Windows Server<br>2012  | 3.2.2.869 (Block )    | 7.1.13                  | 34           |

### Storage Array Interoperability Matrix

Table 7 lists the storage array models that are supported with this version of the Unified Computing System. Cisco's interoperability guidelines in this table apply to the following topologies and protocols:

- FC/FCoE-attached storage arrays (Fabric Interconnects in NPV mode or FC Switching Mode); unless otherwise indicated FCoE NPV connections are supported to the devices listed in the FC switch table
- UCSM-configured iSCSI boot
- iSCSI data LUN access if the storage array is directly connected to UCS Fabric Interconnects using Appliance Ports
- NFS or CIFS data access if the storage array is directly connected to UCS Fabric Interconnects using Appliance Ports


**Note**

Cisco UCS has no interoperability requirements for storage arrays configured to use iSCSI (Data Only), NFS, or CIFS when connected through UCS Fabric Interconnect Uplink Port.

**Table 7: Storage Array**

| <b>Vendor</b>   | <b>Storage Array Model</b>  | <b>Array Firmware</b>   | <b>Notes</b>        |
|-----------------|---|---|---------------------|
| Dell Compellent | SC040, SC8000   | Refer to storage vendor's support list, <a href="http://www.compellent.com/Support.aspx">http://www.compellent.com/Support.aspx</a>               | 5,6, 7,32           |
| EMC             | EMC Symmetrix family (VMAX & DMX), EMC CLARiiON (AX & CX)<br>EMC Unified Storage VNX/VNXe<br>EMC Celerra (Native Block) EMC Isilon (NFS/CIFS) EMC VPLEX | Refer to storage vendor's support list, <a href="https://elabnavigator.emc.com">https://elabnavigator.emc.com</a>                                 | 5, 6, 7, 12, 26, 32 |
| HDS             | USP-V, USP-VM, VSP, AMS 1000, 2000 Series: AMS 2100, AMS 2300, AMS 2500, HUS100 Series, HUS-VM  | Refer to storage vendor's support list, <a href="http://www.hds.com/products/interoperability/">http://www.hds.com/products/interoperability/</a> | 5, 6, 7, 12         |
| HP              | EVA 4000/6000/8000/4100/6100/8100, EVA 4400/6400/8400 XP 10000/12000, XP 20000/24000, P9500, MSA 2000, P2000  |   | 6, 7                |

| <b>Vendor</b> | <b>Storage Array Model</b>   | <b>Array Firmware</b>  | <b>Notes</b> |
|---------------|--|--|--------------|
| HP            | HP 3PAR F200, F400, T400, T800 HP 3PAR StoreServ 10000 Storage HP 3PAR StoreServ 7000 Storage                              |  | 5, 6, 7      |
| IBM           | DS 3500, DS 4800, DS 5300, DS 8100, DS 8800, SVC, Storwize V7000, IBM N-Series, XIV(Gen 2), XIV(Gen3)                      |  | 5, 6, 7, 33  |
| Netapp        | FAS2000 series, FAS3000 series, FAS6000 series, FAS3100 series, FAS3200 series, FAS6200 series, V3000 series, V6000 series | Refer to storage vendor's support list, <a href="http://support.netapp.com/">http://support.netapp.com/</a>                      | 5, 6, 7, 12  |
| Nimble        | CS-Series Family   | Refer to storage vendors support list, <a href="http://www.nimblestorage.com/support/">http://www.nimblestorage.com/support/</a> | 6, 7, 12     |
| Tintri        | Tintri VMstore T540  | Refer to storage vendors support list, <a href="http://www.tintri.com/support/">http://www.tintri.com/support/</a>               | 26           |

### Enterprise Backup Interoperability Matrix

Table 8 lists the tape library models that are supported with this version of the Unified Computing System.



**Note**

Direct connect of tape libraries is not supported.

**Table 8: Tape Libraries**

| <b>Vendor</b> | <b>Tape Library Model</b>   | <b>Backup Application</b> | <b>Firmware</b>   | <b>Notes</b> |
|---------------|---|---------------------------|---|--------------|
| Oracle        | SL500: HP LTO6  | Symantec Netbackup 7.5    | Refer to storage vendor's support list, <a href="http://www.quantum.com/swcompguide.aspx">http://www.quantum.com/swcompguide.aspx</a> | 24           |
| Oracle        | SL500: HP LTO3, HP LTO4, HP LTO5, IBM LTO3, IBM LTO4, IBM LTO5 SL3000: HP LTO3, HP LTO4, HP LTO5, IBM LTO3, IBM LTO4, IBM LTO5, T10000C | EMC Networker 7.6.3       |   | 24           |

| <b>Vendor</b> | <b>Tape Library Model</b>   | <b>Backup Application</b> | <b>Firmware</b>  | <b>Notes</b> |
|---------------|---|---------------------------|--|--------------|
| Oracle        | SL8500: T10000B, T10000C  | IBM TSM6.2 , IBM TSM6.3.3 |  | 24,30        |
| Quantum       | i500: HP LTO4, HP LTO5, IBM LTO4, IBM LTO5<br>DXi6702: All supported emulated tape drives | Symantec Netbackup 7.5    | Refer to storage vendor's support list,<br><a href="http://www.quantum.com/swcompguide.aspx">http://www.quantum.com/swcompguide.aspx</a> | 24           |
| Quantum       | i500: HP LTO5, IBM LTO4, IBM LTO5   | Symantec Backup Exec      | Refer to storage vendor's support list,<br><a href="http://www.quantum.com/swcompguide.aspx">http://www.quantum.com/swcompguide.aspx</a> | 24           |
| IBM           | TS3584: IBM LTO4  | TSM 6.3                   |  | 24           |

### Switch Interoperability Matrix

Table 9 lists the switch models that are supported with this version of the Unified Computing System.

**Table 9: Switch**

| <b>Vendor</b> | <b>Switch Model</b>  | <b>Notes</b> |
|---------------|--|--------------|
| Brocade       | 6510: 7.1.0a, 7.1.0c, 7.0.2, 7.0.1b, 7.0.1a  | 2, 16        |
| Brocade       | 300, 5100, 5300: 7.1.0a, 7.1.0c, 7.0.2, 7.0.1b, 7.0.1a, 6.4.3b, 6.3.2e, 6.3.2d, 6.4.2b, 6.4.1b | 2, 16        |
| Brocade       | 4100, 48000, 4900, 5000: 5.2.1, 6.4.1b, 6.3.2a, 6.4.2a   | 2, 16        |
| Brocade       | 7500: 5.2.1, 6.4.1b  | 2, 16        |
| Brocade       | DCX-4S: 7.1.0a, 7.1.0c, 7.0.2, 7.0.1b, 7.0.1a, 6.4.3b, 6.3.2e, 6.3.2d, 6.4.2b, 6.4.1b          | 2, 16        |
| Brocade       | DCX: 7.1.0a, 7.1.0c, 7.0.2, 7.0.1b, 7.0.1a, 6.4.3b, 6.3.2e, 6.3.2d, 6.4.2b, 6.4.1b             | 2, 16        |
| Cisco         | MDS: 4.2.1b  | 1, 2, 9, 36  |
| Cisco         | Nexus 7000: 5.2(4)   | 1, 2, 9      |
| Cisco         | Nexus 5000: 5.1(3)N1(1)  | 1, 2, 9, 36  |

## Notes

- 1 Code levels greater than or equal to these listed versions are deemed by Cisco to be interoperable
- 2 The storage vendor's interoperability matrix should be consulted for switch software revisions that are supported with their arrays
- 3 SAN Boot requires removal of all local disks
- 4 Ethernet or FC driver required for installation not included in OS image or not supported, download driver from cisco.com
- 5 Direct Connect FC/FCoE topologies are supported with this array
- 6 Non-default adapter settings are typically required by storage vendors and found on their support list
- 7 Multiple array and switch models supported with UCS by the storage vendor are on their support list
- 8 Fiber Channel Storage that supports equivalent adapters and drivers is supported by UCS. UCS M71KR-E is equivalent to Emulex LP2100x, UCS M71KR-Q is equivalent to QLogic QLE804x, UCS M72KR-Q is equivalent to QLogic QLE8142/QUE8152, UCS M72KR-E is equivalent to Emulex OCe10102-F, UCS M73KR-Q is equivalent to QLogic QLE8242, UCS M73KR-E is equivalent to Emulex Oce11102-F
- 9 Specific switch features must be supported on all switches used, please consult release notes for each switch product to determine support for the desired feature
- 10 To upgrade to ESXi 4.0 U3 or U4 and ESXi 4.1 U1 or U2, 1st install the Cisco custom image (refer to note 23)
- 11 The listed driver version is required for support. The updated Driver CD is available from VMware.com > All Downloads > VMware vSphere > Drivers & Tools > VMware ESX/ESXi Driver CD for Cisco FCoE CNA
- 12 iSCSI Boot is supported. Both Appliance and Uplink ports are supported unless otherwise noted
- 13 Refer to the UCS 82598KR-CI 10-Gigabit Ethernet Adapter for the supported Ethernet driver on this Converged Network Adapter
- 14 The 2104XP fabric extender is not compatible when the 1240 and 1280 or 1240 and VIC Port Expander are combined on the same blade. Applies to B22 M3 and B200 M3 as well as B420 with 1240 and adapter slot 2 populated
- 15 Listed support is for the UEK Kernel only. For the RHEL compatible kernel, please refer to the RHEL versions
- 16 UCS Fabric Interconnect must be in FC End Host mode and upstream switch NPIV enabled
- 17 iSCSI Boot is not supported on Windows Server Core
- 18 All variations of OS are supported for this version, including Windows Server Core, Full and Hyper-V Standalone
- 19 The listed driver version is required for support. They are contained in the Cisco OEM Customized ESX ISO available from VMware.com > downloads > VMware vSphere Hypervisor (ESXi)
- 20 For C-Series servers managed by UCSM, unless stated in this document, the supported firmware and drivers will be in the 1.4(7) and 1.4(8) C-Series Compatibility guide
- 21 For ENIC and FNIC, use the drivers found on the B-Series Driver ISO

- 22** Listed support is for the UEK Kernel only. For the Red Hat Enterprise Linux compatible kernel, please refer to the Red Hat Enterprise Linux versions
- 23** Updating drivers during OS installation is currently not supported by Oracle. Update driver after the OS has completed installation.
- 24** Enable FCP error recovery in the service profile adapter policy
- 25** NIC Teaming driver is not currently supported with Hyper-V
- 26** Supported for NFS/CIFS access via appliance ports on the Fabric Interconnect
- 27** Requires Errata RHSA-2013:0168, reference bugzilla 884740
- 28** Requires Oracle OVM patch 14775391
- 29** For SAN installations, requires Citrix Hotfix CTX137403 during the installation, after installation is complete, apply CTX138731
- 30** Supported only with library management software version ACSLS8.2.
- 31** ESX NPIV Host Feature is not supported
- 32** Legacy Mode support only
- 33** Virtual Storage appliances are NPV Mode only. These require target to target zoning in direct connect topologies which is not supported with UCSM zoning.
- 34** Only UCS 785GB MLC Fusion-io ioDrive2, serial numbers FIO1717xxxx and newer, are supported on the B420 M3
- 35** NPV mode is not supported with this array
- 36** Certain Cisco Fabric Interconnects of the 6200 series have an OUI which will prevent FC port channels from connecting. This issue is outlined in CSCty04686 and can be mitigated by having your upstream Nexus 5000 code at a minimum version 6.0(2)N1(2), or MDS as minimum version 5.2(1)N1(4).

### Related Documentation

Links to the latest versions of related Cisco documentation are available in the *Cisco UCS Documentation Roadmap*, located at:

<http://www.cisco.com/go/unifiedcomputing/b-series-doc>

Cisco UCS B-Series Blade Server Software is available for download here:

<http://www.cisco.com/cisco/software/type.html?mdfid=283853163&flowid=25821>

### Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

<http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html>

Subscribe to the *What's New in Cisco Product Documentation* as a Really Simple Syndication (RSS) feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service and Cisco currently supports RSS version 2.0.