



INDEX

A

- activating server with Deactivated status [2-1](#)
- alerts, setting up notification of server status changes [1-2](#)
- automatic status changes
 - by server with Primary, events [3-8](#)
 - by server with Secondary, events [3-9](#)

C

- calls in progress, effects of changing server status [3-7](#)
- changing
 - cluster settings [1-3](#)
 - server status, manually [2-1](#)
 - server with Secondary status to Deactivated [2-1](#)
 - server with Secondary status to Primary [2-1](#)
- cluster, how it works [3-1](#)
- Cluster Configuration page, changing settings [1-3](#)
- configuring
 - task list [1-1](#)
 - the cluster [1-1](#)
- Connection Server Role Manager service, about [3-2](#)
- critical service, effects of stopping [3-7](#)
- customizing cluster settings [1-3](#)

D

- database replication [3-1](#)

E

- effects
 - of a split-brain condition [3-8](#)
 - of stopping a critical service [3-7](#)
 - on calls in progress when server status changes [3-7](#)
 - on web applications when server status changes [3-7](#)
- events when server status changes [3-8](#)

M

- manual status changes, events [3-9](#)
- message store replication [3-1](#)
- monitoring server status [3-2](#)

N

- notification of server status change alerts, setting up [1-2](#)

P

- ports
 - assignments of voice messaging to each server [3-4](#)
 - restarting to take calls [2-3](#)
 - stopping from taking new calls [2-3](#)
- publisher server, about [3-2](#)

R

- replication
 - of database and message store [3-1](#)
 - of voice messages [3-1](#)
- requirements for a cluster [3-6](#)

restarting all ports to take calls [2-3](#)

S

servers

- assignments of voice messaging ports [3-4](#)
- cluster requirements [3-6](#)
- configuring the cluster [1-1](#)
- effects on calls in progress when status changes [3-7](#)
- events when status changes [3-8](#)
- manually changing status [2-1](#)
- order for starting [2-1](#)
- publisher, about [3-2](#)
- shutting down [2-3](#)
- status functions in cluster [3-3](#)
- status monitoring [3-2](#)

server status changes, setting up notification of [1-2](#)

settings, customizing cluster [1-3](#)

setting up notification of server status change alerts [1-2](#)

shutting down servers [2-3](#)

split-brain condition, effects of [3-8](#)

starting servers, order [2-1](#)

status

- automatic change by server with Primary, events [3-8](#)
- automatic change by server with Secondary, events [3-9](#)
- Deactivated, activating manually [2-1](#)
- events when server changes [3-8](#)
- manual change, events [3-9](#)
- of servers [3-2](#)
- Secondary to Deactivated, changing manually [2-1](#)
- Secondary to Primary, changing manually [2-1](#)
- server, functions in cluster [3-3](#)

stopping a critical service, effects of [3-7](#)

stopping all ports from taking new calls [2-3](#)

V

voice message replication [3-1](#)

voice messaging ports, assignments to each server [3-4](#)

W

web applications, effects on when server status changes [3-7](#)

T

task list for configuring cluster [1-1](#)