



## CHAPTER 22

# Cisco Unity Connection SRSV Supported Platforms List

This chapter contains the following sections:

- [Hardware Supported by Cisco Unity Connection SRSV, page 22-1](#)
- [Specifications for Virtual Platform Hardware Supported by Cisco Unity Connection SRSV 9.1\(1\), page 22-2](#)

## Hardware Supported by Cisco Unity Connection SRSV

This section lists the supported hardware platforms and the minimum Cisco IOS software release required to support the hardware platform Cisco Unity Connection SRSV.

**Table 1**      *Specifications for Cisco Unity Connection SRSV*

Cisco Platform	Connection SRSV on SM-SRE-900-K9	Connection SRSV on SM-SRE-910-K9
Cisco 2911	15.1(4)M	15.1(4)M
Cisco 2921		
Cisco 2951		
Cisco 3925	15.1(4)M	15.1(4)M
Cisco 3945		
Cisco 3925E	15.1(4)M	15.1(4)M
Cisco 3945E		



### Note

A different Cisco IOS software release may be required depending on the version of Cisco Unified Communications Manager Express or Cisco Unified Survivable Remote Site Telephony (SRST) being used. For more information refer to Cisco Unified Communications Manager Express documentation available at <http://www.cisco.com/en/US/products/sw/voicesw/ps4625/index.html>.

# Specifications for Virtual Platform Hardware Supported by Cisco Unity Connection SRSV 9.1(1)

This section lists the supported hardware platforms and the minimum Cisco IOS software release required to support the hardware platform Cisco Unity Connection SRSV.

**Table 2** *Specifications for Cisco Unity Connection SRSV*

	<b>SM-SRE-900-K9</b>	<b>SM-SRE-910-K9</b>	<b>UCS E 140S</b>	<b>UCS E140D, E140DP, E160D, and E160 DP</b>
<b>Minimum Connection SRSV Version</b>	9.1(1)	9.1(1)	9.1(1)	9.1(1)
<b>vCPU (Number of Virtual Processors) Cores and Speed per Core</b>	<i>Connection 9.1(1) and later only: 1 @ a minimum of 2.0 GHz</i>	<i>Connection 9.1(1) and later only: 1 @ a minimum of 2.0 GHz</i>	<i>Connection 9.1(1) and later only: 1 @ a minimum of 2.0 GHz</i>	<i>Connection 9.1(1) and later only: 1 @ a minimum of 2.0 GHz</i>
<b>vRAM (Amount of Virtual RAM)</b>	4 GB	4 GB	4 GB	4 GB
<b>vDisk (Size of Virtual Hard Disks)</b>	1x160GB	1x160GB	1x160GB	1x160GB
<b>Total number of available voice ports<sup>1</sup></b>	8	8	8	8
<b>Total number of users with mailboxes</b>	200	200	200	200
<b>Approximate message storage, G-711 codec, minutes</b>	72,944	72,944	72,944	72,944
<b>Number of public distribution lists</b>	500	500	500	500
<b>Number of Call Handlers</b>	200	200	500	500
<b>Number of languages supported</b>	2	2	2	2

1. 8 ports G.711 or G.729a (combined TUI or TTS) and 2 ports iLBC or G.722