

Release Notes for *Cisco Unified Business/Department Attendant Console* Release v8.0.3.9

Revised: October 7th, 2010, OL-20133-01

These release notes describe the new features and caveats for Cisco Unified Business/Department Attendant Console Release v8.0.3.9

For a list of the open and resolved caveats for the Cisco Unified Business/Department Attendant Console see Resolved Caveats - Release v8.0.3.9 section on Page 13, and Open Caveats - Release v8.0.3.9 section on Page 14.

You can access the most current Cisco documentation at this URL: http://www.cisco.com/techsupport

You can access the Cisco website at this URL: http://www.cisco.com

You can access international Cisco websites at this URL: http://www.cisco.com/public/countries_languages.shtml



Contents

Introduction	2
Performance Information	2
Product Feature Table	3
System Requirements	6
Hardware/Software Supported	7
SQL Considerations and Scalability	8
Software Compatibility	12
Installation Notes	12
New and Changed Information	12
Caveats	13
Resolved Caveats - release v8.0.3.9	13
Open Caveats - release v8.0.3.9	14
Software	14
Related Documentation	15
Software Documents	15
Obtaining Documentation, Obtaining Support, and Security	15
Cisco Product Security Overview	15

Introduction

Cisco Unified Business/Department Attendant Console is an efficient application specially designed for handling calls and messages. This application enables you to answer calls from predefined set of queues and transfer them to desired extensions.

The application enables you to perform comprehensive tasks like Call Conference, Call Transfer, Call Parking and Call Retrievals. The user-friendly design of the application gives speed and flexibility and facilitates you to manipulate calls with simple mouse clicks or keystrokes.

Further detailed information can be obtained from the related documents, See "Related Documentation" on page 15

Performance Information

Performance of Cisco Unified Business/Department Attendant applications can be measured in several ways,

- 1. Number of Attendant (Operators)
- 2. Number of Contacts Supported
- 3. Number of Console Queues
- 4. Busy Hours Call Completions (BHCC)

Performance Item	Maximum numbers with Cisco Unified Business Attendant Console	Maximum numbers with Cisco Unified Department Attendant Console
Number of Attendant (Operators)	6	10
Number of Contacts Supported	500	750
Number of Console Queues	3	5
Busy Hours Call Completions (BHCC)	500	1000

Table 1-1 shows the performance of Cisco Unified Business/Department Attendant Console

Product Feature Table

The following table displays a break down by feature of the following products.

- Cisco Unified Department Attendant Console (CUDAC)
- Cisco Unified Business Attendant Console (CUBAC)
- Cisco Unified Enterprise Attendant Console (CUEAC)

The symbols denote the level of support within the product :-

```
\bullet = Supported, \bullet = Partial Support, \bullet = Unsupported
```

Table 1-2Product Feature table

Feature	CUDAC	CUBAC	CUEAC
Installation	Web & Wizard	Web & Wizard	Web & Wizard
Configuration	Browser	Browser	Browser
Support	Cisco TAC 3rd tier - Arc	Cisco TAC 3rd tier - Arc	Cisco TAC 3rd tier - Arc
Queue Features			
Queues supported	• 1 per instance (5 instances on a server)	• 3	• >50
Configurable queue names and priority	0	•	•
Show all calls in all queues option	0	•	•
Queue salutations	0	0	

Feature	CUDAC	CUBAC	CUEAC
Show & pick calls from each Queue	•	•	•
Queue wait time overflow	0	0	•
Queue limit overflow (no of calls)	•	•	•
Operator overflow (no operators)	•	•	•
Queue overflow destinations supported	•	•	•
Overflow options	•	•	•
Music in Queue	0	•	•
Operator Handset Ringing	•	•	•
Service options			
Emergency mode switch	0	•	•
Emergency mode destination	0	•	•
Night service switch	0	•	•
Night service hours/timing	0	•	•
Night service destination	0	•	•
Directory features			
Directory size supported	150 per instance (5 instances on a server)	500	100k
Search fields	3	4	6
Mobile number support	•	•	•
Internal directory support	•	•	•
External directory support		▶	



I

Feature	CUDAC	CUBAC	CUEAC
Speed dials	•	•	•
Alternative number search (hotkey)	•	•	•
Alternate Contacts search	0	0	•
Directory to XML phones	0	0	0
Cross tab searching	0	0	●
Notes against person	•	•	•
Presence / Status features			
Busy Lamp Fields / Phone Status supported	150 per instance (5 instances on a server)	500	7000
Presence integration with CUPS	•	•	•
Presence integration with OCS	• Locally	• Locally	• Locally
Telephony features			
Transfer Reversion (Call Recall)	•	•	•
Hold Recall	•	•	•
Call toggle	•	•	•
Camp on	0	0	•
Call hold with notes	0	0	●
Undirected Call park (finds first slot)	•	•	●
Directed Call Park (to specific Park location)	•	•	●
Call Hold	•	•	●

Table 1-2Product Feature table

L

Feature	CUDAC	CUBAC	CUEAC
Park recall	•	•	•
Transfer	•	•	•
Conference	•	•	•
System features		I	
No of Clients	2	6	25
Keyboard driven	•	•	•
System logging		▶	•
System Reports	0	•	
VMWare (ESXI-4)	•	•	•
Cisco Unified CallManager Supported			
CallManager Supported	7.0,7.1, 8.0	7.0,7.1, 8.0	7.0,7.1, 8.0
Localisation and accessibility			
Languages supported	1*(15)	1*(15)	1*(15)
Accessibility support (with JAWS Script)	•	•	•
Legend: \bullet = Supported, \bullet = Partial Suppo	rt, $O = Unsuppose$	rted	•

 Table 1-2
 Product Feature table

* The initial CUBAC / CUDAC (v8.0.3.9) release supports English. This will be expanded to the 15 core languages within later versions scheduled 2010.

Core Languages

When this product goes to full market release it is supported in 15 core languages. There are: English, French, Italian, German, Spanish, Portugese, Chinese (simpl), Chinese (trad.), Japanese, Korean, Arabic, Dutch, Swedish, Russian & Danish

System Requirements

The following section is broken into two parts:-

- Hardware/Software Supported
- Software Compatibility

Hardware/Software Supported

The information provided below gives details of the minimum hardware/software required to run Cisco Unified Business/Department Attendant applications.

Applies To	PC Specification
Cisco Unified	Pentium 4 2.2 GHz
Attendant Server	2 GB RAM
	72 GB Hard Drive
	CD-ROM/DVD-Rom
	Network Card
	SVGA (1024x768) display card with correct drivers
	Windows 2003 Server SP2 running Windows English Regional Settings. Windows 2008 Server R1 (32 bit) is also supported.
	For non-English characters the relevant language pack needs to be installed for the locale.
	Internet Information Service (IIS) 6.0 (or later). Windows 2008 Server R1 (32 bit) is also supported.
	.Net Framework 3.5
	MS SQL Server 2008 (Express) * (See "SQL Considerations and Scalabil- ity" on page 8 for further details).
	Internet Explorer 6.0 (or higher)**
	* Note: The Attendant Console Server installation will install this application automatically. If MS SQL Express 2008 is installed manually, is must be installed as the Default instance for the Attendant Console to function. Cisco Unified Attendant applications will not work with a Name instance of SQLExpress.
	** Note: If IIS is installed seperately to the Attendant Console Server Installation the ASP.NET component must be enabled and installed. This is via the <i>Add/Remove Windows Component > Applications Server</i> and <i>Details</i>

The Server should be connected to the network via the TCP/IP protocol.

You will require appropriate Operating System Licenses.

100
ver
d.
d

Cisco Unified Attendant Server is not supported within a 64 bit Operating System.

<u>Note</u>

Cisco Unified Attendant Server is not supported on the Cisco MCS (Media Convergence Server) Operating System

<u>Note</u>

If the Cisco Unified Attendant Server is installed on Windows 2003 or Windows 2008 Operating System then 'Data Execution Prevention (DEP)' must be enabled. This is documented in the 'Cisco Unified Business/Department Attendant Console Web Admin / Installation Guide' OL-20132-01



Cisco Unified Attendant Server is only supported in a live environment on VMWare EXSI version 4.0 and above. Cisco Unified Attendant Server is not supported in a live environment on HyperV or any other virtual based operating system.



Note

Access to the Cisco Unified Attendant Server is not supported at any time via Remote Desktop (RDP), Terminal Services (TS) or any other session based application. These applications can cause stability problems with the required TAPI/TSP and Wave Driver operation. Only local connection or VNC Connection is supported. See http://support.microsoft.com/kb/308405

SQL Considerations and Scalability

CUEAC installs SQL 2008 Express by default as part of its standard installation process. The performance limitation that SQL Server 2008 Express possesses is that it can access only a single CPU and 1 GB of RAM with a maximum database size of 4Gb.

In sites where one or more of the following are expected;-

- A large number of operators more than 10,
- A high call volume greater than 500 calls per operator per day,
- A Large Directory greater than 10,000 contacts;

The use of SQL Server 2008 Standard or Enterprise should be strongly considered. Where a system out grows the SQL2008 Express deployment, the Standard or Enterprise versions of SQL 2008 can be used to upgrade the existing implementation with minimal effort.



For future versions of CUEAC to benefit from some features, SQL 2008 express will not be an option and SQL 2008 Standard or Enterprise will be required.

2. The minimum specification required by Cisco Unified Business/Department Attendant Console is as follows,

Applies To	PC Specification
Applies to Cisco Unified Business/Depart- ment Attendant Console	Pentium 4 Entry Level Specification 1 GB RAM 1GB available Hard Drive space CD-ROM/DVD-ROM Network Card Connected to Network via TCP/IP SVGA (1024x768) display card Windows Small Fonts 17 inch Monitor highly recommended XP Professional / Vista Professional (32 bit and WoW64) / Windows 2003/2008 and Windows 7 (32 bit and WoW64) (See Note below this table). SoundBlaster compatible sound card and speakers are recommended
	for the Console Operator.

<u>Note</u>

If the Cisco Unified Business/Department Attendant Console is installed on Windows 2003 or Windows 2008 Operating System then 'Data Execution Prevention (DEP)' must be enabled. This is documented in the 'Cisco Unified Business/Department Attendant Console Web Admin / Installation Guide' OL-20132-01.



If you are installing Cisco Unified Business/Department Attendant Console client on Windows Vista or Windows 2008, there is an additional process that you need to complete by disabling the User Account Control. This is documented in the '*Cisco Unified Business/Department Attendant Console Web Admin / Installation Guide' OL-20132-01.*



Cisco Unified Attendant Server is only supported in a live environment on VMWare EXSI version 4.0 and above.

Cisco Unified Attendant Server is not supported in a live environment on HyperV or any other virtual based operating system.



Access to the Cisco Unified Attendant Server is not supported at any time via Remote Desktop (RDP), Terminal Services (TS) or any other session based application. These applications can cause stability problems with the required TAPI/TSP and Wave Driver operation. Only local connection or VNC Connection is supported. See http://support.microsoft.com/kb/308405

Note

If the Attendant Operator is using a 7931 handset maximum calls on the UCM needs to be configured to a minimum of two.



If the Attendant Operator is using 89xx and 99xx phones as their handsets they will need to disable rollover feature on the UCM.

3. Backups – As with all systems, we advise that backup facilities are provided to ensure application and data integrity, should an unforeseen circumstance arise.

Examples:

CD Writer Tape streamer. DLT, DAT, Travan etc Zip / Jaz drive or other type of Magneto Optical drive

If possible, choose a solution that gives a one step disaster recovery. This is a solution that has the ability to restore the complete contents of a hard drive from a bootable floppy disk and the restore media.

4. Server Redundancy – It is strongly recommended that the PC Server should be a redundant system with the following redundancy methods. This is at the discretion of the customer

Multiple hot-swap power supplies Hot-swap Hard Drive arrays UPS / power conditioners RAID

5. AntiVirus support on a Cisco Unified Business/Department Attendant Console Server

There are many different AntiVirus products that are supported on a Cisco Unified Business/Department Attendant Console system server. Supporting guidelines on AntiVirus software can be found on the following site:-

http://www.cisco.com/en/US/prod/collateral/voicesw/ps6788/vcallcon/ps556/prod_bulletin0900aec d806f6221.html

Folder/File Exclusions

It is important that the AntiVirus product supports "Exclusions". This is the ability for the user to specify specific files and/or folders that will NOT be scanned by the AntiVirus program.

The following exclusions should be set when using AntiVirus on a Cisco Unified Business/Department Attendant Console Server

File Location	Use
\\DBData	This folder is where the System Configuration Databases are located
\\Program Files\Cisco\Logging	This is where all the system log files are stored.
\\Temp\Cisco\Trace	This is where the Cisco TSP Trace files are located



The "File Locations" and "File Names" may be changed by your System Administrator.

The files in the above table are constantly being written to and updated during standard operation of the Cisco Unified Business/Department Attendant Console system.

Due to this, these files are permanently being accessed - an AntiVirus "Scan on access" policy for these files will mean that the files are constantly being scanned for Viruses. This will in turn slow down the operation of the Server. Therefore, excluding these files from being continuously scanned will allow the Server to function as expected.

Applies To	Network Specification
All Network	The network will need to support/run TCP/IP.
Types	Cisco Unified Business/Department Attendant Admin application will need to run under an Administrator profile. (Local Administrator is acceptable)
Microsoft Windows Network	If the network uses DHCP then the PC Server will need a <u>static IP address</u> allocated to it.

6. The following table outlines the network requirements for running Cisco Unified Business/Department Attendant applications.

Software Compatibility

CUBAC/CUDAC Version	CUBAC/CUDAC-CM TSP Version	Cisco Unified Communication Manager (CUCM)
v8.0.3.9	7.0 (1.6)	7.0
	7.1(1.4)	7.1
	7.1(1.5)	7.1(2A)
	7.1(3.4)	7.1(3)
	7.1(5.2)	7.1(5)
	8.0(1.6)	8.0

Installation Notes

The installation instructions for Cisco Unified Business/Department Attendant Console are covered in Chapter 4 of the Cisco Unified Business/Department Attendant Consoles Web Admin / Installation Guide which is available via the following address:

http://www.cisco.com/en/US/products/ps7282/prod_maintenance_guides_list.html

New and Changed Information

New software Features in Release v8.0.3.9

Cisco Unified Business/Department Attendant Console v8.0.3.9 includes the following features:

- Music in Queue (Not available in Cisco Unified Department Attendant Console)
- Wait Time Overflow (Not available in Cisco Unified Department Attendant Console)
- Forced Delivery (Operator Handset Ringing)
- Microsoft OCS 2007 Presence Status
- System Reports (Not available in Cisco Unified Department Attendant Console)
- GUI improvements to the Attendant Console to improve access to Preferences and Contact Details.
- Switch from UCM End User to UCM Application User
- Session Based Licensing (Not available in Cisco Unified Department Attendant Console)
- Allow 1 Attendant per queue This is Cisco Unified Department Attendant Console Only)
- Unicode Support enhancements to improve localization of data for the core 15 languages.
- Support for VMWare (ESXI-4).
- Windows 7 (32 bit and WoW64) support for the Attendant Console
- Support for JAWS 10 accessibility software
- Support for CUPs 7 and 8

Caveats

This section contains these topics:

- Resolved Caveats Release v8.0.3.9, Page 11
- Open Caveats Release v8.0.3.9, page 11

Resolved Caveats - Release v8.0.3.9

Table 3 lists Severity 3 Caveats that have been resolved in Cisco Unified Business/DepartmentAttendant Console v8.0.3.9

The following table shows a list of caveats that have been found during testing.

Application	Description
CSCta22478	CUBAC should interpret the CtiProgressingState received from the CUCM
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCta22478
CSCti81645	Console server crashes and does logs/lock out users
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCti81645
CSCtf65400	CUxAC is unable to get Presence states if CUPS is on multi cluster
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtf65400
CSCti16473	BLF Display Inconsistency
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCti16473
CSCth83651	CUEAC Server becoming slow and/or unresponsive due to CPU utilization sp
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCth83651
CSCti14229	CUxAC CUPS Service (engine) crash
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCti14229
CSCth96971	Not showing CLI on CUEAC Desktop for External Calls
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCth96971
CSCth04364	BLF delay 10-15 seconds when search users in Operator Console
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCth04364
CSCtg35613	CUxAC Installation Guide reflect stand alone server/PC
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtg35613

Table 3 Resolved Caveats for Cisco Unified Business/Department Attendant Console - v8.0.3.9

CSCtg09271	CUxAC Installation Doc - create template with unique DN
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtg09271
CSCte83877	Download Page Should List the Release Date
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCte83877
CSCtj21625	Documentation for all versions should list NIC Teaming is not supported
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtj21625
CSCtj21646	Windows 7 32 and 64 bit is not supported on the AC PC
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtj21646
CSCtg27977	CUxAC LDAP directory sync does not update MAC address
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtg27977
CSCtd44265	Mute button on the client console does not perform expected behavior
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtd44265
CSCti88240	CUEAC 3.1.1.10 getting stuck, need to restart
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCti88240

Open Caveats - Release v8.0.3.9

 Table 4 lists Severity 3 Caveats that have been Opened in Cisco Unified Business/Department Attendant

 Console v8.0.3.9

The following table shows a list of caveats that have been found during testing.

Application	Description
CSCti31896	BLF Fails in CUxAC 8.0.0.5 when Route Partition is Configured
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCti31896
CSCtj21684	Cisco UCS virtualization is not supported
	http://tools.cisco.com/Support/BugToolKit/search/getBugDetails.do?method=fetch BugDetails&bugId=CSCtj21684

Table 4 Open Caveats for Cisco Unified Business/Department Attendant Console - v8.0.3.9

Software

The Cisco Unified Business/Department Attendant Console software can be downloaded from the following website:- http://www.cisco.com/go/ac

Related Documentation

Software Documents

The documents related to this product include:

- Cisco Design Guide v8_0_x
- Cisco Unified Business/Department Attendant Console User Guide
- Cisco Unified Business/Department Attendant Console Web Admin / Installation Guide -

Obtaining Documentation, Obtaining Support, and Security

For information on obtaining documentation, obtaining support, providing documentation feedback, security guidelines, and also recommended aliases and general Cisco documents, see the monthly *What's New* in Cisco Product Documentation, which also lists all new and revised Cisco technical documentation, at:

http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html

Cisco Product Security Overview

This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product you agree to comply with applicable laws and regulations. If you are unable to comply with U.S. and local laws, return this product immediately.

A summary of U.S. laws governing Cisco cryptographic products may be found at: http://www.cisco.com/wwl/export/crypto/tool/stqrg.html. If you require further assistance please contact us by sending email to export@cisco.com. This document is to be used in conjunction with the documents listed in the "Related Documentation" section.

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco Ironport, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco Stackpower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flip Video, Flip Video (Design), Flipshare (Design), Flip Ultra, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Store, and Flip Gift Card are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0907R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2010 Cisco Systems, Inc. All rights reserved.

Printed in the USA on recycled paper containing 10% postconsumer waste.