

Backing Up and Restoring Data

Last updated: April 13, 2010

Cisco Unified Messaging Gateway backup and restore functions use an FTP server to store and retrieve data. The backup function copies the files from the Cisco UMG module to the FTP server and the restore function copies the files from the FTP server to the Cisco UMG application. The FTP server can reside anywhere in the network as long as the backup and restore functions can access it with an IP address or hostname.

Note

Setting up a backup server is part of the initial configuration process. If you have not already done this, see "Setting Backup Parameters" on page 22.

Do backups regularly to preserve configuration data.

Backing up and restoring both require offline mode, so they are best done when call traffic is least impacted. Before you take the system offline, decide what type of files you will back up:

- **all** files (configuration and data)
- **only data** files (includes dynamic data such as local endpoint IDs, mailboxes and system distribution lists)



Caution

n We strongly discourage doing the 'data only' type of backup and restore because of its potential to introduce inconsistency between configuration and data files.

• **only configuration** files (includes the local messaging gateway ID, messaging gateway peers, manually configured endpoints, registration credentials, and NAT data)



Offline mode terminates message forwarding and directory exchange. We recommend doing backups when call traffic is least impacted.

This chapter contains the following sections:

- Restrictions, page 46
- Backing Up Files, page 46
- Restoring Files, page 49

Restrictions

Cisco UMG does not support the following backup and restore capabilities:

- Scheduled backup and restore operations. The backup and restore procedures begin when the appropriate command is entered.
- Centralized message storage arrangement. Cisco UMG backup files cannot be used or integrated with other message stores.
- Selective backup and restore. Only full backup and restore functions are available. Individual messages or other specific data can be neither stored nor retrieved.



If you delete an endpoint, then do a system restore, the update will erase the information that the endpoint was deleted. You must reset it from the endpoint's primary messaging gateway.

Backing Up Files

Three types of backups are available: data only, configuration only, or all.

- Data—includes local endpoint IDs, mailboxes and system distribution lists (SDLs).
- Configuration—includes local peers, manually configured endpoints, credentials, and NAT.
- All—Backs up all data and configuration information.

Perform backups only in offline mode.

Cisco UMG automatically assigns a backup ID to each backup. Although there are the three different types of backups, backup ID assignment takes no account of data type, so that you would never find two backups with the same backup ID, even if one is a configuration file and the other a data file.

To determine the backup ID of the file you want to restore, use the **show backup server** or **show backup history** command in either EXEC or offline mode. That command lists all available back copies on the remote backup server and their respective backup IDs.



We recommend that you back up your configuration files whenever you make changes to the system or application files.



Offline mode terminates all message forwarding. We recommend doing backups when call traffic is least impacted.

SUMMARY STEPS

- 1. offline
- 2. backup category {all | configuration | data}
- 3. continue
- 4. show backup history
- 5. show backup server

DETAILED STEPS

	Command or Action	Purpose
Step 1	offline	Enters offline mode. All message forwarding is terminated.
	Example: umg-1# offline	
Step 2	backup category {all configuration data}	Specifies the type of data to be backed up and stored.
	Example: umg-1(offline)# backup category all umg-1(offline)# backup category configuration umg-1(offline)# backup category data	
Step 3	continue	Exits offline mode and enters EXEC mode.
	Example: umg-1(offline)# continue	
Step 4	show backup history	Displays the success or failure of the backup and restore procedures, and also the backup IDs.
	Example:	
	umg-1# show backup history	
Step 5	show backup server	Displays the backup files available on the backup server, the date of each backup, and the backup file
	Fxamnle [,]	ID.
	umg-1# show backup server	
Step 5	Example: umg-1# show backup history show backup server Example: umg-1# show backup server	Displays the backup files available on the backup server, the date of each backup, and the backup file ID.

Examples

The following examples display the output from the **show backup history** and **show backup server** commands:

```
#Start Operation
Category:
          Configuration
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation: Backup
Backupid:
             2
Restoreid:
            -1
Description: test backup 1
            Sun Jun 13 12:32:48 PDT 1993
Date:
Result:
             Success
Reason:
#End Operation
#Start Operation
Category: Data
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation: Backup
Backupid:
            2
Restoreid:
             -1
Description: umg-1 test backup
```

umg-1# show backup history

```
Sun Jun 13 12:32:57 PDT 1993
Date:
Result:
              Success
Reason:
#End Operation
#Start Operation
Category: Configuration
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation: Restore
Backupid:
              2
Restoreid:
              1
Description:
              Sun Jun 13 12:37:52 PDT 1993
Date:
Result:
             Success
Reason:
#End Operation
#Start Operation
Category:
              Data
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation:
              Restore
Backupid:
              2
Restoreid:
              1
Description:
             Sun Jun 13 12:38:00 PDT 1993
Date:
Result:
             Success
Reason:
#End Operation
umg-1# show backup server
Category:
             Data
Details of last 5 backups
Backupid: 1
             Tue Jul 22 10:55:52 PDT 2003
Date:
Description:
Backupid:
             2
             Tue Jul 29 18:06:33 PDT 2003
Date:
Description:
Backupid: 3
Date: Tue Jul 29 19:10:32 PDT 2003
Description:
             Configuration
Category:
Details of last 5 backups
Backupid:
           1
             Tue Jul 22 10:55:48 PDT 2003
Date:
Description:
Backupid:
             2
Date:
             Tue Jul 29 18:06:27 PDT 2003
Description:
Backupid:
             3
             Tue Jul 29 19:10:29 PDT 2003
Date:
Description:
umg-1#
```

Restoring Files

After you create the backup files, you can restore them when needed. Restoring is done in offline mode, which terminates all message forwarding calls. You should therefore consider restoring files when call traffic is least impacted.

To determine the backup ID of the file you want to restore, use the **show backup server** or **show backup history** command in either EXEC or offline mode.

SUMMARY STEPS

- 1. show backup server
- 2. offline
- 3. restore id *backup-id* category {all | configuration | data}
- 4. show backup history
- 5. reload

DETAILED STEPS

	Command or Action	Purpose
Step 1	show backup server	Lists the data and configuration backup files. Look in the backup ID field for the revision number of the file
	Example: umg-1# show backup server	that you want to restore.
Step 2	offline	Enters offline mode. All message forwarding is terminated.
	Example: umg-1# offline	
Step 3	<pre>restore id backupid category {all configuration data}</pre>	Specifies the backup ID <i>backupid</i> value and the file type to be restored.
	Example: umg-1(offline)# restore id 22 category all umg-1(offline)# restore id 8 category configuration umg-1(offline)# restore id 3 category data	
Step 4	show backup history	Displays the success or failure of backup and restore procedures, and also the backup IDs.
	Example: umg-1# show backup history	
Step 5	reload	Resets Cisco UMG so that the restored values take effect.
	Example: umg-1(offline)# reload	

Examples

The following examples display the contents of the backup server and the backup history:

umg-1# show backup server

Data

Category:

Details of last 5 backups Backupid: 1 Tue Jul 22 10:55:52 PDT 2003 Date: Description: Backupid: 2 Date: Tue Jul 29 18:06:33 PDT 2003 Description: Backupid: 3 Tue Jul 29 19:10:32 PDT 2003 Date: Description: Configuration Category: Details of last 5 backups Backupid: 1 Tue Jul 22 10:55:48 PDT 2003 Date: Description: 2 Backupid: Tue Jul 29 18:06:27 PDT 2003 Date: Description: Backupid: 3 Tue Jul 29 19:10:29 PDT 2003 Date: Description: uma-1# umg-1# show backup history Start Operation Configuration Category: Backup Server: ftp://10.100.10.215/umg-1_backup Operation: Backup 1 Backupid: Restoreid: -1 Description: test backup 1 Sun Jun 13 12:23:38 PDT 1993 Date: Result: Failure Reason: Script execution failed: /bin/BR_VMConfg_backup.sh: returnvalue:1 ; Server Url:ftp://10.100.10.215/umg-1_backup: returnvalue:9 Unable to authenticate #End Operation #Start Operation Category: Data Backup Server: ftp://10.100.10.215/umg-1_backup Operation: Backup Backupid: 1 -1 Restoreid: Description: test backup 1 Sun Jun 13 12:23:44 PDT 1993 Date: Result: Failure Reason: Script execution failed: /bin/BR_VMData_backup.sh: returnvalue:1 Messaging Backup failed; Server Url:ftp://10.100.10.215/umg-1_backup: returnvalue:9 Unable to authenticate

#End Operation

```
#Start Operation
Category: Configuration
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation: Backup
Backupid:
             2
Restoreid:
             -1
Description: umg-1 test backup
             Sun Jun 13 12:32:48 PDT 1993
Date:
             Success
Result:
Reason:
#End Operation
#Start Operation
Category: Data
Backup Server: ftp://10.100.10.215/umg-1_backup
Operation: Backup
Backupid:
             2
Restoreid:
             -1
Description: umg-1 test backup
Date:
             Sun Jun 13 12:32:57 PDT 1993
Result:
             Success
Reason:
#End Operation
```