



Error and Event Messages

This appendix lists the CLI error and event messages.

Conventions

System error messages are displayed in the format shown in [Table C-1](#).

Table C-1 **System Error Message Format**

Message Component	Description	Example
Error identifier	A string categorizing the error.	STATION_ROLE
Software component	A string identifying the software component of the error.	AUTO_INSTALL
Severity Level	A string indicating the severity of the error.	LOG_DEBUG—debug information (not serious) LOG_INFO—informational (not serious) LOG_NOTICE—notice that may be of concern to user LOG_WARNING—warning that user can ignore if they prefer LOG_ERR—warning of error condition, most features functional; user should exercise care LOG_CRIT—warns of a possible serious critical error LOG_ALERT—alerts user to a very serious problem LOG_EMERG—emergency situation, nothing is functional

Table C-1 System Error Message Format (continued)

Message Component	Description	Example
Action Flags	Internal to the code for which additional action is displayed.	0—No action flag MSG_TRACEBACK—includes traceback with message MSG_PROCESS—includes process information with message MSG_CLEAR—indicates condition had cleared MSG_SECURITY—indicates as security message MSG_NOSCAN—suppresses EEM pattern screening
%d	An integer number.	2450
%e	A MAC address.	000b.fcff.b04e
%s	A message string which provides more detail of the error.	“Attempt to protect port 1640 failed.”
%x	A hexadecimal number.	0x001

Software Auto Upgrade Messages

Error Message FATAL_FAILURE, SW_AUTO_UPGRADE, LOG_CRIT, MSG_PROCESS: “Attempt to upgrade software failed, software on flash may be deleted. Please copy software into flash.

Explanation Auto upgrade of the software failed. The software on the flash might have been deleted. Copy software into the flash.

Recommended Action Copy software before rebooting the unit.

Error Message DHCP_CLIENT_FAILURE, SW_AUTO_UPGRADE, LOG_DEBUG, MSG_TRACEBACK | MSG_PROCESS, “%s”: Auto upgrade of the software failed.”

Explanation Auto upgrade of the software failed.

Recommended Action Make sure that the DHCP client is running.

Error Message DHCP_SERVER_FAILURE, SW_AUTO_UPGRADE, LOG_DEBUG, MSG_TRACEBACK | MSG_PROCESS, “%s”: Auto upgrade of the software failed.”

Explanation Auto upgrade of the software failed.

Recommended Action Make sure that the DHCP server is configured correctly.

Error Message BOOT_FAILURE, SW_AUTO_UPGRADE, LOG_DEBUG, MSG_TRACEBACK, MSG_PROCESS, "%s": Auto upgrade of the software failed."

Explanation Auto upgrade of the software failed.

Recommended Action Reboot the unit. If the message appears again, copy the error message exactly as it appears and report it to your technical support representative.

Error Message STATION_ROLE, AUTO_INSTALL, LOG_WARNING, 0, "%s": The radio is operating in automatic install mode."

Explanation The radio is operating in automatic install mode.

Recommended Action Use the **station-role** configuration interface command to configure the radio for a role other than install mode.

Error Message IP_ADDRESS_DHCP, AUTO_INSTALL, LOG_WARNING, 0: "The radio is operating in automatic install mode and has set ip address dhcp."

Explanation The radio is operating in automatic install mode and is configured to receive an IP address through DHCP.

Recommended Action Use the **station-role** configuration interface command to configure the radio for a role other than install mode.

Error Message STATUS_AUTO_INSTALL, LOG_INFO, 0, "%s" %s. RSSI=-%d dBm.: The radio is operating in install mode."

Explanation The radio is operating in automatic install mode.

Recommended Action Use the **station-role** configuration interface command to configure the radio for a role other than install mode.

Error Message AUTO-INSTALL-6_STATUS: "%s" %s. RSSI=-%d dBm.: The radio is operating in install mode."

Explanation The radio is operating in automatic install mode.

Recommended Action Use the **station-role** configuration interface command to configure the radio for a role other than install mode.

Association Management Messages

Error Message BADSTATE, DOT11, LOG_ERR, 0, "%s %s ->%s."

Explanation 802.11 association and management uses a table-driven state machine to keep track and transition an association through various states. A state transition occurs when an association receives one of many possible events. When this error occurs, it means that an association received an event that it did not expect while in this state.

Recommended Action The system can continue but may lose the association that generates this error. Copy the message exactly as it appears and report it to your technical service representative.

Error Message ASSOC, DOT11, LOG_INFO, 0, "Interface %s, Station %s e% %s KEY_MGMT (%s)."

Explanation The indicated station associated to an access point on the indicated interface.

Recommended Action None.

Error Message ADD, DOT11, LOG_INFO, 0 "Interface %s, Station %e associated to parent %e."

Explanation The indicated station associated to the parent access point on the indicated interface.

Recommended Action None.

Error Message DISASSOC, DOT11, LOG_INFO, 0, "Interface %s, Deauthenticating Station %e %s."

Explanation The indicated station disassociated from the access point on the indicated interface.

Recommended Action None.

Error Message ROAMED, DOT11, LOG_INFO, 0, "Station %e roamed to %e."

Explanation The indicated station roamed to the indicated new access point.

Recommended Action None.

Error Message ENCRYPT_MISMATCH, DOT11, LOG_WARNING, 0, "Possible encryption key mismatch between interface %s and station %e."

Explanation The encryption setting of the indicated interface and indicated station may be mismatched.

Recommended Action Check the encryption configuration of this interface and the failing station to ensure that the configurations match.

Unzip Messages

Error Message UNZIP_OVERFLOW, SOAP, LOG_WARNING, MSG_TRACEBACK: "Failed to unzip %s, exceeds maximum uncompressed html size."

Explanation The HTTP server cannot retrieve a compressed file in response to an HTTP GET request because the file is too large for the buffers used in the uncompression process.

Recommended Action Make sure that the file is a valid HTML page. If it is, you need to copy an uncompressed version of the file into Flash to retrieve it through HTTP.

802.11 Subsystem Messages

Error Message FREQ_USED, DOT11, LOG_INFO, 0 "Interface %s, frequency %d selected."

Explanation After scanning for an unused frequency, the indicated interface selected the displayed frequency.

Recommended Action None.

Error Message NO_VALID_INFRA_SSID, DOT11, LOG_WARNING, 0, "No infrastructure SSID configured. %s not started."

Explanation No infrastructure SSID was configured and the indicated interface was not started.

Recommended Action Add at least one infrastructure SSID to the radio configuration.

Error Message VERSION_UPGRADE, DOT11, LOG_WARNING, 0, "Interface %d, upgrading radio firmware."

Explanation When starting the indicated interface, the access point found the wrong firmware version. The radio will be loaded with the required version.

Recommended Action None.

Error Message VERSION_INVALID, DOT11, LOG_CRIT, 0, "Interface %d, unable to find required radio version %x.%x/ %d/

Explanation When trying to re-flash the radio firmware on the indicated interface, the access point recognized that the indicated radio firmware packaged with the Cisco IOS software had the incorrect version.

Recommended Action None.

Error Message RADIO_OVER_TEMPERATURE, DOT11, LOG_ERR, 0, "Interface %s Radio over temperature detected."

Explanation The radio's internal temperature exceeds maximum limits on the indicated radio interface.

Recommended Action Take steps necessary to reduce the internal temperature. These steps will vary based on your specific installation.

Error Message RADIO_TEMPERATURE_NORMAL, DOT11, LOG_INFO, 0, "Interface %s radio temperature returned to normal."

Explanation The radio's internal temperature has returned to normal limits on the indicated radio interface.

Recommended Action None.

Error Message TX_PWR_OUT_OF_RANGE, DOT11, LOG_ERR, 0, "Interface %s Radio transmit power out of range."

Explanation The transmitter power level is outside the normal range on the indicated radio interface.

Recommended Action Remove unit from the network and service.

Error Message RADIO_RF_LO, DOT11, LOG_ERR, 0, "Interface %s Radio cannot lock RF freq."

Explanation The radio phase lock loop (PLL) circuit is unable to lock the correct frequency on the indicated interface.

Recommended Action Remove unit from network and service.

Error Message RADIO_IF_LO, DOT11, LOG_ERR, 0, "Interface %s Radio cannot lock IF freq."

Explanation The radio intermediate frequency (IF) PLL is unable to lock the correct frequency on the indicated interface.

Recommended Action Remove unit from network and service.

Error Message FREQ_SCAN, DOT11, LOG_INFO, 0, "Interface %s Scanning frequencies for %d seconds."

Explanation Starting a scan for a least congested frequency on the interface indicated for a the time period indicated.

Recommended Action None.

Error Message NO_CHAN_AVAIL, DOT11, LOG_CRIT, 0, "Interface %s, no channel available."

Explanation No frequency is available, likely because RADAR has been detected within the previous 30 minutes.

Recommended Action None.

Error Message DFS_SCAN_COMPLETE, DOT11, LOG_INFO, 0, "DFS scan complete on frequency %d MHz."

Explanation The device has completed its Dynamic Frequency Scan (DFS) frequency scanning process on the displayed frequency.

Recommended Action None.

Error Message DFS_SCAN_START, DOT11, LOG_INFO, 0, "DFS: Scanning frequency %d MHz for %d seconds."

Explanation The device has begun its DFS scanning process.

Recommended Action None.

Error Message DFS_TRIGGERED, DOT11, LOG_INFO, 0, "DFS: triggered on frequency %d MHz."

Explanation DFS has detected RADAR signals on the indicated frequency.

Recommended Action None. The channel will be placed on the non-occupancy list for 30 minutes and a new channel will be selected.

Error Message DFS_STORE_FAIL, DOT11, LOG_WARNING, 0, "DFS: could not store the frequency statistics."

Explanation A failure occurred writing the DFS statistics to flash.

Recommended Action None.

Error Message NO_SSID, DOT11, LOG_WARNING, 0, "No SSIDs configured, %d not started."

Explanation All SSIDs were deleted from the configuration. At least one must be configured for the radio to run.

Recommended Action Configure at least one SSID on the access point.

Error Message NO_SSID_VLAN, DOT11, LOG_WARNING, 0, "No SSID with VLAN configured. %s not started."

Explanation No SSID was configured for a VLAN. The indicated interface was not started.

Recommended Action At least one SSID must be configured per VLAN. Add at least one SSID for the VLAN on the indicated interface.

Error Message NO_MBSSID_VLAN, DOT11, LOG_WARNING, 0, "No VLANs configured in MBSSID mode. %s not started."

Explanation No VLAN configured in MBSSID mode. The indicated interface was not started.

Recommended Action Add at least one SSID with the VLAN on the indicated interface configuration.

Error Message FW_LOAD_DELAYED, DOT11, LOG_WARNING, 0, "Interface %s, network filesystem not ready. Delaying firmware (%s) load."

Explanation The network filesystem was not running or not ready when trying to flash new firmware into the indicated interface. Loading the identified firmware file has been delayed.

Recommended Action Make sure the network is up and ready before attempting to reflash the new firmware.

Error Message FLASH_UNKNOWN_RADIO, DOT11, LOG_CRIT, 0, "Interface %s has an unknown radio."

Explanation The radio type could not be determined when the user attempted to flash new firmware into the indicated interface.

Recommended Action Reboot the system and see if the firmware upgrade completes.

Error Message UPLINK_ESTABLISHED, DOT11, LOG_WARNING, 0, "Interface %s associated to AP %s %e %s."

Explanation The indicated repeater has associated to the indicated root access point. Clients can now associate to the indicated repeater and traffic can pass.

Recommended Action None.

Error Message UPLINK_FAILED, DOT11, LOG_CRIT, 0 "Uplink to parent failed: %s."

Explanation The connection to the parent access point failed for the displayed reason. The uplink will stop its connection attempts.

Recommended Action Try resetting the uplink interface. Contact Technical Support if the problem persists.

Error Message CANT_ASSOC, DOT11, LOG_WARNING, 0 "Interface %, cannot associate %s."

Explanation The indicated interface device could not associate to an indicated parent access point.

Recommended Action Check the configuration of the parent access point and this unit to make sure there is a match.

Error Message PROCESS_INITIALIZATION_FAILED, DOT11, LOG_CRIT, 0 "The background process for the radio could not be started: %s)

Explanation The initialization process used by the indicated interface failed for some reason, possibly a transient error.

Recommended Action Perform a reload of the access point. If this fails to rectify the problem, perform a power cycle. If this still fails, try downgrading the access point firmware to the previous version.

Error Message RADIO_HW_RESET, DOT11, LOG_CRIT, 0 "Radio subsystem is undergoing hardware reset to recover from problem."

Explanation An unrecoverable error occurred that could not be resolved by a soft reset.

Recommended Action None.

Error Message MAXRETRIES, DOT11, LOG_WARNING, 0, "Packet to client %e reached max retries, removing the client."

Explanation The maximum packet send retry limit has been reached and the client is being removed.

Recommended Action Investigate and correct the client malfunction.

Error Message RM_INCAPABLE, DOT11, LOG_WARNING, 0 "Interface %s

Explanation Indicated interface does not support the radio management feature.

Recommended Action None.

Error Message RM_INCORRECT_INTERFACE, DOT11, LOG_WARNING, 0, "Invalid interface, either not existing or non-radio."

Explanation A radio management request discovered that the interface either does not exist or is not a radio interface.

Recommended Action None.

Error Message POWERS_INVALID, DOT11, LOG_ERR, 0, "Interface %s, no valid power levels available."

Explanation The radio driver found no valid power level settings.

Recommended Action Investigate and correct the power source and settings.

Error Message RADIO_INVALID_FREQ, DOT11, LOG_WARNING, 0, "Operating frequency (%d) invalid - performing a channel scan."

Explanation The indicated frequency is invalid for operation. A channel scan is being performed to select a valid frequency.

Recommended Action None.

Error Message RADIO_INITIALIZATION_ERRO, DOT11, LOG_CRIT, 0, "The radio subsystem could not be initialized (%s)."

Explanation A critical error was detected while attempting to initialize the radio subsystem.

Recommended Action Reload the system.

Error Message UPLINK_NO_ID_PWD, DOT11, LOG_WARNING, 0 "Interface %s, no username/password supplied for uplink authentication."

Explanation The user failed to enter a username and/or password.

Recommended Action Enter the username and/or password and try again.

Error Message NO_IE_CFG, DOT11, LOG_WARNING, MSG_TRACEBACK, "No IEs configured for %s (ssid index %u)."

Explanation When attempting to apply a beacon or probe response to the radio, the beacon or probe was undefined on the indicated SSID index.

Recommended Action Check the IE configuration.

Error Message FLASHING_RADIO, DOT11, LOG_WARNING, 0, "Interface %s, flashing radio firmware (%s)."

Explanation The indicated interface radio has been stopped to load the indicated new firmware.

Recommended Action None.

Error Message LOADING_RADIO, DOT11, LOG_WARNING, 0, "Interface %s, loading the radio firmware (%s)."

Explanation The indicated interface radio has been stopped to load new indicated firmware.

Recommended Action None.

Error Message NO_FIRMWARE, DOT11, LOG_CRIT, 0 "Interface %s, no radio firmware file (%s) was found."

Explanation When trying to flash new firmware, the file for the radio was not found in the Flash file system.

Recommended Action The wrong image has been loaded into the unit. Locate the correct image based on the type of radio used.

Error Message BAD_FIRMWARE DOT11, LOG_CRIT, 0, "Interface %s, radio firmware file (%s) is invalid."

Explanation When trying to Flash new firmware into the indicated interface the indicated radio firmware file was found to be invalid.

Recommended Action Make sure the correct firmware image file is located in the place where the unit expects to find it.

Error Message RADIO_FAILED, DOT11, LOG_CRIT, MSG_TRACEBACK, "Interface %s, failed - %s."

Explanation The radio driver on the indicated interface found a severe error and is shutting down for the indicated reason.

Recommended Action None.

Error Message FLASH_RADIO_DONE, DOT11, LOG_WARNING, 0, "Interface %s, flashing radio firmware completed."

Explanation The indicated interface radio firmware flash is complete, and the radio will be restarted with the new firmware.

Recommended Action None.

Error Message UPLINK_LINK_DOWN, DOT11, LOG_WARNING, 0, "Interface %s, parent lost: %s."

Explanation The connection to the parent access point on the indicated interface was lost for the reason indicated. The unit will try to find a new parent access point.

Recommended Action None.

Error Message CANT_ASSOC: Cannot associate: [chars]

Explanation The unit could not establish a connection to a parent access point for the displayed reason.

Recommended Action Verify that the basic configuration settings (SSID, WEP, and others) of the parent access point and this unit match.

Error Message DOT11-4-MAXRETRIES: Packet to client [mac] reached max retries, remove the client

Explanation A packet sent to the client has not been successfully delivered many times, and the max retries limit has been reached. The client is deleted from the association table.

Recommended Action None.

Error Message BRIDGE_LOOP, DOT11, LOG_WARNING, 0, "Bridge loop detected between WGB %e and device %e."

Explanation The indicated workgroup bridge reported the address of one of its indicated Ethernet clients and the access point already had that address marked as being somewhere else on the network.

Recommended Action Click **Refresh** on the Associations page on the access point GUI, or enter the **clear dot11 statistics** command on the CLI.

Error Message ANTENNA_INVALID, DOT11, LOG_WARNING, 0, "Interface %s, current antenna position not supported, radio disabled."

Explanation The Indicated AIR-RM21A radio module does not support the high-gain position for the external antenna (the high-gain position is folded flat against the access point). The access point automatically disables the radio when the antenna is in the high-gain position.

Recommended Action Fold the antenna on the AIR-RM21A radio module so that it is oriented 90 degrees to the body of the access point.

Error Message RF_LOOPBACK_FAILURE, DOT11, LOG_ERR, 0, "Interface %s Radio failed to pass RF loopback test."

Explanation Radio loopback test failed for the interface indicated.

Recommended Action None.

Error Message RF_LOOPBACK__FREQ_FAILURE, DOT11, LOG_ERR, 0, "Interface %s failed to pass RF loopback test."

Explanation Radio loopback test failed at a given frequency for the indicated interface.

Recommended Action None.

Error Message AUTH_FAILED, DOT11, LOG_DEBUG, 0, "Station %e Authentication failed," MSDEF_LIMIT_MEDIUM

Explanation The indicated station failed authentication.

Recommended Action Verify that the user entered the correct username and password, and verify that the authentication server is online.

Error Message CCKM_AUTH_FAILED, DOT11, LOG_DEBUG, 0, "Station %e CCKM authentication failed."

Explanation The indicated station failed CCKM authentication.

Recommended Action Verify that the topology of the access points configured to use the WDS access point is functional.

Error Message TKIP_MIC_FAILURE, DOT11, LOG_WARNING, 0, "Received TKIP Michael MIC failure report from the station %e on the packet (TSC=0x%11x) encrypted and protected by %s key."

Explanation TKIP Michael MIC failure was detected from the indicated station on a unicast frame decrypted locally with the indicated pairwise key.

Recommended Action A failure of the Michael MIC in a packet usually indicates an active attack on your network. Search for and remove potential rogue devices from your wireless LAN.

Error Message TKIP_MIC_FAILURE_REPORT, DOT11, LOG_WARNING, 0, "Received TKIP Michael MIC failure report from the station %e on the packet (TSC=0x0) encrypted and protected by %s key"

Explanation The access point received an EAPOL-key from the indicated station notifying the access point that TKIP Michael MIC failed on a packet transmitted by this access point.

Recommended Action None.

Error Message TKIP_MIC_FAILURE_REPEATED, DOT11, LOG_ERR, 0, "Two TKIP Michael MIC failures were detected within %s seconds on %s interface. The interface will be put on MIC failure hold state for next %d seconds"

Explanation Two TKIP Michael MIC failures were detected within the indicated time on the indicated interface. Because this usually indicates an active attack on your network, the interface will be put on hold for the indicated time. During this hold time, stations using TKIP ciphers are disassociated and cannot reassociate until the hold time ends. At the end of the hold time, the interface operates normally.

Recommended Action MIC failures usually indicate an active attack on your network. Search for and remove potential rogue devices from your wireless LAN. If this is a false alarm and the interface should not be on hold this long, use the **countermeasure tkip hold-time** command to adjust the hold time.

Error Message WGB_CLIENT_VLAN_SOAP, LOG_ERR, 0: "Workgroup Bridge Ethernet client VLAN not configured."

Explanation No VLAN is configured for client devices attached to the workgroup bridge.

Recommended Action Configure a VLAN to accommodate client devices attached to the workgroup bridge.

Error Message ERROR, SAOP, LOG_ERR, MSG_TRACEBACK "Reported on line %d in file %s.%s."

Explanation An internal error occurred on the indicated line number in the indicated filename in the controller ASIC.

Recommended Action None

Inter-Access Point Protocol Messages

Error Message DSTANDBY_ACTIVE, DOT11, LOG_INFO, 0, "Standby to Active, Reason = %s (%d)." "

Explanation The access point is transitioning from standby mode to active mode for the indicated reason.

Recommended Action None.

Error Message ROGUE_AP, DOT11, LOG_INFO, 0, "Rogue AP %e reported. Reason: %s."

Explanation A station has reported a potential rogue access point for the indicated reason.

Recommended Action None.

Error Message STANDBY_REQUEST, DOT11, LOG_INFO, 0, "Hot Standby request to shutdown radios from %e."

Explanation The indicated standby access point has requested that this access point shut down its radio interfaces because a failure has been detected on one of this access point's radio interfaces.

Recommended Action None.

Local Authenticator Messages

Error Message RADSRV-4-NAS_UNKNOWN: Unknown authenticator: [ip-address]

Explanation The local RADIUS server received an authentication request but does not recognize the IP address of the network access server (NAS) that forwarded the request.

Recommended Action Make sure that every access point on your wireless LAN is configured as a NAS on your local RADIUS server.

Error Message RADSRV-4-NAS_KEYMIS: NAS shared key mismatch.

Explanation The local RADIUS server received an authentication request but the message signature indicates that the shared key text does not match.

Recommended Action Correct the shared key configuration on either the NAS or on the local RADIUS server.

Error Message RADSRV-4-BLOCKED: Client blocked due to repeated failed authentications

Explanation A user failed authentication the number of times configured to trigger a block, and the account been disabled.

Recommended Action Use the **clear radius local-server user *username*** privileged EXEC command to unblock the user, or allow the block on the user to expire by the configured lockout time.

WDS Messages

Error Message WLCCP_WDS-6-REPEATER_STOP: WLCCP WDS on Repeater unsupported, WDS is disabled.

Explanation Repeater access points do not support WDS.

Recommended Action None.

Error Message WLCCP_WDS-6-PREV_VER_AP: A previous version of AP is detected.

Explanation The WDS device detected a previous version of the access point.

Recommended Action None.

Error Message WLCCP_AP-6-INFRA: WLCCP Infrastructure Authenticated

Explanation The access point successfully authenticated to the WDS device.

Recommended Action None.

Error Message WLCCP_AP-6-STAND_ALONE: Connection lost to WLCCP server, changing to Stand-Alone Mode

Explanation The access point lost its connection to the WDS device and is in stand-alone mode.

Recommended Action None.

Error Message WLCCP_AP-6-PREV_VER_WDS: A previous version of WDS is detected

Explanation The access point detected a previous version of WDS.

Recommended Action Check for an unsupported version of WDS on your network.

Error Message WLCCP_AP-6-UNSUP_VER_WDS: An unsupported version of WDS is detected

Explanation The access point detected an unsupported version of WDS.

Recommended Action Check for an unsupported version of WDS on your network.

Error Message WLCCP_NM-3-WNM_LINK_DOWN: Link to WNM is down

Explanation The network manager is not responding to keep-active messages.

Recommended Action Check for a problem with the network manager or with the network path to the network manager.

Error Message WLCCP_NM-6-WNM_LINK_UP: Link to WNM is up

Explanation The network manager is now responding to keep-active messages.

Recommended Action None.

Error Message WLCCP_NM-6-RESET: Resetting WLCCP_NM

Explanation A change in the network manager IP address or a temporary out-of-resource state might have caused a reset on the WDS network manager subsystem, but operation will return to normal shortly.

Recommended Action None.

Mini IOS Messages

Error Message PROTECT_PORT_FAILURE, MTS, LOG_CRIT, MSG_PROCESS: An attempt to protect port [number] failed

Explanation Initialization failed on attempting to protect port.

Recommended Action None.

Error Message SET_PW_FAILURE, MTS, LOG_CRIT, MSG_PROCESS: Error %d enabling secret password.

Explanation Initialization failed when the user attempted to enable a secret password.

Recommended Action None