

# Cisco Wide Area Virtualization Engine

## Product Overview

The Cisco® Wide Area Application Virtualization Engine (WAVE) product line consists of cost-effective, cloud-ready, video-enabled solutions for the branch office and the data center (Figure 1). With the industry's broadest product portfolio and flexible deployment models, Cisco Wide Area Application Services (WAAS) cost-effectively addresses the WAN optimization needs of small, medium-sized, and large customers.

**Figure 1.** Cisco Wide Area Virtualization Engines



## Cisco WAVE Appliances for Branch-Office and Core Deployments

In Cisco WAAS Software Release 5.2 and later, the Cisco WAVE 294, 594, and 8541 can optionally be equipped with solid-state drives (SSDs). SSDs provide more reliable storage than existing hard disk drives (HDDs). Table 1 lists the supported SSD sizes for these platforms.

**Table 1.** Cisco WAVE Platforms That Support SSDs with Cisco WAAS 5.2 and Later

Appliance Part Number	Media Description	Quantity of Per Appliance
<b>WAVE-294-K9</b>	200-GB HDD	1
<b>WAVE-294-SSD-K9</b>	200-GB SSD	1
<b>WAVE-594-K9</b>	500-GB HDD or 400-GB SSD	1 or 2 (optional)
<b>WAVE-8541-K9</b>	600-GB HDD or 600-GB SSD	8

For more information, refer to the hardware specifications in Table 3 later in this document.

Benefits include the following:

- Improve employee productivity by enhancing the user experience for important business applications delivered over the WAN.
- Reduce the cost of branch-office operations by centralizing IT resources in the data center and lowering the cost of WAN bandwidth and by hosting Microsoft Windows applications on the Cisco WAVE branch-office appliance.
- Deliver enterprise-class video while reducing WAN bandwidth consumption with the Cisco WAAS video application optimizer or hosted Cisco Application and Content Networking System (ACNS) virtual blade.

- Increase IT agility by reducing the time and resources needed to deliver new IT services to the branch office.
- Simplify branch-office data protection for regulatory compliance purposes.

## Cisco WAVE Appliances for the Data Center




Cisco WAVE data center appliances provide the high performance and scalable WAN optimization that data center solutions require. Benefits include:




- User-selectable I/O modules with support for 10 Gigabit Ethernet fiber, 1 Gigabit Ethernet copper, and 1 Gigabit Ethernet fiber
- Flexible deployment models including inline and Web Cache Communication Protocol (WCCP) for high performance, scalability, and network availability
- High performance for video, virtual desktop infrastructure (VDI), and cloud applications as well as traditional enterprise applications; using context-aware data redundancy elimination (DRE), Cisco WAVE appliances can adapt caching behavior on the basis of the characteristics of individual applications, resulting in higher throughput and lower application latency

## Main Features





Table 2 summarizes the main features of the Cisco WAVE appliances, and Table 3 summarizes the main features of I/O options modules.

**Table 2.** Cisco WAVE Appliances

Platform	Deployment Scenarios and Features
<b>Cisco WAVE 294 Wide Area Virtualization Engine (WAVE-294-K9 or WAVE-294-SSD-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for edge deployments at small branch and remote offices</li> <li>• Supports up to 200 TCP connections (upgradable to 400)</li> <li>• Offers 250-GB HDD and 200-GB SSD (SSD) data storage options</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Provides 4-port inline I/O module (IOM) bundled by default, with optional upgrade to 8-port inline IOM</li> <li>• Hosts up to 2 virtual blades</li> </ul>
<b>Cisco WAVE 594 Wide Area Virtualization Engine (WAVE-594-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for edge deployments at small and medium-sized branch offices</li> <li>• Supports up to 750 TCP connections (upgradable to 1300)</li> <li>• Offers 500-GB HDD and 400-GB SSD data storage options (with optional second HDD or SSD for RAID 1 redundancy)</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Provides 4-port Gigabit Ethernet copper inline, 8-port Gigabit Ethernet copper inline, or 4-port Gigabit Ethernet SX fiber</li> <li>• Offers optional second power supply for 1 + 1 redundancy</li> <li>• Hosts up to 4 virtual blades</li> </ul>
<b>Cisco WAVE 694 Wide Area Virtualization Engine (WAVE-694-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for edge deployments at large enterprise branch offices</li> <li>• Excellent for core deployments at small data centers</li> <li>• Supports up to 2500 TCP connections (upgradable to 6000)</li> <li>• Offers 600-GB HDD data storage with RAID 1 redundancy</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Offers optional 4-port Gigabit Ethernet copper inline, 8-port Gigabit Ethernet copper inline, or 4-port Gigabit Ethernet SX fiber inline</li> <li>• Offers optional second power supply for 1 + 1 redundancy</li> <li>• Hosts up to 6 virtual blades</li> </ul>

Platform	Deployment Scenarios and Features
<b>Cisco WAVE 7541 Wide Area Virtualization Engine (WAVE-7541-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for core deployments at medium-sized data centers and large enterprise branch offices</li> <li>• Supports up to 18,000 TCP connections</li> <li>• Offers 2.2-TB HDD data storage with RAID 5 redundancy</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Offers optional 8-port Gigabit Ethernet copper inline, 4-port Gigabit Ethernet SX fiber inline, or 2-port 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+)</li> </ul>
<b>Cisco WAVE 7571 Wide Area Virtualization Engine (WAVE-7571-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for core deployments at large data centers</li> <li>• Supports 60,000 TCP connections</li> <li>• Offers 3.2-TB HDD data storage with RAID 5 redundancy</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Offers Optional 8-port Gigabit Ethernet copper inline, 4-port Gigabit Ethernet SX fiber inline, or 2-port 10 Gigabit Ethernet SFP+</li> </ul>
<b>Cisco WAVE 8541 Wide Area Virtualization Engine (WAVE-8541-K9)</b> 	<ul style="list-style-type: none"> <li>• Excellent for core deployments at large data centers and for service providers and cloud providers</li> <li>• Supports 150,000 TCP connections</li> <li>• Offers 4.2-TB HDD or SSD data storage with RAID 5 redundancy</li> <li>• Has 2 onboard Gigabit Ethernet ports</li> <li>• Offers optional 8-port Gigabit Ethernet copper inline, 4-port Gigabit Ethernet SX fiber inline, or 2-port 10 Gigabit Ethernet SFP+</li> </ul>

**Table 3.** I/O Modules for Cisco WAVE Appliances

I/O Module	Features
<b>4-port Gigabit Ethernet copper module (WAVE-INLN-GE-4T)</b> 	<ul style="list-style-type: none"> <li>• Fail-to-wire capability</li> <li>• Support for inline and WCCP deployments</li> </ul>
<b>8-port Gigabit Ethernet copper module (WAVE-INLN-GE-8T)</b> 	<ul style="list-style-type: none"> <li>• Fail-to-wire capability</li> <li>• Support for inline and WCCP deployments</li> </ul>
<b>4-port Gigabit Ethernet fiber module (WAVE-INLN-GE-4SX)</b> 	<ul style="list-style-type: none"> <li>• Fail-to-wire capability</li> <li>• Support for inline and WCCP deployments</li> </ul>
<b>2-port 10 Gigabit Ethernet module WAVE-10GE-2SFP</b> 	<ul style="list-style-type: none"> <li>• Support for Cisco SFP+ short reach (SR) transceivers</li> <li>• Support for WCCP interception only</li> </ul>

## Hardware Specifications

Table 4 lists the hardware specifications for the Cisco WAVE appliances.

**Table 4.** Hardware Specifications for Cisco WAVE Appliances

	Cisco WAVE 294	Cisco WAVE 594 and 694	Cisco WAVE 7541 and 7571	Cisco 8541
<b>Hardware Features</b>				
<b>DRAM</b>	4 to 8 GB	<ul style="list-style-type: none"> <li>Cisco WAVE 594: 8 to 12 GB</li> <li>Cisco WAVE 694: 16 to 24 GB</li> </ul>	<ul style="list-style-type: none"> <li>Cisco WAVE 7541: 24 GB</li> <li>Cisco WAVE 7571: 48 GB</li> </ul>	96 GB
<b>Usable storage</b>	<ul style="list-style-type: none"> <li>250 GB with HDD</li> <li>200 GB with SSD</li> </ul>	<ul style="list-style-type: none"> <li>Cisco WAVE 594: 500 GB with HDD or 400 GB with SSD</li> <li>Cisco WAVE 694: 600 GB</li> </ul>	<ul style="list-style-type: none"> <li>Cisco WAVE 7541: 2.2 TB</li> <li>Cisco WAVE 7571: 3.1 TB</li> </ul>	4.2 TB
<b>Maximum data storage</b>	<ul style="list-style-type: none"> <li>1 x 250-GB HDD</li> <li>1 x 200-GB SSD<sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>Cisco WAVE 594: 2 x 500-GB HDD or 400-GB SSD<sup>1</sup></li> <li>Cisco WAVE 694: 2 x 600 GB HDD</li> </ul>	<ul style="list-style-type: none"> <li>Cisco WAVE 7541: 6 x 450 GB HDD</li> <li>Cisco WAVE 7571: 8 x 450 GB HDD</li> </ul>	8 x 600 GB HDD or SSD <sup>1</sup>
<b>RAID support</b>	-	RAID 1 (optional on Cisco WAVE 594)	RAID 5	RAID 5
<b>Virtual blades</b>	Up to 2	Up to 6	Not supported	Not supported
<b>Network interfaces</b>	Two 10/100/1000BASE-T	Two 10/100/1000BASE-T	Two 10/100/1000BASE-T	Two 10/100/1000BASE-T
<b>Power</b>	One 400-watt (W) AC power supply	<ul style="list-style-type: none"> <li>One 450W AC power supply</li> <li>Redundant power available as an option</li> </ul>	<ul style="list-style-type: none"> <li>Two 650W AC power supplies</li> <li>1 + 1 redundancy; hot swappable</li> </ul>	<ul style="list-style-type: none"> <li>Two 650W AC power supplies</li> <li>1 + 1 redundancy; hot swappable</li> </ul>
<b>Fan</b>	Five fans	Redundant 40-mm fans; hot swappable	Redundant 40- and 60-mm fans; hot swappable	Redundant 40- and 60-mm fans; hot swappable
<b>Rack units</b>	1 (can be used as a desktop unit as well)	1	2	2
<b>I/O module</b>	4-port Gigabit Ethernet inline bundled (8-port optional)	4-port or 8-port Gigabit Ethernet inline (optional)	2-port 10 Gigabit Ethernet SFP+, 8-port Gigabit Ethernet inline, or 4-port Gigabit Ethernet inline fiber (optional)	2-port 10 Gigabit Ethernet SFP+, 8-port Gigabit Ethernet inline, or 4-port Gigabit Ethernet inline fiber (optional)
<b>Console</b>	USB, mini-USB, and RJ-45 serial console; autodetect	USB, mini-USB, and RJ-45 serial console; autodetect	USB, mini-USB, and RJ-45 serial console; autodetect	USB, mini-USB, and RJ-45 serial console; autodetect
<b>Dimensions</b>				
<b>Height</b>	1.69 in. (42 mm)	1.69 in. (42 mm)	3.42 in. (87 mm)	3.42 in. (87 mm)
<b>Width</b>	16.89 in. (429 mm)	429 mm (16.89 in.)	16.89 in. (429 mm)	16.89 in. (429 mm)
<b>Depth</b>	14.55 in. (370 mm)	20.33 in. (516 mm); includes power-supply handles	24.88 in. (632 mm); includes power supply handles	24.88 in. (632 mm); includes power supply handles
<b>Maximum weight</b>	16.40 lb (7.44 kg)	22.51 lb (10.21 kg)	47.66 lb (21.62 kg)	47.66 lb (21.62 kg)
<b>Shipping dimensions (with packaging)</b>	21.69 x 19.88 x 7.75 in. (55 x 50.5 x 19.7 cm)	26.50 x 21.69 x 7.75 in. (67.3 x 55 x 19.7 cm)	30.75 x 21.69 x 10.19 in. (78 x 55 x 25.9 cm)	30.75 x 21.69 x 10.19 in. (78 x 55 x 25.9 cm)
<b>Shipping weight</b>	22.0 lb (10.0 kg)	28.50 lb (12.93 kg)	53.0 lb (24.0 kg)	53.0 lb (24.0 kg)
<b>Operating Specifications</b>				
<b>Universal input</b>	<ul style="list-style-type: none"> <li>Range line voltage: 90 to 132 VAC</li> <li>180 to 264 VAC</li> </ul>	<ul style="list-style-type: none"> <li>Range line voltage: 90 to 132 VAC</li> <li>180 to 264 VAC</li> </ul>	<ul style="list-style-type: none"> <li>Range line voltage: 90 to 132 VAC</li> <li>180 to 264 VAC</li> </ul>	<ul style="list-style-type: none"> <li>Range line voltage: 90 to 132 VAC</li> <li>180 to 264 VAC</li> </ul>

	Cisco WAVE 294	Cisco WAVE 594 and 694	Cisco WAVE 7541 and 7571	Cisco 8541
<b>Operating temperature</b>	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
<b>Nonoperating temperature</b>	(-22 to 140°F (-30 to 60°C) <sup>2</sup>	(-22 to 140°F (-30 to 60°C) <sup>2</sup>	(-22 to 140°F (-30 to 60°C) <sup>2</sup>	(-22 to 140°F (-30 to 60°C) <sup>2</sup>
<b>Humidity</b>	<ul style="list-style-type: none"> <li>Operating: 10 to 90% RH (noncondensing)</li> <li>Nonoperating: 5 to 95% RH (noncondensing)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10 to 90% RH (noncondensing)</li> <li>Nonoperating: 5 to 95% RH (noncondensing)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10 to 90% RH (noncondensing)</li> <li>Nonoperating: 5 to 95% RH (noncondensing)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10 to 90% RH (noncondensing)</li> <li>Nonoperating: 5 to 95% RH (noncondensing)</li> </ul>
<b>Altitude</b>	<ul style="list-style-type: none"> <li>Operating: 10,000 ft (3050m)</li> <li>Nonoperating: 15,000 ft (4572m)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10,000 ft (3050m)</li> <li>Nonoperating: 15,000 ft (4572m)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10,000 ft (3050m)</li> <li>Nonoperating: 15,000 ft (4572m)</li> </ul>	<ul style="list-style-type: none"> <li>Operating: 10,000 ft (3050m)</li> <li>Nonoperating: 15,000 ft (4572m)</li> </ul>
<b>Regulatory Compliance</b>				
<b>Compliance</b>	CE marking			
<b>EMC</b>	47 CFR Part 15 Class A, AS/NZS CISPR22 Class A, CISPR22 Class A, EN 55022 Class A, ICES 003 Class A, VCCI Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, CISPR24, GB9254-2008, KN22 Class A, and KN24 (all platforms)			
<b>Safety</b>	UL 60950-1 Second Edition, 21 CFR 1040, CSA22.2-No. 60950-1 Second Edition, IEC/EN 60950-1 Second Edition, AS/NZS 60950, and GB4943-1995 (all platforms)			

**Notes:**

- Existing systems cannot be upgraded to use SSDs. When ordering, SSDs can optionally be added to Cisco WAVE 294, 594, and 8541 when ordering with initial system only. Cisco WAAS Software Release 5.2 or later is required for SSDs.
- All temperature ratings shown are for sea level to 3281 feet (1000 meters). If operating location is above 3281 feet (1000 meters), deduct 5.4°F (3°C) from the maximum operating temperature for each additional 3281 feet (1000 meters).

## Services and Support

Cisco offers a wide range of services to accelerate customer success, delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco Services helps you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, visit [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

## For More Information

For more information about Cisco WAAS, visit <http://www.cisco.com/go/waas> or contact your local Cisco account representative.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)