



Cisco WAE-512 and WAE-612 Wide Area Application Engines

Cisco Systems® is announcing the availability of the new Cisco® WAE-512 and WAE-612 Wide Area Application Engines. These new products can ship installed with the latest Cisco Application and Content Networking System (ACNS) Software Version 5.4.3 or 5.5.1, the Cisco Wide Area File Services (WAFS) Software Version 3.0.7, or Cisco Wide Area Application Services (WAAS) Software Version 4.0.1. A separate license is required for each software version, and the two cannot run concurrently.

The Cisco Wide Area Application Engine (WAE) product family offers a single, consolidated platform allowing users to run either Cisco ACNS or Cisco WAFS Software and also rely on a common hardware sparing model, simplifying operations and lowering overall cost. These new WAE models offer a superior solution for application acceleration for Web-based and applications servers, file servers, and streaming video.

For more information about the latest Cisco ACNS Software releases and features, refer to the Cisco ACNS Software data sheet at:

<http://www.cisco.com/en/US/products/sw/conntsw/ps491/index.html>

For more information about the latest Cisco WAFS Software releases and features, refer to the Cisco WAFS Software data sheet at:

<http://www.cisco.com/en/US/products/ps6469/index.html>

For more information about the latest Cisco WAAS Software releases and features, refer to the Cisco WAAS product area at:

http://www.cisco.com/en/US/products/ps5680/Products_Sub_Category_Home.html

Based on the same hardware architecture as the Cisco WAE-511 and WAE-611 appliances, the new Cisco WAE-512 and WAE-612 appliances come with enhanced hardware components, such as increased internal storage capacity and memory size, and increased performance.

The Cisco WAE-512 replaces the Cisco WAE-511 Wide Area Application Engine as the new low-end delivery platform for small to midsize branch offices, offering a wide capacity range from 80 to 500 GB of internal storage*. The Cisco WAE-511 can be configured as a content engine in a Cisco ACNS deployment. It cannot be configured as a content distribution manager (CDM) for Cisco ACNS. For an additional software license cost, it can be configured as a file engine or core engine in a Cisco WAFS deployment or as core or edge engine for Cisco WAAS (refer to Table 1). Also for an additional cost, it can be configured as a Cisco WAAS Central Manager.

The Cisco WAE-612 replaces the Cisco WAE-611 as a midrange edge delivery platform for regional offices or larger branch offices. The Cisco WAE-612 can be configured as a content engine, CDM, or content router in a Cisco ACNS deployment. For an additional software license cost, it can be configured as a file engine or core engine in a Cisco WAFS deployment or as a core and edge engine for Cisco WAAS (refer to Table 1). For an additional cost, it can be configured as a Cisco WAAS Central Manager.

NEW FEATURES

New features of the Cisco WAE-512 include the following:

- Offers new 3.0-GHz Pentium 4 processor with 1-MB Layer 2 cache and 800-MHz front side bus (FSB)
- Offers default synchronous dynamic RAM (SDRAM) memory size to 1 GB with the option to add another 1-GB SDRAM module; memory speed increases to 533 MHz (PC2-4200)
- Provides internal storage capacity that is configurable up to 500 GB on two internal hard disk drives (HDDs)
- Runs Cisco ACNS, Cisco WAFS, or Cisco WAAS Software

New features of the Cisco WAE-612 include the following:

- Offers new 3.0-GHz Pentium D (dual-core) processor with 1-MB Layer 2 cache per core and 800-MHz FSB
- Starts with a default SDRAM of 2 GB with the option to upgrade to 4 GB with the addition of a two 1-GB SDRAM modules; memory speed increases to 533 MHz (PC2-4200)
- Runs Cisco ACNS, Cisco WAFS, or Cisco WAAS Software

For more information about these new products, refer to the Cisco WAE data sheet at:

http://www.cisco.com/en/US/products/ps6474/products_data_sheets_list.html

AVAILABILITY

Customers can place orders through their normal sales channels, starting mid May, 2006, for both the Cisco WAE-512 and Cisco WAE-612 Wide Area Application Engines.

CISCO WAE PRODUCT LINE COMPATIBILITY

Table 1 lists the Cisco software functions supported by the new WAEs. Note that the WAE products cannot be configured to perform all and ACNS functions simultaneously; they can perform one at a time (content engine, content router, or CDM). However, they can have both WAFS software and WAFS central manager functions running simultaneously.

Table 1. Cisco WAE Product Function Matrix

	Cisco WAE-512	Cisco WAE-612
Cisco ACNS Content Engine	X	X
Cisco ACNS CDM	—	X
Cisco ACNS Content Router	—	X
Cisco WAFS Software	X	X
Cisco WAFS Central Manager	X	X
Cisco WAAS Software	X	X
Cisco WAAS Central Manager	X	X

UPGRADING

All Cisco WAE products participate in the Cisco Technology Migration Program (TMP). Customers can use the Cisco TMP to trade in products and receive credit toward the purchase of new Cisco equipment. For more information about this program, visit: <http://www.cisco.com/go/tradein/>

ORDERING INFORMATION

Table 2 lists the Cisco WAE-512 and WAE-612 part numbers.

Table 2. Ordering Information

Product Part Number	Hardware and Software Configuration Options
WAE-512-K9	Software options: Cisco ACNS Software, Cisco WAFS Software, or Cisco WAAS Software Storage options: One of the following two HDD bay configuration options*: <ul style="list-style-type: none">• One or two 80-GB SATA drives (part number DISK-SATA2-80GB) for a total of 160 GB of internal storage• One or two 250-GB SATA drives (part number DISK-SATA2-250GB) for a total of 500 GB of internal storage Default memory size: One 1-GB memory module (part number MEM-WAE-1GB) Memory options: One additional 1-GB memory module (part number MEM-WAE-1GB) for a total of 2-GB internal memory size Additional options for Cisco ACNS Software only: MPEG decoder card (part number CE-VIDEO-1P-D)
WAE-612-K9	Software options: Cisco ACNS Software, Cisco WAFS Software, or Cisco WAAS Software Storage options: One of the following two HDD bay configuration options*: <ul style="list-style-type: none">• Two 146-GB SATA drives (part number DISK-SAS-146GB) for a total of 292 GB of internal storage• Two 300-GB SATA drives (part number DISK-SAS-300GB) for a total of 600 GB of internal storage Default memory size: Two 1-GB SDRAM modules for a total of 2 GB of memory Memory options: Two additional 1-GB modules (part number MEM-WAE-2GB) for a total of 4 GB internal memory Additional options for Cisco ACNS Software only: MPEG decoder card (part number CE-VIDEO-1P-D)
WAE Hardware Spares	
CE-VIDEO-1P-D=	MPEG 1,2 video decoder, spare
DISK-SATA2-80GB(=)	80-GB HDD (SATA2), spare
DISK-SATA2-250GB(=)	250-GB HDD (SATA2), spare
DISK-SAS-146GB(=)	146-GB HDD (SAS), spare
DISK-SAS-300GB(=)	300-GB HDD (SAS), spare
MEM-WAE-1GB(=)	1 WAE 1-GB memory module
MEM-WAE-2GB(=)	2 WAE 1-GB memory modules
Single power cord	

* The combination of different hard-drive sizes is not supported on the Cisco WAE product line

FOR MORE INFORMATION

For more information about the Cisco WAE product line, contact your local Cisco account representative or visit:

<http://www.cisco.com/en/US/products/hw/contnetw/index.html>

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

