



CISCO AS5400XM AND AS5350XM SERIES MIGRATION AT-A-GLANCE

CISCO UNIVERSAL GATEWAYS OFFER BEST IN CLASS VOICE, FAX AND REMOTE ACCESS SERVICES

The new Cisco AS5400XM and AS5350XM Universal Gateways offer unparalleled capacity and the flexibility to deploy advanced voice, fax and remote access services. With over 18 million ports deployed Cisco customers worldwide have proven that AS5000s provide the scale, reliability, and services required to meet market demands.

TOP 10 REASONS TO MIGRATE TO AS5400XM AND AS5350XM

1. Up to double the performance of previous models
2. Improved capacity for advanced voice applications
3. Dual Gigabit Ethernet (10/100/1000 Mbps) interfaces
4. Uses current IOS configuration for easy conversion
5. Seamless migration from AS5350, AS5400, AS5400HPX to AS5350XM or AS5400XM
6. PCI card slot for future expansion (AS5400XM)
7. Improved performance for Voicemail and Prepaid Calling Card
8. Support for double the number of VxML sessions
9. CT3 to CT3 TDM switching (AS5400XM)
10. All current applications run with lower CPU utilization allowing for more SNMP monitoring or additional logging



INCREASED PERFORMANCE & EXPANDED FEATURES

Feature	Cisco AS5350	Cisco AS5400	Cisco AS5400HPX	Cisco AS5350XM	Cisco AS5400XM
Relative CPU Performance	0.8	0.8	1.0	2.0	2.0
Minimum Memory	256 MB Main, 64 MB shared SDRAM	256 MB Main, 64 MB shared SDRAM	256 MB Main, 64 MB shared SDRAM	512 MB DDR	512 MB
Boot Flash	8 MB Flash SIMM	8 MB Flash SIMM	8 MB Flash SIMM	N/A	N/A
System Flash	32 MB Flash SIMM	32 MB Flash SIMM	32 MB Flash SIMM	128 MB Compact Flash	128 MB Flash
NVRAM	512 KB	512 KB	512 KB	2 MB	2 MB
Ethernet	2 FE	2 FE	2 FE	2 GE	2 GE
High Speed Serial (2T)	Yes	Yes	Yes	Yes	Yes
Alarm	Yes	Yes	Yes	Yes	Yes
BITs	Yes	Yes	Yes	Yes	Yes
Card Slots	3	7	7	3	7
Expansion Slot	No	No	No	No	Yes