

Cisco SFS 7012P and 7024P InfiniBand Server Switches

The Cisco® SFS 7012P and 7024P InfiniBand server switches set the standard for high-density, 10 Gbps (4X), low-latency InfiniBand switching for building high-performance clusters.

High-performance computing (HPC) applications that solve complex, computationally intensive problems are widely deployed within academic and research communities and enterprises as they deliver significant business benefits. A key enabler for the broad adoption of HPC applications is the practice of clustering multiple industry-standard servers using a high-speed network to provide supercomputer performance, at a fraction of the cost of traditional supercomputers.

PRODUCT OVERVIEW

The Cisco SFS 7012P and 7024P InfiniBand server switches (Figure 1) are a new class of data center infrastructure that delivers scalable, high-performance, low-latency server switching to build and manage high-performance clusters and grids that deliver the full potential of HPC applications. The Cisco SFS 7012P and 7024P are optimized for very large, high-density HPC environments to deliver non-blocking, high-bandwidth, low-latency switching in a cost-effective form factor.

The Cisco SFS 7012P SFS 7024P provides non-blocking switching for up to 144 and 288 10-Gbps InfiniBand ports respectively. The Cisco SFS 7012P and 7024P, in common with the Cisco SFS 7008P InfiniBand Server Switch, also support fully redundant, hot-swappable components that are ideal for building large-scale, highly available clusters for high-performance computing applications.

Figure 1. Cisco SFS 7012P and 7024P InfiniBand Server Switches



BENEFITS

The Cisco SFS 7012P and 7024P offer the following benefits:

- Comprehensive performance and fabric diagnostics tools in a fully managed switch
- High-performance, industry standards-based InfiniBand interconnect technology
- Integration with other Cisco SFS 7000 Series InfiniBand server switches
- Easy configuration, monitoring, and maintenance in-band and out-of-band

FEATURES

The following features are included with the Cisco SFS 7012P and 7024P:

- Up to 288 ports of non-blocking, 10-Gbps (4X) InfiniBand connectivity with full bisectional bandwidth
- Hot-swappable components, including online insertion and removal (OIR), redundant fans, and power supplies
- InfiniBand 1.0a and 1.1 compliant
- Optional standalone, high-performance Cisco Subnet Manager

FABRIC DENSITY AND SCALABILITY

The Cisco SFS 7012P and 7024P are among the highest-density InfiniBand switches in the industry today. With twelve 10-Gbps (4X) InfiniBand ports per slot, the Cisco SFS 7012 and Cisco SFS 7024P can support up to 144 10-Gbps (4X), or 288 10-Gbps (4X) of non-blocking InfiniBand ports respectively within a single chassis for server and inter-switch connectivity. When combined with other Cisco SFS 7000 Series InfiniBand switches, the Cisco SFS 7012P and 7024P provide the foundation for building very large HPC clusters consisting of thousands of nodes to support the most demanding HPC applications.

HIGH RELIABILITY AND AVAILABILITY

The Cisco SFS 7012P and 7024P deliver the performance, scalability, and director-class uptime required for the most demanding HPC environments. Minimizing downtime requires rapid hardware serviceability and software upgrades. The Cisco SFS 7012P and 7024P are optimized for reliability and availability and support hot-swappable components to help eliminate downtime and maximize the availability of the cluster or compute environment. This includes hot-pluggable, redundant fan trays and power supplies that can be field-upgraded without requiring the switch to power down.

SIMPLIFIED MANAGEMENT

Configuration, remote management, monitoring, diagnostics, and updates are supported through Telnet, Secure Shell Protocol Version 2 (SSHv2), and serial command-line interface (CLI) as well as a powerful, fully featured, browser-based GUI that enables the Cisco SFS 7012P and 7024P to be deployed in a ready-to-use fashion in the network within minutes. The Cisco SFS 7012P and 7024P can be managed using the Cisco SFS management suite or with existing network management systems using standard protocols such as Simple Network Management Protocol (SNMP), with supported SNMPv3 security.

FABRIC INTELLIGENCE

The Cisco SFS-7012P and 7024P offer sophisticated system and network management capability that simplifies monitoring, diagnostics, and maintenance. The comprehensive management capability quickly identifies and isolates trouble areas, or “hot spots.” Each field-replaceable unit (FRU) supports a full suite of system-level diagnostic health checks that assess the health of all components to detect potential problems, such as rising temperature or internal error rates, and report these anomalies in real time to proactively notify the system administrator. The Cisco SFS 7012P and 7024P also support a full complement of real-time performance monitoring, including graphing of bandwidth utilization and error rates, to give system administrators an unprecedented view of fabric performance.

VALUE

The Cisco SFS 7012P and 7024P are IBTA 1.0a and 1.1 standards-compliant, and are interoperable with other IBTA standards-compliant InfiniBand products. The high-performance Cisco InfiniBand Subnet Manager and Cisco SFS 7012P and 7024P deliver the performance required to build the largest InfiniBand switch networks.

COMPLETE SERVER SWITCHING SOLUTION

The Cisco SFS 7012P and 7024P are a part of the Cisco SFS 7000 Series of InfiniBand server switches which, combined with the Cisco Catalyst® 6000 Series switches and Cisco MDS 9000 Series switches, deliver a comprehensive, industry-leading data center switching solution. The Cisco SFS solution also includes integrated Ethernet and Fiber Channel gateway modules, and 10-Gbps InfiniBand host channel adapters (HCAs) with a complete suite of upper-layer protocols: IP over InfiniBand, Messaging Passing Interface (MPI), Sockets Direct Protocol (SDP), SCSCI RDMA Protocol (SRP), and user Data Access Provider Layer (uDAPL). The Cisco SFS 7012P and 7024P share common switch software with all the other Cisco SFS 7000 and SFS 3000 series server switches, offering a clear growth path while protecting existing investments.

PRODUCT SPECIFICATIONS

Table 1 describes the systems architecture for the Cisco SFS 7012P and 7024P. Tables 2 and 3 list the mechanical and environmental specifications, and Table 4 lists the management features.

Table 1. Systems Architecture

	Cisco SFS 7012P	Cisco SFS 7024P
Cards, Ports, Slots	<ul style="list-style-type: none">• Up to 144 non-blocking 10-Gbps (4X) InfiniBand ports• 12 slots, each taking a 12-port 4X InfiniBand line card• Copper or optical interfaces• One RS-11 serial port, one Ethernet management port	<ul style="list-style-type: none">• Up to 288 non-blocking 10-Gbps (4X) InfiniBand ports• 24 slots, each taking a 12-port 4X InfiniBand line card• Copper or optical interfaces• Two RS-11 serial ports, two Ethernet management ports
Performance	All ports non-blocking and wire-speed, 2.8-Tbps aggregate bandwidth (144 ports x 10 Gbps x bidirectional)	All ports non-blocking and wire-speed, 5.76-Tbps aggregate bandwidth (288 ports x 10 Gbps x bidirectional)
Chassis	<ul style="list-style-type: none">• 7-RU, 19-inch rack-mountable chassis• Passive mid-plane design with cable connections on opposite side of active components• All modules hot-swappable• IBTA 1.0a and 1.1 compliant• RoHS compliant	<ul style="list-style-type: none">• 14-RU, 19-inch rack-mountable chassis• Passive mid-plane design with cable connections on opposite side of active components• All modules hot-swappable• IBTA 1.0a and 1.1 compliant• RoHS compliant
Switch Fabric and Management Module	<ul style="list-style-type: none">• Up to 3 per system• Hot-swappable FRU• Operation status, active fabric controller, and alert LEDs	<ul style="list-style-type: none">• Up to 6 per system• Hot-swappable FRU• Operation status, active fabric controller, and alert LEDs

	Cisco SFS 7012P	Cisco SFS 7024P
Line Interface Module	<ul style="list-style-type: none"> Up to 12 per system 12 ports 4X InfiniBand or 4 ports 12X InfiniBand Supports hot-pluggable optical media converter on a port-by-port basis Physical connection and traffic LEDs for each port Hot-swappable FRU Port status, operation status, and alert LEDs 	<ul style="list-style-type: none"> Up to 24 per system 12 ports 4X InfiniBand or 4 ports 12X InfiniBand Supports hot-pluggable optical media converter on a port-by-port basis Physical connection and traffic LEDs for each port Hot-swappable FRU Port status, operation status, and alert LEDs
Switch Fabric Modules	<ul style="list-style-type: none"> 1 Management Switch Fabric Module required; Up to 3 per system for non-blocking switching and HA 	<ul style="list-style-type: none"> 2 Management Switch Fabric Modules required; Up to 6 per system for non-blocking switching and HA
Power Supply	<ul style="list-style-type: none"> Up to 6 per system Redundant, hot-swappable FRU 350W per power supply Operation status and alert LEDs 	<ul style="list-style-type: none"> Up to 12 per system Redundant, hot-swappable FRU 350W per power supply Operation status and alert LEDs
Fan Module	<ul style="list-style-type: none"> Up to 4 fan trays (2 fans per tray) per system Cooling: front to back Redundant, hot-swappable FRU Operation status and alert LEDs 	<ul style="list-style-type: none"> Up to 8 fan trays (2 fans per tray) per system Cooling: front to back Redundant, hot-swappable FRU Operation status and alert LEDs

Table 2. Mechanical Specifications

	Cisco SFS 7012P	Cisco SFS 7024P
Mounting	Mountable in a standard 19-inch Electronic Industries Alliance (EIA) rack	Mountable in a standard 19-inch EIA rack
Size	<ul style="list-style-type: none"> Standard 19-inch rack-mountable 7-RU height (12.25 inches) 25.75-inch depth 	<ul style="list-style-type: none"> Standard 19-inch rack-mountable 14-RU height (24.5 inches) 25.75-inch depth
Air Flow	Front to back	Front to back
Weight	65–110 lbs, based on configuration	100–200 lbs, based on configuration

Table 3. Environmental Specifications

	Cisco SFS 7012P	Cisco SFS 7024P
Temperature	<ul style="list-style-type: none"> Operating: 50 to 113°F (10 to 45°C) Storage: –40 to 167°F (–40 to 75°C) 	<ul style="list-style-type: none"> Operating: 50 to 113°F (10 to 45°C) Storage: –40 to 167°F (–40 to 75°C)
Altitude	<ul style="list-style-type: none"> Operating: 10,000 ft Storage: 40,000 ft 	<ul style="list-style-type: none"> Operating: 10,000 ft Storage: 40,000 ft
Humidity	<ul style="list-style-type: none"> Operating: 20 to 80% non-condensing Storage 5 to 90% non-condensing 	<ul style="list-style-type: none"> Operating: 20 to 80% non-condensing Storage 5 to 90% non-condensing

	Cisco SFS 7012P	Cisco SFS 7024P
Shock	<ul style="list-style-type: none"> Operating: 5G maximum, 11 ms half-sine wave 10G maximum, 5 ms half-sine wave Storage: 10G maximum, 11 ms half-sine wave 	<ul style="list-style-type: none"> Operating: 5G maximum, 11 ms half-sine wave 10G maximum, 5 ms half-sine wave Storage: 10G max, 11 ms half-sine wave
Vibration	<ul style="list-style-type: none"> Operating: 0.50G maximum, 3–200 Hz, 15 min (Sinusoidal); 1.02Grms, 3-axis, bottom/top, left/right, front/back (random) Storage: 0.50G maximum, 3–200 Hz, 15 min (Sinusoidal); 2.09Grms, 3-axis, bottom/top, left/right, front/back (random) 	<ul style="list-style-type: none"> Operating: 0.50G maximum, 3–200 Hz, 15 min (Sinusoidal); 1.02Grms, 3-axis, bottom/top, left/right, front/back (random) Storage: 0.50G maximum, 3–200 Hz, 15 min (Sinusoidal); 2.09Grms, 3-axis, bottom/top, left/right, front/back (random)
Power	<ul style="list-style-type: none"> 90–264 V AC automatic-ranging, 47–63 Hz, 350W maximum per power supply 	<ul style="list-style-type: none"> 90–264 V AC automatic-ranging, 47–63 Hz, 350W maximum per power supply

Table 4. Management Features

	Cisco SFS 7012P	Cisco SFS 7024P
Subnet Management	External subnet manager for scalable deployments	External subnet manager for scalable deployments
Network Management	<ul style="list-style-type: none"> Easy configuration, monitoring, and maintenance in-band and out-of-band Web-based systems management GUI CLI through Telnet, SSHv2, and serial console 	<ul style="list-style-type: none"> Easy configuration, monitoring, and maintenance in-band and out-of-band Web-based systems management GUI CLI through Telnet, SSHv2, and serial console
Management Framework	Supports Simple Network Management Protocol Version 2 (SNMPv2)	Supports SNMPv2

SERIES OF PRODUCTS

The Cisco SFS 7012P and 7024P are part of a complete family of server switches including the Cisco SFS 7000 Series InfiniBand server switches, Cisco SFS 3000 Series multifabric server switches and Cisco InfiniBand PCI-X and PCI Express Host Channel Adapters.

ORDERING INFORMATION

To place an order, visit the [Cisco Ordering Home Page](#). Table 5 lists the ordering information for the Cisco SFS 7012P and 7024P.

Table 5. Ordering Information

Part Number	Description
SFS-7012P	Cisco SFS 7012P InfiniBand Server Switch, 144-port switch, non-blocking fabric
SFS-7012P-X	Cisco SFS 7012P InfiniBand Server Switch, 144-port upgradeable chassis, ships with 108 ports, 67% blocking fabric
SFS-7024P	Cisco SFS 7024P InfiniBand Server Switch, 288-port switch, non-blocking fabric
SFS-7024P-X	Cisco SFS 7024P InfiniBand Server Switch, 288-port upgradeable chassis, ships with 156 ports, 67% blocking fabric
SFSX7012/24-4X12	Cisco SFS 7012P/7024P InfiniBand 4X 12-Port Line Card
SFS-7012/24-FM	Cisco SFS 7012P/7024P Switch Fabric Module—no management
SFS-7012/24-MM-K9	Cisco SFS 7012P/7024P Switch Fabric Module—with management
PWR-SFS7012/24	Cisco SFS 7012P/7024P Power Supply

SERVICE AND SUPPORT

Cisco Systems® offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, see [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

FOR MORE INFORMATION

For more information about the Cisco SFS 7012P and 7024P visit <http://www.cisco.com> or contact your local account representative.



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

