

Cisco TelePresence Conductor

Simple, Natural Conferencing

Product Overview


Cisco TelePresence® Conductor software simplifies multiparty video communications, orchestrating the different resources needed for each conference as required. It allows the video network to be configured so that conferences can be easily provisioned, initiated, and accessed.

The Cisco TelePresence Conductor simplifies and enhances conference resource management, making conferences easy to join and administer. It uses knowledge of all available conferencing resources and their capabilities to help ensure dynamic, intelligent conference placement and optimum resource usage. It delivers powerful, comprehensive administrative control, making simple, natural conferencing a reality.

Administrators can specify the exact service level and experience required for each user. For example, administrators can determine whether users enjoy standard- or high-definition video, how many participants may connect, the maximum service level available to attendees, and even which Cisco TelePresence Server or Cisco TelePresence Multipoint Control Unit (MCU) is selected, according to geographic location.

Figure 1 shows a sample deployment of Cisco TelePresence Conductor working with Cisco® Unified Communications Manager (Cisco UCM). Cisco TelePresence Conductor also works in conjunction with Cisco TelePresence Video Communication Server (VCS) where required; for example, to support H.323 and Session Initiation Protocol (SIP) interworking and/or provide firewall traversal.

Figure 1. Conference Resource Orchestration with Cisco TelePresence Conductor



Cisco TelePresence Conductor is a key component of the Cisco® Pervasive Conferencing architecture, and is deployed with Cisco TelePresence Server in order to provide flexible and scalable conferencing capabilities to organizations of all sizes.

Cisco TelePresence Conductor offers many benefits:

- Supports service differentiation, allowing administrators to define specific classes of service for conference attendees to ensure that conferences are effectively delivered to maximize the value each attendee gains
- Eases the administration and management of conference configuration through virtualization and intelligent optimization of multipoint resources (note that intelligent optimization is supported only on Cisco TelePresence Server)
- Supports spontaneous, rendezvous (MeetMe), and scheduled conferencing modes to help ensure that the user experience is always consistent irrespective of user, meeting type, and endpoint
- Allows conferences to dynamically grow and even exceed the capacity of individual conferencing resources; it is ideal for larger conferences, or when the number of participants expected on a conference is unknown
- Scales from small businesses to large enterprises, supporting expansion as usage increases

Cisco TelePresence Conductor is available as a virtualized application running on Cisco Unified Computing System™ (Cisco UCS®) platforms or third-party server platforms. It is also available as a dedicated appliance (Figure 2). Alternatively, Cisco TelePresence Conductor can also be licensed in conjunction with Cisco TelePresence Server on a per-user basis, within Named Host licenses for Personal Multiparty conferences. For more details visit <http://www.cisco.com/go/personalmultiparty>.

Figure 2. Cisco TelePresence Conductor Appliance



Features of Cisco TelePresence Conductor include:

- Cisco TelePresence Conductor supports the industry-leading Cisco TelePresence Server and Cisco TelePresence MCUs.
- It offers conference virtualization: Cisco TelePresence Conductor dynamically selects the most appropriate Cisco TelePresence resources for each new conference.
- Pooled resource orchestration and load balancing mean that having a Cisco TelePresence Server or an MCU out of service need not affect service availability.
- Customizable templates that define the characteristics of a conference and that can be tailored for each participants specific requirements and their service level entitlements.
- Conference personalization helps ensure the conferencing experience is tailored to meet each user's personal preferences for settings such as layout and personal identification numbers (PINs).
- Supported Cisco conference modes follow:
 - **Meeting:** The conference has one type of participant, and all participants are given the same priority.
 - **Lecture:** There are two types of participants with different levels of priority; each participant type has a different alias to dial in to the conference.
 - **Role configuration for conference attendees:** Roles include chairperson, guest, and participant.
- Cisco TelePresence Conductor supports dynamic conference growth and ad-hoc conference escalations, allowing dynamic two- to three-way conferencing.

System Capacity

Cisco TelePresence Conductor Essentials

- Cisco TelePresence Conductor software can be downloaded as a virtualized application and installed without a release key in limited-capacity mode, enabling conference resource orchestration for a single, standalone Cisco TelePresence Server or Cisco TelePresence MCU.
- Support in limited-capacity mode is provided through [Cisco Support Community](#) forums.

Cisco TelePresence Conductor Select

- For small to medium-sized deployments, an option key is available that enables support for up to 50 concurrent call sessions, enabling conference resource orchestration for more than one Cisco TelePresence Server or Cisco TelePresence MCU.
- Two medium sized Conductor virtual machines supporting up to 50 concurrent call sessions can be clustered together to provide resilience.

Cisco TelePresence Conductor

- For larger deployments, a full-capacity version of Cisco TelePresence Conductor is required.
- Up to 2400 concurrent call sessions or up to 30 Cisco TelePresence Servers or TelePresence MCUs are supported by one full-capacity Cisco TelePresence Conductor appliance or cluster.
- Up to three full-capacity Cisco TelePresence Conductors can be clustered to provide resilience.

Table 1 Summarizes capacity and clustering capability of Cisco TelePresence Conductor.

Table 1. Capacity and Clustering Capability for Different Sized Deployments of Cisco TelePresence Conductor

	Cisco TelePresence Conductor Essentials	Cisco TelePresence Conductor Select	Cisco TelePresence Conductor
	Limited Capacity Virtual Application	Medium Capacity Virtual Application	Full capacity virtual application or dedicated appliance
Suitable deployment	Small	Small to medium-sized	Medium-sized to large
Total number of conference bridges supported	1 (standalone)	30	30
Maximum number of concurrent call sessions supported	The number of calls supported by the conference bridge	50	2400
Clustering of TelePresence Conductors supported for resilience	No	Yes (limited to 2 medium capacity TelePresence Conductors)	Yes (up to 3 TelePresence Conductors)
Access to TAC support	No. (Support in limited-capacity mode is provided through Cisco Support Community forums)	Yes	Yes
Available as virtual machine or appliance	Virtual machine only	Virtual machine only	Virtual machine and appliance
Release and option keys required to install	No release or option key required	Upgrade option key to support 50 concurrent call sessions required	Full capacity TelePresence Conductor release key required

System Specifications

Table 2 lists specifications of Cisco TelePresence Conductor.

Table 2. Specifications of Cisco TelePresence Conductor

User interface	<ul style="list-style-type: none"> Supports Internet Explorer 8 or 9, Firefox 3 or later, Google Chrome, and Safari web browsers
Supported Cisco UCM and Cisco VCS versions	<ul style="list-style-type: none"> Supports Cisco UCM 8.6.2 or later (Version 9.1.1 or later is recommended to support encryption of rendezvous and ad-hoc calls using Secure Real-Time Transport Protocol (SRTP) and SIP Transport Layer Security (TLS). Refer to the Optimized Conferencing for Cisco Unified Communications Manager Solution Guide for more information.) Supports Cisco VCS Version X6.0 or later
Management interfaces	<ul style="list-style-type: none"> Supports industry standards such as RS-232, Secure HTTP (HTTPS), XML, Simple Network Management Protocol (SNMP), secure copy (SCP), and Secure Shell (SSH) Protocol Supports embedded setup wizard on serial port for initial configuration Supports management and monitoring of Cisco TelePresence Conductor Conferences with Cisco TelePresence Management Suite (TMS) (Version 14.3 or later of Cisco TMS is recommended) Supports call logging and diagnostics Supports logging to a syslog server
Resilience	<ul style="list-style-type: none"> Full-capacity versions can be deployed in triple-redundant cluster Two medium-sized Conductor virtual machines, supporting up to 50 concurrent call sessions, can be clustered together Supports duplicated databases and duplicated data
Cisco TelePresence Server and MCU support	<ul style="list-style-type: none"> Supports Cisco TelePresence Server Version 3.0 or later Supports Cisco TelePresence MCU 4200 Series Version 4.2 or later Supports Cisco TelePresence MCU 4500 Series Version 4.2 or later Supports Cisco TelePresence MCU 5300 Series Version 4.3 or later Supports Cisco TelePresence MCU MSE 8420 and 8510 Version 4.2 or later <p>Note: Cisco TelePresence Server Version 3.1 or later and Cisco TelePresence MCU Version 4.4 software are strongly recommended.</p>
Language	<ul style="list-style-type: none"> English
Cisco TelePresence Conductor Virtualized Application	
Server requirements for Cisco TelePresence Conductor Virtualized Application	<ul style="list-style-type: none"> Cisco UCS B- or C-Series Servers or third-party servers that meet the minimum requirements VMware vSphere or vCentre server running ESXi v4.1 or 5.0 update 1 Two 2.8-GHz (minimum) host CPU cores per Cisco TelePresence Conductor Virtual Machine; 6-GB RAM per virtual machine; 132-GB disk space per virtual machine (4-GB virtual disk 1 plus 128-GB virtual disk 2) <p>For full details, refer to the Cisco TelePresence Conductor Deployment Guide.</p>
Cisco TelePresence Conductor Appliance	
Physical dimensions (H x W x D)	<ul style="list-style-type: none"> 1.72 x 16.8 x 18 in. (43.5 x 426 x 457.2 mm) 1-rack-unit (1RU) rack-mount chassis
Interfaces	<ul style="list-style-type: none"> Four 10/100/1000BASE-TX Ethernet ports (RJ-45) (front) One RS-232 console port (RJ-45) (front)
Weight	<ul style="list-style-type: none"> 17.6 lb (8 kg) (unpacked)
Power	<ul style="list-style-type: none"> Auto-sensing 250W (maximum) 580-BTU-per-hour power supply 90-264 VAC full range at 47 or 63 Hz
Cooling system	<ul style="list-style-type: none"> Five 1.58-in. (40-mm) fans for system cooling
System control and indications	<ul style="list-style-type: none"> One power LED, one alarm LED, and four act/link/10/100/1000 LEDs on Ethernet ports One power on/off switch (rear)
Environmental data	<ul style="list-style-type: none"> Operating temperatures: 32 to 104°F (0 to 40°C) Storage temperatures: -4 to 140°F (-20 to 60°C) Relative humidity: 10 to 90% (noncondensing)
Certification	<ul style="list-style-type: none"> LVD 73/23/EC EMC 89/366/ECC

Approvals and compliance	<ul style="list-style-type: none"> • Directive 73/23/EEC (Low Voltage Directive) and directive 89/336/EEC (EMC Directive) • Standards EN 60950, EN 55022 Class A, EN 55024, and EN 61000-3-2/-3-3 • Approved according to UL 60950 and CAN/CSA C22.2 No. 60950 • Compliance with FCC15B Class A
---------------------------------	---

Ordering Information

To order Cisco TelePresence Conductor virtual applications or appliances, visit the [Cisco Ordering Home Page](#) and refer to Table 3, below. For details on how to order TelePresence Conductor on a per-user basis, as part of a Personal Multiparty conferencing solution for Named Hosts visit <http://www.cisco.com/go/personalmultiparty>.

Table 3. Ordering Information

Product Name	Part Number
Cisco TelePresence Conductor Essentials	
Limited capacity Virtual TelePresence Conductor; supports a single standalone TelePresence Server or TelePresence MCU	N/A (TelePresence Conductor .ova software can be downloaded from http://software.cisco.com/download)
Cisco TelePresence Conductor Select	
Mid-market Virtual TelePresence Conductor , supports up to 50 Call Sessions	R-VMCNDTRM-K9
Upgrade from TelePresence Conductor Select for Mid-market to Full Capacity Virtual TelePresence Conductor	L-CNDTR-UG-PAK
Full Capacity Cisco TelePresence Conductor	
Cisco TelePresence Conductor-30 MCUs/2400 Call Sessions (Virtualized Application)	R-VMCNDTR-K9
Cisco TelePresence Conductor-30 MCUs/2400 Call Sessions (Appliance)	CTI-CNDTR-K9

Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco Services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, visit <http://www.cisco.com/go/services>.

For More Information

For more information, visit the Cisco [TelePresence Conductor](#) homepage at <http://www.cisco.com/go/telepresenceconductor> or contact your local Cisco account representative.

This product includes software developed by Computing Services at [Carnegie Mellon University](#). This product includes software developed by the University of California, Berkeley, and its contributors.




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA

C78-709046-10 1/14