

CISCO 7600 SERIES SPA INTERFACE PROCESSOR-600

The Cisco® Interface Flexibility (I-Flex) design combines shared port adapters (SPAs) and SPA interface processors (SIPs), taking advantage of an extensible design that helps enable service prioritization for voice, video, and data services. Enterprise and service provider customers benefit from the improved economics of modular port adapters that are interchangeable across Cisco Systems® routing platforms.

Modular port adapters and programmable interface processors, which are interchangeable across Cisco routing platforms, protect network investments and reduce total cost of ownership (TCO). The Cisco I-Flex design maximizes connectivity options and offers superior service intelligence through programmable interface processors operating at line rate. This data sheet contains the specifications for the Cisco 7600 Series SPA Interface Processor-600 (7600 SIP 600; refer to Figure 1).

Figure 1. Cisco 7600 SIP 600 with 10-Port Gigabit Ethernet SPA



PRODUCT OVERVIEW

Ideal for both service provider and enterprise applications, the Cisco 7600 SIP 600 supports up to 10 Gbps of bandwidth and a wide range of interfaces; it provides the unique ability to combine both Layer 2 and Layer 3 services on the same line card. The combination of native Layer 2 bridging and Layer 3 routing distinguishes this line card among other products on the market, particularly in Metro Ethernet applications.

The innovative architecture of this industry-leading WAN services module is designed to deliver cost-effective high-touch features, combining both application-specific integrated circuit (ASIC) and network processor technology for an optimal combination of performance and flexibility. The Cisco 7600 SIP 600 provides distributed forwarding with proven ASIC technology in the forwarding path (routing and switching, NetFlow, access control lists [ACLs]) as well as for queuing and shaping functions to provide the maximum performance for these foundation features; additionally, a programmable network processor is included in the forwarding plane to facilitate flexibility and feature growth. This ideal technology combination provides customers with the necessary flexibility for future service deployments and allows them to scale the system capacity as required.

Table 1 lists primary features and benefits.

Table 1. Key Features and Benefits

Feature	Cisco 7600 SIP 600	Benefit
Modularity	One SPA per Cisco 7600 SIP 600 module	Offers high-performance, dense services while maintaining attractive footprint and scalability
Performance	Up to 24 millions of packets per second (Mpps)	Capable of line-rate performance with 41-byte IP packets
Packet Memory	256 MB	Up to 200 ms combined bidirectional buffering
Switch Fabric Connectivity	20-Gbps fabric channel	Uses 720-Gbps fabric modules for data forwarding
Online Insertion and Removal (OIR)	Support for OIR of the SIP and SPA	Provides hitless OIR to minimize impact of add, change, and remove operations

PRODUCT SPECIFICATIONS

Table 2. Product Specifications

Chassis Compatibility	<ul style="list-style-type: none"> All Cisco 7600 Series router and Cisco Catalyst® 6500 services switch chassis except the Cisco 7603
Central Forwarding Engine Compatibility	<ul style="list-style-type: none"> Cisco Catalyst® 6500 Series supervisor engines 720-3B, 720-3BXL, and later Requires switch fabric connectivity; therefore, the Cisco 7600 SIP 600 is not supported with Supervisor Engine 32
Distributed Forwarding Card (DFC)	<ul style="list-style-type: none"> DFC-3BXL Up to 24 Mpps, distributed forwarding Up to one million hardware forwarding entries Up to 256,000 NetFlow entries
Minimum Software Compatibility	<ul style="list-style-type: none"> Cisco IOS® Software Release 12.2(18)SXF or later Cisco IOS Software releases
Slot Configuration	<ul style="list-style-type: none"> One single- or double-height SPA per Cisco 7600 SIP 600 module
Memory	<ul style="list-style-type: none"> Route memory: 1 GB Packet memory: 256 MB (200 ms combined input/output buffering at 10 Gbps)
Supported SPAs	<ul style="list-style-type: none"> Cisco 1-Port 10 Gigabit Ethernet Shared Port Adapter (pluggable IEEE LAN PHY XFP optics) Cisco 10-Port Gigabit Ethernet Shared Port Adapter (SFP pluggable optics) Cisco 5-Port Gigabit Ethernet Shared Port Adapter (SFP pluggable optics) Cisco 1-Port OC-192/STM-64 POS Shared Port Adapter (XFP pluggable optics) Cisco 1-Port OC-192/STM-64 POS Shared Port Adapter (long-reach fixed optics)
Link Encapsulations	<ul style="list-style-type: none"> Ethernet II with optional IEEE 802.1q encapsulation Packet over SONET/SDH (POS) with either Point-to-Point Protocol (PPP) or Cisco High-Level Data Link Control (HDLC) encapsulation
Hardware Queues	<ul style="list-style-type: none"> 8000 queues (dynamically shared between ingress and egress processing) Hierarchical Quality of Service (HQoS): Up to 1000 parent queues
MAC Addresses	<ul style="list-style-type: none"> MAC-learning in hardware, at wire speed

Environmental Conditions	<ul style="list-style-type: none"> • Operating temperature: 32 to 104°F (0 to 40°C) • Storage temperature: –40 to 167°F (–40 to 75°C) • Relative humidity: 10 to 90%, noncondensing • Operating altitude: <ul style="list-style-type: none"> – UL Approval: –60 to 2000m – Functionally Tested to 3000m
MIBs	<ul style="list-style-type: none"> • Cisco Entity MIB (CISCO-ENTITY-MIB) • Cisco Entity Asset MIB • Cisco Entity Field-Replaceable Unit (FRU) Control MIB • Cisco Entity Alarm MIB • Interface IF MIB (RFC 2233) • Definitions of Managed Objects for Bridges (RFC 1493) • Evolution of Interfaces Group of MIB-II (RFC 1573) • Simple Network Management Protocol (SNMP) MIB II (RFC 1213) • Remote Monitoring (RMON) MIB (RFC 1757) • Switch Monitoring (SMON) MIB <p>Details on these MIBs are available at: http://www.cisco.com/en/US/products/hw/routers/ps368/prod_technical_reference_list.html</p>
Network Management	<ul style="list-style-type: none"> • Supported with CiscoWorks—CiscoView, CiscoWorks Resource Manager Essentials (RME) • Integrated Solution Center (ISC)
Physical Specifications	<ul style="list-style-type: none"> • Occupies one slot in a Cisco 7600 or Cisco Catalyst 6500 Series Chassis • Up to eight Cisco 7600 SIP 600s in a 9-slot chassis • Requires Supervisor Engine 720-3B or 3BXL • Dimensions (H x W x D): 1.75 x 15.375 x 16 in. • Weight: 13 lb (without SPA)
Power	<ul style="list-style-type: none"> • 341W maximum power consumption per Cisco 7600 SIP 600 with one SPA
Indicators	<ul style="list-style-type: none"> • Cisco 7600 SIP 600 module status: green (operational); orange (faulty)
Regulatory Compliance	<ul style="list-style-type: none"> • CE marking
Safety	<ul style="list-style-type: none"> • UL 60950 • CSA C22.2 No. 60950 • EN60950 • TS001 • IEC 60950 • AS/NZS3260

Electromagnetic Compatibility (EMC)	<ul style="list-style-type: none"> • FCC Part 15 Class A • ICES-003 Class A • VCCI Class A • EN55022 Class A • CISPR22 Class A • AS/NZS3548 Class A • EN61000-3-2 • EN61000-3-3 • EN61000-3-1 • EN55024 • EN50082-1 • EN300 386 • FCC Part 15 Class A • ICES-003 Class A • VCCI Class A • EN55022 Class A • CISPR22 Class A • AS/NZS CISPR 22 Class A • EN61000-3-2 • EN61000-3-3 • EN61000-6-1 • EN55024 • EN50082-1 • EN300 386
Telecommunications Standards	<ul style="list-style-type: none"> • ITU-T G.691 • ITU-T G.707 • ITU-T G.783 Sections 9-10 • ITU-T G.784 • ITU-T G.803 • ITU-T G.813 • ITU-T G.825 • ITU-T G.826 • ITU-T G.841 • ITU-T G.957 Table 3 • ITU-T G.958

[REFERENCE TABLE 3 IN TEXT.]

Table 3. Feature Support

Feature	Benefits
Network Protocols	<ul style="list-style-type: none">• IPv4 Unicast and Multicast• IPv6 Unicast and Multicast• Multiprotocol Label Switching (MPLS)• Ethernet bridging
QoS	<ul style="list-style-type: none">• Modular QoS CLI (MQC)
Congestion Avoidance	<ul style="list-style-type: none">• Weighted Random Early Detection (WRED) based on IP Precedence, differentiated services code point (DSCP), MPLS experimental bit (EXP)
Queuing and Shaping	<ul style="list-style-type: none">• Egress Class-Based Weighted Fair Queuing (CBWFQ)• Egress Low-Latency Queuing (LLQ)• Two levels of queuing hierarchy• Egress shaping
Traffic Classification and Bandwidth Policing	<ul style="list-style-type: none">• Classification based on:<ul style="list-style-type: none">– Extended ACL– IP Precedence and IP DSCP– MPLS EXP– VLAN– Input VLAN• Policer ingress single and dual rate, three color
ACLs and Security	<ul style="list-style-type: none">• Up to 32,000 access-list entries with no forwarding degradation• Hardware counters for ACL hits
Layer 2 and Layer 3 VPNs	<ul style="list-style-type: none">• Layer 2 VPNs<ul style="list-style-type: none">– Ethernet over MPLS with MAC learning– Virtual private LAN service (VPLS) (MPLS edge or dot1q edge)• Layer 3 VPNs<ul style="list-style-type: none">– MPLS VPN (RFC 2547-bis)– Inter-AS and CsC– Multicast VPN
Link Protection and Link Bundling	<ul style="list-style-type: none">• SONET automatic protection switching (APS) (1 + 1, revertive and nonrevertive)• MPLS Fast Reroute• EtherChannel®

ORDERING INFORMATION

To place an order, visit the [Cisco Ordering Home Page](#) or refer to Table 4.

Table 4. Ordering Information

Product Name	Part Number
Cisco 7600 Series SPA Interface Processor-600	7600-SIP-600

DOWNLOADING THE SOFTWARE

Visit the [Cisco Software Center](#) to download Cisco IOS Software Release 12.2(18)SXF (when used with Supervisor Engine 720).

SERVICE AND SUPPORT

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, refer to [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

FOR MORE INFORMATION

For more information about the Cisco 7600 SIP 600, visit <http://www.cisco.com/en/US/products/hw/modules/ps2706/ps4221/index.html> or contact your local Cisco account representative.

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright 2005 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, *Packer*, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StrataView Plus, TeleRouter, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R)

205258.N_ETMG_SP_8.05