

## Cisco CRS-1 8-Slot Single-Shelf System

The Cisco® CRS-1 Carrier Routing System is the industry's first carrier router offering continuous system operation, unprecedented service flexibility, and system longevity. The Cisco CRS-1 is powered by Cisco IOS® XR Software – a unique self-healing, distributed operating system designed for always-on operation while scaling system capacity up to 92 Tbps. The innovative system architecture combines the Cisco Silicon Packet Processor, the first programmable 40-Gbps application-specific integrated circuit (ASIC), with the Cisco Service Separation Architecture for unprecedented service flexibility and speed to service. The Cisco CRS-1 marks a new era in carrier IP Communications by powering the foundation for network and service convergence today while protecting investments for decades to come.

This data sheet provides detailed product specifications for the Cisco CRS-1 8-Slot Single-Shelf System. For more information about the Cisco CRS-1 or other interfaces available on the Cisco CRS-1, visit: <http://www.cisco.com/go/crs>.



### Product Specifications

**Table 1.** Specifications of Cisco CRS-1 8-Slot Single-Shelf System

Feature	Description
<b>Product Compatibility</b>	Compatible with all current Cisco CRS-1 physical layer interface modules (PLIMs) and the modular services card (MSC)
<b>Software Compatibility</b>	Cisco IOS XR Software Release 03.00
<b>Protocols</b>	<ul style="list-style-type: none"> <li>• Cisco Discovery Protocol</li> <li>• IPv4 and IPv6 addressing</li> <li>• Internet Control Message Protocol (ICMP)</li> <li>• Layer 3 routing protocols, including <ul style="list-style-type: none"> <li>◦ Border Gateway Protocol Version 4 (BGPv4)</li> <li>◦ Open Shortest Path First Version 2 (OSPFv2)</li> <li>◦ OSPFv3</li> <li>◦ Intermediate System-to-Intermediate System Protocol (IS-IS)</li> </ul> </li> <li>• Multicast forwarding with support for source-based and shared distribution trees and the following protocols <ul style="list-style-type: none"> <li>◦ Protocol Independent Multicast sparse mode (PIM-SM)</li> <li>◦ Bi-directional PIM (Bidir-PIM)</li> <li>◦ PIM Source Specific Multicast (PIM SSM)</li> <li>◦ Automatic Rendezvous Point (AutoRP)</li> </ul> </li> </ul>

Feature	Description
	<ul style="list-style-type: none"> <li>◦ Internet Group Management Protocol (IGMP) versions 1, 2 and 3</li> <li>◦ Multiprotocol BGP (MBGP)</li> <li>◦ Multicast Source Discovery Protocol (MSDP)</li> <li>• Multiprotocol Label Switching (MPLS) <ul style="list-style-type: none"> <li>◦ MPLS Label Distribution Protocol (LDP)</li> <li>◦ Resource Reservation Protocol (RSVP)</li> <li>◦ Diffserv Aware TE</li> </ul> </li> <li>• MPLS Traffic Engineering control plane (RFCs 2702 and 2430)</li> <li>• Route Policy Language (RPL)</li> <li>• Management <ul style="list-style-type: none"> <li>◦ Simple Network Management Protocol (SNMP)</li> <li>◦ Programmatic interfaces (XML)</li> </ul> </li> <li>• Security <ul style="list-style-type: none"> <li>◦ Message Digest Algorithm (MD5)</li> <li>◦ IP Security (IPSec) Protocol</li> <li>◦ Secure Shell (SSHv2)</li> <li>◦ Secure FTP (SFTP)</li> <li>◦ Secure Sockets Layer (SSL)</li> </ul> </li> </ul>
<b>Components</b>	<p>Each Cisco CRS-1 8-Slot Line-Card Chassis includes:</p> <ul style="list-style-type: none"> <li>• 1 CRS-1 8-Slot Line Card Chassis Route Processor (part number CRS-8-RP)</li> <li>• 4 Cisco CRS-1 8-slot fabric cards (part number CRS-8-FC/S)</li> <li>• 2 power supplies (either DC, AC type Wye, or AC type Delta)</li> <li>• 2 fan trays</li> </ul> <p>Optional items follow:</p> <ul style="list-style-type: none"> <li>• 8 Cisco CRS-1 line cards (part number CRS-MSC)</li> <li>• 8 Cisco CRS-1 PLIMs</li> <li>• Redundant CRS-1 8-slot route processor (part number CRS-8-RP/R)</li> </ul>
<b>Cards, Ports, and Slots</b>	<p>1-port OC-768c/STM-256c packet over SONET (POS)  4-port OC-192c/STM-64c POS/.Dynamic Packet Transport (DPT)  16-port OC-48c/STM-16 POS/DPT  8-port 10 Gigabit Ethernet  Plus support for all future PLIMs supported on Cisco CRS-1</p>
<b>Connectivity</b>	Initial interfaces: POS, DPT, and 10 Gigabit Ethernet; Future interfaces: Gigabit Ethernet and ATM
<b>Features and Functions</b>	<p>IP Features</p> <ul style="list-style-type: none"> <li>• Control-plane packet handling</li> <li>• IPv4 host services</li> <li>• IPv4 unicast forwarding</li> <li>• IPv4 equal-cost multipath (ECMP)</li> <li>• IPv6 host services</li> <li>• IPv6 forwarding services</li> <li>• IPv6 ECMP</li> </ul> <p>Forwarding Features</p> <ul style="list-style-type: none"> <li>• Access control lists (ACLs)</li> <li>• Quality of service (QoS) and class of service (CoS) using Modular QoS CLI (MQC)</li> <li>• IP packet classification and marking</li> <li>• Queuing – Both ingress and egress</li> <li>• Policing (both ingress and egress)</li> <li>• Diagnostic and network-management support</li> </ul> <p>Routing Features</p> <ul style="list-style-type: none"> <li>• Multiprotocol BGP Version 4 (MP-BGP v4)</li> <li>• OSPFv2</li> <li>• OSPFv3</li> <li>• IS-IS</li> <li>• Static routes</li> <li>• Routing Policy Language (RPL)</li> </ul> <p>IPv4 Multicast Features</p> <ul style="list-style-type: none"> <li>• Dynamic registration using IGMP</li> </ul>

Feature	Description
	<ul style="list-style-type: none"> <li>• Multicast Reverse Path Forwarding (RPF)</li> <li>• PIM SX</li> <li>• PIM source specific mode (PIM SSM)</li> <li>• Automatic route processing</li> <li>• MSDP</li> <li>• MBGP</li> <li>• Bidirectional PIM</li> <li>• Source specific multicast with IGMP v3</li> <li>• Explicit tracking of hosts, group, and channels for IGMPv3</li> <li>• Multicast nonstop forwarding (NSF)</li> </ul> <p>MPLS Features</p> <ul style="list-style-type: none"> <li>• MPLS forwarding and load balancing</li> <li>• LDP</li> <li>• RSVP</li> <li>• MPLS traffic-engineering features</li> <li>• Use-Network Interface (UNI)</li> <li>• Link Management Protocol (LMP)</li> </ul> <p>Security Features</p> <ul style="list-style-type: none"> <li>• Message Digest Algorithm 5 (MD5)</li> <li>• Secure Sockets Layer (SSL)</li> <li>• Secure Shell (SSH) Protocol and Secure FTP (SFTP)</li> <li>• Secure HTTP (SHTTP) support</li> <li>• Control packet policing</li> <li>• IP Security (IPSec)</li> </ul> <p>Manageability Features</p> <ul style="list-style-type: none"> <li>• Alarms management</li> <li>• Configuration management</li> <li>• Accounting and statistics management</li> <li>• Performance management</li> <li>• Control point and network management – Generic requirements</li> <li>• Terminal services enhancements</li> <li>• Enhanced command-line interface (CLI)</li> <li>• Extensible Markup Language (XML) interface</li> <li>• XML schemas (refer to specifications given previously)</li> <li>• Craft Works Interface (CWI)</li> <li>• Common Object Request Broker Architecture (CORBA) support</li> <li>• Simple Network Management Protocol (SNMP) and MIB support (refer to specifications given previously)</li> </ul>
<b>Memory</b>	Dependent on option chosen for route processor, up to 4 GB supported per Cisco CRS-1 8-Slot Line-Card Chassis Route Processor (part number CRS-8-RP)
<b>Options</b>	Cisco CRS-1 8-Slot Line-Card Chassis Route Processor (part number CRS-8-RP)
<b>Performance</b>	640-Gbps switching capacity
<b>Reliability and Availability</b>	<p>System Redundancy</p> <ul style="list-style-type: none"> <li>• Power-shelf redundancy 1:1</li> <li>• Fan-tray redundancy 1:1</li> <li>• Route-processor redundancy 1:1</li> <li>• Fabric-card redundancy 1:4</li> <li>• Dual homing with line cards</li> <li>• Support for APS</li> </ul> <p>Software Features</p> <ul style="list-style-type: none"> <li>• NSF using graceful restart for: IS-IS, OSPF, BGP, LDP, and RSVP</li> <li>• SONET APS (1:1)</li> <li>• Line-card OIR support</li> <li>• Fabric-card OIR support</li> <li>• Out-of-resource management</li> <li>• Process restartability</li> <li>• MPLS Fast Reroute (FRR)</li> <li>• Hot Standby Router Protocol (HSRP) and Virtual Router Redundancy Protocol (VRRP)</li> </ul>

Feature	Description
<b>MIBs</b>	<p>SNMP Framework Support</p> <ul style="list-style-type: none"> <li>• SNMP v1</li> <li>• SNMP v2c</li> <li>• SNMP v3</li> <li>• MIB II, including interface extensions (RFC 1213)</li> <li>• SNMP-FRAMEWORK-MIB</li> <li>• SNMP-TARGET-MIB</li> <li>• SNMP-NOTIFICATION-MIB</li> <li>• SNMP-USM-MIB</li> <li>• SNMP-VACM-MIB</li> </ul> <p>System Management</p> <ul style="list-style-type: none"> <li>• CISCO- BULK-FILE-MIB</li> <li>• CISCO-CONFIG-COPY-MIB</li> <li>• CISCO-CONFIG-MAN-MIB</li> <li>• CISCO-FLASH-MIB</li> <li>• CISCO-MEMORY-POOL-MIB</li> <li>• Cisco FTP Client MIB</li> <li>• Cisco Process MIB</li> <li>• Cisco Syslog MIB</li> <li>• CISCO-SYSTEM-MIB</li> <li>• CISCO-CDP-MIB</li> <li>• IF-MIB (RFC 2233/RFC 2863)</li> </ul> <p>Chassis</p> <ul style="list-style-type: none"> <li>• ENTITY-MIB ( RFC 2737)</li> <li>• CISCO-entity-asset-MIB</li> <li>• CISCO-entity-sensor-MIB</li> <li>• CISCO-FRU-MIB (Cisco-Entity-FRU-Control-MIB)</li> </ul> <p>Fabric MIB</p> <ul style="list-style-type: none"> <li>• CISCO-Fabric-HFR-MIB</li> <li>• CISCO-Fabric-Mcast-MIB</li> <li>• CISCO-Fabric-Mcast-Appl-MIB</li> </ul> <p>Routing Protocols</p> <ul style="list-style-type: none"> <li>• BGP4-MIB Version 1</li> <li>• OSPFv1MIB (RFC1253)</li> <li>• CISCO-IETF-IP-FORWARDING-MIB</li> <li>• IP-MIB (was RFC2011-MIB)</li> <li>• TCP-MIB (RFC 2012)</li> <li>• UDP-MIB</li> <li>• CISCO-HSRP-EXT-MIB</li> <li>• CISCO-HSRP-MIB</li> <li>• CISCO-BGP-POLICY-ACCOUNTING-MIB</li> </ul> <p>QoS</p> <ul style="list-style-type: none"> <li>• MQC-MIB (Cisco Class-Based QoS MIB)</li> <li>• CISCO-PING-MIB</li> </ul> <p>Traps</p> <ul style="list-style-type: none"> <li>• RFC 1157</li> <li>• Authentication</li> <li>• Linkup</li> <li>• Linkdown</li> <li>• Coldstart</li> <li>• Warmstart</li> </ul>
<b>Network Management</b>	<ul style="list-style-type: none"> <li>• Enhanced CLI</li> <li>• XML interface</li> <li>• CWI</li> <li>• SNMP and MIB support</li> </ul>
<b>Programming Interfaces</b>	XML schema support
<b>Physical Dimensions</b>	<p>Chassis Height: 38.5 in. (97.79 cm, with base cosmetics)</p> <p>Chassis Width: 17.5 in. (44.45 cm)</p>

Feature	Description
	<p>Chassis Depth: 36.6 in (92.964 cm); 40.5 in. (102.87 cm), including Cosmetics* (Includes full cosmetics)</p> <p>Weight</p> <ul style="list-style-type: none"> <li>• 330.8 lb (148.86 kg) chassis with fans, PDUs, and blanks (as shipped)</li> <li>• 650 lb (292.5 kg) chassis as shipped, including power shelves, and all line cards and route processors</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>• Maximum power consumption when chassis is fully configured with line cards with traffic running: 4834W</li> <li>• Chassis power supply maximum output capacity: 7.5kW for both DC power supply and AC power supply</li> </ul>
<b>Environmental Conditions</b>	<p>Storage temperature: -40 to 70°C (-40 to 158°F)</p> <p>Operating temperature:</p> <ul style="list-style-type: none"> <li>• Normal: 5 to 40°C (41 to 104°F)</li> <li>• Short-term: -5 to 50°C (23 to 122°F)</li> </ul> <p>Relative humidity:</p> <ul style="list-style-type: none"> <li>• Normal: 5 to 85 percent</li> <li>• Short-term: 5 to 90 percent but not to exceed 0.024 kg water per kg of dry air</li> </ul> <p>Note: Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. (This refers to a total of 360 hours in any given year, but, no more than 15 occurrences during that 1-year period.)</p>

## Approvals and Compliance

**Table 2.** Approvals and Compliance for Cisco CRS-1 8-Slot Single-Shelf System

Feature	Description
<b>Safety Standards</b>	<ul style="list-style-type: none"> <li>• UL/CSA/IEC/EN 60950-1</li> <li>• IEC/EN 60825 laser safety</li> <li>• AS/NZS 60950</li> <li>• FDA – Code of Federal Regulations laser safety</li> </ul>
<b>EMI</b>	<ul style="list-style-type: none"> <li>• FCC Class A</li> <li>• ICES 003 Class A</li> <li>• AS/NZS 3548 Class A</li> <li>• CISPR 22 (EN55022) Class A</li> <li>• VCCI Class A</li> <li>• BSMI Class A</li> <li>• IEC/EN 61000-3-2: Power Line Harmonics</li> <li>• IEC/EN 61000-3-3: Voltage Fluctuations and Flicker</li> </ul>
<b>Immunity (Basic Standards)</b>	<ul style="list-style-type: none"> <li>• IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8-kV Contact, 15-kV Air)</li> <li>• IEC/EN-61000-4-3: Radiated Immunity (10 V/m)</li> <li>• IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2-kV Power, 1-kV Signal)</li> <li>• IEC/EN-61000-4-5: Surge AC Port (4-kV CM, -2kV DM)</li> <li>• IEC/EN-61000-4-5: Signal Ports (1 kV)</li> <li>• IEC/EN-61000-4-5: Surge DC Port (1 kV)</li> <li>• IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms)</li> <li>• IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m)</li> <li>• IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations</li> </ul>
<b>ETSI and EN</b>	<ul style="list-style-type: none"> <li>• EN300 386: Telecommunications Network Equipment (EMC)</li> <li>• EN55022: Information Technology Equipment (Emissions)</li> <li>• EN55024: Information Technology Equipment (Immunity)</li> <li>• EN50082-1/EN-61000-6-1: Generic Immunity Standard</li> </ul>
<b>Network Equipment Building Standards (NEBS)</b>	<p>This product is designed to meet the following requirements (qualification in progress):</p> <ul style="list-style-type: none"> <li>• SR-3580: NEBS Criteria Levels (Level 3)</li> <li>• GR-1089-CORE: NEBS EMC and Safety</li> <li>• GR-63-CORE: NEBS Physical Protection</li> </ul>

**System Capacity**

**Table 3.** System Capacity for Cisco CRS-1 8-Slot Single-Shelf System

Number of Interface Slots	Maximum Capacity per Slot	Total Capacity
8	40 Gbps per slot ingress + 40 Gbps per slot egress	640 Gbps per single-shelf system

## Ordering Information

To place an order, visit the [Cisco Ordering Home Page](#) or refer to Table 4.

**Table 4.** Ordering Information for Cisco CRS-1 8-Slot Single-Shelf System

Product Name	Product Part Number
Cisco CRS-1 8-Slot Single-Shelf System	CRS-8/S

## Service and Support

Cisco Systems® offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, refer to [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

## For More Information

For more information about the 8-slot single-shelf configuration of the Cisco CRS-1 and the new world of networking, visit Cisco at <http://www.cisco.com/go/crs> or contact your local Cisco account representative.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

CCDE, CCENT, Cisco Eos, Cisco HealthPresence, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Alcatel, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CDPF, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quiktest, IOS, iPhone, iQuickStudy, iSendPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PO-Net, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TeraPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (081205)