

Cisco Catalyst 3750-X Fiber Switch

Cisco is introducing the new Cisco® Catalyst® 3750-X 12-port and 24-port Gigabit Ethernet Small Form-Factor Pluggable (SFP) switches. The Cisco Catalyst 3750-X fiber switches are enterprise-class stackable switches and can be used for aggregation solutions in small core, midmarket, or branch office environments. These switches provide high availability, scalability, security, energy efficiency, and ease of operation with innovative features such as Cisco StackPower™, four optional network modules, redundant power supplies, and Media Access Control Security (MACsec) features. The Cisco Catalyst 3750-X Series with StackWise® Plus technology provides scalability, ease of management, and investment protection for evolving business needs.

Primary Features and Benefits

Cisco Catalyst 3750-X fiber switches primary features:

- 12 and 24 Gigabit Ethernet SFP models
- Four optional uplink network modules with Gigabit Ethernet or 10 Gigabit Ethernet
- Dual redundant, modular power supplies and fans
- MACsec hardware-based encryption
- Flexible NetFlow and switch-to-switch hardware encryption with the uplink service module
- Open Shortest Path First (OSPF) for routed access in IP Base image
- IPv4 and IPv6 routing, multicast routing, advanced quality of service (QoS), and security features in hardware
- Enhanced limited lifetime warranty (LLW) with next business day (NBD) advance hardware replacement and 90-day access to Cisco Technical Assistance Center (TAC) support
- Enhanced Cisco EnergyWise for operational cost optimization
- USB Type-A and Type-B ports for storage and console respectively and an out-of-band Ethernet management port
- Cisco StackPower technology: An innovative feature and industry first for sharing power among stack members
- Cisco StackWise Plus technology for ease of use and resiliency with 64 Gbps of throughput

Switch Configurations

All switch models can be configured with four optional uplink network modules with Gigabit Ethernet or 10 Gigabit Ethernet ports. The switch models are available with either the IP Base or IP Services feature set. (See Table 1.)

Table 1. Cisco Catalyst 3750-X Fiber Switch Configurations

Feature Set	Models	Total Gigabit Ethernet Ports	Default AC Power Supply	Cisco StackPower
IP Base	WS-C3750X-12S-S	12 Gigabit Ethernet SFP	350W	Yes
	WS-C3750X-24S-S	24 Gigabit Ethernet SFP	350W	
IP Services	WS-C3750X-12S-E	12 Gigabit Ethernet SFP	350W	
	WS-C3750X-24S-E	24 Gigabit Ethernet SFP	350W	

Cisco Catalyst 3750-X and 3560-X Series Software

The two feature sets available with the Cisco Catalyst 3750-X fiber switches are:

- IP Base: Baseline Enterprise Services
- IP Services: Enterprise Services

The IP Base feature set provides comprehensive Layer 2 features and baseline enterprise services. IP Base also includes the support for OSPF for routed access, Cisco StackPower, and MACsec. The IP Services feature set provides full enterprise services that include advanced Layer 3 features such as Enhanced Interior Gateway Routing Protocol (EIGRP), OSPF, Border Gateway Protocol (BGP), Protocol Independent Multicast (PIM), and IPv6 routing such as OSPFv3 and EIGRPv6. All software feature sets support advanced security, QoS, and management features.

Availability

Cisco Catalyst 3750-X fiber switches will be available and orderable in June 2011.

Ordering Information

Table 2 provides ordering information for the new Cisco Catalyst 3750-X fiber switches.

Table 2. Cisco Catalyst 3750-X Fiber Switches Ordering Information

Product Number	Product Description
WS-C3750X-12S-S	Stackable 12 Gigabit Ethernet SFP Ethernet ports, with 350W AC power supply 1 RU, IP Base feature set
WS-C3750X-24S-S	Stackable 24 Gigabit Ethernet SFP Ethernet ports, with 350W AC power supply 1 RU, IP Base feature set
WS-C3750X-12S-E	Stackable 12 Gigabit Ethernet SFP Ethernet ports, with 350W AC power supply 1 RU, IP Services feature set
WS-C3750X-24S-E	Stackable 24 Gigabit Ethernet SFP Ethernet ports, with 350W AC power supply 1 RU, IP Services feature set

For More Information

For more information about the Cisco Catalyst 3750-X fiber switches, visit <http://www.Cisco.com>.

Service and Support

The Cisco Catalyst 3750-X fiber switches come with an enhanced limited lifetime warranty (E-LLW) that includes next business day delivery of replacement hardware where available and 90 days of 8x5 Cisco TAC support.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)