

## Cisco SGE2010 48-Port Gigabit Switch Cisco Small Business Managed Switches



### Performance and Reliability to Support Small Business Networks

#### Highlights

- 48 high-speed ports optimized for the network core or to support bandwidth-intensive applications
- Resilient clustering provides the ability to manage several switches as a single switch to support growing businesses
- Advanced security protects network traffic to keep unauthorized users off the network
- Simplified, web-based management for easy installation and configuration
- Limited lifetime warranty

**Figure 1.** Cisco SGE2010 48-Port Gigabit Switch



#### Product Overview

The Cisco® SGE2010 48-Port Gigabit Switch (Figure 1) allows you to expand your network securely. Web-based configuration of the switch is secured using SSL.

The Cisco SGE2010 is optimized for maximum system availability, with fully redundant stacking, redundant power options, and dual images for resilient firmware upgrades. The switch helps secure the network through IEEE 802.1Q VLANs, IEEE 802.1X port authentication, access control lists (ACLs), denial-of-service DoS prevention, and MAC-based filtering. The enhanced quality of service (QoS) and traffic-management features help ensure clear and reliable voice and video communications.

The Cisco SGE2010 provides resilient stacking for up to four units, or 192 ports. A stack of units is managed as a single switch with one web management interface. The Cisco SGE2010 can coexist in a stack with the Cisco SGE2000 and SGE2000P 24-Port Gigabit Switches and the Cisco SGE2010P 48-Port Gigabit Switch, for a maximum of 192 ports in a stack. The stacking capability includes master/backup unit behavior, ring and chain architecture, and hot insertion and removal of units.

An intuitive, highly secure management interface provides access to the comprehensive feature set of the Cisco SGE2010, for a better-optimized, more secure network.

## Features

- Forty-eight 10/100/1000 Ethernet ports
- Four mini Gigabit Interface Converter (mini-GBIC) slots (shared with four Ethernet ports) for fiber Gigabit Ethernet expansion
- Dual images for resilient firmware upgrades
- 96-Gbps nonblocking, store-and-forward switching capacity
- Simplified QoS management using 802.1p, differentiated services (DiffServ), or type of service (ToS) traffic prioritization
- Power redundancy when used with the Cisco RPS1000 380W Redundant Power Supply Unit
- Fully resilient stacking provides optimized growth with simplified management
- ACLs for granular security and QoS implementation
- Configuration and monitoring from a standard web browser
- Secure remote management of the switch via Secure Shell (SSH) and SSL encryption
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge (PVE) simplifies network isolation of guest connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)
- User/network port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate-limiting capabilities, including back pressure and multicast, broadcast, and flood control
- Port mirroring for noninvasive monitoring of switch traffic
- Jumbo frame support up to 10 KB
- Simple Network Management Protocol (SNMP) versions 1, 2c, and 3 and Remote Monitoring (RMON) support
- Fully rack mountable using included rack-mounting hardware

## Specifications

Table 1 contains the specifications, package contents, and minimum requirements for the Cisco SGE2010 48-Port Gigabit Switch

**Table 1.** Specifications for the Cisco SGE2010 48-Port Gigabit Switch

Feature	Description
<b>Specifications</b>	
<b>Ports</b>	48 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T with 4 Gigabit combo ports shared between mini-GBIC ports; console port; auto MDI/ MDI-X; auto negotiate/manual setting; RPS port for connecting to redundant power supply unit
<b>Buttons</b>	Reset button
<b>Cabling type</b>	Unshielded twisted pair (UTP) Category 5 or better for 10BASE-T/100BASE-TX; UTP Category 5 Ethernet or better for 1000BASE-T
<b>LEDs</b>	PWR, Fan, Link/Act, PoE, Speed, RPS, Master, Stack ID 1 through 8
<b>Performance</b>	
<b>Switching capacity</b>	96 Gbps nonblocking
<b>Forwarding capacity</b>	71.4 mpps (64-byte packets)
<b>Stacking</b>	

Feature	Description
<b>Stack operation</b>	<ul style="list-style-type: none"> <li>Up to 192 ports in a stack</li> <li>Hot insertion and removal</li> <li>Ring and chain stacking options</li> <li>Master and backup master for resilient stack control</li> <li>Auto-numbering or manual configuration of units in stack</li> </ul>
<b>Layer 2</b>	
<b>MAC table size</b>	8000
<b>Number of VLANs</b>	256 active VLANs (4096 range)
<b>VLAN</b>	Port-based and 802.1Q tag-based VLANs, protocol-based VLAN, management VLAN, multicast TV VLAN, PVE, GVRP
<b>Head-of-line (HOL) blocking</b>	HOL blocking prevention
<b>Layer 3</b>	
<b>Layer 3 options</b>	Static routing; classless interdomain routing (CIDR); 60 static routes; IPv4; forwarding in silicon – wire-speed forwarding of Layer 3 traffic
<b>IPv6</b>	
<b>IPv6 options</b>	IPv6 over Ethernet, dual stack, IPv6 over IPv4 network with Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnel, IPv6 neighbor discovery, stateless address configuration, maximum transmission unit (MTU) discovery, WEB, SSL, Telnet, Ping, Traceroute, Simple Network Time Protocol (SNTP), Trivial File Transfer Protocol (TFTP), SNMP, RADIUS, ACLs, QoS, protocol-based VLANs
<b>Management</b>	
<b>Web user interface</b>	Built-in web user interface for easy browser-based configuration (HTTP/HTTPS)
<b>SNMP</b>	SNMP versions 1, 2c, and 3 with support for traps
<b>SNMP MIBs</b>	<ul style="list-style-type: none"> <li>RFC1213 MIB-2,</li> <li>RFC2863 interface MIB</li> <li>RFC2665 Ether-like MIB</li> <li>RFC1493 bridge MIB</li> <li>RFC2674 extended bridge MIB (P-bridge, Q-bridge)</li> <li>RFC2819 RMON MIB (groups 1, 2, 3, and 9 only)</li> <li>RFC2737 entity MIB</li> <li>RFC 2618 RADIUS client MIB,</li> <li>RFC 1215 traps</li> </ul>
<b>RMON</b>	Embedded RMON software agent supports 4 RMON groups (history, statistics, alarms, and events) for enhanced traffic management, monitoring, and analysis)
<b>Firmware upgrade</b>	<ul style="list-style-type: none"> <li>Web browser upgrade (HTTP/HTTPS) and TFTP</li> <li>Dual images for resilient firmware upgrades</li> </ul>
<b>Port mirroring</b>	Traffic on a port can be mirrored to another port for analysis with a network analyzer or RMON probe.
<b>Other management</b>	Traceroute, single IP management, SSL security for web user interface, SSH, RADIUS, port mirroring, TFTP upgrade, Dynamic Host Configuration Protocol (DHCP) client, BOOTP, SNTP, Xmodem upgrade, cable diagnostics, Ping, syslog, Telnet client (SSH secure support)
<b>Security</b>	
<b>IEEE 802.1X</b>	802.1X RADIUS authentication, MD5 hash; guest VLAN; single/multiple host mode
<b>ACLs</b>	<ul style="list-style-type: none"> <li>Drop or rate limit based on source and destination MAC or IP address, protocol, port, VLAN, differentiated services code point (DSCP)/IP precedence, TCP/ User Datagram Protocol (UDP) source and destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP) packets, Internet Group Management Protocol (IGMP) packets, DHCP snooping, Address Resolution Protocol (ARP) inspection, and IP source address guard</li> <li>Up to 1018 rules</li> </ul>
<b>Advanced Security</b>	<ul style="list-style-type: none"> <li>IP Source Guard</li> <li>STP Root Guard</li> <li>Dynamic ARP Inspection</li> <li>DHCP Snooping</li> </ul>
<b>Availability</b>	
<b>Link aggregation</b>	Using IEEE 802.3ad LACP, up to 8 ports in up to 8 groups
<b>Storm control</b>	Broadcast, multicast, and unknown unicast
<b>DoS prevention</b>	DoS attack prevention

Feature	Description
<b>Spanning Tree</b>	<ul style="list-style-type: none"> <li>• IEEE 802.1D Spanning Tree</li> <li>• IEEE 802.1w Rapid Spanning Tree</li> <li>• IEEE 802.1s Multiple Spanning Tree and Fast Linkover</li> </ul>
<b>IGMP (version 1 and 2) snooping</b>	Limits bandwidth-intensive multicast traffic to only the requestors; supports 256 multicast groups
<b>Power redundancy</b>	Connection to RPS unit for power redundancy
<b>Quality of Service</b>	
<b>Priority levels</b>	4 hardware queues
<b>Scheduling</b>	Priority queuing and weighted round-robin (WRR)
<b>Class of service</b>	Port based; 802.1p VLAN priority based; IPv4/v6 IP precedence/ToS/DSCP based; DiffServ; classification and re-marking ACLs
<b>Rate limiting</b>	Ingress policer; egress rate control; per VLAN
<b>Statistics</b>	16 meters
<b>Standards</b>	
<ul style="list-style-type: none"> <li>• 802.3 10BASE-T Ethernet</li> <li>• 802.3u 100BASE-TX Fast Ethernet</li> <li>• 802.3ab 1000BASE-T Gigabit Ethernet</li> <li>• 802.3z Gigabit Ethernet</li> <li>• 802.3x flow control</li> <li>• 802.3ad; 802.1D Spanning Tree Protocol (STP)</li> <li>• 802.1Q/p VLAN</li> <li>• 802.1w Rapid STP</li> <li>• 802.1s Multiple STP</li> <li>• 802.1X port access authentication</li> </ul>	
<b>Environmental</b>	
<b>Dimensions W x D x H</b>	17.32 x 14.70 x 1.73 in. (440 x 375 x 44 mm)
<b>Unit weight</b>	10.89 lb (4.94 kg)
<b>Power</b>	100–240V 47–63 Hz, internal, universal; also equipped with external redundant power supply connector for external power supply, –48V DC
<b>Certification</b>	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47)
<b>Operating temperature</b>	32° to 104°F (0° to 40°C)
<b>Storage temperature</b>	–4° to 158°F (–20° to 70°C)
<b>Operating humidity</b>	10% to 90%, relative, noncondensing
<b>Storage humidity</b>	10% to 95%, relative, noncondensing
<b>Package Contents</b>	
<ul style="list-style-type: none"> <li>• Cisco SGE2010 48-Port Gigabit Switch</li> <li>• AC power adapter with power cord</li> <li>• Two rack-mounting kits with eight screws</li> <li>• CD-ROM with user documentation (PDF) included</li> <li>• Registration card</li> <li>• Console cable</li> </ul>	
<b>Minimum Requirements</b>	
<ul style="list-style-type: none"> <li>• Web browser: Mozilla Firefox version 1.5 or later, or Microsoft Internet Explorer version 5.5 or later</li> <li>• Category 5 Ethernet network cable</li> <li>• TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in the network</li> </ul>	
<b>Product Warranty</b>	
Limited lifetime warranty with return to factory replacement, one year telephone support and software fixes for the warranty term.	

## Service & Support

Cisco Small Business switches are backed by the Cisco Small Business Support Service, which provides affordable peace-of-mind coverage. This subscription-based service helps you protect your investment and derive maximum value from Cisco Small Business products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes software updates, access to the Cisco Small Business Support Center, and expedited hardware replacement.

Cisco Small Business products are supported by professionals in Cisco Small Business Support Center locations worldwide who are specifically trained to understand your needs. The Cisco Small Business Support Community, an online forum, enables you to collaborate with your peers and reach Cisco technical experts for support information.

## Cisco Limited Lifetime Hardware Warranty

This Cisco Small Business product offers a limited lifetime hardware warranty with return to factory replacement and a 1-year limited warranty for fans and power supplies. In addition, Cisco offers telephone technical support at no charge for the first 12 months following the date of purchase and software bug fixes for the warranty term. To download software updates, go to: <http://www.cisco.com/cisco/web/download/index.html>.

Product warranty terms and other information applicable to Cisco products are available at <http://www.cisco.com/go/warranty>.

## For More Information

For more information on Cisco Small Business products and solutions, visit: <http://www.cisco.com/smallbusiness>



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)