

Cisco Catalyst 4900M Switch DC Power Supply

PB508309

Cisco is pleased to announce the availability of DC power supplies for the Cisco Catalyst® 4900M Switch. The 1000-watt (W) DC power supply is ideal for customers with a DC power environment. The Cisco Catalyst 4900M supports dual internal power supplies. The addition of the DC power supply broadens the capability of the Cisco Catalyst 4900M to be deployed in an environment that requires a dual DC power supply or AC-to-DC failover for resiliency.

Catalyst 4900M DC Power Supply Features and Specifications

- Hot swappable
- AC-to-DC failover
- 1+1 redundancy
- Power supply output: 960W
- DC input operating range: –48 to –60 VDC
- DC voltage output: 12V

Availability

The Cisco Catalyst 4900M Switch DC power supply is available for ordering and shipment in Q4CY08. Table 1 provides ordering information for the product. Table 2 provides ordering information for the minimum Cisco IOS® Software support required.

Table 1. Ordering Information

Product Name	Part Number
4900M DC power supply 1000 watts	PWR-C49M-1000DC
Redundant DC PS for 4900M	PWR-C49M-1000DC/2
4900M DC power supply 1000 watts (spare)	PWR-C49M-1000DC (=)

Table 2. Minimum Cisco IOS Software Support

Product Name	Part Number
Cisco CAT4900M IOS IP BASE W/O CRYPTO	S49MIPB-12246SG
Cisco CAT4900M IOS IP BASE SSH	S49MIPBK9-12246SG
Cisco CAT4900M IOS ENTERPRISE SERVICES W/O CRYPTO	S49MES-12246SG
Cisco CAT4900M IOS ENTERPRISE SERVICES SSH	S49MESK9-12246SG

Service and Support

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco® services help you protect your network investment, optimize network operations, and prepare your network for new applications

For More Information

For more information about the Cisco Catalyst 4900M DC power supply, visit:
Cisco Catalyst 4900 Series Switches at <http://www.cisco.com/go/4900>
and the Cisco Catalyst 4900M Switch Installation Guide at
<http://www.cisco.com/en/US/docs/switches/lan/catalyst4900/4900M/installation/guide/4900Mod.html>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)