

Cisco Explorer 4642HD and 4652HD High-Definition Set-Tops

Power, flexibility, and advanced security features highlight the Cisco® Explorer® 4642HD and 4652HD High-Definition Set-Tops. Additionally, these set-tops support Multimedia over Coax Alliance (MoCA™) technology, which lets subscribers use their cable wiring for LAN connections.

The 4642HD and 4652HD set-tops support tru2way™ (formerly OCAP™). The set-tops also offer MPEG-4 (H.264) high definition (HD) and standard definition (SD) decoding with HD and SD outputs and DOCSIS® 2.0 data capability. The 4652HD set-top also provides analog tuning.

Figure 1. Cisco Explorer 4652HD Front Panel (image may vary from actual product and specification)



Features

Network Utilization Enhancements

- **1 GHz Tuning** enables cable operators to expand network bandwidth to provide additional services such as VOD, tru2way, DOCSIS 2.0, and high-speed data
- **MPEG-4 (H.264) Decoding** supports compression technology that provides better video quality at approximately half the data rate of MPEG-2
- **DOCSIS 2.0** provides greatly increased upstream throughput for future advanced services and provides a path for future IP video services (optional software)

OpenCable™ and Conventional Network Support

- **PowerKEY® Conditional Access System** secures digital services using symmetric encryption algorithm for content protection
- **Axiom™ Middleware** supports tru2way applications such as Service Navigators, Games, and other future tru2way applications (optional software)
- **DSG (DOCSIS Set-top Gateway)** provides a powerful standard transport mechanism for command and control signaling between the set-top and service provider network (optional software)
- **DAVIC Receiver/Transmitter** allows IP-based, real-time, two-way communication between the set-top and service provider network for on-demand services (optional software)

Home Networking Features

- **USB 2.0 Connection** enables a host connection to peripheral devices such as navigation controllers, network adapters, and memory media readers
- **MoCA Connection** enables an IP LAN connection over coax cable, which minimizes the need for new wiring in the home
- **Ethernet Connection** enables a connection to the home IP LAN for advanced services such as content sharing to the set-top from retail-purchased electronic devices (optional)

Figure 2. Cisco Explorer 4652HD Front Panel (image may vary from actual product and specification)



Table 1. Front Panel

Feature	Description
Controls	Vol+, Vol-, Ch+ Ch-, Select, Guide, Info, Exit, Settings, IR receiver, Power
Connections	USB 2.0 host, software-controlled
Indicators	Four-segment LED digits, Power icon, Message icon, HDTV, 5.1, Auto, 1080i/p, 720i/p, 480i/p
Color	Black, grey text
Branding	Cisco, model number, provision for customer brand

Figure 3. Cisco Explorer 4652HD Back Panel (image may vary from actual product and specification)



Table 2. Back Panel

Feature	Description
Connections In	Cable In with MoCA
Connections-Interactive	USB 2.0 Host, RJ-45 Ethernet, software controlled
Connections Out	HDMI™ (1.3) with CEC, IEEE 1394 (4-pin), L/R Audio, Baseband Video, YPbPr, IR, S-Video, Optical Digital Audio, Coaxial Digital Audio Out, RF Out, Switched Outlet, see Note 1
Output Resolutions	720 x 480i 60 Hz, 1920 x 1080i 60 Hz, 1920 x 1080p 30 Hz, 1920 x 1080p 24 Hz, 1280 x 720p 60 Hz, 720 x 480p 60 Hz, 720 x 480i 60 Hz, software controlled, see Note 1
Output Control	Scaled video in graphics, scaled HD video in graphics, graphics on HD and SD outputs, aspect ratio control, native resolution pass-thru, HD down convertible to SD, software controlled
Power Input	Polarized 2-prong modular cord plug, 115 VAC, 60 Hz
Power Output	Polarized 2-prong outlet, at input line voltage, software controlled
Labels	Serial Number, eCM MAC Address, RF MAC Address (on bottom panel)

Product Specifications

Table 3. Product Specifications

Specification	Value
Tuning and Decoding	
Tuning	Analog (4652HD), QAM 64 or 256, In-Band 54 MHz-1 GHz, A/V in display, QPSK out-of-band (OOB) 70-130 MHz, DOCSIS 91-867 MHz, MoCA 1.0-1.5 GHz
Video Decoders	MPEG-2 MP@ML, MP@HL (SD, 720 x 480i), MPEG-4 (H.264) up to HP@L4.0 (HD), VC1, Video Scaling, software controlled
Audio Decoders	Dolby™ Digital to 5.1, MPEG-1 and MPEG-2, Dolby Digital+, AAC, AAC+, AC3, MP3
Conditional Access	Embedded PowerKEY
Graphics Engine	Up to 960 x 540 resolution, 32 bit (16 million) color
DAVIC	FDC (Forward Data Channel) 1.54 Mbps QPSK, RDC (Reverse Data Channel) 1.54 Mbps QPSK, FAT QAM Channel Downstream, Software Controlled
DOCSIS	OOB and interaction via DOCSIS 2.0, DOCSIS Set-top Gateway, Baseline Privacy Interface, Software Controlled
Memory/Storage	
RAM	Minimum of 128 MB, see Note 2
Flash	Minimum of 32 MB
NVM	Minimum of 16 KB
Processors	
Application/CPU	700 MHz (approximately 1000 dMIPs)
DOCSIS	200 MHz CPU
Network	400 MHz CPU
Dimensions	
Product (HxWxD)	2.25 in. x 13.75 in. x 9 in. (5.7 cm x 34.9 cm x 22.9 cm)
Product Weight	4.0 lbs (1.8 kg)
Carton (HxWxD)	Carton of 5 units = 16.5 in. x 11.25 in. x 16.5 in. (41.9 cm x 28.6 cm x 41.9 cm)
Total Weight	Carton of 5 units = 24.0 lbs (10.9 kg)
Environment Specifications	
Placement	Locate with at least 2 inches of open space above and on each side
Room Temperature	32° to 105°F (0° to 40°C) during operation
Storage Temperature	14° to 158°F (-10° to 70°C)
Power Dissipation	50W maximum peak, ENERGY STAR Tier 1

Table 4. Accessories

Specification	Value
In Carton	
	Power Cord, HDMI Cable, Quick Reference Guide
Sold Separately	
	License, Axiom OCAP (tru2way) Middleware, non-DVR, see Note 2
	SARA Software License, 1 year term
	SARA Software License, 2 year term
	AllTouch® AT8550 Remote Control
	AllTouch AT8650 Remote Control
	RGB Adapter and Cables
	Part Number
	4014594
	4020466
	4020467
	4006369 is EOL
	4016237
	749790 is EOL

Specification	Value	
	IR Extender - 12 ft (3.65 m)	1001807 is EOL
	IR Extender - 24 ft (7.32 m)	4006725 is EOL
	IR Extender - 12 ft (3.65 m)	1004648
	HDMI-to-HDMI Cable (additional or replacement)	1002048

Ordering Information

Table 5. Ordering Information

Model	Description	Part Number Set-Top with PowerKEY M-Card Module
Cisco Explorer 4642HD	Cisco Explorer 4642HD High Definition Interactive Set-Top (with 512 MB)	4034487 is EOL
Cisco Explorer 4652HD	Cisco Explorer 4652HD High Definition Interactive Set-Top (with 512 MB)	4024131 is EOL
Cisco Explorer 4642HD	Cisco Explorer 4642HD High Definition Interactive Set-Top (with 512 MB)	4043844

Notes:

- 1080p/24 or 1080p/30 output formats are available on HDMI, if those formats are presented to the set-top box at its input. Incoming video formats will not be converted to either of these for output. Output of these formats is under software control.
- Axiom Middleware for tru2way (formerly OCAP) support is recommended only for the 4600 models that have a minimum of 256 MB RAM.

AVC Video License

With respect to each AVC/H.264 product, we are obligated to provide the following notice:

THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD ("AVC VIDEO") AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE <http://www.mpegla.com>.

Accordingly, please be advised that service providers, content providers, and broadcasters are required to obtain a separate use license from MPEG LA prior to any use of AVC/H.264 encoders and/or decoders.

HDMI

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)