


RF Amplifier Accessories



22365

Part Number	Type	Tap/Thru Leg	Typical Insertion Loss (dB) at Various Frequencies (MHz)										
			5	30	50	300	330	400	450	550	600	750	860
467778	Jumper		0.02	0.03	0.05	0.10	0.11	0.11	0.12	0.12	0.13	0.13	0.16
502110	2-way		3.3	3.3	3.3	3.5	3.6	3.6	3.7	3.8	3.9	4.0	4.4
502115	DC-8	Thru Tap	1.4	1.3	1.2	1.3	1.3	1.4	1.4	1.5	1.6	2.1	2.5
			8.1	8.1	8.1	8.0	8.0	7.9	7.8	7.7	7.7	7.7	7.9
502120	DC-12	Thru Tap	1.3	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.1	1.3	1.4
			12.2	12.2	12.2	12.3	12.3	12.2	12.2	12.1	12.1	12.0	11.9

PLUG-IN PASSIVES

Plug-in passives are used in the System Amplifier I, II and III, and Variable FITT products to eliminate or reduce the need for external devices (jumper is used for continuity) at amplifier stations. The two-way splitter is also used as a reverse combiner in some amplifier products. Order by part number from the table above.

TRUE TILT CORRECTION NETWORKS (TTCN)

True Tilt Correction Networks are used during initial setup of broadband plant. It allows direct conversion of true tilt signals to a flat response. The TTCN is connected between the amplifier test point and the field test equipment with a short piece of 75 Ohm test cable. This results in a flat signal amplitude (frequency response observed when signals are properly tilted). Measurements can thus be made without lengthy, error-producing calculations to ascertain flatness of response. Order by part number from the table below.



22361

Part Number	True Tilt (dB)	Frequency Range (MHz)	Insertion Loss @ High Frequency (dB)
344332	3	50-550	7
344331	9	50-550	15
503782	9	46-750	15
507720	6	46-750	15
509709	11	46-750	15

CIRCUIT BREAKERS

Circuit breakers can be used in place of fuses, fuse shunts, or jumpers in several product applications. Order by part number from the table below.

Part Number	Ampere Rating	Product Application
501026	5	System Amplifier I
511216	5	System Amplifier II and III
511217	8	System Amplifier II and III



22369




21355

LONG REACH TEST POINT ADAPTER

The 75 ohm push-in test point adapter allows access to amplifier test points without opening the amplifier housing (when housings with external test point access are used). Order part number 501111.

CABLE SEIZURE WRENCH

The cable seizure wrench is machined from high grade stainless steel and is used to secure the cable seizure fittings in the Line Extender II and III. Order part number 143190.



10049



21462

REVERSE TEST POINT ADAPTER FOR LEII

The reverse test point adapter for the LEII is a device that permits a test cable to be connected to reverse test points in a Line Extender II module. Order part number 500477.

REVERSE INJECTION TEST PROBE (3 DB) FOR SYSTEM AMPLIFIER I, II AND III

The reverse injection test probe is used to inject a reverse test carrier into the network during system alignment. It has a 3 dB insertion loss, thus the measurement is 23 dB below actual level $[(-20 \text{ dB test point}) + (-3 \text{ dB test probe})]$. Order part number 276982.



22446

REVERSE INJECTION FILTER FOR LEII

The reverse injection filter for the LEII is used to inject a reverse test carrier into the network during system alignment. It replaces the reverse input filter during this process and has a -20 dB coupler in the filter module. Order part number that corresponds to system reverse split.

- #539356 - Reverse Injection Filter (30/46 MHz split)
- #538643 - Reverse Injection Filter (40/51 MHz split)
- #539358 - Reverse Injection Filter (50/70 MHz split)
- #548531 - Reverse Injection Filter (65/88 MHz split)

SYSTEM AMPLIFIER HIGH CURRENT SEIZURE KIT

The High Current Seizure Kit allows upgrading of existing System Amplifier II housings from 10 ampere current capacity to 15 ampere (steady state). This is achieved by replacing the tin plated connectors with silver plated ones. It is very important when upgrading that the System Amplifier module is also a high current version (with silver plated "F" connectors). This will be indicated by blue insulation on the "F" connector itself (the seizure assembly also has blue insulation). The High Current Seizure Kit consists of 4 seizure assemblies, 4 anvils, 2 housing labels, and installation instructions. Order part number 548775.

EXTERNAL DIPLEX FILTERS

External diplex filters are used wherever it is necessary to separate the forward and reverse path and an amplifier is not present. The filter is contained in a two-way splitter housing. The table on the following page lists the external diplex filters available. Order by part number.



22359

External Diplex Filters

High Frequency (MHz)	Band Split (MHz)	Part Number	AC Power Passing (Yes/No)
550	30/46	234250	No
750	30/46	509748	No
750	30/46	510505	Yes
750	40/51	540028	Yes
750	40/51	540557	No
750	50/70	541384	No

Specifications for External Diplex Filters

	Part Number					
Specifications	234250	509748	510505	540028	540557	541384
Return Loss (Forward/Reverse)	19.0/19.0	16.0/15.0	16.5/15.0	16.0/15.0	16.5/16.5	19.0/19.0
Insertion Loss (dB)	0.5	0.6	1.5	1.0	1.0	1.0
Frequency Response (dB)	±0.4	±0.25	±0.5	±1.0	±0.75	±0.4

Forward Group Delay ¹

Part Number											
234250		509748		510505		540028		540557		541384	
ns @ 3.58	Freq. (MHz)	ns @ 3.58	Freq. (MHz)	ns @ 3.58	Freq. (MHz)	ns @ 3.58	Freq. (MHz)	ns @ 3.58	Freq. (MHz)	ns @ 3.58	Freq. (MHz)
2.8	55.25	TBD	55.25	3.1	55.25	TBD	55.25	8.9	55.25	TBD	67.25
1.6	61.25	TBD	61.25	1.8	61.25	TBD	61.25	3.9	61.25	TBD	77.25
1.1	67.25	TBD	67.25	1.3	67.25	TBD	67.25	2.2	67.25	TBD	83.25
0.6	77.25	TBD	77.25	0.7	77.25	TBD	77.25	1.1	77.25	TBD	91.25

Reverse Group Delay ²

Part Number											
234250		509748		510505		540028		540557		541384	
ns @ 2.0	Freq. (MHz)	ns @ 2.0	Freq. (MHz)	ns @ 2.0	Freq. (MHz)	ns @ 2.0	Freq. (MHz)	ns @ 2.0	Freq. (MHz)	ns @ 2.0	Freq. (MHz)
0.4	5-7	TBD	5-7	63.0	5-7	TBD	5-7	0.15	5-7	TBD	5-7
0.5	7-9	TBD	7-9	21.7	7-9	TBD	7-9	0.2	7-9	TBD	7-9
0.6	9-11	TBD	9-11	9.4	9-11	TBD	9-11	0.2	9-11	TBD	9-11
4.7	24-26	TBD	24-26	6.7	24-26	TBD	34-36	6.5	34-36	TBD	44-46
6.6	26-28	TBD	26-28	9.4	26-28	TBD	36-38	10.3	36-38	TBD	46-48
10.4	28-30	TBD	28-30	19.3	28-30	TBD	38-40	19.0	38-40	TBD	48-50

Notes:

¹ Chrominance / Luminance delay @ 3.58 MHz above video carrier

² Propagation delay in 2 MHz bandwidth

Specifications shown are typical. Actual measurements may vary.

RF Amplifier Accessories



Scientific-Atlanta, Inc. <http://www.sciatl.com>
United States: 4261 Communications Drive, Norcross, GA 30093; Tel: 800-433-6222; Fax: 770-903-4617
Canada: 7725 Lougheed Highway, Burnaby, BC V5A 4V8; Tel: 604-420-5322; Fax: 604-420-5941
United Kingdom: Home Park Estate, Kings Langley, Herts WD4 8LZ, England; Tel: 44-923-266-133; Fax: 44-192-327-0448
Singapore: 1 Claymore Drive, #08-11 Orchard Towers, Singapore 229594; Tel: 65-733-4314; Fax: 65-733-2706
Hong Kong: Suite 56 & 57, 5/F New Henry House, 10 Ice House Street, Central, Hong Kong; Tel: 852-2522-5059; Fax: 852-2522-5624

88D116Z © 1996 Scientific-Atlanta, Inc. All rights reserved. Printed in USA. 0996M