

## Continuum DVP™ eXtra Dense QAM Array (XDQA) for Video-on-Demand Delivery

### Description

The Scientific-Atlanta® Continuum DVP™ eXtra Dense QAM Array (XDQA) is specifically targeted to cable operators looking for a high-end, cost and space-efficient solution for their video-on-demand (VOD/SVOD) rollout. It is a self-contained device combining GbE Interfacing, Routing, Multiplexing, QAM modulation and up-conversion functions.



Scientific-Atlanta's DirectRF™ technology ensures QAM specifications meeting or exceeding the DOCSIS standard <sup>(1)</sup>. Superior RF performance is especially critical when migrating to IP backbones for distributing broadcast services. The Continuum DVP XDQA allows one QAM product for narrowcast and broadcast services.

The Continuum DVP eXtra Dense QAM array is an ideal bridge between flexible IP and Gigabit Ethernet based backbone networks and existing QAM set-top boxes. Its hot swappable modular design allows for scalability by adding QAM cards only when more capacity is needed. QAM cards are configured automatically when inserted, which reduces set-up and maintenance time to a minimum.

The Continuum DVP eXtra Dense QAM Array can be configured via an embedded user interface that can be accessed with a standard Web browser. There is a dedicated Ethernet port for system management and control. An open communication protocol (SNMP) is provided to interface with the VOD management system.

### Features

- Integrated solution combining GbE Interfacing, Routing, Multiplexing, QAM modulation and up-conversion
- Compact design, up to 12 QAM channels in 1 RU
- Hot swappable, auto-configurable QAM cards containing two QAM channels on single RF connector
- Fully redundant powering (AC/DC, DC/DC, or AC/AC)
- Total capacity of 120 VOD streams (4 Mbps, 6 MHz, 256 QAM)
- New DirectRF technology significantly reduces the price per stream
- RF specifications meeting or exceeding DOCSIS <sup>(1)</sup>
- Works with all major VOD servers and STB brands
- Supports HD streams
- Direct interfacing from all major IP/Gigabit Ethernet backbone solutions
- Extremely low power consumption
- Modular design allowing for easy expansion, upgrade and maintenance
- Available for all QAM modulation standards (64 & 256 QAM for ITU-A, B & C)
- Fully agile from 45 to 860 MHz
- Dual GbE inputs - optical (SFP) and electrical (RJ-45) are standard
- Supports pre-encryption
- Self-cooling system for efficient space usage (stackable)
- Easy setup using a Web browser
- SNMP management interface

(1) RF Output Level not taken into account



## Specifications

|  |  |
|--|--|
| <b>GbE Input Interface</b>                               |  |
| Number of inputs   | 1+1 (for redundancy)   |
| Connector  | Electrical RJ-45 and Optical Small Form Factor Pluggable (SFP) <sup>(2)</sup>                      |
| Interface type   | Gigabit Ethernet according to IEEE 802.3ab (Electrical) or IEEE 802.3z (Optical)                   |
| Data rate  | 960 Mbps   |
| Syntax   | CBR MPEG SPTS on UDP (RFC-768)   |
| <b>RF Outputs</b>  |  |
| Number of outputs  | Max. 6 x 1 (each with 2 adjacent QAM channels)   |
| Connector  | F-type, 75 $\Omega$  |
| Frequency<br>Range<br>Step size<br>Stability<br>Accuracy | Channel edges between 45 and 870 MHz (tunable)<br>25 kHz<br>$\pm 3$ ppm<br>$\pm 3$ ppm             |
| Channel Bandwidth  | 6, 7 or 8 MHz depending on QAM transmission standard   |
| Level<br>Range<br>Stability<br>Accuracy                  | 45 to 55 dBmV RMS per QAM Channel in 0.5 dB steps<br>$\pm 1$ dB<br>$\pm 1$ dB                      |
| Return loss  | > 14 dB in channel   |
| <b>Management Interface</b>                              |  |
| Interface type   | Ethernet 10 Base-T   |
| Connector  | 2 x RJ-45  |
| Protocols  | HTTP, SNMP, HTML, JAVA, FTP  |
| <b>Signal Specifications</b>                             |  |
| Channel encoding   | Scrambling, Reed-Solomon, Trellis and Interleaving according to ITU-T Annex A, B or C              |
| MER (before equalizer)                                   | $\geq 34$ dB (at RF)   |
| MER (after equalizer)                                    | $\geq 41$ dB (at RF)   |
| BER (256 QAM)  | $\leq 5 \cdot 10^{-9}$ (ITU-A/C pre FEC)<br>$\leq 1 \cdot 10^{-13}$ (ITU-B pre FEC / post trellis) |
| QAM constellations                                       | 64 & 256 QAM   |
| <b>Environmental Specifications</b>                      |  |
| Operating temperature                                    | +32°F to +122°F (0° to 50°C)   |
| Storage temperature                                      | -4°F to +158°F (-20° to 70°C)  |
| Operating humidity                                       | 5% to 95%, non-condensing  |
| Power supply (nominal)                                   | 115 to 230 V AC $\pm 10\%$ or -48 V DC   |
| Power consumption (fully loaded)                         | < 175 W  |
| <b>Chassis Mechanical Specifications</b>                 |  |
| Height   | 1.75 in. / 44.45 mm (1 RU)   |
| Width  | 19 in. / 482.6 mm  |
| Depth  | 21.0 in. / 533.4 mm  |
| Weight   | 16.5 lbs / 7.48 kg   |

(2) SFP Module not included

## Ordering Information

| Continuum DVP Dense QAM Array components                                  | Part Number |
|---|-------------|
| <b>Housings</b>   |             |
| 1 RU Chassis (AC/DC powering slots, ITU-A)                                | 4004009     |
| 1 RU Chassis (AC/DC powering slots, ITU-B)                                | 4004010     |
| 1 RU Chassis (AC/DC powering slots, ITU-C)                                | 4004011     |
| 1 RU Chassis (DC/DC powering slots, ITU-A)                                | 4004012     |
| 1 RU Chassis (DC/DC powering slots, ITU-B)                                | 4004013     |
| 1 RU Chassis (DC/DC powering slots, ITU-C)                                | 4004014     |
| 1 RU Chassis (AC/AC powering slots, ITU-A)                                | 4004016     |
| 1 RU Chassis (AC/AC powering slots, ITU-B)                                | 4004017     |
| 1 RU Chassis (AC/AC powering slots, ITU-C)                                | 4004018     |
| <b>Power Supplies</b>   |             |
| AC Power Supply   | 1001815     |
| DC Power Supply   | 1001773     |
| <b>QAM Modulator</b>  |             |
| Dual QAM Modulator Card, High output 55 dBmV (2 QAM Channels on 1 RF out) | V9524811    |
| <b>SFP Plug-ins – WDM types (only when Optical GbE will be used)</b>      |             |
| GbE SFP Module 850 nm (LC, up to 500 m)                                   | 4002019     |
| GbE SFP Module 1310 nm (LC, up to 5 km)                                   | 4002020     |
| GbE SFP Module 1310 nm (LC, up to 10 km)                                  | 4003461     |
| GbE SFP Module 1310 nm (LC, up to 25 km)                                  | 4002021     |
| GbE SFP Module 1310 nm (LC, up to 40 km)                                  | 4003466     |
| GbE SFP Module 1550 nm (LC, up to 40 km)                                  | 4002022     |
| GbE SFP Module 1550 nm (LC, up to 70 km)                                  | 4002023     |
| <b>SFP Plug-ins – CWDM types (only when Optical GbE will be used)</b>     |             |
| GbE SFP Module 1470 nm (LC, up to 40 km)                                  | 4002003     |
| GbE SFP Module 1490 nm (LC, up to 40 km)                                  | 4002004     |
| GbE SFP Module 1510 nm (LC, up to 40 km)                                  | 4002005     |
| GbE SFP Module 1530 nm (LC, up to 40 km)                                  | 4002006     |
| GbE SFP Module 1550 nm (LC, up to 40 km)                                  | 4002007     |
| GbE SFP Module 1570 nm (LC, up to 40 km)                                  | 4002008     |
| GbE SFP Module 1590 nm (LC, up to 40 km)                                  | 4002009     |
| GbE SFP Module 1610 nm (LC, up to 40 km)                                  | 4002010     |
| GbE SFP Module 1470 nm (LC, up to 70 km)                                  | 4002011     |
| GbE SFP Module 1490 nm (LC, up to 70 km)                                  | 4002012     |
| GbE SFP Module 1510 nm (LC, up to 70 km)                                  | 4002013     |
| GbE SFP Module 1530 nm (LC, up to 70 km)                                  | 4002014     |
| GbE SFP Module 1550 nm (LC, up to 70 km)                                  | 4002015     |
| GbE SFP Module 1570 nm (LC, up to 70 km)                                  | 4002016     |
| GbE SFP Module 1590 nm (LC, up to 70 km)                                  | 4002017     |
| GbE SFP Module 1610 nm (LC, up to 70 km)                                  | 4002018     |



Scientific-Atlanta, the Scientific-Atlanta logo, and Continuum are registered trademarks of Scientific-Atlanta, Inc.  
 Continuum DVP is a trademark of Scientific-Atlanta, Inc.  
 DirectRF is a trademark of Scientific-Atlanta Europe NV.  
 Specifications and product availability are subject to change without notice.  
 © 2005 Scientific-Atlanta, Inc. All rights reserved.

Europe & Asia  
 +32 56 445 000 or +49-6173-928-0  
[www.saeurope.com](http://www.saeurope.com)  
 Americas  
 1-800-722-2009 or 770-236-6900  
[www.scientificatlanta.com](http://www.scientificatlanta.com)

Part Number 7002787 Rev C  
 April 2005