

## Cisco Unified Wireless IP Phone 7921G Multi-Charger

Cisco® Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, delivering a media-rich collaboration experience across business, government agency, and institutional workspaces. These applications use the network as the platform to enhance comparative advantage by accelerating decision time and reducing transaction time. The security, resilience, and scalability of the network enable users in any workspace to easily connect anywhere, anytime, and anyplace, using any media, device, or operating system. Cisco Unified Communications is part of a comprehensive solution that includes network infrastructure, security, wireless, management applications, lifecycle services, flexible deployment and outsourced management options, and third-party applications.

### Features

The Cisco Unified Wireless IP Phone 7921G Multi-Charger (Figure 1) is ideal for environments where customers have multiple shifts and need to keep their Cisco Unified Wireless IP Phone 7921G charged throughout the day. The multi-charger can charge up to 6 phones and 6 batteries simultaneously. Its flexible design allows the unit to be either placed on a desk or mounted on the wall to save desk space. Table 1 gives features of the multi-charger, Table 2 gives its specifications, and Table 3 gives certification and compliance information.

**Figure 1.** Cisco Unified Wireless IP Phone 7921G Multi-Charger



**Table 1.** Features

Feature	Description
<b>Charging capacity</b>	6 phones and 6 batteries (standard or extended)
<b>Mounting options</b>	Desk or wall mount
<b>Material</b>	Lead and latex free

**Table 2.** Specifications

Item	Description
<b>Dimensions (H x W x D)</b>	4.4 x 20.7 x 6.8 in. (112 x 525 x 173 mm)
<b>Weight</b>	<ul style="list-style-type: none"> <li>• Multi-charger: 3.4 lb (1.5 kg)</li> <li>• Power supply: 1.1 lb (0.5 kg)</li> <li>• Mounting bracket: 2.2 lb (1 kg)</li> <li>• Total weight: 6.7 lb (3 kg)</li> </ul>
<b>Power supply</b>	<ul style="list-style-type: none"> <li>• Input: 100–240V, 2A, 50/60 Hz</li> <li>• Output: 19V, 5.26A</li> <li>• AC adapters (by geographical region)</li> </ul>
<b>Power consumption</b>	100 watts
<b>Operating temperature</b>	32 to 104°F (0 to 40°C)
<b>Storage temperature</b>	–22 to 140°F (–30 to 60°C)
<b>Relative humidity</b>	10 to 95% (noncondensing)
<b>Drop specification</b>	2.5 ft (75 cm) to concrete
<b>Vibration</b>	1.5 Grms maximum, 0.1" double amplitude @0.887 octaves per minute from 5-500-5 Hz sweep, 10-minute dwell on three major peaks, in each of the three major mutually perpendicular axes
<b>Thermal shock</b>	–22°F (–30°C) 24 hours; 158°F (70°C) 24 hours
<b>Charging time</b>	<ul style="list-style-type: none"> <li>• Standard battery only: 3.5 hours</li> <li>• Extended battery only: 5 hours</li> <li>• Phone with standard battery: 3 hours</li> <li>• Phone with extended battery: 4.5 hours</li> </ul>

**Table 3.** Safety and Compliance

Item	Description
<b>Safety</b>	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CSA 22.2 No. 60950-1</li> <li>• EN 60950</li> <li>• IEC 60950-1</li> <li>• AS/NZS 60950-1</li> </ul>
<b>Electromagnetic compatibility (EMC) and electromagnetic interference (EMI)</b>	<ul style="list-style-type: none"> <li>• CFR 47 Part 15 Class A</li> <li>• ICES-003 Class A</li> <li>• EN 55022 Class A</li> <li>• CISPR 22 Class A</li> <li>• VCCI Class A</li> <li>• AS/NZS CISPR22</li> <li>• CSCR 24</li> <li>• EN 55024</li> <li>• EN 50082-1</li> <li>• EN 61000-6-1</li> <li>• EN 61000-3-2</li> <li>• EN 61000-3-3</li> <li>• EN 61000-4-2</li> <li>• EN 61000-4-3</li> <li>• EN 61000-4-4</li> <li>• EN 61000-4-5</li> <li>• EN 61000-4-6</li> <li>• EN 61000-4-11</li> </ul>

## Ordering Information

Table 4 gives ordering information for the Cisco Unified Wireless IP Phone 7921G Multi-Charger.

**Table 4.** Ordering Information

Part Number	Description
<b>CP-MCHGR-7921G-BUN</b>	Cisco Unified Wireless IP Phone 7921G Multi-Charger bundle (includes multi-charger, power supply, and AC power cord)
<b>CP-MCHGR-7921G=</b>	Cisco Unified Wireless IP Phone 7921G Multi-Charger spare
<b>CP-PWR-MC7921G=</b>	Cisco Unified Wireless IP Phone 7921G Multi-Charger power supply spare
<b>CAB-AC2AUS=</b>	AC power cord for Australia spare
<b>CAB-AC2E=</b>	AC power cord for Europe spare
<b>CAB-AC2J=</b>	AC power cord for Japan spare
<b>CAB-AC2=</b>	AC power cord for North America spare
<b>CAB-AC2UK=</b>	AC power cord for United Kingdom spare
<b>CAB-AC2CHI=</b>	AC power cord for China spare

## Warranty

The Cisco Unified Wireless IP Phone 7921G Multi-Charger is covered by a Cisco standard 1-year replacement warranty. A Cisco SMARTnet<sup>®</sup> optional service agreement is available.

## Cisco Unified Communications Services and Support

Using the Lifecycle Services approach, Cisco and its partners offer a broad portfolio of end-to-end services to support the Cisco Unified Communications System. These services are based on proven methodologies for deploying, operating, and optimizing IP communications solutions. Upfront planning and design services, for example, can help you meet aggressive deployment schedules and minimize network disruption during implementation. Operate services reduce the risk of communications downtime with expert technical support, and optimize services enhance solution performance for operational excellence. Cisco and its partners offer a system-level service and support approach that can help you create and maintain a resilient, converged network that meets your business needs.



**Americas Headquarters**  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883

**Asia Pacific Headquarters**  
Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

**Europe Headquarters**  
Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: +31 0 800 020 0791  
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0708R)