

Cisco MCS 7835-H2 Unified Communications Manager Appliance

Cisco Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks enabling easy collaboration every time from any workspace.

Product Overview

The Cisco MCS 7835-H2 Unified Communications Manager Appliance is a high-availability server platform for Cisco Unified Communications Manager and an integral part of a complete, scalable architecture for a new generation of high-quality unified communications solutions for enterprise data networks. Delivering the high performance and availability that today's enterprise networks demand, this solution is easy to deploy and highly cost-effective. The server appliance is preinstalled with an operating system and Cisco Unified Communications Manager — it is fully operational upon startup, requiring entry of just a few configuration variables such as IP address and domain. At just 2 rack units (2RU) high, the Cisco MCS 7835-H2 offers tremendous power in a low-profile chassis that minimizes rack space. It supports up to 2500 Cisco Unified IP Phones per appliance and up to 10,000 Cisco Unified IP Phones in a cluster configuration.

Key Features and Benefits

Performance

The Cisco MCS 7835-H2 Unified Communications Manager Appliance is a robust, highly available server platform designed to support today's unified communications applications; it uses a Smart Array P400 Controller with a 256-MB cache to provide onboard Redundant Array of Independent Disks (RAID) support. The appliance occupies only 2RU of space while providing the features most requested in a high-availability server platform.

High Availability

High availability on the Cisco MCS 7835-H2 is achieved through the following mechanisms:

- Redundant hot-swap power supplies
- Redundant hot-swap fans
- Hot-swap Serial Attached SCSI (SAS) hard drives configured using RAID 1

Serviceability

System Health LEDs

The Cisco MCS 7835-H2 provides system health LEDs and unit identification lights on the front and back of the server to ease identification of system problems. When an internal component fails, this indication is made on an internal component LED (amber) and on the front panel of the appliance. If the item is serviceable without removing the server hood, as in the case of a redundant power supply, the external health LED illuminates. If the item is serviceable by removing the hood, as in the case of a fan failure, the internal health LED illuminates. If no failures have occurred, the system health LEDs are green. If a failure has occurred but a redundant feature has

enabled the system to continue running, the LED is amber. If the failure is critical and has caused the system to shut down, the LED is red.

Integrated Lights Out 2

The Integrated Lights Out 2 (iLO2) standard is included on this server. Combining essential management functions and diagnostics with basic lights-out functions as standard components of the server, iLO2 is available at no charge. The iLO2 standard feature offers maximum security, availability, and control over business-critical servers without the need to visit the systems physically.

- The iLO2 standard feature provides fundamental server control and monitoring by integrating essential lights-out technology directly into the Cisco MCS 7835-H2 Unified Communications Manager Appliance architecture.
- Essential lights-out features include remote power control, text-based console, logs, status, and alert forwarding.
- The easy-to-use, dedicated lights-out LAN port is accessible through a browser interface.
- The iLO2 standard feature saves a valuable peripheral-component-interconnect (PCI) slot for additional functions and reduces installation and setup time.
- The iLO2 standard feature eliminates the need for an external power adapter or any other internal or external cables.
- The iLO2 standard feature provides a rich suite of security features, including Secure Sockets Layer (SSL).
- The iLO2 standard feature provides a scalable solution by allowing group administration of iLO processors.

DAT Tape Support

The Cisco MCS 7835-H2 Appliance can support an optional 36- or 72-GB universal-serial-bus (USB) external Digital Audio Tape (DAT) drive or an optional USB rack-mount DAT drive. This tape drive connects through one of the 4 USB 2.0 ports provided by the Cisco MCS 7835-H2 Appliance.

Product Specifications

The following tables list the configuration by product ID.

Table 1. Configuration of MCS7835H2-K9-CMA2

Component	Value
Preload	Cisco Unified Communications Manager 5.1
Processor	Single Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 72-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Table 2. Configuration of MCS7835H2-K9-CMA2D

Component	Value
Preload	Cisco Unified Communications Manager 5.1
Processor	Single Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 146-GB SAS 2.5-in. hot-swap

Remote management	HP iLO Advanced License
--------------------------	-------------------------

Table 3. Configuration of MCS7835H2-K9-CMB1

Component	Value
Preload	Cisco Unified Communications Manager 6.0
Processor	Single Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 72-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Table 4. Configuration of MCS7835H2-K9-CMB1D

Component	Value
Preload	Cisco Unified Communications Manager 6.0
Processor	Single Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 146-GB SAS 2.5-in. hot swap
Remote management	HP iLO Advanced License

Table 5. Configuration of MCS7835H2-K9-CMB2

Component	Value
Preload	Cisco Unified Communications Manager 6.1
Processor	Single Intel 5140 2.33-GHz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 72-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Table 6. Configuration of MCS7835H2-K9-CMB2D

Component	Value
Preload	Cisco Unified Communications Manager 6.1
Processor	Single Intel 5140 2.33Ghz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 146-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Table 7. Configuration of MCS7835H2-K9-CMC2

Component	Value
Preload	Cisco Unified Communications Manager 7.1
Processor	Single Intel 5140 2.33Ghz 4M L2
Memory	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Hard disks	Two 146-GB SAS 2.5-in. hot-swap
Remote management	HP iLO Advanced License

Table 8 lists the detailed product specifications for the Cisco MCS 7835-H2 Unified Communications Manager Appliance.

Table 8. Product Specifications

Processor	
Maximum processors	2
Processors installed	1
Basic input/output system (BIOS) type	Flash memory
Memory	
Memory maximum	32 GB
Memory bus clock	667 MHz
Memory technology	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs
Multibit error mitigation	Advanced Error Checking and Correcting (AECC)
Total RAM slots	8
RAID Controller	
Controller model	HP Integrated Smart Array P400 Controller
Interface	PCI Express
Cache	256 MB
Battery-backed write cache	Yes
RAID levels supported	1
Hard disk	
Hard-disk revolutions per minute (RPM)	10,000
Hard-disk average seek time	4 ms
Hot-swappable bays	8
Hard-disk interface type	SAS
Data-transfer rate	300 MB per second
Network Connectivity	
Network interface card (NIC)	Dual onboard 10/100/1000
Connector	Two RJ-45 connectors on rear of server
10BASE-T cable support	Category 3, 4, or 5 unshielded twisted pair (UTP) (2 or 4 pair) up to 328 ft (100m)
100BASE-TX cable support	Category 5 UTP (2 pair) up to 328 ft (100m)
1000BASE-T cable support	Category 5 UTP, 5E UTP, or 6 UTP (2 pair) up to 328 ft (100m)
Interfaces	
Serial ports	1
Parallel ports	0
USB 2.0 ports	5 (2 front, 2 back, 1 inside)
Keyboard ports	1 PS2
Mouse ports	1 PS2
Audio ports	None
System management ports	RJ-45 for HP iLO2
VGA ports	1 front and 1 back
Security	

<ul style="list-style-type: none"> • Power-on password • Keyboard password • Selectable boot device • Diskette drive control • QuickLock, network server mode • Serial interface control • Administrator's password • Disk configuration lock 	
Industry-Standard Compliance	
<ul style="list-style-type: none"> • Advanced Configuration and Power Interface (ACPI) 2.0 compliant • PCI 2.2 compliant • Wake On LAN (WOL) support • Microsoft Logo certifications • USB 2.0 support 	
Expansion Options	
PCI-X non-hot plug 133-MHz 64-bit slots	1
PCI-X non-hot plug 100-MHz 64-bit slots	2
Power	
Maximum input power	735W
Steady-state output power	575W
Autoranging AC mains input	Yes
Power Factor Correction (PFC)	Yes
Maximum hot-swap power supplies	2
Hot-swap power supplies installed	2
Mains input frequency range	50–60 Hz
Input voltage low range	<ul style="list-style-type: none"> • 100 VAC minimum • 132 VAC maximum
Input voltage high range	<ul style="list-style-type: none"> • 200 VAC minimum • 265 VAC maximum
Input current	<ul style="list-style-type: none"> • 7.5A (100 VAC) • 3.8A (200 VAC)
Environmental	
Air temperature: Server on	50 to 95°F (10 to 35°C)
Air temperature: Server off	40 to 158°F (40 to 70°C)
Humidity: Server on	10 to 90%
Humidity: Server off	5 to 95%
BTU rating	1475 BTU per hour
Sound emissions idle	7.4 bels
Sound emissions maximum	7.4 bels
Bystander sound pressure idle	58 dBa
Bystander sound pressure operating	58 dBa
Cooling system	<ul style="list-style-type: none"> • 5 fans installed: Base systems • 8 fans installed: Redundant fan systems
Dimensions	
Form factor	Rack-mount 2RU
Rack-mounting	Included for standard third-party rack
Weight: Maximum	60 lb (27.22 kg)
Weight: No drives	47.18 lb (20.41 kg)

Height	3.38 in. (8.59 cm)
Width	17.54 in. (44.54 cm)
Depth	26.01 in. (66.07 cm)

Ordering Information

To place an order, visit the Cisco Ordering Home Page and refer to Tables 9 and 10.

You can order the Cisco MCS 7835-H2 in two ways. You can enter UNIFIED-CM-7.1 or UNIFIED-CM-6.1 into the Dynamic Configuration tool on Cisco.com and view a list of Cisco Unified Communications Manager appliances and their associated licenses. You can also order the components individually using the following product part numbers:

- MCS7835H2-K9-CMC2 (preloaded with Cisco Unified Communications Manager 7.1)
- MCS7835H2-K9-CMC1 (preloaded with Cisco Unified Communications Manager 7.0)
- MCS7835H2-K9-CMB2D (preloaded with Cisco Unified Communications Manager 6.1)
- MCS7835H2-K9-CMB1D (preloaded with Cisco Unified Communications Manager 6.0)
- MCS7835H2-K9-CMA2D (preloaded with Cisco Unified Communications Manager 5.1)
- LIC-CM7.0-7835=
- LIC-CM6.1-7835=
- LIC-CM6.0-7835=
- LIC-CM5.1-7835=
- KEY-CCM-ADMIN-K9= (order a minimum quantity of 2)
- DAT-USB-EXT-72= (optional external USB DAT tape drive)
- DAT-USB-RM-72= (optional rack-mount USB DAT tape drive)

Appliance Spares

To order spare appliances, refer to Table 9.

Table 9. Ordering Information for Spare Appliances

Application	Spare Part Number
Cisco Unified Communications Manager 7.1	MCS7835H2-K9-CMC2
Cisco Unified Communications Manager 7.0	MCS7835H2-K9-CMC1
Cisco Unified Communications Manager 6.1	MCS7835H2-K9-CMB2D
Cisco Unified Communications Manager 6.0	MCS7835H2-K9-CMB1D
Cisco Unified Communications Manager 5.1	MCS7835H2-K9-CMA2D

Field-Replaceable Spares

To order spare parts for the appliance, refer to Table 10.

Table 10. Ordering Information for Appliance Spare Parts

Spare Part Number	Description
Spare 72-GB SAS 2.5 inch Hot Swap Drive for Cisco MCS 7835-H2	HDD-7835-H2-72=
Spare 146-GB SAS 2.5 inch Hot Swap Drive for Cisco MCS 7835-H2	HDD-7835-H2-146=
Spare 575W power supply for Cisco MCS 7835-H2	PWR-7835-H2=
Spare fan for Cisco MCS 7835-H2	FAN-7835-H2=
Spare external USB 36-/72-GB DAT drive	DAT-USB-EXT-72=

Spare rack-mount USB 36-/72-GB DAT drive

DAT-USB-RM-72=

Replacement Part Numbers

With the introduction of the new configurations using 146-GB disks in place of 72-GB disks, the orderability of the old configuration expired. Table 11 provides the replacement part numbers for those products that are no longer orderable.

Table 11. Replacement Part Numbers

Old Part Number	Replacement Part Number
MCS7835H2-K9-CMA2	MCS7835H2-K9-CMA2D
MCS7835H2-K9-CMB1	MCS7835H2-K9-CMB1D
MCS7835H2-K9-CMB2	MCS7835H2-K9-CMB2D

Warranty Information

Cisco offers a 1-year limited hardware warranty on Media Convergence Servers. For terms and conditions of this warranty, refer to

http://www.cisco.com/univercd/cc/td/doc/es_inpk/1y1cen_.htm.

Cisco Unified Communications Services

Cisco Unified Communications Services allows you to accelerate cost savings and productivity gains associated with deploying a secure, resilient Cisco Unified Communications solution. Delivered by Cisco and our certified partners, our portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks. Our unique lifecycle approach to services enhances your technology experience to accelerate true business advantage.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCSI, CCENT, Cisco Eos, Cisco HealthPresence, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco Stackpower, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0903R)