

Cisco HGA9N High-Gain Omnidirectional Antenna for N-Type Connectors

Cisco Small Business Wireless Antennas

Increase the Wireless Network Coverage Area for Your Small Business

Highlights

- Improves signal strength to increase range and provide coverage in hard-to-reach areas
- Weatherproof, lightning-protected casing for safe deployment on the exterior of your building
- Easy installation, with no software or configuration required

Figure 1. Cisco HGA9N High-Gain Omnidirectional Antenna for N-Type Connectors



Product Overview

Use the Cisco® HGA9N High-Gain Omnidirectional Antenna for N-Type Connectors (Figure 1) to increase the range of your wireless network. Attach the antenna to the exterior access point to increase both the effective strength of the outgoing signals and the receive sensitivity of the incoming signals.

The added signal strength and sensitivity also improve midrange communication reliability, because every packet comes through loud and clear, reducing retransmissions due to weak signal reception.

The 9-dBi signal strength allows the signals to travel farther and provides better signal detection in a 360-degree radius.

The weatherproof housing is able to withstand harsh outdoor conditions. The antenna also includes a lightning surge protector, mounting kit, and cable.

Features

- National Electrical Manufacturers Association (NEMA) rated, lightning-protected, weatherproof housing
- 9-dBi omnidirectional antenna gives clients unconstrained access
- Easy to install - no configuration necessary

Specifications

Table 1 gives the specifications, package contents, and minimum requirements for the Cisco HGA9N High-Gain Omnidirectional Antenna for N-Type Connectors.

Table 1. Specifications for the Cisco HGA9N High-Gain Omnidirectional Antenna for N-Type Connectors

Specifications	
Ports	1 N-type female connector
Cabling type	Coax: 50-ohm impedance
Electrical Specifications	
Frequency range	2400 MHz to 2500 MHz
Gain	9 dBi
Voltage standing wave ratio (VSWR)	1.92 : 1 max
Polarization	Linear, vertical
Half-power beamwidth (HPBW): horizontal	360°
HPBW: vertical	11°
Maximum power	4W
Impedance	50 ohms
Range	Maximum outdoor range:* 120 m (0.078 mi) at 54 Mbps, 880 m (0.55 mi) at 11 Mbps *Range estimation is based on 1 Cisco WAP200E Access Point with Cisco HGA9N antenna connecting to wireless client with 0-dBi antenna under ideal line-of-sight conditions
Environmental	
Dimensions W x H x D	2.95 x 24.61 x 2.20 in. (75 x 625 x 56 mm)
Unit weight	0.44 lb (0.2 kg)
Mounting options	Mounting kit provided
Certification	FCC, IC
Operating temperature	-22° to 176°F (-30° to 80°C)
Storage temperature	-22° to 176°F (-30° to 80°C)
Operating humidity	5% to 95% noncondensing
Storage humidity	5% to 95% noncondensing
Package Contents	
<ul style="list-style-type: none"> • Antenna body • Antenna cable • Lightning protector • User guide on CD • Quick installation guide 	
Minimum Requirements	
<ul style="list-style-type: none"> • Cisco WAP200E Access Point 	
Product Warranty	
90-day limited hardware warranty with return to factory replacement	

Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 90-day limited hardware warranty with return to factory replacement. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to: <http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at <http://www.cisco.com/go/warranty>.

For More Information

For more information on Cisco Small Business products and solutions, visit: <http://www.cisco.com/smallbusiness>



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0809R)