Supp	liers Declaration of Conformity for USGv6 Prod	ducts						SDOC-v1.	.9 Page 1	
1	The Document Requiring Conformity:							(NIST SI	P500-267)	
2	Product Identifier:					Cisco DX650				
	Supplier's Name, Address and SDOC Contact	Details								
	Systems, Inc.									
170 V	Vest Tasman Dr.									
San J	ose, CA 95134									
4	4 Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.									
-	10.2(1)									
			•	,						
5	Product Family (other products using same IPv6	stack(s) to	which thes	e results ar	e declared	to apply). Check Produ	ıct Fan	nily attesta	ation belo	
	DX650, Cisco DX70, Cisco DX80									
6	USGv6 Capability summary. (For each distinct	IDv6 stock	in the produ	ict provide (o cummary	of its USGV6 capabilitie	c holos	wand inclu	ıdo o	
· ·	detailed test result summary). e.g. example-prod		•	•	•					
			ole: IPv6 Ba			I-AIGHTICSEC-VS+INEVZ	+SLAC	+LIIIK=LIII	erriet.	
	00	ovo capai	ne. II vo ba	ISC T OLAA	C T Auui					
7	Solf Contained or Composite SDOC2 (Must indicate and)									
	Self Contained or Composite SDOC? (Must indicate one).									
YES	All of the declared USGv6 capabilities of this product are addressed by orginal test results reported in this SDOC.					Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified				
						components that have their o				
	the relevant referenced SDOCs are identified in section 8 and							ction 8 and		
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite									
	Component Supplier			Product ID:				Stack ID: Notes:		
[1]	остроном очерно				1 TOGGOT II		Otaon		Trotoo.	
[2]									+	
									+	
[3]									+	
[4]							ļ			
9	Supplementary Attestations (Answer all).									
	YES	,	,			ts.That is, no claimed	YES	This product		
		environment.		itnis product is	operated in a	a dual stack (6 and 4)network		functional in environment		
	VES								oducts listed	
	YES					ented, and how their lpv6	163	in the produc		
							section 5 are			
								implemented		
								their USGv6	6 capabilities I in form and	
40	Cianatura		1				Dete	are identical	ini ionni and	
10	Signature						Date			
	Print Name / Title		Darryll Gad	Ison, Lead I	JSGv6 Cis	co Systems			$\overline{}$	
				,	2 2 3 . 3 0 10					
See ins	structions for fields 1-12 on Page 4.									

11	Suppl	ers Declaration of Conformity for USGv6	Products: De	clared	Capabil	ities an	d Test Results Sum	mary	US	GV6-v1 SDOC-v1.9 Page		
roduct l	d:	Cisco DX650			Stack I	d:			N/A			
			Supported Capabilities				USGv6 Testing Program Results					
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #		
eference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
P500-267	6.1	IPv6 Basic Requirements										
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)		Р			Basic_v1.*_C	UNH/IOL-18282	Basic_V1.*_I	UNH/IOL-18285		
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH/IOL-18283	SLAAC-V1.0_I	UNH/IOL-18286		
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test			
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I			
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test			
		support of neighbor discovery security extensions	SEND				Self Test		Self Test			
P500-267	6.6	Addressing Requirements										
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH/IOL-18281	Addr_Arch_v1.*_I	UNH/IOL-18284		
		support of cryptographically generated addresses	CGA				Self Test		Self Test			
P500-267	6.7	IP Security Requirements	.= -									
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I			
		support for automated key management					IKEv2_v1.*_C		IKEv2_v2.*_I			
DE00.05-		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I			
P500-267	6.11	Application Requirements	DNO OF 11				O.U.T.		O-11 T (
	<u> </u>	support of DNS client/resolver functions					Self Test		Self Test			
	<u> </u>	support of Socket application program interfaces	SOCK URI				Self Test		Self Test Self Test	1		
		support of IPv6 uniform resource identifiers					Self Test					
		support of a DNS server application	DNS-Server DHCP-Server				Self Test		Self Test			
DE00 007	0.0	support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I			
P500-267	6.2	Routing Protocol Requirements	IGW				Call Tabl		0005:04 * 1			
		support of the intra-domain (interior) routing					Self Test		OSPFv3_v1.*_I			
P500-267	6.4	support for inter-domain (exterior) routing protocols Transition Mechanism Requirements	EGW				Self Test		BGP_v1.*_I			
2500-267	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test			
		support of interoperation with IP v4-only systems support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
P500-267	6.8	Network Management Requirements	OFE				Sell Test		Self Test			
F300-207	0.0	support of network management services	SNMP				Self Test		Self Test			
P500-267	6.9	Multicast Requirements	OIVIVII				Jen Test		Och Test			
1 300-201	0.9	support of basic multicast	Mcast				Self Test					
		full support of multicast communications					Self Test		Self Test			
P500-267	6.10	Mobility Requirements					<i>301. 1 301</i>		30.1.100.			
	00	support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities					Self Test		Self Test			
P500-267	6.3	Quality of Service Requirements										
		support of Differentiated Services capabilities	DS				Self Test		Self Test			
P500-267	6.12	Network Protection Device Requirements										
		support of common NPD regts	NPD				N1 N2 N3 N4_v1.3					
	1	support of basic firewall capabilities					N1_FW_v1.3			1		
	1	support of application firewall capabilities					Self Test					
	1	support of intrusion detection capabilities					N3_IDS_v1.3					
		support of intrusion protection capabilities					N4_IPS_v1.3					
P500-267	6.5	Link Specific Technologies										
		support of robust packet compression services	ROHC				Self Test		Self Test			
		support of link technology [O:1]					Self Test		Self Test			
		(repeat as needed) support of link technology	Link=									
12		< Check HERE if this stack's DOC included	les additional	informa	ation ab	out tes	ted capabilities and	options on an attached page	3 of notes.			
Level	Level of support for USGv6-v1 Requirements for capability.				Color	Color Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
	Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-V1 requirements for these capabilities.						Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile. Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
P												
 N	See notes page for details on the level of support of USGv6-v1 reequirements for this capability.						Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
X		capability not supported in product.	i recquirements	ioi ulis Ca	ιμαυιιιίχ.		mulcales capability trial is	Tert optional / ochulilonal by the feco	al by the recommedations of the USGVO-VT Profile.			
st Suite -	Specific	USGv6 Test suite used for test. See: http://www.ant	d.nist.gov/usav6/te	est-specif	ications h	tml		Note # - reference to a	detailed note about this o	apability or result on attached p		
		 Abbreviation of accredited laboratory and its local id 			.54.10110.111		Component Ref	- Supplier / Product / Stack ID of dist				
· · · ·		und it acordance laboratory and no local it		Journ			33	- sppo. ,	, locioù dempendit	p. c capability		

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v1.9 Page 3											
Field	Product Id:	Stack Id:									
13				Context /	Supported Capabilities		Notes about USG		Gv6-v1 Capabilities.		
Note #	Spec / Reference	Continu	USCAC and Destilla Descriptorments	Configuration	Heet	Douter	NDD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite	Took Lab / Dooult ID, Note
Note #	Reference	Section	USGv6-v1 Profile Requirements	Option	HUST	Router	NPD	Conformance/NPD	rest Lab / Result ID, Note	Interoperability	Test Lab / Result ID, Note
1											
Discussio	n:				1				,		
2											
Discussio	n:				ı		ı				
3											
Discussio	n:										
4											
Discussio	n:				ı	,					
5											
Discussio	n:										
6											
Discussio	n:				1				,		
7											
Discussio	n:				ı	•	ı				
8											
Discussio	n:					•					
9											
Discussio	n:		Γ	.	ı	1		<u></u>			
10											
Discussio	n: Sonoral Natas	/ Discussi	on about this Product / Stack's capabilities:								
veriuoi s	Serierai NOLES	, Discussi	on about this Froudet / Stack's Capabilities:								

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.
- 2 **Product Identifier**: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- **8** Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

3 Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.